



FCC TEST REPORT

FCC ID: 2BNOC-WIPC1S-BDEHP

Product	:	WIFI Camera
Model Name	:	IPC-B1410C-S2-L-W
Brand	:	N/A
Report No.	:	PTC25010808201E-FC02
Prepared for		
HANGZHOU ZANUO TECHNOLOGY CO.,LTD		
Room 2001,Building 3,No. 1217,Wenyi West Road,Cangqian Street,Yuhang District, Hangzhou, ZheJiang, China		
Prepared by		
Precise Testing & Certification Co., Ltd.		
Building 1, No. 6, Tongxin Road, Dongcheng Street, Dongguan, Guangdong, China.		



Report No.: PTC25010808201E-FC02

TEST RESULT CERTIFICATION

Applicant's name : HANGZHOU ZANUO TECHNOLOGY CO.,LTD

Address : Room 2001,Building 3,No. 1217,Wenyi West Road,Cangqian Street,Yuhang District, Hangzhou, ZheJiang, China

Manufacture's name : HANGZHOU ZANUO TECHNOLOGY CO.,LTD

Address : Room 2001,Building 3,No. 1217,Wenyi West Road,Cangqian Street,Yuhang District, Hangzhou, ZheJiang, China

Product name : WIFI Camera

Model name : IPC-B1410C-S2-L-W

Test procedure : FCC CFR47 Part 1.1307(b)(1)

Test Date : Jan. 10, 2025 to Feb. 7, 2025

Date of Issue : Feb. 14, 2025

Test Result : PASS

This device described above has been tested by PTC, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of PTC, this document may be altered or revised by PTC, personal only, and shall be noted in the revision of the document.

Test Engineer:

A handwritten signature in black ink, appearing to read 'Jack Zhou'.

Jack Zhou / Engineer

Technical Manager:

A handwritten signature in black ink, appearing to read 'Simon Pu'.

Simon Pu / Manager



Contents

	Page
2 TEST SUMMARY	4
3 GENERAL INFORMATION	5
3.1 GENERAL DESCRIPTION OF E.U.T.	5
4 RF EXPOSURE	6
4.1 REQUIREMENTS	6
4.2 THE PROCEDURES / LIMIT	6
4.3 MPE CALCULATION METHOD	7
4.4 TEST RESULT	7



Report No.: PTC25010808201E-FC02

2 Test Summary

Test Items	Test Requirement	Result
Maximum Permissible Exposure (Exposure of Humans to RF Fields)	15.247 (i)	PASS
Remark:		
N/A: Not Applicable		



3 General Information

3.1 General Description of E.U.T.

Product Name	:	WIFI Camera
Model Name	:	IPC-B1410C-S2-L-W
Additional model	:	IPC-B1XXXX-XXX-L-W, ZN-IPC-B1XXXX-XXX-L-W, IPC-B1XXXX-XXX-W, ZN-IPC-B1XXXX-XXX-W, IPC-B2XXXX-XXX-L-W, ZN-IPC-B2XXXX-XXX-L-W, IPC-B2XXXX-XXX-W, ZN-IPC-B2XXXX-XXX-W, IPC-B1XXXX-XXX-XXX-L-W, ZN-IPC-B1XXXX-XXX-XXX-L-W, IPC-B1XXXX-XXX-XXX-W, ZN-IPC-B1XXXX-XXX-XXX-W, IPC-B2XXXX-XXX-XXX-L-W, ZN-IPC-B2XXXX-XXX-XXX-L-W, IPC-B2XXXX-XXX-XXX-W, ZN-IPC-B2XXXX-XXX-XXX-W, IPC-B1XXXX-XXX-FL-W, ZN-IPC-B1XXXX-XXX-FL-W, IPC-B2XXXX-XXX-FL-W, ZN-IPC-B2XXXX-XXX-FL-W, IPC-B1XXXX-XXX-XXX-FL-W, ZN-IPC-B1XXXX-XXX-XXX-FL-W, IPC-B2XXXX-XXX-XXX-FL-W, ZN-IPC-B2XXXX-XXX-XXX-FL-W, IPC-P4A-4F-L, ZN-IPC-P4A-4F-L, IPC-H4A-4F-L, ZN-IPC-H4A-4F-L, IPC-PXX-XXX-XXX-L, IPC-HXX-XXX-XXX-L, IPC-CXX-XXX-XXX-L, IPC-FXX-XXX-XXX-L, IPC-DXX-XXX-XXX-L, IPC-LXX-XXX-XXX-L, IPC-TXX-XXX-XXX-L, IPC-BXX-XXX-XXX-L, IPC-DBXX-XXX-XXX-L, IPC-DSXX-XXX-XXX-L, IPC-PXX-XXX-XXX-FL, IPC-HXX-XXX-XXX-FL, IPC-CXX-XXX-XXX-FL, IPC-FXX-XXX-XXX-FL, IPC-DXX-XXX-XXX-FL, IPC-LXX-XXX-XXX-FL, IPC-TXX-XXX-XXX-FL, IPC-BXX-XXX-XXX-FL, IPC-DBXX-XXX-XXX-FL, IPC-DSXX-XXX-XXX-FL, IPC-PXX-XXX-XXX, IPC-HXX-XXX-XXX, IPC-CXX-XXX-XXX, IPC-FXX-XXX-XXX, IPC-DXX-XXX-XXX, IPC-LXX-XXX-XXX, IPC-TXX-XXX-XXX, IPC-BXX-XXX-XXX, IPC-DBXX-XXX-XXX, IPC-DSXX-XXX-XXX (X stands for the numbers 0-9, and the letters A-Z)
Specification	:	802.11b/g/n HT20/HT40
Operation Frequency	:	2412-2462MHz for 802.11b/g/ n(HT20) 2422-2452MHz for 802.11 n(HT40)
Number of Channel	:	11 channels for 802.11b/g/ n(HT20) 7 channels for 802.11n(HT40)
Type of Modulation	:	DSSS with DBPSK/DQPSK/CCK for 802.11b; OFDM with BPSK/QPSK/16QAM/64QAM for 802.11g/n;
Antenna installation	:	External antenna
Antenna Gain	:	3.18 dBi
Power supply	:	DC 12V/1A,5V/2A
Hardware Version	:	GK7205V20_MB_V02_RA
Software Version	:	30.13.101301102.R



4 RF Exposure

Test Requirement : FCC Part 1.1307(b)(1)

Evaluation Method : KDB 447498 D01 General RF Exposure Guidance v06

4.1 Requirements

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2 m normally can be maintained between the user and the device.

4.2 The procedures / limit

(A) Limits for Occupational / Controlled Exposure

Frequency Range	Electric Field	Magnetic Field	Power Density (S)	Averaging Time
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range	Electric Field	Magnetic Field	Power Density (S)	Averaging Time
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz ; *Plane-wave equivalent power density



4.3 MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } P_d \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric field (V/m)

P = Peak RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$P_d = \frac{30 \times P \times G}{377 \times d^2} \theta_{\phi}$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained

4.4 Test Result

Mode	Antenna Gain (numeric)	Max. Peak Output Power (dBm)	Tune up tolerance (dBm)	Max Tune Up Power (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)	Result
2412	2.08	19.98	19.98 ± 1	125.314117	0.051848	1	Pass

Conclusion:

1. Calculate in the worst-case mode.
2. Max. Tune Up Power is declared by manufacturer, and used to calculate.

*******THE END REPORT*******