

Technical Parameter /技术参数

1.Antenna/天线		
No/序号	Part Name/项目	SPEC/规格
1	Frequency Range/ 频率范围	433MHz
2	Impendence/阻抗	50 ohm nominal
3	Gain/增益	> -3dBi
4	Polarization/极化	LINE
5	VSWR/驻波比	≤1.5
6	Efficiency/效率	≥18%
2. Environmental Characteristics/环境特性		
No/序号	Part Name/项目	SPEC/规格
1	Operation Humidity/ 工作湿度	5~95%不冷凝
2	Operating Temperature/工 作温度	-20~+60℃
3	Store Temperatuer/储存温 度	-30~+70℃

射频性能测量报告

RF Performance Test Report


客户名称 Customer Name	深圳润洋电子有 限公司	项目名称 Project Name	NYFZ-S110-981-0 B	料号 P/N	
频段 Band	433MHz	测试日期 Test Date	2024/3/28	测试人 Inspector	

天线测试设备简介

Antenna Test Equipment Introduction

测试天线输入特性使用 Agilent E5071C and Agilent 5062A 矢量网络分析仪；辐射特性利用 Satimo 三维近场暗室进行测试，并分别使用 8960 E5515 和 Agilent E4438C 进行了分析。暗房的测试坐标如下：

Test of antenna input characteristics using Agilent E5071C and Agilent 5062A vector network analyzer; The radiation pattern of the antenna are tested using the Satimostarlab3D near fieldAnechoic Chamber, and the instrument is used to agilent8960 E5515 and Agilent E4438C. The test coordinates of the darkroom are as follows:




1.S11 参数测量/*S11 Parameter-VSWR*

使用一根 50Ω 同轴电缆连接到天线，然后该电缆连接到网络分析仪测量 S11 参数，被测量产品远离金属至少 20 厘米。


MeasuringMethod is a 50Ωcoaxial cable is connected to the antenna. Then this cable isconnected to a networkanalyzer to measure the S11 parameter, Keeping this fixture away from metal at least 20cm.

S11 Parameter




Frequency(MHz)	430	433	435
VSWR	1.14	1.14	1.25

2. 天线匹配网络/Antenna Matching Network




PCB板端匹配电路未改动


2D Pattern



$\Phi = 0$



$\Phi = 90$



$\Theta = 90$

3. Gain & Efficiency-ANT

Frequency (MHz)	Efficiency (%)	Peak GAIN (dBi)
430	21.27	-1.33
433	21.66	-1.22
435	20.19	-1.53

