



Technical drawing of a 10-pin D-sub connector. The drawing shows a side view of the connector with dimensions in millimeters. Key dimensions include: overall length 223max, mounting hole spacing 230max, pin pitch 2.54, pin diameter 0.5, and various internal and external radii and widths. The connector is labeled '10' and 'D-SUB'.

No	Line size	number of turns	Whether the tail lines cross
1	Silk-covered wire 0.08*105P	9Ts	Yes

100KHz/1V_{rms} , TEMPERATURE:25±10 ℃, RELATIVE HUMIDITY:65±20%

No	Rating	Coil 1	Coil 2	Coil 3	Coil 4	Coil 5
1	Ls	6.3±10% uH	6.3±10% uH	6.3±10% uH	6.3±10% uH	6.3±10% uH
2	DCR	55 mΩ MAX	55 mΩ MAX	55 mΩ MAX	55 mΩ MAX	55 mΩ MAX

Coil 6	Coil 7	Coil 8	Coil 9
$6.3 \pm 10\%$ uH	$6.3 \pm 10\%$ uH	$6.3 \pm 10\%$ uH	$6.3 \pm 10\%$ uH
55 m Ω MAX	55 m Ω MAX	55 m Ω MAX	55 m Ω MAX

Add: Unit B, 3/F, Double Diamond, No. 29, Avenida do Conselheiro Mazzei, Macau