

FCC ID:2BNQW-F68
Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot \sqrt{f(\text{GHz})} \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where:

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

BT:

Modulation	Channel Freq. (GHz)	Conduct ed power (dBm)	Conducte d power (mW)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)	Result calculatio n	SAR Exclusion threshold	SAR test exclusion
GFSK	2.402	-3.14	0.49	-3±1	-2.00	0.63	<5	0.19558	3.00	YES
	2.441	-2.17	0.61	-2±1	-1.00	0.79	<5	0.24821	3.00	YES
	2.480	-0.96	0.80	0±1	1.00	1.26	<5	0.39651	3.00	YES
Pi/4 DQPSK	2.402	-2.32	0.59	-2±1	-1.00	0.79	<5	0.24622	3.00	YES
	2.441	-1.28	0.74	-1±1	0.00	1.00	<5	0.31247	3.00	YES
	2.480	-0.11	0.97	0±1	1.00	1.26	<5	0.39651	3.00	YES
8DPSK	2.402	-1.63	0.69	-1±1	0.00	1.00	<5	0.30997	3.00	YES
	2.441	-0.66	0.86	0±1	1.00	1.26	<5	0.39338	3.00	YES
	2.480	0.39	1.09	1±1	2.00	1.58	<5	0.49918	3.00	YES

BLE:

Modulation	Channel Freq. (GHz)	Conduct ed power (dBm)	Conducte d power (mW)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)	Result calculatio n	SAR Exclusion threshold	SAR test exclusion
GFSK1M bps	2.402	-3.16	0.48	-3±1	-2.00	0.63	<5	0.19558	3.00	YES
	2.44	-2.24	0.60	-2±1	-1.00	0.79	<5	0.24816	3.00	YES
	2.480	-0.99	0.80	0±1	1.00	1.26	<5	0.39651	3.00	YES
GFSK 2Mbps	2.402	-3.12	0.49	-3±1	-2.00	0.63	<5	0.19558	3.00	YES
	2.44	-2.13	0.61	-2±1	-1.00	0.79	<5	0.24816	3.00	YES
	2.480	-0.93	0.81	0±1	1.00	1.26	<5	0.39651	3.00	YES

Conclusion:

For the max result : $0.49918 \leq \text{FCC Limit } 3.0$ for 1g SAR. The Product unsupported at the same time to Transmitting.