

Inverted F Antenna Specification

MANUFACTURE : Zhongshan Chuangqi Electronic Technology Co., Ltd.

PRODUCT NAME : 2.4G-2DB

DATE : 2019-10-30


1. Antenna describe

Antenna plate: PCB Antenna

Frequency range: 2.4GHz-2.48GHz

ITEM Name	PCB Antenna
Model Name	2.4G-2DB
Polarization	Horizontal and Vertical
Azimuth Beam Patten	Omni-directional
Impedance	50 Ohm
Antenna Lengh	40mm
Gain(Max)	2.71dBi

2. Antenna Photo& Lengh (mm)



3. Gain


Frequency	Gain (dBi)
2400MHz	2.67
2410MHz	2.71
2420MHz	2.64
2430MHz	2.59
2440MHz	1.01
2450MHz	1.26
2460MHz	1.50
2470MHz	1.49
2480MHz	1.42
2490MHz	0.36
2500MHz	0.33

4. Return Loss/VSWR/Input Impedance

Frequency	Return Loss (dB)	VSWR	Input Impedance(Ω)
2400MHz	-7.23	2.53	25.37
2400MHz	-6.47	2.80	17.99
2450MHz	-6.22	2.90	17.18
2480MHz	-5.18	3.44	15.55
2500MHz	-4.56	3.89	15.48

Annex A Photographs


1. Test Setup




Annex B Figures

1. 2D Radiation Pattern


$\Phi=0^\circ$




Phi=90°




Theta=90°




2. 3D Radiation Pattern



2400MHz




2450MHz




2500MH

3. Return Loss



4. VSWR



END