

RF EXPOSURE EVALUATION

EUT Specification

EUT	LED Security light
Model Number	SL03-35L-T-5CCT
FCC ID	2BNT6-SL01SL02SL03
Antenna Gain	2.04dBi
Operation Frequency	2412 MHz to 2462 MHz
Modulation	IEEE 802.11b: DSSS(CCK, DQPSK, DBPSK) IEEE 802.11g/n: OFDM(64-QAM, 16-QAM, QPSK, BPSK)
Power Supply	120Vac
Max. output power	IEEE 802.11b: 18.7 dBm IEEE 802.11g: 15.73 dBm IEEE 802.11n-HT20: 15.82 dBm

Test Requirement:

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density(mW/cm ²)	Average Time
(A) Limits for Occupational/Control Exposures				
300-1500	--	--	F/300	6
1500-100000	--	--	5	6
(B) Limits for General Population/Uncontrol Exposures				
300-1500	--	--	F/1500	6
1500-100000	--	--	1	30

Friis transmission formula: $P_d = \frac{P_{out} \cdot G}{4 \cdot \pi \cdot R^2}$

Where

P_d = Power density in mW/cm^2

P_{out} = output power to antenna in mW

G = Numeric gain of the antenna relative to isotropic antenna

$\pi = 3.1416$

R = distance between observation point and center of the radiator in cm = 20cm

P_d the limit of MPE, $1\text{mW}/\text{cm}^2$. If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

Measurement Result

Antenna gain: 2.04dBi

WIFI:

Mode	Channel Freq. (MHz)	Measured power (dBm)	Tune-up power (dBm)	Max tune-up power (dBm)	Antenna Gain (Numeric)	Evaluation result (mW/cm ²)	Power density Limits (mW/cm ²)
802.11b	2412	18.44	18±1	19	1.5596	0.025278	1
	2437	18.7	19±1	19	1.5596	0.025278	1
	2462	18.27	18±1	19	1.5596	0.025278	1
802.11g	2412	15.73	16±1	17	1.5596	0.015949	1
	2437	15.17	15±1	16	1.5596	0.012669	1
	2462	15.61	16±1	17	1.5596	0.015949	1
802.11n HT20	2412	15.69	16±1	17	1.5596	0.015949	1
	2437	15.19	15±1	16	1.5596	0.012669	1
	2462	15.82	16±1	17	1.5596	0.015949	1
802.11n HT40	2422	18.44	18±1	19	1.5596	0.025278	1
	2437	18.7	19±1	22	1.5596	0.050436	1
	2452	18.27	18±1	19	1.5596	0.025278	1

Signature:

Shawn Wen

Shawn Wen

Date: 2025-3-10

