## Product specification sheet



Specification 2025002026004 number Availability 2025/2/26

	duto
Customer name	Ai Xi aodi an
Product type	A11 coi l
Top intelligence	TX-DZ43.505.3008-K6. 5-L35 (open double slot)
Customer part	AWIR0038

[ New release, version revision] [This specification contains a total of 3 pages of the catalogue] [RoHS Compliant Parts]

Authorized strength	Exami ne and veri fy	Rati fy
Li Pinghui	/	Ma Xiangping

#### Guangdong Dingzhi Electronic Technology Co., LTD

Factory address: No.1231 Yingbin Avenue, Longmen County, Huizhou City,

Guangdong Province, first floor

Tel: 13147097490

This letter of recognition shall be signed and returned within 30 days after receipt by the customer. If not, it shall be deemed that the production shall follow the standard of this letter of recognition.

[Client approval] Status of recogniti	date: on: full recognition	conditional recog	nition refusal	to
recogni ze				
Ratify	Examine and verify	Recheck	Check up	

expl ai n:

# Product specification sheet

Customer name	Ai Xiaodian	Customer part number	AWIR0038
Top intelligence number	TX-DZ43.505.3008-K6. 5-L35 (open double slot)	Specification number	2025002026004

#### Issue/revision record

di ti on	Availability date	Change content/ca		Approval
01	2025/2/26	New specification re	el ease	Ma Xiangping
Aut	horized strength	Examine and verify	Rati fy	
	Li Pinghui	1	Ma Xiangping	
	Li i i i i gi idi	,	wa Arangping	

### Product specification sheet

		Product	specii	ication sne	eı			
Customer name	Ai	Xi aodi an		Customer part number		AWIR0038		
Top intellige- nce number	TX-DZ43.505.3008-slot)	K6. 5-L35 (ope	en double	Specification number	2025002026004		Editi on	° 1
, outline dim	ensi on			ı	ı		(u ni t: mm )	I
						*	5.3	±0.5
	a						20.5	±1.0
						c	39.0	±1.0
			1	2		0	43.5	±0.5
			(	7111			43.5	±.1.0
		14		*		,	35.0	±3.0
				J		ā	3.0	±2.0
						×	1.8	±0.5
						ı	0.80 ± (magnet ss)	0.2 thickne-
						24P*2	ire diame enameled	ter: 0. 08* wire vindings: 10
						(3) Wh	nether th	e tail line
						(4) The		wrapped with temperature
						(5) Th	should b	nd magnetic be glued in
							oply 3 wh ck of the	ite glue on disc
, Electrical	characteri sti cs	<u> </u>						
Paramete r	Spec ific atio		condi ti on		Measuring and test instruments			
L0		H 100	KHz/1V		■TH1816B	1		
Q	>30 m	in 100	KHz/1V		■TH1816B			
DC R		Ω @	<b>25</b> ℃		■CH-502BC			
, Temperature	cl ass:							
Service tempe- rature	-40℃~ 125℃						1	T
, Material li	st:							
Order num- ber	Name of a part	Material s ficati	speci - on	Supplier	Remarks			
1	Magnetic sh- eet	43.5 * 5.3 open doubl	* 0.8T	PC40 Mangan	ese Zinc	1		
2	Copper line	0. 08*2 2	4P*		Varni shed wi re			

3	High temper- ature tape	8MM	Environmental tape				
4	GI ue	Al ban	Environmental glue tape				
5	Tin	107Н	Qian Dao environmental pro tection tin		0-		
6	GI ue	Yellow glue	Environmental glue				
Authorized strength		Examine and verify		,			
Li Pinghui		1		Ma Xi ang pi ng			