



RF Exposure Evaluation Report

Application No.: DNT2507180451R7700-08942
Applicant: SANSUI Yongmai (SHENZHEN) Technology Co., LTD
Address of Applicant: Room 1202, Block D, Building 1, Lianjian Industrial Park, Shanghenglang Community, Dalang Street, Longhua District, Shenzhen
EUT Description: Bluetooth Headset
Model No.: W12
FCC ID: 2BNUA-W12
Power Supply (Charging Box): Input DC 5V; DC 3.7V From rechargeable lithium-ion battery
Power Supply (Earphone): DC 3.7V From rechargeable lithium-ion battery
Trade Mark: /
Standards: 47 CFR Part 2.1093
FCC KDB 447498 D04 v01
Date of Receipt: 2025/7/18
Date of Test: 2025/7/18 to 2025/7/25
Date of Issue: 2025/7/28
Test Result: **PASS**

Prepared By: Wayne Lin (Testing Engineer)

Reviewed By: Pengfei Chen (Project Engineer)

Approved By: Yeise Chen (Manager)



Note: If there is any objection to the results in this report, please submit a written inquiry to the company within 15 days from the date of receiving the report. The test report is effective only with both signature and specialized stamp, and is issued by the company in accordance with the requirements of the "Conditions of Issuance of Test Reports" printed in the attached page. Unless otherwise stated, the results presented in this report only apply to the samples tested this time. Partial reproduction of this report is not allowed unless approved by the

Dongguan DN Testing Co., Ltd.

Add: No. 1, West Fourth Street, Xingfa South Road, Wusha Community, Chang 'an Town, Dongguan City, Guangdong P.R.China

Web: www.dn-testing.com

Tel: +86-769-88087383

E-mail: service@dn-testing.com



company in writing.

Report Revise Record

Report Version	Revise Time	Issued Date	Valid Version	Notes
V2.0	/	July 28, 2025	Valid	Original Report



Contents

RF EXPOSURE EVALUATION REPORT1

1 GENERAL INFORMATION 4

 1.1 TEST LOCATION4

 1.2 GENERAL DESCRIPTION OF EUT4

 1.3 TEST FACILITY 5

 1.4 MEASUREMENT UNCERTAINTY (95% CONFIDENCE LEVELS, K=2) 5

2 RF EXPOSURE EVALUATION6

 2.1 RF EXPOSURE COMPLIANCE REQUIREMENT 6



1 General Information

1.1 Test Location

Company:	Dongguan DN Testing Co., Ltd
Address:	No. 1, West Fourth Street, South Xinfu Road, Wusha Liwu, Chang 'an Town, Dongguan City, Guangdong P.R.China
Test engineer:	Wayne Lin

1.2 General Description of EUT

Manufacturer:	SANSUI Yongmai (SHENZHEN) Technology Co., LTD
Address of Manufacturer:	Room 1202, Block D, Building 1, Lianjian Industrial Park, Shanghenglang Community, Dalang Street, Longhua District, Shenzhen
Factory:	Hunan Xiangdang Intelligent Technology Co., LTD
Address of Factory:	Honghuayuan Industrial Park, Lufeng Town, Xupu County, Huaihua City, Hunan Province
EUT Description:	Bluetooth Headset
Model No.:	W12
Additional Model(s):	/
Power Supply (Charging Box):	Input DC 5V; DC 3.7V From rechargeable lithium-ion battery
Power Supply (Earphone):	DC 3.7V From rechargeable lithium-ion battery
Trade Mark:	/
Hardware Version:	V1.0
Software Version:	V1.0
Serial number:	PR2507180451R7700
Chip Type:	C1654F
Sample Type:	☒ Portable Device, ☐ Module, ☐ Mobile Device
Antenna Type:	☐ External, ☒ Integrated
Antenna Ports:	☒ Ant 1, ☐ Ant 2, ☐ Ant 3
Antenna Gain:	☒ Provided by applicant 2.7dBi

Note:

*Since the above data and/or information is provided by the client relevant results or conclusions of this report are only made for these data and/or information, DNT is not responsible for the authenticity, integrity and results of the data and information and/or the validity of the conclusion.



1.3 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

Lab A:

• **FCC, USA**

Designation Number: CN1348

• **A2LA (Certificate No. 7050.01)**

DONGGUAN DN TESTING CO., LTD. is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 7050.01.

• **Innovation, Science and Economic Development Canada**

DONGGUAN DN TESTING CO., LTD. EMC Laboratory has been recognized by ISED as an accredited testing laboratory. CAB identifier is CN0149.

IC#: 30755.

1.4 Measurement Uncertainty (95% confidence levels, k=2)

No.	Item	Measurement Uncertainty
1	20dB Emission Bandwidth	$\pm 0.0196\%$
2	Carrier Frequency Separation	$\pm 1.9\%$
3	Number of Hopping Channel	$\pm 1.9\%$
4	Time of Occupancy	$\pm 0.028\%$
5	Max Peak Conducted Output Power	± 0.743 dB
6	Band-edge Spurious Emission	± 1.328 dB
7	Conducted RF Spurious Emission	9KHz-1GHz: ± 0.746 dB 1GHz-26GHz: ± 1.328 dB

No.	Item	Measurement Uncertainty
1	Conduction Emission	± 3.0 dB (150kHz to 30MHz)
2	Radiated Emission	± 4.8 dB (Below 1GHz)
		± 4.8 dB (1GHz to 6GHz)
		± 4.5 dB (6GHz to 18GHz)
		± 5.02 dB (Above 18GHz)



2 RF Exposure Evaluation

2.1 RF Exposure Compliance Requirement

2.1.1 Limits

Human exposure to RF emissions from portable devices (47 CFR §2.1093), as defined by the FCC, must be evaluated with respect to the FCC-adopted limits for SAR. Evaluation of mobile devices, as defined by the FCC, may also be performed with respect to SAR limits, but in such cases it is usually simpler and more cost-effective to evaluate compliance with respect to field strength or power density limits. For certain devices that are designed to be used in both mobile and portable configurations similar to those described in 47 CFR §2.1091(d)(4), such as certain desktop phones and wireless modem modules, compliance for mobile configurations is also satisfied when the same device is evaluated for SAR compliance in portable configurations.

Refer to 47 CFR §2.1093:

A portable device is defined as a transmitting device designed to be used in other than fixed locations and to generally be used in such a way that the RF source's radiating structure(s) is/are within 20 centimeters of the body of the user.

Evaluation of compliance with the exposure limits in § 1.1310 of this chapter, and preparation of an EA if the limits are exceeded, is necessary for portable devices having single RF sources with more than an available maximum time-averaged power of 1 mW, more than the ERP listed in Table 1 to § 1.1307(b)(3)(i)(C), or more than the P_{th} in the following formula, whichever is greater. The following formula shall only be used in conjunction with portable devices not exempt by § 1.1307(b)(3)(i)(C) at distances from 0.5 centimeters to 20 centimeters and frequencies from 0.3 GHz to 6 GHz.



$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases} \quad (\text{B.2})$$

where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right)$$

and f is in GHz, d is the separation distance (cm), and $ERP_{20 \text{ cm}}$ is per Formula (B.1). The example values shown in Table B.2 are for illustration only.

Table B.2—Example Power Thresholds (mW)

Frequency (MHz)	Distance (mm)									
	5	10	15	20	25	30	35	40	45	50
300	39	65	88	110	129	148	166	184	201	217
450	22	44	67	89	112	135	158	180	203	226
835	9	25	44	66	90	116	145	175	207	240
1900	3	12	26	44	66	92	122	157	195	236
2450	3	10	22	38	59	83	111	143	179	219
3600	2	8	18	32	49	71	96	125	158	195
5800	1	6	14	25	40	58	80	106	136	169

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 300 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.



2.1.2 Test Procedure

Software provided by client enabled the EUT to transmit data at lowest, middle and highest channel individually

2.1.3 EUT RF Exposure Evaluation

Left earphone

Mode	Fre (MHz)	Peak Conducted output Power (dBm)	Target power (dBm)	Antenna Gain (dBi)	Max. E.R.P (dBm)	Max. Target power (mW)	SAR Test Exemption Limit (mW)	Distance (mm)
GFSK	2402	-3.78	-3±1	2.7	-1.45	0.716	3	5
	2441	-0.36	0±1	2.7	1.55	1.429	3	5
	2480	0.25	0±1	2.7	1.55	1.429	3	5
$\pi/4$ -DQPSK	2402	-3.26	-3±1	2.7	-1.45	0.716	3	5
	2441	-0.50	0±1	2.7	1.55	1.429	3	5
	2480	-0.07	0±1	2.7	1.55	1.429	3	5
8-DPSK	2402	-2.98	-2±1	2.7	-0.45	0.902	3	5
	2441	-0.14	0±1	2.7	1.55	1.429	3	5
	2480	-0.78	0±1	2.7	1.55	1.429	3	5

Right earphone

Mode	Fre (MHz)	Peak Conducted output Power (dBm)	Target power (dBm)	Antenna Gain (dBi)	Max. E.R.P (dBm)	Max. Target power (mW)	SAR Test Exemption Limit (mW)	Distance (mm)
GFSK	2402	-3.98	-3±1	2.7	-1.45	0.716	3	5
	2441	-0.37	0±1	2.7	1.55	1.429	3	5
	2480	-0.19	0±1	2.7	1.55	1.429	3	5
$\pi/4$ -DQPSK	2402	-3.44	-3±1	2.7	-1.45	0.716	3	5
	2441	-0.36	0±1	2.7	1.55	1.429	3	5
	2480	-0.16	0±1	2.7	1.55	1.429	3	5
8-DPSK	2402	-2.96	-2±1	2.7	-0.45	0.902	3	5
	2441	-0.28	0±1	2.7	1.55	1.429	3	5
	2480	-0.80	0±1	2.7	1.55	1.429	3	5



Note:

1. E.R.P=Conducted output Power+Antenna Gain -2.15.
2. SAR Test Exclusion Thresholds is 3mW for separation distance 5mm. Therefore, SAR test is not required.

The End Report