

FCC §15.247 (i), §2.1091 – RF Exposure

FCC ID: 2BNWI-JS9818AHD-GW4

Applied procedures / limit

According to FCC §15.247(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6

Note: *f* is frequency in MHz

* = Power density limit is applicable at frequencies greater than 100 MHz

Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: *f* = frequency in MHz

* = Plane-wave equivalent power density

MPE PREDICTION

Predication of MPE limit at a given distance, Equation from OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where: S = power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna, R=20cm

Test Result of RF Exposure Evaluation

	Tune up Produce power	Maximum peak output power (dBm)	Output power to antenna (mW)	Antenna Gain (numeric)	Power Density (S) (mW/ cm ²)	Limit (mW / cm ²)	Result
LTE BAND 2	23±1	24	251.188 ₆	0.4508 (-3.46dB _i)	0.0225	1	Pass
LTE BAND 4	22±1	23	199.526 ₂	0.8531 (-0.69dB _i)	0.0339	1	Pass
LTE BAND 5	23±1	24	251.188 ₆	0.7603 (-1.19dB _i)	0.038	0.6	Pass
LTE BAND 12	23±1	24	251.188 ₆	0.7638 (-1.17dB _i)	0.0382	0.5	Pass
LTE BAND 13	23±1	24	251.188 ₆	0.7482 (-1.26dB _i)	0.0374	0.5	Pass
LTE BAND 66	23±1	24	251.188 ₆	0.8531 (-0.69dB _i)	0.0427	1	Pass
LTE BAND 71	23±1	24	251.188 ₆	0.8974 (-0.47dB _i)	0.0449	0.4	Pass
2.4GWIFI	15±1	16	39.8107	0.3926 (-4.06dB _i)	0.0031	1	Pass

$$S=0.0427/1+0.0031/1=0.0458 < 1, \text{ The result is pass}$$