

FCC Appendix RF Test Data for BLE

FCC ID : 2BNXK-P-LFPO1

Company: : Shenzhen Limpet Technology Co., Ltd.

EUT : Wali Smart Pet Feeder With AI Camera

Model Number : P-LFP01

Report No. : CTA25070500601


Reviewed By : Eric Wang

-6dB Bandwidth


Condition	Mode	Frequency (MHz)	Antenna	-6 dB Bandwidth (MHz)	Limit -6 dB Bandwidth (MHz)	Verdict
NVNT	BLE 1M	2402	Ant1	0.659	≥ 0.5	Pass
NVNT	BLE 1M	2440	Ant1	0.658	≥ 0.5	Pass
NVNT	BLE 1M	2480	Ant1	0.667	≥ 0.5	Pass

Test Graphs


-6dB Bandwidth NVNT BLE 1M 2402MHz Ant1



-6dB Bandwidth NVNT BLE 1M 2440MHz Ant1



-6dB Bandwidth NVNT BLE 1M 2480MHz Ant1




Maximum Peak Conducted Output Power


Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Limit (dBm)	Verdict
NVNT	BLE 1M	2402	Ant1	-1.95	30	Pass
NVNT	BLE 1M	2440	Ant1	0.68	30	Pass
NVNT	BLE 1M	2480	Ant1	-0.25	30	Pass

Test Graphs


Power NVNT BLE 1M 2402MHz Ant1



Power NVNT BLE 1M 2440MHz Ant1



Power NVNT BLE 1M 2480MHz Ant1




Maximum Power Spectral Density Level


Condition	Mode	Frequency (MHz)	Antenna	Conducted PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
NVNT	BLE 1M	2402	Ant1	-18.42	8	Pass
NVNT	BLE 1M	2440	Ant1	-15.58	8	Pass
NVNT	BLE 1M	2480	Ant1	-16.5	8	Pass

Test Graphs


PSD NVNT BLE 1M 2402MHz Ant1



PSD NVNT BLE 1M 2440MHz Ant1



PSD NVNT BLE 1M 2480MHz Ant1




Band Edge


Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	BLE 1M	2402	Ant1	-53.76	-20	Pass
NVNT	BLE 1M	2480	Ant1	-55.54	-20	Pass

Test Graphs


Band Edge NVNT BLE 1M 2402MHz Ant1 Ref




Band Edge NVNT BLE 1M 2402MHz Ant1 Emission



Band Edge NVNT BLE 1M 2480MHz Ant1 Ref



Band Edge NVNT BLE 1M 2480MHz Ant1 Emission




Conducted RF Spurious Emission


Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	BLE 1M	2402	Ant1	-52.9	-20	Pass
NVNT	BLE 1M	2440	Ant1	-55.54	-20	Pass
NVNT	BLE 1M	2480	Ant1	-53.57	-20	Pass

Test Graphs


Tx. Spurious NVNT BLE 1M 2402MHz Ant1 Ref




Tx. Spurious NVNT BLE 1M 2402MHz Ant1 Emission




Tx. Spurious NVNT BLE 1M 2440MHz Ant1 Ref




Tx. Spurious NVNT BLE 1M 2440MHz Ant1 Emission



Tx. Spurious NVNT BLE 1M 2480MHz Ant1 Ref



Tx. Spurious NVNT BLE 1M 2480MHz Ant1 Emission




Duty Cycle


Condition	Mode	Frequency (MHz)	Antenna	Duty Cycle (%)	Correction Factor (dB)	1/T (kHz)
NVNT	BLE 1M	2402	Ant1	72	1.43	0.74
NVNT	BLE 1M	2440	Ant1	72.05	1.42	0.74
NVNT	BLE 1M	2480	Ant1	72.03	1.42	0.74

Test Graphs


Duty Cycle NVNT BLE 1M 2402MHz Ant1



Duty Cycle NVNT BLE 1M 2440MHz Ant1



Duty Cycle NVNT BLE 1M 2480MHz Ant1




Restrict Band


Condition	Mode	Frequency (MHz)	Antenna	Spur Freq (MHz)	Power (dBm)	Gain (dBi)	Duty Factor (dB)	E (dBuV/m)	Detector	Limit (dBuV/m)	Verdict
NVNT	BLE 1M	2402	Ant1	2310	-50.11	2	-	47.15	Peak	74	Pass
NVNT	BLE 1M	2402	Ant1	2310	-58.8	2	1.43	39.89	Average	54	Pass
NVNT	BLE 1M	2402	Ant1	2347.056	-48.23	2	-	49.03	Peak	74	Pass
NVNT	BLE 1M	2402	Ant1	2370.672	-58.28	2	1.43	40.41	Average	54	Pass
NVNT	BLE 1M	2402	Ant1	2390	-50.74	2	-	46.52	Peak	74	Pass
NVNT	BLE 1M	2402	Ant1	2390	-58.49	2	1.43	40.2	Average	54	Pass
NVNT	BLE 1M	2480	Ant1	2483.5	-49.61	2	-	47.65	Peak	74	Pass
NVNT	BLE 1M	2480	Ant1	2483.5	-58.01	2	1.42	40.67	Average	54	Pass
NVNT	BLE 1M	2480	Ant1	2485.672	-44.88	2	-	52.38	Peak	74	Pass
NVNT	BLE 1M	2480	Ant1	2483.584	-57.76	2	1.42	40.92	Average	54	Pass
NVNT	BLE 1M	2480	Ant1	2500	-50.42	2	-	46.84	Peak	74	Pass
NVNT	BLE 1M	2480	Ant1	2500	-58.3	2	1.42	40.38	Average	54	Pass

Test Graphs


Restrict Band NVNT BLE 1M 2402MHz Ant1 Peak



Restrict Band NVNT BLE 1M 2402MHz Ant1 Average



Restrict Band NVNT BLE 1M 2480MHz Ant1 Peak



Restrict Band NVNT BLE 1M 2480MHz Ant1 Average

