



# Maximum Permissible Exposure Evaluation

**FCC ID: 2BNXO-S800PRO**

## 1. General Information about EUT

### 1.1 Client Information

<b>Applicant</b>	:	SILICONTEK INTERNATIONAL COMPANY LIMITED
<b>Address</b>	:	FLAT B8., 4/FLOOR, BLOCK 2, CAMEL PAINT BUILDING, 62 HOI YUEN ROAD, KWUN TONG, KOWLOON HONGKONG, CHINA
<b>Manufacturer</b>	:	SILICONTEK INTERNATIONAL COMPANY LIMITED
<b>Address</b>	:	FLAT B8., 4/FLOOR, BLOCK 2, CAMEL PAINT BUILDING, 62 HOI YUEN ROAD, KWUN TONG, KOWLOON HONGKONG, CHINA

### 1.2 General Description of EUT (Equipment Under Test)

<b>EUT Name</b>	:	Bone conduction earphone	
<b>Models No.</b>	:	S800Pro, S800Pro+	
<b>Model Different</b>	:	All of these models are identical in the same PCB, layout and circuit, the only difference is the model name and color appearance.	
<b>Brand Name</b>	:	SilisoundTek	
<b>Sample ID</b>	:	HC-C-202502-0103-01-01	
<b>Product Description</b>	:	Operation Frequency:	Bluetooth: 2402MHz~2480MHz
		Antenna Gain:	2.5dBi Chip Antenna
<b>Power Rating</b>	:	USB Input: DC 5V DC 3.8V 170mAh Rechargeable Li-ion battery	
<b>Software Version</b>	:	S800Pro168-EN-V1	
<b>Hardware Version</b>	:	X16TF V04	
<b>Remark:</b> The above antenna information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications, the laboratory shall not be held responsible.			

**TB-RF-074-1.0**

## SAR Test Exclusion Calculations

1. FCC: According to KDB 447498 D01V06 Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies D01V06.
  - (1) Clause 4.3: General SAR test reduction and exclusion guidance
    - Sub clause 4.31: Standalone SAR test exclusion considerations
      - 1) The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6GHz at test separation distance  $\leq 5$  mm are determined by:
 
$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation, mm})] * [\sqrt{f_{(\text{GHz})}}]$$

$f_{(\text{GHz})} \leq 3.0$  for 1-g SAR

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation, mm})] * [\sqrt{f_{(\text{GHz})}}]$$

$f_{(\text{GHz})} \leq 7.5.0$  for 10-g SAR

### 2. Summary simultaneous transmission for SAR Exclusion

The SAR exemption limits outlined in clause 4.3.2(b) of KDB 447498 D01V06 have been derived based on an approximate SAR value of 0.4 W/kg using half-wave dipole antennas Footnote 1. As such, when simultaneous transmitter SAR evaluations include transmitters that have been exempt from routine SAR evaluation, the SAR must be estimating based on the ratio between the maximum tune-up tolerance limit of the transmitter that has been exempt and the exemption limit at the specific distance and frequency for that transmitter. This ratio must be multiplied by 0.4 W/kg (2.0 W/kg for controlled use and 1.0 W/kg for limb worn devices) in order to calculate the estimated SAR level.

The estimate SAR value is calculated based the following equation:

(maximum power level including tune-up tolerance for transmitter A / maximum power level of exemption at the same frequency and distance) \* 0.4W/kg

- 1)  $[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] * [\sqrt{f_{(\text{GHz})}}/x]$  W/kg, for test separation distances  $\leq 50$  mm;  
where  $x = 7.5$  for 1-g SAR and  $x = 18.75$  for 10-g SAR.
- 2) 0.4 W/kg for 1-g SAR and 1.0 W/kg for 10-g SAR, when the test separation distance is  $> 50$  mm.<sup>37</sup>

The  $[\sum$  of (the highest measured or estimated SAR for each standalone antenna configuration, adjusted for maximum tune-up tolerance) / 1.6 W/kg] + [ $\sum$  of MPE ratios] is  $\leq 1.0$ .

The SAR to peak location separation ratios of all simultaneously transmitting antenna pairs operating in portable device exposure conditions are all  $\leq 0.04$ , and the [ $\sum$  of MPE ratios] is  $\leq 1.0$ .



## 3. Calculation:

Test separation: 5mm						
Bluetooth Mode (GFSK)						
Frequency (GHz)	Conducted Power (dBm)	Turn-up Power Tolerance (dB)	Max power of tune up tolerance (dbm)	Max power of tune up tolerance (mw)	Calculation Value	Threshold Value
2402	1.807	2±1	3	1.995	0.618	3.0
2441	2.446	2±1	3	1.995	0.623	3.0
2480	3.104	3±1	4	2.512	0.791	3.0
Bluetooth Mode ( $\pi/4$ -DQPSK)						
Frequency (GHz)	Conducted Power (dBm)	Turn-up Power Tolerance (dB)	Max power of tune up tolerance (dbm)	Max power of tune up tolerance (mw)	Calculation Value	Threshold Value
2402	2.21	3±1	4	2.512	0.779	3.0
2441	2.791	3±1	4	2.512	0.785	3.0
2480	3.45	3±1	4	2.512	0.791	3.0
Bluetooth Mode (8-DPSK)						
Frequency (GHz)	Conducted Power (dBm)	Turn-up Power Tolerance (dB)	Max power of tune up tolerance (dbm)	Max power of tune up tolerance (mw)	Calculation Value	Threshold Value
2402	2.853	3±1	4	2.512	0.779	3.0
2441	3.485	3±1	4	2.512	0.785	3.0
2480	4.066	4±1	5	3.162	0.996	3.0

## Conclusion:

The measurement results comply with the FCC Limit per 47 CFR 2.1093 for the uncontrolled RF Exposure and SAR Exclusion Threshold per KDB 447498 D01V06.

-----END OF REPORT-----

