

LTE

Data List								
Test Mode	Frequency [MHz]	Reading [dBm]	Level [dBm]	Factor [dB]	Limit [dBm]	Margin [dB]	Pol.	Det
LTE_B2_5M_CH18900	111.5208	-53.08	-50.08	3.00	-13.00	37.08	V	PK
	884.5123	-50.53	-41.94	8.59	-13.00	28.94	H	PK
	1410.2051	-38.57	-34.81	3.76	-13.00	21.81	H	PK
	2352.6763	-52.95	-44.96	7.99	-13.00	31.96	H	PK
	3764.0000	-59.66	-45.12	14.54	-13.00	32.12	H	PK
	5176.4353	-56.70	-38.46	18.24	-13.00	25.46	V	PK
	5646.0000	-61.67	-42.99	18.68	-13.00	29.99	H	PK
	7528.0000	-62.79	-38.99	23.80	-13.00	25.99	V	PK
	9410.0000	-67.24	-43.59	23.65	-13.00	30.59	V	PK
	11292.0000	-68.23	-43.24	24.99	-13.00	30.24	V	PK
	13174.0000	-68.17	-42.08	26.09	-13.00	29.08	V	PK
	15056.0000	-69.19	-41.05	28.14	-13.00	28.05	H	PK
	16938.0000	-69.41	-36.02	33.39	-13.00	23.02	V	PK
LTE_B4_5M_CH20175	110.5503	-67.61	-64.80	2.81	-13.00	51.80	V	PK
	825.7979	-68.35	-63.62	4.73	-13.00	50.62	V	PK
	3468.0000	-54.41	-41.24	13.17	-13.00	28.24	H	PK
	5202.0000	-62.20	-43.99	18.21	-13.00	30.99	H	PK
	6936.0000	-62.14	-40.06	22.08	-13.00	27.06	H	PK
	8670.0000	-64.20	-42.10	22.10	-13.00	29.10	H	PK
	10404.0000	-67.54	-43.04	24.50	-13.00	30.04	H	PK
	12138.0000	-67.81	-42.68	25.13	-13.00	29.68	V	PK
	13872.0000	-68.78	-42.46	26.32	-13.00	29.46	H	PK
	15606.0000	-68.33	-39.01	29.32	-13.00	26.01	H	PK
	17340.0000	-67.76	-33.40	34.36	-13.00	20.40	V	PK
LTE_B12_5M_CH23095	111.0355	-52.64	-49.71	2.93	-13.00	36.71	V	PK
	885.968	-50.82	-42.30	8.52	-13.00	29.30	H	PK
	1418.0000	-50.40	-35.73	14.67	-13.00	22.73	H	PK
	2127.0000	-59.65	-39.51	20.14	-13.00	26.51	V	PK

	2836.0000	-58.45	-36.05	22.40	-13.00	23.05	V	PK
	3545.0000	-60.38	-46.81	13.57	-13.00	33.81	V	PK
	4254.0000	-61.56	-45.72	15.84	-13.00	32.72	H	PK
	4963.0000	-61.71	-45.09	16.62	-13.00	32.09	V	PK
	5672.0000	-61.87	-43.12	18.75	-13.00	30.12	V	PK
	6381.0000	-61.78	-40.82	20.96	-13.00	27.82	H	PK
	7090.0000	-63.18	-41.25	21.93	-13.00	28.25	H	PK
LTE_B66_5M_CH132322	111.0355	-52.42	-49.49	2.93	-13.00	36.49	V	PK
	880.1451	-50.39	-41.60	8.79	-13.00	28.60	H	PK
	2143.5718	-56.20	-36.31	19.89	-13.00	23.31	V	PK
	3494.0000	-56.87	-43.43	13.44	-13.00	30.43	H	PK
	5241.0000	-61.42	-43.00	18.42	-13.00	30.00	H	PK
	6988.0000	-61.75	-40.40	21.35	-13.00	27.40	H	PK
	8735.0000	-66.42	-43.98	22.44	-13.00	30.98	H	PK
	10482.0000	-68.40	-43.29	25.11	-13.00	30.29	V	PK
	12229.0000	-68.56	-43.60	24.96	-13.00	30.60	V	PK
	13976.0000	-68.71	-42.36	26.35	-13.00	29.36	V	PK
	15723.0000	-69.13	-39.04	30.09	-13.00	26.04	V	PK
	17470.0000	-69.39	-34.84	34.55	-13.00	21.84	V	PK

Note:(1)Level=Reading+Factor

(2)Margin=Limit-Level

(3)V=Vertical,H= Horizontal