



Shenzhen Huaxia Testing Technology Co., Ltd.

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Telephone: +86-755-26648640
Fax: +86-755-26648637
Website: www.cqa-cert.com

Report Template Version: V05
Report Template Revision Date: 2021-11-03

RF Exposure Evaluation Report

Report No.: CQASZ20250701775E-03
Applicant: Changsha Angsi E-commerce Co., Ltd.
Address of Applicant: Room 139, Bldg A1, No. 1839 Fenglin 3rd Rd, Leifeng St, Xiangjiang New Dist, Changsha, Hunan 410200 China
Equipment Under Test (EUT):
EUT Name: Diagnostic Tools, GOOLOO OBD, Deepscan
Model No.: DeepScan, DS100, DS200
Test Model No.: DeepScan
Brand Name: 
FCC ID: 2BNZ7-DSCAN
Standards: 47 CFR Part 1.1307
47 CFR Part 1.1310
447498 D04 Interim General RF Exposure Guidance v01
Date of Receipt: 2025-07-31
Date of Test: 2025-07-31 to 2025-08-11
Date of Issue: 2025-8-14
Test Result: PASS*

*In the configuration tested, the EUT complied with the standards specified above

Tested By:

lewis zhou

(Lewis Zhou)

Reviewed By:

Timo Lei

(Timo Lei)

Approved By:

Jack Ai

(Jack Ai)



1 Version

Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20250300543E-03	Rev.01	Initial report	2025-4-15
CQASZ20250701775E-03	Rev.02	Update report	2025-8-14

Note:

This test report (Ref. No.: CQASZ20250701775E-03)

All test data comes from source test reports (Ref. No.: CQASZ20250300543E-03).

Only on the basis of the original report Add EUT Name, the series model No., Brand Name, add Photographs of EUT.

2 Contents

	Page
1 VERSION	2
2 CONTENTS	3
.....	3
3 GENERAL INFORMATION	4
3.1 CLIENT INFORMATION	4
3.2 GENERAL DESCRIPTION OF EUT	4
3.3 GENERAL DESCRIPTION OF BT CLASSIC	4
3.4 GENERAL DESCRIPTION OF BLE	4
4 MPE EVALUATION	6
4.1 RF EXPOSURE COMPLIANCE REQUIREMENT	6
4.1.1 <i>Limits</i>	6
4.1.2 <i>Test Procedure</i>	6
4.1.3 <i>EUT RF Exposure</i>	7

3 General Information

3.1 Client Information

Applicant:	Changsha Angsi E-commerce Co., Ltd.
Address of Applicant:	Room 139, Bldg A1, No. 1839 Fenglin 3rd Rd, Leifeng St, Xiangjiang New Dist, Changsha, Hunan 410200 China
Manufacturer:	Changsha Angsi E-commerce Co., Ltd.
Address of Manufacturer:	Room 139, Bldg A1, No. 1839 Fenglin 3rd Rd, Leifeng St, Xiangjiang New Dist, Changsha, Hunan 410200 China
Factory:	Changsha Angsi E-commerce Co., Ltd.
Address of Factory:	Room 139, Bldg A1, No. 1839 Fenglin 3rd Rd, Leifeng St, Xiangjiang New Dist, Changsha, Hunan 410200 China

3.2 General Description of EUT

Product Name:	Diagnostic Tools, GOOLOO OBD, Deepscan
Model No.:	DeepScan, DS100, DS200
Test Model No.:	DeepScan
Trade Mark:	 GOOLOO ALWAYS GOOD TO GO
Software Version:	DeepScan 1.0
Hardware Version:	TP015_BT_V0_2
EUT Power Supply:	Power supply DC12V

3.3 General Description of BT Classic

Operation Frequency	2402MHz~2480MHz
Bluetooth Version:	Bluetooth Spec 5.0
Modulation Technique:	Frequency Hopping Spread Spectrum(FHSS)
Modulation Type:	GFSK, π/4DQPSK
Number of Channel:	79
Transfer Rate:	1Mbps/2Mbps
Hopping Channel Type:	Adaptive Frequency Hopping systems
Sample Type:	<input checked="" type="checkbox"/> Mobile <input type="checkbox"/> Portable
Antenna Type:	PCB antenna
Antenna Gain:	0.06dBi
Cable loss:	1.0 dB

3.4 General Description of BLE

Operation Frequency	2402MHz~2480MHz
Bluetooth Version:	Bluetooth Spec 5.0
Modulation Type:	GFSK

Number of Channel:	40
Transfer Rate:	1Mbps/2Mbps
Sample Type:	<input checked="" type="checkbox"/> Mobile <input type="checkbox"/> Portable
Antenna Type:	PCB antenna
Antenna Gain:	0.06dBi
Cable loss:	1.0 dB

Note:

Model No.: DeepScan, DS100, DS200.

Their electrical circuit design, layout, components used and internal wiring are identical,
Only the appearance color and the components on the PCBA board are different.

4 MPE Evaluation

4.1 RF Exposure Compliance Requirement

4.1.1 Limits

The table applies to any RF source (i.e., single fixed, mobile, and portable transmitters) and specifies power and distance criteria for each of the five frequency ranges used for the MPE limits. These criteria apply at separation distances from any part of the radiating structure of at least $\lambda/2\pi$. The thresholds are based on the general population MPE limits with a single perfect reflection, outside of the reactive near-field, and in the main beam of the radiator. For mobile devices that are not exempt per Table B.1 [Table 1 of § 1.1307(b)(1)(i)(C)] at distances from 20 cm to 40 cm and in 0.3 GHz to 6 GHz, evaluation of compliance with the exposure limits in § 1.1310 is necessary if the ERP of the device is greater than ERP_{20cm} in Formula (B.1) [repeated from § 2.1091(c)(1) and § 1.1307(b)(1)(i)(B)].

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

If the ERP is not easily obtained, then the available maximum time-averaged power may be used (i.e., without consideration of ERP only if the physical dimensions of the radiating structure(s) do not exceed the electrical length of $\lambda/4$ or if the antenna gain is less than that of a half-wave Dipole).

SAR-based exemptions are constant at separation distances between 20 cm and 40 cm to avoid discontinuities in the threshold when transitioning between SAR-based and MPE-based exemption criteria at 40 cm, considering the importance of reflections.

4.1.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

4.1.3 EUT RF Exposure

1) For BT Classic

Output Power Into Antenna & RF Exposure Evaluation Distance:

Measurement Data

GFSK mode					
Test channel	EIRP (dBm)	ERP (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
				(dBm)	(mW)
Lowest(2402MHz)	-0.91	-3.06	-3±1	-2	0.63
Middle(2441MHz)	0.20	-1.95	-2.0±1	-1	0.79
Highest(2480MHz)	0.60	-1.55	-1.5±1	-0.5	0.89
π/4DQPSK mode					
Test channel	EIRP (dBm)	ERP (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
				(dBm)	(mW)
Lowest(2402MHz)	-0.89	-3.04	-3±1	-2	0.63
Middle(2441MHz)	0.24	-1.91	-2.0±1	-1	0.79
Highest(2480MHz)	1.03	-1.12	-1.0±1	0	1.00

The ERP of this product is less than 3060mW

Note: 1) Refer to report No. CQASZ20250701775E-01 for EUT test Max Conducted Peak Output Power value.

2) EUT's module is more than 20cm away from the human body.

2) For BLE

Output Power Into Antenna & RF Exposure Evaluation Distance:

Measurement Data

GFSK mode(1Mbps)					
Test channel	EIRP (dBm)	ERP (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
				(dBm)	(mW)
Lowest(2402MHz)	-0.89	-3.04	-3±1	-2	0.63
Middle(2440MHz)	0.37	-1.78	-1.5±1	-0.5	0.89
Highest(2480MHz)	0.61	-1.54	-1.5±1	-0.5	0.89
GFSK mode(2Mbps)					
Test channel	EIRP (dBm)	ERP (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
				(dBm)	(mW)
Lowest(2402MHz)	-0.73	-2.88	-3±1	-2	0.63
Middle(2440MHz)	0.49	-1.66	-1.5±1	-0.5	0.89
Highest(2480MHz)	0.76	-1.39	-1.5±1	-0.5	0.89

The ERP of this product is less than 3060mW

Note: 1) Refer to report No. CQASZ20250701775E-01 for EUT test Max Conducted Peak Output Power value.
2) EUT's module is more than 20cm away from the human body.

***** END OF REPORT *****