

TEST REPORT

Reference No. : WTN25D04087672W003
FCC ID : 2BO39-RXVGR01
Applicant : L&S Deutschland GmbH
Address : Daimlerring 34 32289 Roedinghausen, Germany
Manufacturer : Ningbo Technic Lighting Co., Ltd
Address : No.8, CaiYuan Road, Lizhou Street, Yuyao City, Zhejiang Province, China
Product : IR Door Contact Switch
Model(s) : IR Door Contact Switch
Standards : FCC 47CFR Part 2 Subpart J Section 2.1091
Date of Receipt sample : 2025-04-11
Date of Test : 2025-04-14 to 2025-05-06
Date of Issue : 2025-05-06
Test Result : Pass

Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

Prepared By:
Waltek Testing Group Co., Ltd.

Address: No. 77, Houjie Section, Guantai Road, Houjie Town, Dongguan City, Guangdong, China
Tel: +86-769-2267 6998
Fax: +86-769-2267 6828

Compiled by:

Frank Yin

Frank Yin / Project Engineer

Approved by:



Deval Qin / Designated Reviewer

2. Contents

	Page
1. COVER PAGE.....	1
2. CONTENTS.....	2
3. REVISION HISTORY.....	3
4. GENERAL INFORMATION.....	4
4.1. GENERAL DESCRIPTION OF E.U.T.....	4
4.2. DETAILS OF E.U.T.	4
4.3. TEST FACILITY	4
4.4. SUBCONTRACTED	5
4.5. ABNORMALITIES FROM STANDARD CONDITIONS.....	5
5. TEST SUMMARY.....	6
6. RF EXPOSURE.....	7
6.1. REQUIREMENTS	7
6.2. THE PROCEDURES / LIMIT	7
6.3. MPE CALCULATION METHOD.....	8
6.4. RADIO FREQUENCY RADIATION EXPOSURE EVALUATION.....	9

3. Revision History

Test Report No.	Date of Receipt Sample	Date of Test	Date of Issue	Purpose	Comment	Approved
WTN25D04087672W003	2025-04-11	2025-04-14 to 2025-05-06	2025-05-06	Original	-	Valid

4. General Information

4.1. General Description of E.U.T.

Product:	IR Door Contact Switch
Model(s):	IR Door Contact Switch
Model Description:	N/A
Test Sample No.:	1-1/1
Hardware Version:	A01
Software Version:	V1.0.0

4.2. Details of E.U.T.

Frequency Range:	2440MHz
Type of Modulation:	GFSK
Antenna installation:	PCB Antenna
Antenna Gain:	2.76dBi
Note:	#: The antenna gain is provided by the applicant, and the applicant should be responsible for its authenticity, WALTEK lab has not verified the authenticity of its information.
Ratings:	Input voltage: 12/24V DC

4.3. Test Facility

The test facility has a test site registered with the following organizations:

ISED CAB identifier: CN0013. Test Firm Registration No.: 7760A.

Waltek Testing Group Co., Ltd. Has been registered and fully described in a report filed with the Industry Canada. The acceptance letter from the Industry Canada is maintained in our files. Registration number 7760A, October 15, 2016.

FCC Designation No.: CN1201. Test Firm Registration No.: 523476.

Waltek Testing Group Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration number 523476, September 10, 2019.

4.4. Subcontracted

Whether parts of tests for the product have been subcontracted to other labs:

Yes No

If Yes, list the related test items and lab information:

Test Lab: N/A

Lab address: N/A

Test items: N/A

4.5. Abnormalities from Standard Conditions

None.

5. Test Summary

Test Items	Test Requirement	Result
Maximum Permissible Exposure (Exposure of Humans to RF Fields)	FCC Part 2.1091	PASS

6. RF Exposure

Test Requirement: FCC 47CFR Part 2 Subpart J Section 2.1091
 Evaluation Method: FCC 47CFR Part 1 Subpart I Section 1.1310,
 KDB 447498 D01 General RF Exposure Guidance v06

6.1. Requirements

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2 m normally can be maintained between the user and the device.

6.2. The procedures / limit

Table 1 to § 1.1310(e)(1) - Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(i) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*(100)	≤6
3.0-30	1842/f	4.89/f	*(900/f ²)	<6
30-300	61.4	0.163	1	<6
300-1,500			f/300	<6
1,500-100,000			5	<6
(ii) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	<30
1.34-30	824/f	2.19/f	*(180/f ²)	<30
30-300	27.5	0.073	0.2	<30
300-1,500			f/1500	<30
1,500-100,000			1	<30

f = frequency in MHz. * = Plane-wave equivalent power density.

6.3. MPE Calculation Method

$$S = \frac{P \times G}{4 \times \pi \times R^2}$$

S = power density (in appropriate units, e.g. mW/cm²)

P = output power to the antenna (in appropriate units, e.g., mW).

G = power gain of the antenna in the direction of interest relative to an isotropic radiator,
the power gain factor, is normally numeric gain.

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

From the peak EUT RF output power, the minimum mobile separation distance, R=20cm,
as well as the gain of the used antenna, the RF power density can be obtained

6.4. Radio Frequency Radiation Exposure Evaluation

According to ANSI C63.10:2013 clause 9.5

Calculate the EIRP from the radiated field strength in the far field using Equation (22):

$$\text{EIRP} = E_{\text{Meas}} + 20 \log(d_{\text{Meas}}) - 104.7 \quad (22)$$

where

E_{IRP} is the equivalent isotropically radiated power, in dBm
 E_{Meas} is the field strength of the emission at the measurement distance, in dB μ V/m
 d_{Meas} is the measurement distance, in m

NOTE—Because this equation yields the identical result whether the field strength is extrapolated using the default 20 dB/decade of distance extrapolation factor, or the field strength is not extrapolated for distance, this equation can generally be applied directly (with no further correction) to determine EIRP. In some cases, a different distance correction factor may be required; see 9.1.

Frequency(MHz)	E-Field Strength (dB μ V/m)	Measurement Distance (m)	EIRP (dBm)
2440	91.89	3	-3.27

Frequency (MHz)	Antenna Gain (dBi)	Antenna Gain (numeric)	Max Power (dBm)	Max Power (mW)	Power Density (mW/cm ²)	Limit (mW/cm ²)
2440	2.76	1.89	-6.03	0.25	0.000094	1

Note:

1. EIRP (dBm)= Max Power (dBm) + G (dBi).
2. Chose the maximum power to do MPE analysis.

Conclusion:

RF Exposure is FCC compliant.

=====End of Report=====