

## FCC RF Exposure

EUT Description:SENSOR\_ID

ModelNo.:SENSOR\_ID

FCC ID: 2BO4S-EL7001

Equipment type: Portable Device

According to KDB447498 D01 General RF Exposure Guidance v06 Section 4.3.1      Standalone SAR test exclusion considerations: Unless specifically required by the      published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Test Exclusion Threshold      condition(s), listed below, is (are) satisfied. These test exclusion conditions are based on      source-based time-averaged maximum conducted output power of the RF channel      requiring evaluation, adjusted for tune-up tolerance, and the minimum test separation      distance required for the exposure conditions. The minimum test separation distance      defined in 4. 1 f) is determined by the smallest distance from the antenna and radiating      structures or outer surface of the device, according to the host form factor, exposure      conditions and platform requirements, to any part of the body or extremity of a user or      bystander. To qualify for SAR test exclusion, the test separation distances applied must be fully explained and justified, typically in the SAR measurement or SAR analysis report, by the operating configurations and exposure conditions of the transmitter and applicable host platform requirements, according to the required published RF exposure KDB procedures. When no other RF exposure testing or reporting are required, a statement of justification and compliance must be included in the equipment approval, in lieu of the SAR report, to qualify for SAR test exclusion. When required, the device specific conditions described in the other published RF exposure KDB procedures must be satisfied before applying these SAR test exclusion provisions; for example, handheld PTT two-way radios, handsets,      laptops and tablets, etc.

### § 2.1093 Radiofrequency radiation exposure evaluation: portable devices.

c) For frequencies below 100 MHz, the following may be considered for SAR test exclusion (also illustrated in Appendix C):

1) For test separation distances  $> 50$  mm and  $< 200$  mm, the power threshold at the corresponding test separation distance at 100 MHz in step b) is multiplied by

$$[ 1 + \log(100/f(\text{MHz})) ]$$

2) For test separation distances  $\leq 50$  mm, the power threshold determined by the equation in c) 1) for 50 mm and 100 MHz is multiplied by  $\frac{1}{2}$

$$(1) Pb(mW) * [ 1 + \log(100/f(\text{MHz})) ] = 474 \text{mW} * [ 1 + \log(100/f(\text{MHz})) ]$$

$$(2) Pb(mW) * [ 1 + \log(100/f(\text{MHz})) ] * 0.5 = 474 \text{mW} * [ 1 + \log(100/f(\text{MHz})) ] * 0.5 = 237 * [ 1 + \log(100/f(\text{MHz})) ]$$

### Test Procedure:

TX frequency range: 125KHz

Device category: Fixed equipment (Distance:20cm) Max.

Field Strength: 71.13dBuV/m @3m

EIRP=E-104.7+20logD=71.13-104.7+20log3=-24.03dBm

Maximum Conducted Output Power: -24.03dBm

Here,

Frequency(MHz)	Min. Distance (mm)	Max Power (dBm)	Tune-up power (dBm)	Max Power (mW)	Limit (mW)	SAR Test Exclusion
0.125	20	-24.03	-24.03 ± 1	0.004	925	Yes

So a SAR test is not required