

FCC Test Report

Report No. : 1816C50006912501

Applicant : **Fuzhou Nanrobot Information Technology Co., LTD**

Address : **127 Commercial, 1st Floor, Building 45#, Zhonghai Huanyutianxia, No. 1-1, Gaoxin Avenue, Shangjie Town, Minhou County, Fuzhou City, Fujian Province, China**

Product Name : **Electric scooter**

Report Date : **2025-06-12**

Shenzhen Anbotek Compliance Laboratory Limited



Contents

1. General Information.....	5
1.1. Client Information	5
1.2. Description of Device (EUT)	5
1.3. Auxiliary Equipment Used During Test	6
1.4. Description of Test Configuration.....	6
1.5. Description Of Test Setup	7
1.6. Test Equipment List	8
1.7. Measurement Uncertainty	9
1.8. Description of Test Facility	9
1.9. Disclaimer.....	10
2. Summary of Test Results	11
3. Conducted Emission Test	12
3.1. Test Standard and Limit	12
3.2. Test Setup	12
3.3. Test Procedure	12
3.4. Test Data	12
4. Radiated Spurious Emissions and Field Strength of Fundamental.....	15
4.1. Test Standard and Limit	15
4.2. Test Setup	16
4.3. Test Procedure	16
4.4. Test Data	17
5. Frequency Tolerance	23
5.1. Test Requirement.....	23
5.2. Test Setup	23
5.3. Test Procedure	23
5.4. Test Data	23
6. 20dB Occupy Bandwidth Test	24
6.1. Test Standard and Limit	24
6.2. Test Setup	24
6.3. Test Procedure	24
6.4. Test Data	25
7. Antenna Requirement	26
7.1. Test Standard and Requirement.....	26
7.2. Antenna Connected Construction	26
APPENDIX I -- TEST SETUP PHOTOGRAPH	27
APPENDIX II -- EXTERNAL PHOTOGRAPH.....	27
APPENDIX III -- INTERNAL PHOTOGRAPH	27

TEST REPORT

Applicant : Fuzhou Nanrobot Information Technology Co., LTD
Manufacturer : Xiamen Quneng gongjin Trading Co., LTD
Product Name : Electric scooter
Model No. : LS7+
Trade Mark : N/A
Rating(s) : Input: 84V=2A(with DC 72V, 35Ah Battery inside)

Test Standard(s) : 47 CFR Part 15.225

Test Method(s) : ANSI C63.10: 2020

The device described above is tested by Shenzhen Anbotek Compliance Laboratory Limited to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The measurement results are contained in this test report and Shenzhen Anbotek Compliance Laboratory Limited is assumed full of responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT (Equipment Under Test) is technically compliant with the 47 CFR Part 15.225 requirements.

This report applies to above tested sample only and shall not be reproduced in part without written approval of Shenzhen Anbotek Compliance Laboratory Limited.

Date of Receipt 2025-04-09

Date of Test 2025-04-09 to 2025-05-08

Prepared By


(THaidi Huang)

Approved & Authorized Signer


(Kingkong Jin)

Revision History

Report Version	Description	Issued Date
R00	Original Issue.	2025-06-12

1. General Information

1.1. Client Information

Applicant	:	Fuzhou Nanrobot Information Technology Co., LTD
Address	:	127 Commercial, 1st Floor, Building 45#, Zhonghai Huanyutianxia, No. 1-1, Gaoxin Avenue, Shangjie Town, Minhou County, Fuzhou City, Fujian Province, China
Manufacturer	:	Xiamen Quneng gongjin Trading Co., LTD
Address	:	Room B215, No. 31, Xinghu Road, Huli District, Xiamen City, Fujian Province, China
Factory	:	Xiamen Quneng gongjin Trading Co., LTD
Address	:	Room B215, No. 31, Xinghu Road, Huli District, Xiamen City, Fujian Province, China

1.2. Description of Device (EUT)

Product Name	:	Electric scooter
Model No.	:	LS7+
Trade Mark	:	N/A
Test Power Supply	:	AC 120V/60Hz for adapter, DC 72V battery inside
Test Sample No.	:	1-2-1(Normal Sample), 1-2-2(Engineering Sample)
Adapter	:	Model: FY1698402000 Input: 100-240V~, 50/60Hz, 2.5A Output: 84V=2A

RF Specification

Operation Frequency	:	13.56MHz
Number of Channel	:	1 Channel
Modulation Type	:	ASK
Antenna Type	:	PCB Antenna

Remark: 1) All of the RF specification are provided by customer. 2) For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

1.3. Auxiliary Equipment Used During Test

Title	Manufacturer	Model No.	Serial No.
/	/	/	/


1.4. Description of Test Configuration

The engineering test program was provided and the EUT was programmed to be in transmitting mode.


Channel	Freq.(MHz)
01	13.56

1.5. Description Of Test Setup

CE



RE



1.6. Test Equipment List

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	L.I.S.N. Artificial Mains Network	Rohde & Schwarz	ENV216	100055	Sep. 09, 2024	1 Year
2.	Three Phase V- type Artificial Power Network	CYBERTEK	EM5040DT	E215040DT00 1	Jan. 13, 2025	1 Year
3.	EMI Test Receiver	Rohde & Schwarz	ESCI	100627	Jan. 13, 2025	1 Year
4.	EMI Test Receiver	Rohde & Schwarz	ESR26	101481	Jan. 14, 2025	1 Year
5.	MXA Spectrum Analysis	Agilent	N9020A	MY51170037	Sep. 09, 2024	1 Year
6.	EMI Preamplifier	SKET Electronic	LNPA-0118G- 45	SKET-PA-002	Jan. 13, 2025	1 Year
7.	Double Ridged Horn Antenna	SCHWARZBECK	BBHA 9120D	02555	Oct. 16, 2022	3 Year
8.	Bilog Broadband Antenna	Schwarzbeck	VULB9163	345	Oct. 23, 2022	3 Year
9.	Loop Antenna(9K- 30M)	Schwarzbeck	FMZB1519B	00053	Sep. 12, 2024	1 Year
10.	Horn Antenna	A-INFO	LB-180400-KF	J211060628	Jan. 22, 2024	3 Year
11.	Pre-amplifier	SONOMA	310N	186860	Jan. 14, 2025	1 Year
12.	EMI Test Software EZ-EMC	SHURPLE	N/A	N/A	N/A	N/A
13.	MXA Spectrum Analysis	KEYSIGHT	N9020A	MY53280032	Sep. 09, 2024	1 Year
14.	MXG RF Vector Signal Generator	Agilent	N5182A	MY47420647	Jan. 14, 2025	1 Year
15.	Signal Generator	Agilent	E4421B	MY41000743	Feb. 21, 2025	1 Year
16.	DC Power Supply	IVYTECH	IV3605	1804D360510	Sep. 09, 2024	1 Year
17.	Constant Temperature Humidity Chamber	ZHONGJIAN	ZJ-KHWS80B	N/A	Oct. 14, 2024	1 Year
18.	Spectrum Analyzer	Rohde & Schwarz	FSV40-N	102150	May. 04, 2025	1 Year

1.7. Measurement Uncertainty

Parameter	Uncertainty
Conducted emissions (AMN 150kHz~30MHz)	3.2dB
Occupied Bandwidth	925Hz
Frequency tolerance	74.60Hz
Conducted Spurious Emission	1.24dB
Radiated spurious emissions (Below 30MHz)	3.26dB
Radiated spurious emissions (30MHz~1GHz)	Horizontal: 3.70dB; Vertical: 4.42dB
Radiated spurious emissions (above 1GHz)	1G-6GHz: 4.64dB 6G-18GHz: 4.82dB 18G-40GHz: 5.62dB
The measurement uncertainty and decision risk evaluated according to AB/WI-RF-F-032. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	

1.8. Description of Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

FCC-Registration No.: 279531

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No. 279531.

Test Location

Shenzhen Anbotek Compliance Laboratory Limited.

Sogood Industrial Zone Laboratory & 1/F. of Building D, Sogood Science and Technology Park, Sanwei Community, Hangcheng Subdistrict, Bao'an District, Shenzhen, Guangdong, China.

1.9. Disclaimer

1. The test report is invalid if not marked with the signatures of the persons responsible for preparing and approving the test report.
2. The test report is invalid if there is any evidence and/or falsification.
3. The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein.
4. This document may not be altered or revised in any way unless done so by Anbotek and all revisions are duly noted in the revisions section.
5. Content of the test report, in part or in full, cannot be used for publicity and/or promotional purposes without prior written approval from the laboratory.
6. The authenticity of the information provided by the customer is the responsibility of the customer and the laboratory is not responsible for its authenticity.
7. The data in this report will be synchronized with the corresponding national market supervision and management departments and cross-border e-commerce platforms as required by regulatory agencies.

The laboratory is only responsible for the data released by the laboratory, except for the part provided by the applicant.

2. Summary of Test Results

Standard Section	Test Item	Result
15.203	Antenna Requirement	PASS
15.207	Conducted Emission	PASS
15.205/15.209/15.225	Radiated Spurious Emissions and Field Strength of Fundamental	PASS
15.215(c)	20dB Occupied Bandwidth	PASS
15.225(e)	Frequency Tolerance	PASS

Remark: "N/A" is an abbreviation for Not Applicable.


3. Conducted Emission Test

3.1. Test Standard and Limit

Test Standard	FCC Part15 Section 15.207		
Test Limit	Frequency	Maximum RF Line Voltage (dBuV)	
		Quasi-peak Level	Average Level
	150kHz~500kHz	66 ~ 56 *	56 ~ 46 *
	500kHz~5MHz	56	46
	5MHz~30MHz	60	50

Remark: (1) *Decreasing linearly with logarithm of the frequency.
 (2) The lower limit shall apply at the transition frequency.

3.2. Test Setup



3.3. Test Procedure

The EUT system is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to FCC ANSI C63.10: 2020 on Conducted Emission Measurement.

The bandwidth of test receiver (ESCI) set at 9kHz.


The frequency range from 150kHz to 30MHz is checked.

3.4. Test Data

Please to see the following pages.

Conducted Emission Test Data


Test Site: 1# Shielded Room
 Operating Condition: 13.56MHz
 Test Specification: AC 120V/60Hz for adapter
 Comment: Live Line
 Temp.(°C)/Hum.(%RH): 22.1°C/50%RH



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Over Limit (dB)	Detector	Remark
1	0.2580	28.38	17.83	46.21	51.49	-5.28	AVG	
2	0.4300	23.76	17.82	41.58	47.25	-5.67	AVG	
3	0.4340	32.43	17.82	50.25	57.18	-6.93	QP	
4	0.6060	31.48	17.86	49.34	56.00	-6.66	QP	
5	0.8180	31.90	17.86	49.76	56.00	-6.24	QP	
6	0.9900	21.02	17.85	38.87	46.00	-7.13	AVG	
7	1.1539	31.26	17.85	49.11	56.00	-6.89	QP	
8	1.1620	22.36	17.85	40.21	46.00	-5.79	AVG	
9	1.3340	22.28	17.84	40.12	46.00	-5.88	AVG	
10	1.4940	22.48	17.84	40.32	46.00	-5.68	AVG	
11	1.8980	31.68	17.83	49.51	56.00	-6.49	QP	
12	2.4660	32.76	17.83	50.59	56.00	-5.41	QP	

Conducted Emission Test Data

Test Site: 1# Shielded Room
 Operating Condition: 13.56MHz
 Test Specification: AC 120V/60Hz for adapter
 Comment: Neutral Line
 Temp.(°C)/Hum.(%RH): 22.1°C/50%RH



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Over Limit (dB)	Detector	Remark
1	0.2561	35.90	17.84	53.74	61.55	-7.81	QP	
2	0.6060	23.32	17.87	41.19	46.00	-4.81	AVG	
3	0.6460	24.59	17.87	42.46	46.00	-3.54	AVG	
4	0.8180	28.94	17.87	46.81	56.00	-9.19	QP	
5	0.9340	28.99	17.86	46.85	56.00	-9.15	QP	
6	0.9940	29.88	17.86	47.74	56.00	-8.26	QP	
7	1.1620	30.95	17.86	48.81	56.00	-7.19	QP	
8	1.1620	23.94	17.86	41.80	46.00	-4.20	AVG	
9	1.3340	32.24	17.86	50.10	56.00	-5.90	QP	
10	1.4980	22.89	17.85	40.74	46.00	-5.26	AVG	
11	2.2940	22.60	17.85	40.45	46.00	-5.55	AVG	
12	3.2540	22.59	17.85	40.44	46.00	-5.56	AVG	

4. Radiated Spurious Emissions and Field Strength of Fundamental

4.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.205, 15.209 and 15.225				
Test Limit	Frequency (MHz)	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
	0.009MHz~0.490MHz	2400/F(kHz)	-	Quasi-peak	300
	0.490MHz~1.705MHz	24000/F(kHz)	-	Quasi-peak	30
	1.705MHz~30MHz	30	-	Quasi-peak	30
	30MHz~88MHz	100	40.0	Quasi-peak	3
	88MHz~216MHz	150	43.5	Quasi-peak	3
	216MHz~960MHz	200	46.0	Quasi-peak	3
	960MHz~1000MHz	500	54.0	Quasi-peak	3
	Above 1000MHz	500	54.0	Average	3
		-	74.0	Peak	3

Remark:

(1)The lower limit shall apply at the transition frequency.

(2) 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.

(3) According to §15.209, the frequency bands 9-90 kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.

- (a) The field strength of any emissions within the band 13.553–13.567 MHz shall not exceed 15,848 microvolts/meter at 30 meters.
- (b) Within the bands 13.410–13.553 MHz and 13.567–13.710 MHz, the field strength of any emissions shall not exceed 334 microvolts/meter at 30 meters.
- (c) Within the bands 13.110–13.410 MHz and 13.710–14.010 MHz the field strength of any emissions shall not exceed 106 microvolts/meter at 30 meters.
- (d) The field strength of any emissions appearing outside of the 13.110–14.010 MHz band shall not exceed the general radiated emission limits in §15.209.

Note:

- (1) The tighter limit shall apply at the boundary between two frequency range.
- (2) Limitation expressed in dBuV/m is calculated by $20\log$ Emission Level (uV/m).
- (3) If measurement is made at 3m distance, then F.S Limitation at 3m distance is adjusted by using the formula of $Ld1 = Ld2 * (d2/d1)^2$.

Example:

F.S Limit at 30m distance is 30uV/m, then F.S Limitation at 3m distance is adjusted as

$$Ld1 = L1 = 30\mu V/m * (10)^2 = 100 * 30 \mu V/m$$

4.2. Test Setup




Figure 1. Below 30MHz




Figure 2. 30MHz to 1GHz

4.3. Test Procedure

For below 1GHz: The EUT is placed on a turntable, which is 12mm above the ground plane.

The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT is set 3 meters away from the receiving antenna which is mounted on a antenna tower. The antenna can be moved up and down from 1 to 4 meters to find out the maximum emission level. Rotated the EUT through three orthogonal axes to determine the maximum emissions, both horizontal and vertical polarization of the antenna are set on test. The EUT is tested in 9*6*6 Chamber. The device is evaluated in xyz orientation.

For 9kHz to 150kHz, Set the spectrum analyzer as:

RBW = 200Hz, VBW =1kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For 150kHz to 30MHz, Set the spectrum analyzer as:

RBW = 9KHz, VBW =30kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For 30MHz to 1000MHz, Set the spectrum analyzer as:

RBW = 100kHz, VBW =300kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.


4.4. Test Data

PASS

During the test, Pre-scan all kind of the place mode (coplane, coaxial), and found the coplane is the worst case.

Test Results (9KHz~0.15MHz)


Test Mode: 13.56MHz
 Power Source: DC 72V battery inside
 Polarization: Coplane
 Temp.(°C)/Hum.(%RH): 24.4°C/47%RH



No.	Freq. (MHz)	Reading (dBuV)	Factor ()	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Remark
1	0.0111	-13.90	20.07	6.17	126.50	-120.33	AV	
2	0.0185	-17.85	20.25	2.40	122.09	-119.69	AV	
3	0.0382	-19.23	20.43	1.20	115.83	-114.63	AV	
4	0.0649	-19.50	20.38	0.88	111.25	-110.37	AV	
5	0.1000	-13.69	20.29	6.60	107.52	-100.92	QP	
6	0.1204	-19.01	20.34	1.33	105.92	-104.59	AV	

Test Results (0.15MHz~30MHz)


Test Mode: 13.56MHz
 Power Source: DC 72V battery inside
 Polarization: Coplane
 Temp.(°C)/Hum.(%RH): 24.4°C/47%RH
 Frequency



No.	Freq. (MHz)	Reading (dBuV)	Factor ()	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Remark
1	0.1894	-5.03	20.32	15.29	102.01	-86.72	AV	
2	0.5701	-6.25	20.28	14.03	72.49	-58.46	QP	
3	1.2892	-1.38	20.26	18.88	65.42	-46.54	QP	
4	2.4090	-7.52	20.29	12.77	69.50	-56.73	QP	
5	3.8399	-13.64	20.36	6.72	69.50	-62.78	QP	
6	13.5600	25.40	20.53	45.93	69.50	-23.57	QP	

Test Results (30~1000MHz)


Test Mode: 13.56MHz
 Power Source: DC 72V battery inside
 Polarization: Horizontal
 Temp.(°C)/Hum.(%RH): 24.4°C/47%RH



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Remark
1	47.1599	51.22	-16.92	34.30	40.00	-5.70	QP	
2	67.6751	56.49	-21.26	35.23	40.00	-4.77	QP	
3	87.7248	56.17	-20.57	35.60	40.00	-4.40	QP	
4	135.5062	59.91	-22.66	37.25	43.50	-6.25	QP	
5	162.6106	60.18	-22.18	38.00	43.50	-5.50	QP	
6	189.7384	59.49	-20.71	38.78	43.50	-4.72	QP	


Test Results (30~1000MHz)

Test Mode: 13.56MHz
 Power Source: DC 72V battery inside
 Polarization: Vertical
 Temp.(°C)/Hum.(%RH): 24.4 °C/47%RH



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Remark
1	31.6202	52.67	-19.55	33.12	40.00	-6.88	QP	
2	46.9948	53.79	-16.89	36.90	40.00	-3.10	QP	
3	54.0711	52.69	-17.64	35.05	40.00	-4.95	QP	
4	67.9129	53.57	-21.36	32.21	40.00	-7.79	QP	
5	89.2764	58.75	-19.90	38.85	43.50	-4.65	QP	
6	154.2786	55.36	-22.29	33.07	43.50	-10.43	QP	

Test Results (Inband)




5. Frequency Tolerance

5.1. Test Requirement

Test Standard	FCC Part15 C Section 15.225(e)
Test Limit	$\pm 0.01\%$ (100ppm)

5.2. Test Setup



5.3. Test Procedure

Let the EUT works on temperature variation of -20 degrees to + 50 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.

5.4. Test Data

Temperature:	25.3 °C	Humidity:	48 %	Atmospheric Pressure:	101 kPa
--------------	---------	-----------	------	-----------------------	---------


Voltage (VDC)	Temperature (°C)	Frequency Measured (MHz)	Test data (ppm)	Limit (ppm)	Verdict
72.0	-20	13.560177	13.05	± 100	PASS
	+20	13.560164	12.08	± 100	PASS
	+50	13.560155	11.46	± 100	PASS
61.2	+20	13.560178	13.10	± 100	PASS
82.8	+20	13.560169	12.43	± 100	PASS

6. 20dB Occupy Bandwidth Test

6.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.215(c)
Test Limit	N/A

6.2. Test Setup




6.3. Test Procedure

The bandwidth of the fundamental frequency was measured by spectrum analyzer with 300Hz RBW and $VBW \geq 3 \times RBW$. The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.

6.4. Test Data

Temperature:	25.3 °C	Humidity:	48 %	Atmospheric Pressure:	101 kPa
--------------	---------	-----------	------	-----------------------	---------

Freq.(MHz)	Bandwidth (kHz)	Results
13.56	0.689	PASS



Note: The measured signal is Cw-like, adjusting the RBW per C63.10 would not be practical since measurement bandwidth will always follow the RBW. The RBW is set to 300Hz to perform the occupied bandwidth test.

7. Antenna Requirement

7.1. Test Standard and Requirement

Test Standard	FCC Part15 Section 15.203
Requirement	1) 15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

7.2. Antenna Connected Construction

The antenna is a PCB Antenna which permanently attached. It complies with the standard requirement.

APPENDIX I -- TEST SETUP PHOTOGRAPH

Please refer to separated files Appendix I -- Test Setup Photograph_RF

APPENDIX II -- EXTERNAL PHOTOGRAPH

Please refer to separated files Appendix II -- External Photograph

APPENDIX III -- INTERNAL PHOTOGRAPH

Please refer to separated files Appendix III -- Internal Photograph

----- End of Report -----