



EMC TEST REPORT

Product Name: Handheld GPS

FCC ID: 2BOAT-A8

Trade mark: NiesahYan

Model No.: A8, A6, ZL180, ZL190plus, EM90, ZL166, U9, U8, S9

S/N: /

Report No.: CTB25030401601E02

Applicant: Hefei Zhulindianzikeji Co., Ltd.

Address: Hefei Yaohai District Linquan Road Orange County Wanlv Park H5A Building
605, Hefei, Anhui, China

Manufacturer: Hefei Zhulindianzikeji Co., Ltd.

Address: Hefei Yaohai District Linquan Road Orange County Wanlv Park H5A Building
605, Hefei, Anhui, China

Prepared by: Shenzhen CTB Testing Technology Co., Ltd.

Address: 1&2/F., Building A, No.26, Xinhe Road, Xinqiao, Xinqiao Street, Bao'an District,
Shenzhen, Guangdong, China

Date of Receipt: Mar. 04, 2025

Date of Test(s): Mar. 04, 2025 ~ Mar. 07, 2025

Date of Issue: Mar. 07, 2025

Test Standard(s): CFR47, FCC Part 15 Subpart B, ANSI C63.4: 2014

Test Result: Pass

Compiled by:

Reviewed by:

Approved by:



Michael Niu

Bin Mei

Rita Xiao

In the configuration tested, the EUT complied with the standards specified above.

Note: If there is any objection to the inspection results in this report, please submit a written report to the company within 15 days from the date of receiving the report. The test report is effective only with both signature and specialized stamp. This result(s) shown in this report refer only to the sample(s) tested. Without written approval of Shenzhen CTB Testing Technology Co., Ltd. this report can't be reproduced except in full. The tested sample(s) and the sample information are provided by the client. "★" indicates the testing items were fulfilled by subcontracted lab. "※" indicates the items are not in CNAS accreditation scope.

Table of Contents

1.	Description of version	3
2.	Test summary.....	4
3.	Measurement uncertainty	5
4.	General information.....	6
4.1.	Description of EUT	6
4.2.	Description of accessory device	6
4.3.	Test conditions	6
4.4.	Block diagram of EUT configuration	6
4.5.	Operating condition of EUT	6
5.	List of Test and Measurement Instruments	7
6.	Conducted Emission	9
6.1.	Limit.....	9
6.2.	Test setup	9
6.3.	EMI test receiver setup	9
6.4.	Test procedure	9
6.5.	Test results	10
7.	Radiated emissions.....	12
7.1.	Limit.....	12
7.2.	Test setup	12
7.3.	EMI test receiver setup and spectrum analyzer setup	13
7.4.	Test procedure	13
7.5.	Corrected Amplitude & Margin Calculation	13
7.6.	Test results	14
8.	Photographs of test setup	16

1. Description of version

Report No.	Issue Date	Description	Approved
CTB25030401601E02	Mar. 07, 2025	Original	Valid

2. Test summary

Test procedures according to the technical standards:

Standard	Test Item	Test Result
§15.107	Conducted Emission	PASS
§15.109	Radiated Emission	PASS

3. Measurement uncertainty

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %

Test Item	Frequency	Expanded Uncertainty (U_{Lab})
Conducted Emission	150 kHz to 30 MHz	± 3.1 dB
Radiated Emission	30 MHz to 1000 MHz	± 4.1 dB
Radiated Emission	1000 MHz to 6000 MHz	± 4.8 dB

4. General information

4.1. Description of EUT

Product name	Handheld GPS
Trade mark	NiesahYan
Model No.	A8
Serial Model No.	A6, ZL180, ZL190plus, EM90, ZL166, U9, U8, S9
Model Difference	All the model are the same circuit and RF module, only the model names are different. Test sample model: A8
Configuration	☒ Table-top ☐ Floor-standing
The highest frequency of the internal sources of the EUT	☐ below 1.705 MHz, the measurement shall only be made up to 30 MHz. ☒ between 1.705 MHz and 108 MHz, the measurement shall only be made up to 1 GHz. ☐ between 108 MHz and 500 MHz, the measurement shall only be made up to 2 GHz. ☐ between 500 MHz and 1 GHz, the measurement shall only be made up to 5 GHz. ☐ above 1 GHz, the measurement shall be made up to 5th harmonic of the highest frequency or 40 GHz, whichever is lower.

Note: The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or the User's Manual.


4.2. Description of accessory device

No.	Device Type	Brand	Model	Specification	Note
1.	ADAPTER	JHC	JHC-A248050100	/	EUT

4.3. Test conditions

Temperature: 15-25°C
 Relative Humidity: 30-60 %
 Atmospheric pressure: 800hPa-1060hPa

4.4. Block diagram of EUT configuration



4.5. Operating condition of EUT

Operating condition	Mode 1	Working	Test Voltage	/
Note: This test covers all possible operating modes of the device, only the worst data are list in report. The worst data are shows (*) is the nearest standard limit which were recorded in this report.				

5. List of Test and Measurement Instruments

FCC test lab designation number: CN1276

Continuous disturbance						
No.	Equipment	Manufacturer	Model No.	Serial No.	Firmware version	Calibrated until
1	843 Shield Room	C/ R/ T	843	/	/	2027/6/21
2	AMN	ROHDE&SCHWARZ	ESH3-Z5	831551852	/	2025/6/30
3	Pulse limiter	ROHDE&SCHWARZ	ESH3Z2	357881052	/	2025/6/28
4	EMI TEST RECEIVER	ROHDE&SCHWARZ	ESCI	100428	V4.42.SP3	2025/6/30
5	Coaxial cable	ZDECL	Z302S	18091904	/	2025/6/30
6	ISN	Schwarzbeck	NTFM8158	183	/	2025/6/30
7	Voltage sensor	Schwarzbeck	TK 9420	01189	/	2025/10/25
8	EZ-EMC	Frad	EMC-con3A1.1	/	/	/
9	Current Probe	FCC	F-52B	199453	/	2025/5/27
10	Communication test set	R&S	CMW500	108058	B.19.07 (E1962B)	2025/6/28
11	Communication test set	Agilent	E5515C	MY50102567	V3.5.80	2025/6/28

Radiated emission(No.2 Chamber)						
No.	Equipment	Manufacturer	Model No.	Serial No.	Firmware version	Calibrated until
1	966 Chamber	C/ R/ T	966	/	/	2026/11/14
2	Double Ridged Broadband Horn Antenna	Schwarzbeck	BBHA 9120 D	01911	/	2026/7/07
3	Broadband Antenna	Schwarzbeck	VULB 9168	1471	/	2025/7/06
4	Amplifier	Agilent	8449B	3008A01838	/	2025/6/30
5	Preamplifier	Schwarzbeck	BBV 9743 B	00500	/	2025/5/23
6	EMI TEST RECEIVER	R&S	ESCI7	100861	/	2025/10/25
7	Spectrum Analyzer	KEYSIGHT	N9020A	MY51289897	A.14.16	2025/6/28
8	EMI test software	Farad	EZ-EMC	/	Ver. FARAD-3A1+	/
9	Coaxial cable	Rosenberg	8m	/	/	2025/10/25
10	Coaxial cable	Times	2m	/	/	2025/10/25
11	Coaxial cable	Times	2m	/	/	2025/10/25
12	Coaxial cable	Times	1m	/	/	2025/10/25
13	loop antenna	Schwarzbeck	FMZB 1519B	1519B-224	/	2025/6/29
14	Communication test set	R&S	CMW500	108058	B.19.07 (E1962B)	2025/6/28

15	Communication test set	Agilent	E5515C	MY50102567	V3.5.80	2025/6/28
----	------------------------	---------	--------	------------	---------	-----------

6. Conducted Emission

6.1. Limit

Except for Class A devices:


Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

Note: Decreases with the logarithm of the frequency.

For Class A devices:

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	79	66
0.5-30	73	60

6.2. Test setup



Note: 1.Support units were connected to second LISN.
2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

The setup of EUT is according with ANSI C63.4 measurement procedure. Specification used with FCC Part 15 limits.

6.3. EMI test receiver setup


Frequency Range	9kHz-30MHz
Resolution Bandwidth	200Hz (9kHz-150kHz) 9kHz (150kHz-30MHz)

6.4. Test procedure

1. Measurement was performed in shielded room, and instruments used were followed clause 4 of ANSI C63.4.
2. Detailed test procedure was following clause 7 of ANSI C63.4.
3. Frequency range 150kHz – 30MHz was checked and EMI receiver measurement bandwidth was set to 9 kHz.

6.5. Test results


Temperature:	23°C	Relative Humidity:	54 %
Pressure:	101kPa	Phase :	Line
Test Voltage :	DC 5V	Test Mode:	Mode 1



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	
		MHz	Level	Factor	ment			Detector
			dBuV	dB	dBuV	dBuV	dB	
1		0.1620	40.52	10.85	51.37	65.36	-13.99	QP
2		0.1620	22.56	10.85	33.41	55.36	-21.95	AVG
3		0.6140	36.73	10.63	47.36	56.00	-8.64	QP
4		0.6140	25.18	10.63	35.81	46.00	-10.19	AVG
5	*	0.9300	41.66	10.90	52.56	56.00	-3.44	QP
6		0.9300	19.11	10.90	30.01	46.00	-15.99	AVG
7		1.8340	30.36	11.48	41.84	56.00	-14.16	QP
8		1.8340	16.00	11.48	27.48	46.00	-18.52	AVG
9		2.8380	31.95	11.76	43.71	56.00	-12.29	QP
10		2.8380	13.35	11.76	25.11	46.00	-20.89	AVG
11		4.9300	27.98	12.22	40.20	56.00	-15.80	QP
12		4.9300	14.55	12.22	26.77	46.00	-19.23	AVG

Note: Result=Reading + Factor
Over Limit=Result - Limit

Temperature:	23°C	Relative Humidity:	54 %
Pressure:	101kPa	Phase :	Neutral
Test Voltage :	DC 5V	Test Mode:	Mode 1



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	
		MHz	Level	Factor	ment			Detector
			dBuV	dB	dBuV	dBuV	dB	
1		0.1539	38.13	10.88	49.01	65.79	-16.78	QP
2		0.1539	21.47	10.88	32.35	55.79	-23.44	AVG
3		0.6300	37.42	10.64	48.06	56.00	-7.94	QP
4		0.6300	19.55	10.64	30.19	46.00	-15.81	AVG
5	*	0.9380	37.97	10.90	48.87	56.00	-7.13	QP
6		0.9380	18.29	10.90	29.19	46.00	-16.81	AVG
7		1.6300	30.46	11.35	41.81	56.00	-14.19	QP
8		1.6300	15.91	11.35	27.26	46.00	-18.74	AVG
9		2.5420	29.94	11.70	41.64	56.00	-14.36	QP
10		2.5420	15.87	11.70	27.57	46.00	-18.43	AVG
11		3.5220	29.01	11.91	40.92	56.00	-15.08	QP
12		3.5220	15.48	11.91	27.39	46.00	-18.61	AVG

Note: Result=Reading + Factor

Over Limit=Result – Limit

7. Radiated emissions

7.1. Limit

Except for Class A devices (at 3m):


Frequency of emission (MHz)	Field strength (microvolts/meter)	
	(microvolts/meter)	(dB μ V/m)
30-88	100	40
88-216	150	43.5
216-960	200	46
Above 960	500	54

For Class A devices (at 10m):


Frequency of emission (MHz)	Field strength (microvolts/meter)	
	(microvolts/meter)	(dB μ V/m)
30-88	90	39
88-216	150	43.5
216-960	210	46.4
Above 960	300	49.5

7.2. Test setup

Radiated Emission Test Set-Up Frequency Below 1 GHz



Radiated Emission Test Set-Up Frequency Above 1GHz



The radiated tests were performed in 3 meter Chamber test site, using the setup accordance with the ANSI C63.4:2014.

7.3. EMI test receiver setup and spectrum analyzer setup

During the radiated emission test, the EMI test receiver and Spectrum Analyzer were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30MHz-1000MHz	100kHz	300kHz	120kHz	QP
Above 1GHz	1MHz	3MHz	/	PK
	1MHz	10Hz	/	AVG

7.4. Test procedure

1. The measurement was performed in a semi-anechoic chamber, and instruments used were followed clause 4 of ANSI C63.4
2. Detailed test procedure was following clause 8 of ANSI C63.4.

7.5. Corrected Amplitude & Margin Calculation

1. The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:


$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

2. The “Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

7.6. Test results


Temperature:	23°C	Relative Humidity:	54 %
Pressure:	101kPa	Polarization :	Horizontal
Test Voltage :	DC 5V	Test Mode:	Mode 1



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	93.1131	46.66	-18.17	28.49	43.50	-15.01	QP
2	186.4408	45.79	-15.64	30.15	43.50	-13.35	QP
3 !	266.6090	54.53	-14.28	40.25	46.00	-5.75	QP
4 *	293.0842	55.86	-13.62	42.24	46.00	-3.76	QP
5	560.6928	34.56	-7.00	27.56	46.00	-18.44	QP
6	935.5463	35.04	-0.90	34.14	46.00	-11.86	QP

Note: Result=Reading+Factor
Over Limit=Result-Limit

Temperature:	23°C	Relative Humidity:	54 %
Pressure:	101kPa	Polarization :	Vertical
Test Voltage :	DC 5V	Test Mode:	Mode 1



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	31.9545	47.46	-13.77	33.69	40.00	-6.31	QP
2	80.0805	48.10	-18.02	30.08	40.00	-9.92	QP
3	133.1510	50.71	-14.47	36.24	43.50	-7.26	QP
4	213.7634	49.87	-16.47	33.40	43.50	-10.10	QP
5	293.0842	49.08	-13.62	35.46	46.00	-10.54	QP
6 *	560.6928	47.91	-7.00	40.91	46.00	-5.09	QP

Note: Result=Reading+Factor
Over Limit=Result-Limit

8. Photographs of test setup

RE



CE



End of report