



MPE TEST REPORT

Applicant Hangzhou Zhaotong
Microelectronics Co., Ltd.

FCC ID 2BOBE-ZT9612UV10

Product ZT9612UV10

Brand ZTOP

Model ZT9612UV10

Report No. R2412A1668-M1V1

Issue Date April 22, 2025

Eurofins TA Technology (Shanghai) Co., Ltd. tested the above equipment in accordance with the requirements in **FCC 47 CFR Part 1 1.1310**. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Prepared by: Wei Fangying

Approved by: Xu Kai

Eurofins TA Technology (Shanghai) Co., Ltd.

*Building 3, No.145, Jintang Rd, Pudong Shanghai, P.R.China
TEL: +86-021-50791141/2/3
FAX: +86-021-50791141/2/3-8000*

Table of Contents

1	Test Laboratory	4
1.1	Notes of the Test Report.....	4
1.2	Test Facility.....	4
1.3	Testing Location.....	4
1.4	Laboratory Environment	4
2	Description of Equipment Under Test	5
3	Maximum Output Power (Measured) and Antenna Gain.....	6
4	MPE Limit.....	7
5	RF Exposure Evaluation Result.....	9
	ANNEX A: The EUT Appearance	10

Version	Revision Description	Issue Date
Rev.0	Initial issue of report.	March 25, 2025
Rev.1	Updated information.	April 22, 2025

Note: This revised report (Report No.: R2412A1668-M1V1) supersedes and replaces the previously issued report (Report No.: R2412A1668-M1). Please discard or destroy the previously issued report and dispose of it accordingly.

1 Test Laboratory

1.1 Notes of the Test Report

This report shall not be reproduced in full or partial, without the written approval of **Eurofins TA Technology (Shanghai) Co., Ltd.** The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. Measurement Uncertainties were not taken into account and are published for informational purposes only. This report is written to support regulatory compliance of the applicable standards stated above.

1.2 Test Facility

FCC (Designation number: CN1179, Test Firm Registration Number: 446626)

Eurofins TA Technology (Shanghai) Co., Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform measurements.

1.3 Testing Location

Company: Eurofins TA Technology (Shanghai) Co., Ltd.
Address: Building 3, No.145, Jintang Rd, Pudong Shanghai, P.R.China
City: Shanghai
Post code: 201201
Country: P. R. China
Contact: Xu Kai
Telephone: +86-021-50791141/2/3
Fax: +86-021-50791141/2/3-8000
Website: <https://www.eurofins.com/electrical-and-electronics>
E-mail: Kain.Xu@cpt.eurofinscn.com

1.4 Laboratory Environment

Temperature	Min. = 18°C, Max. = 25°C
Relative humidity	Min. = 20%, Max. = 80%
Ground system resistance	< 0.5 Ω
Ambient noise is checked and found very low and in compliance with requirement of standards. Reflection of surrounding objects is minimized and in compliance with requirement of standards.	

2 Description of Equipment Under Test

Client Information

Applicant	Hangzhou Zhaotong Microelectronics Co., Ltd.
Applicant address	Room 113-11, Building D, Integrated Circuit Design Industrial Park, No. 858, Jianshe 2nd Road, Xiaoshan Economic and Technological Development Zone, Xiaoshan District, Hangzhou City, Zhejiang Province
Manufacturer	Hangzhou Zhaotong Microelectronics Co., Ltd.
Manufacturer address	Room 113-11, Building D, Integrated Circuit Design Industrial Park, No. 858, Jianshe 2nd Road, Xiaoshan Economic and Technological Development Zone, Xiaoshan District, Hangzhou City, Zhejiang Province

General Technologies

EUT Description						
Model	ZT9612UV10					
Lab internal SN	R2412A1668/S01					
Hardware Version	V1.0					
Software Version	C01B190					
Frequency	Band	TX (MHz)	RX (MHz)			
	Bluetooth	2400 ~ 2483.5	2400 ~ 2483.5			
	Wi-Fi 2.4GHz	2400 ~ 2483.5	2400 ~ 2483.5			
	Wi-Fi 5GHz (U-NII-1)	5150 ~ 5250	5150 ~ 5250			
	Wi-Fi 5GHz (U-NII-2A)	5250 ~ 5350	5250 ~ 5350			
	Wi-Fi 5GHz (U-NII-2C)	5470 ~ 5725	5470 ~ 5725			
	Wi-Fi 5GHz (U-NII-3)	5725 ~ 5850	5725 ~ 5850			
Date of Testing	December 2, 2024 ~ March 21, 2025					
Date of Sample Received	December 2, 2024					
Note:						
1. The EUT is sent from the applicant to Eurofins TA and the information of the EUT is declared by the applicant.						
2. All indications of Pass/Fail in this report are opinions expressed by Eurofins TA Technology (Shanghai) Co., Ltd. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only.						

3 Maximum Output Power (Measured) and Antenna Gain

The numeric gain (G) of the antenna with a gain specified in dB is determined by

Numeric gain (G)= $10^{(antenna\ gain/10)}$

Band	Maximum Output Power		Antenna Gain (dBi)	Numeric Gain
	(dBm)	(mW)		
Wi-Fi 2.4GHz	20.23	105.439	4.44	2.780
Wi-Fi 5GHz	20.58	114.288	5.62	3.648
Bluetooth	19.11	81.470	4.44	2.780
Bluetooth (Low Energy)	19.88	97.275	4.44	2.780

4 MPE Limit

According to section 1.1310 of FCC 47 CFR Part 1, limits for maximum permissible exposure (MPE) are as following.

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(i) LIMITS FOR OCCUPATIONAL/CONTROLLED EXPOSURE				
0.3-3.0	614	1.63	*(100)	≤6
3.0-30	1842/f	4.89/f	*(900/f ²)	<6
30-300	61.4	0.163	1.0	<6
300-1,500			f/300	<6
1,500-100,000			5	<6
(ii) LIMITS FOR GENERAL POPULATION/UNCONTROLLED EXPOSURE				
0.3-1.34	614	1.63	*(100)	<30
1.34-30	824/f	2.19/f	*(180/f ²)	<30
30-300	27.5	0.073	0.2	<30
300-1,500			f/1500	<30
1,500-100,000			1.0	<30

*f = frequency in MHz. * = Plane-wave equivalent power density.*

Note1. Occupational/controlled limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational / controlled limits apply provided he or she is made aware of the potential for exposure.

Note2: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or can not exercise control over their exposure.

The maximum permissible exposure for 1500~100,000MHz is 1.0. So

Band	The Maximum Permissible Exposure (mW/cm ²)
Wi-Fi 2.4GHz	1.000
Wi-Fi 5GHz	1.000
Bluetooth	1.000
Bluetooth (Low Energy)	1.000

5 RF Exposure Evaluation Result

RF exposure evaluation method is based on KDB 447498 D01, this calculation is based on the conducted power, maximum power and antenna gain with provides the minimum separation distance. The formula shown below is from OET Bulletin 65 Edition 97-01 Per KDB 447498 D01:

$$S = PG / 4\pi R^2$$

Where: S = power density (in appropriate units, e.g. mW/cm²)

P = Time-average maximum tune up procedure (in appropriate units, e.g., mW)

G = the numeric gain of the antenna

R = distance to the center of radiation of the antenna (20 cm = limit for MPE)

Band	Maximum Output Power (dBm)	Antenna Gain (dBi)	Maximum EIRP (dBm)	PG (mW)	Result (mW/cm ²)	Limit Value (mW/cm ²)	The MPE Ratio
Wi-Fi 2.4GHz	20.23	4.44	24.670	293.089	0.058	1.000	0.058
Wi-Fi 5GHz	20.58	5.62	26.200	416.869	0.083	1.000	0.083
Bluetooth	19.11	4.44	23.550	226.464	0.045	1.000	0.045
Bluetooth (Low Energy)	19.88	4.44	24.320	270.396	0.054	1.000	0.054

Note: R = 20cm
 $\pi = 3.1416$
The MPE Ratio = Mac Result ÷ Limit Value

So the simultaneous transmitting antenna pairs as below:

TER = Wi-Fi 2.4GHz Antenna MPE ratio + Wi-Fi 5GHz Antenna MPE ratio + Bluetooth Antenna MPE ratio = 0.058 + 0.083 + 0.054 = 0.195 < 1

Note: For transmitters, minimum separation distance is 20cm, even if calculations indicate MPE distance is less.

IMPORTANT NOTE: To comply with the FCC RF exposure compliance requirements, the antenna(s) used for this transmitter must be installed to provide a separation distance of at least 20 cm from all persons and must not be co-located or operating in conjunction with any other antenna or transmitter. No change to the antenna or the device is permitted. Any change to the antenna or the device could result in the device exceeding the RF exposure requirements and void user's authority to operate the device.

ANNEX A: The EUT Appearance

The EUT Appearance are submitted separately.

*****END OF REPORT *****