


Test Report

Applicant : Pinned Golf, LLC.
Address : 58 13th Street #128, Charlestown, MA 02129,
USA
Product Name : Golf GPS Tablet
Brand Mark : Pinned
Model : Caddie
FCC ID : 2BOGR-CADDIE
Report Number : BLA-EMC-202502-A6104
Date of Receipt : Feb. 21, 2025
Date of Test : Feb. 21, 2025 to Mar. 24, 2025
Test Standard : 47 CFR Part 15, Subpart E 15.407
Test Result : Pass

Compiled by: *Hugh*Review by: *Sueels*Approved by: *Blue Zheng*

Issued Date: Mar. 24, 2025

BlueAsia of Technical Services(Shenzhen) Co.,Ltd.Address: Building C, No. 107, Shihuan Road, Shiyan Sub-District, Baoan District,
Shenzhen, Guangdong Province, China

The test report is effective only with both signature and specialized stamp and The result(s) shown in this report refer only to the sample(s) tested. Without written approval of BlueAsia, this report can't be reproduced except in full. The results described in this report do not represent the quality or characteristics of the sampled batch, nor do they represent any similar or identical products that are not explicitly stated.

Table of Contents

1	General information	5
1.1	General information	5
1.2	General description of EUT	5
2	Test summary	6
3	Test Configuration	7
3.1	Test mode	7
3.2	Operation frequency and test channel	7
3.3	Configuration diagram of EUT	8
3.4	Auxiliary equipment	8
3.5	Test environment	8
4	Laboratory information	9
4.1	Laboratory and accreditations	9
4.2	Measurement uncertainty	9
5	Test equipment	10
6	Test result	12
6.1	Antenna requirement	12
6.2	Conducted emissions at AC power line (150 kHz-30 MHz)	13
6.3	Frequency Stability	17
6.4	Maximum conducted output Power	18
6.5	Peak power spectrum density	20
6.6	Minimum 6dB bandwidth (5.725-5.85 GHz band)	21
6.7	26dB Emission bandwidth	22
6.8	99% Bandwidth	23
6.9	Duty Cycle	24
6.10	Conducted Band Edges Measurement	25
6.11	Conducted spurious emissions	27
6.12	Radiated emissions	29
6.13	Radiated emissions which fall in the restricted bands	46
6.14	DFS: Channel Closing Transmission Time	57
6.15	DFS: Non-occupancy period	59

7	Appendix A	61
7.1	Duty Cycle	错误！未定义书签。
7.2	Maximum Conducted Output Power	61
7.3	-26dB Bandwidth	76
7.4	Occupied Channel Bandwidth	84
7.5	Maximum Power Spectral Density Level	99
7.6	Band Edge	114
7.7	Frequency Stability	126
7.8	Conducted RF Spurious Emission	141
7.9	-6dB Bandwidth	156
	Appendix B: photographs of test setup	164
	Appendix C: photographs of EUT	166

Revise Record

Version No.	Date	Description
01	Mar. 24, 2025	Original

1 General information

1.1 General information

Applicant	Pinned Golf, LLC.
Address	58 13th Street #128, Charlestown, MA 02129, USA
Manufacturer	Shenzhen Yinuo Digital Technology Co.,Ltd
Address	Room 201, Plant No.34, Zhangyi Residential Quarter, Junzibu Community, Guanlan Street, Longhua District, Shenzhen
Factory	Shenzhen Yinuo Digital Technology Co.,Ltd
Address	Room 201, Plant No.34, Zhangyi Residential Quarter, Junzibu Community, Guanlan Street, Longhua District, Shenzhen

1.2 General description of EUT

Product Name	Golf GPS Tablet
Model No.	Caddie
Series model	N/A
Operation Frequency	Band 1: 5180MHz-5240MHz; Band 4: 5745MHz-5825MHz.
Channel numbers	Band 1: 802.11a/802.11n(HT20)/802.11ac(HT20): 4, 802.11n(HT40)/802.11ac(HT40):2, 802.11ac(HT80): 1 Band 4: 802.11a/802.11(HT20)/802.11ac(HT20): 5, 802.11n(HT40)/802.11ac(HT40): 2, 802.11ac(HT80): 1
Modulation Type	BPSK, QPSK, 16-QAM, 64-QAM, 256QAM
Channel Spacing	802.11a/n/ac(HT20)/ : 20MHz, 802.11n/ac(HT40): 40MHz, 802.11ac(HT80)
Data speed	6Mbps, 9Mbps, 12Mbps, 18Mbps, 24Mbps, 36Mbps, 48Mbps, 54Mbps, Up to 433 Mbps
DFS type	Slave
Antenna Type:	Internal antenna
Antenna Gain:	Band1: 2.33dBi(Provided by customer) Band4: 2.11 dBi(Provided by customer)
Power supply or adapter information	DC3.8V by battery
Hardware Version	P616_MB_V1
Software Version	P6161.QHYN.2+32.Neutral.14.0.V01.20241105

Note: For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.

2 Test summary

No.	Test item	FCC standard	Test Method (Clause)	Result
1	Antenna Requirement	§15.203	N/A	Pass
2	Conducted Emissions at AC Power Line (150kHz-30MHz)	§15.207	ANSI C63.10-2013 Clause 6.2	Pass
3	Frequency Stability	§15.407 (g)	ANSI C63.10-2013 Clause 6.8	Pass
4	Maximum Conducted output power	§15.407 (a)	KDB 789033 D02 II E	Pass
5	Transmitter Power Control	§15.407 (h)(1)	KDB 789033 D02 II E	N/A
6	Peak Power spectrum density	§15.407 (a)	KDB 789033 D02 II F	Pass
7	Minimum 6 dB bandwidth (5.725-5.85 GHz band)	§15.407 (e)	KDB 789033 D02 II C 2	Pass
8	26dB Emission bandwidth	§15.407 (a)	KDB 789033 D02 II C 1	Pass
9	99% Bandwidth	N/A	KDB 789033 II D	Pass
10	Duty Cycle	KDB 789033 D02 II B 1	KDB 789033 II B 1	Pass
11	Conducted Band Edges Measurement	§15.407 (b)(4)	ANSI C63.10-2013 Clause 11.13	Pass
12	Conducted spurious emissions	§15.407(b)	ANSI C63.10-2013 Clause 11.11	Pass
13	Radiated Emissions which fall in the restricted bands	§15.209 §15.407(b)	KDB 789033 D02 II G	Pass
14	Radiated Emissions	§15.209 §15.407(b)	KDB 789033 D02 II G	Pass
15	DFS: Channel Closing Transmission Time	§15.407((h)(2)	KDB 905462 D02 Clause 7.8.3	N/A
16	DFS: Non-occupancy period	§15.407((h)(2)	KDB 905462 D02 Clause 7.8.3	N/A

N/A: Not Applicable

3 Test Configuration

3.1 Test mode

Test Mode ^{Note 1}	Description
TX	Keep the EUT in continuously transmitting mode with modulation. (Duty cycle>98%)

Note 1: The EUT was configured to measure its highest possible emission and/or immunity level. The test modes were adapted according to the operation manual for use; the EUT was operated in the engineering mode ^{Note 2} to fix the TX frequency that was for the purpose of the measurements.


Note 2: EUT test mode is used.

3.2 Operation frequency and test channel

802.11a/n/ac

Band \ Bandwidth	20(MHz)		40(MHz)		80(MHz)	
	Channel number	frequency (MHz)	Channel number	frequency (MHz)	Channel number	frequency(M Hz)
U-NII-1	36	5180	38	5190	42	5210
	40	5200				
	44	5220	46	5230		
	48	5240				
U-NII-3	149	5745	151	5755	155	5775
	153	5765				
	157	5785	159	5795		
	161	5805				
	165	5825	--	--	--	--

3.3 Configuration diagram of EUT



3.4 Auxiliary equipment

Device Type	Manufacturer	Model Name	Serial No.	Remark
PC	Lenovo	E460C	N/A	From lab (No.BLA-ZC-BS-2022005)

Note:

“--” mean no any auxiliary device during testing.

3.5 Test environment

Environment	Temperature	Voltage
Normal	25°C	DC 3.8V

4 Laboratory information

4.1 Laboratory and accreditations

The test facility is recognized, certified, or accredited by the following organizations:

Company name:	BlueAsia of Technical Services(Shenzhen) Co., Ltd.
Address:	Building C, No. 107, Shihuan Road, Shiyan Sub-District, Baoan District, Shenzhen, Guangdong Province, China
CNAS accredited No.:	L9788
A2LA Cert. No.:	5071.01
FCC Designation No.:	CN1252
ISED CAB identifier No.:	CN0028
Telephone:	+86-755-28682673
FAX:	+86-755-28682673

4.2 Measurement uncertainty

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=1.96$.

Parameter	Expanded Uncertainty
Radiated Emission(9kHz-30MHz)	$\pm 4.34\text{dB}$
Radiated Emission(30Mz-1000MHz)	$\pm 4.24\text{dB}$
Radiated Emission(1GHz-18GHz)	$\pm 4.68\text{dB}$
AC Power Line Conducted Emission(150kHz-30MHz)	$\pm 3.45\text{dB}$
Occupied Channel Bandwidth	$\pm 5\%$
RF output power, conducted	$\pm 1.5\text{ dB}$
Power Spectral Density, conducted	$\pm 3.0\text{ dB}$
Unwanted Emissions, conducted	$\pm 3.0\text{ dB}$
Temperature	$\pm 3\text{ }^{\circ}\text{C}$
Supply voltages	$\pm 3\%$
Time	$\pm 5\%$

5 Test equipment

Radiated Spurious Emissions (Below 1GHz)

Equipment	Name	Model	Manufacture	S/N	Cal. Date	Due. Date
BLA-EMC-002-01	Anechoic chamber	9*6*6 chamber	SKET	N/A	2024/3/27	2027/3/26
BLA-EMC-002-02	Control room	966 control room	SKET	N/A	2024/3/27	2027/3/26
BLA-EMC-009	EMI receiver	ESR7	R&S	101199	2024/08/08	2025/08/07
BLA-EMC-043	Loop antenna	FMZB1519B	Schwarzbeck	00102	2024/06/29	2026/06/28
BLA-EMC-065	Broadband antenna	VULB9168	Schwarzbeck	01065P	2024/06/29	2026/06/27
BLA-XC-01	Coaxial Cable	N/A	BlueAsia	V01	N/A	N/A
BLA-XC-02	Coaxial Cable	N/A	BlueAsia	V02	N/A	N/A

Radiated Spurious Emissions (Above 1GHz)

Equipment	Name	Model	Manufacture	S/N	Cal. Date	Due. Date
BLA-EMC-001-01	Anechoic chamber	9*6*6 chamber	SKET	N/A	2023/11/16	2026/11/15
BLA-EMC-001-02	Control Room	966 control room	SKET	N/A	2023/11/16	2025/11/15
BLA-EMC-008	Spectrum	FSP40	R&S	100817	2024/08/08	2025/08/07
BLA-EMC-012	Broadband antenna	VULB9168	Schwarzbeck	00836 P:00227	2022/10/12	2025/10/11
BLA-EMC-013	Horn Antenna	BBHA9120D	Schwarzbeck	01892	2024/06/29	2026/06/28
BLA-EMC-014	Amplifier	PA_000318G-45	SKET	PA201804 3003	2024/08/08	2025/08/07
BLA-EMC-046	Filter bank	2.4G/5G Filter bank	SKET	N/A	2024/06/28	2025/06/27
BLA-EMC-061	Receiver	ESPI7	R&S	101477	2024/06/28	2025/06/27
BLA-EMC-066	Amplifier	LNPA_30M01 G-30	SKET	SK202106 0801	2024/06/28	2025/06/27
BLA-EMC-086	Amplifier	LNPA_18G40 G-50dB	SKET	SK202207 1301	2024/06/28	2025/06/27
BLA-EMC-087	Horn Antenna	BBHA 9170	Schwarzbeck	1106	2024/06/29	2026/06/28
BLA-XC-03	Coaxial Cable	N/A	BlueAsia	V03	N/A	N/A
BLA-XC-04	Coaxial Cable	N/A	BlueAsia	V04	N/A	N/A

Conducted Emissions

Equipment	Name	Model	Manufacture	S/N	Cal. Date	Due. Date
BLA-EMC-003-001	Shield room	8*3*3	SKET	N/A	2023/11/16	2025/11/15
BLA-EMC-009	EMI receiver	ESR7	R&S	101199	2024/08/08	2025/08/07
BLA-EMC-011	LISN	ENV216	R&S	101372	2024/08/08	2025/08/07
BLA-EMC-033	Impedance transformer	DC-2GHz	DFXP	N/A	2024/06/28	2025/06/27
BLA-EMC-041	LISN	AT166-2	ATTEN	AKK180600003	2024/08/08	2025/08/07
BLA-EMC-045	Impedance stable network	ISNT8-cat 6	TESEQ	53580	2024/08/08	2025/08/07
BLA-EMC-095	Single-channel vehicle artificial power network	NNBM 8124	Schwarzbeck	01045	2024/06/28	2025/06/27
BLA-EMC-096	Single-channel vehicle artificial power network	NNBM 8124	Schwarzbeck	01075	2024/06/28	2025/06/27
BLA-XC-05	Coaxial Cable	N/A	BlueAsia	V05	N/A	N/A

RF conducted

Equipment	Name	Model	Manufacture	S/N	Cal. Date	Due. Date
BLA-EMC-003-003	Shield room	5*3*3	SKET	N/A	2023/11/16	2025/11/15
BLA-EMC-016	Signal Generator	N5182A	Agilent	MY52420567	2024/06/28	2025/06/27
BLA-EMC-038	Spectrum	N9020A	Agilent	MY49100060	2024/08/08	2025/08/07
BLA-EMC-042	Power sensor	RPR3006W	DARE	14I00889SN042	2024/08/08	2025/08/07
BLA-EMC-044	Radio communication tester	CMW500	R&S	132429	2024/08/08	2025/08/07
BLA-EMC-064	Signal Generator	N5182B	KEYSIGHT	MY58108892	2024/06/28	2025/06/27
BLA-EMC-079	Spectrum	N9020A	Agilent	MY54420161	2024/08/08	2025/08/07
BLA-EMC-088	Audio Analyzer	ATS-1	Audio Precision	ATS141094	2024/06/28	2025/06/27

Test software

Software No.	Software Name	Manufacture	Software version	Test site
BLA-EMC-S001	EZ-EMC	EZ	EEMC-3A1+	RE(Below 1GHz)
BLA-EMC-S002	EZ-EMC	EZ	EEMC-3A1+	RE(Above 1GHz)
BLA-EMC-S003	EZ-EMC	EZ	EEMC-3A1+	CE
BLA-EMC-S010	MTS 8310	MW	2.0.0.0	RF

6 Test result

6.1 Antenna requirement

Test Standard	47 CFR Part 15, Subpart C 15.203
Test Method	N/A

6.1.1 Requirement

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit permanently attached antenna or of a so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

EUT antenna:

The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is band1: 2.33, band4: 2.11 dBi.

6.2 Conducted emissions at AC power line (150 kHz-30 MHz)


Test Standard	47 CFR Part 15, Subpart C 15.207
Test Method	ANSI C63.10-2013 Cluase6.2
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX

6.2.1 Limit

Frequency of emission(MHz)	Conducted limit(dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

6.2.2 Test setup



Description of test setup connection:

- Connect the control PC to the receiver through a USB to GPIB cable;
- The receiver is connected to the LISN through a coaxial line;
- Connect the power port of LISN to the EUT.


6.2.3 Procedure

- 1) The mains terminal disturbance voltage test was conducted in a shielded room.
- 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50ohm/50H + 5ohm linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.
- 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,
- 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.
- 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.

LISN=Read Level+ Cable Loss+ LISN Factor

6.2.4 Test data

[Test mode: TX]; [Line: Line];[Power:AC120V/60Hz]


Test Result: Pass


[Test mode: TX]; [Line: Neutral];[Power:AC120V/60Hz]

Conducted Emission Measurement

Project No.: CE

Data :#7

2025/02/26



Site: Phase: **N** Temperature: (C)
Limit: FCC Class B Conduction(QP) Power: Humidity: %RH
EUT: Golf GPS Tablet Distance: RBW: 9 KHz
M/N: Caddie VBW: 30 KHz Sweep Time: 10 ms
Mode: 5.1GWIFI TX Mode
Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Antenna Height cm	Table Degree	Comment
1		0.4900	22.88	9.80	32.68	56.17	-23.49	QP		
2		0.4900	12.54	9.80	22.34	46.17	-23.83	AVG		
3		0.6900	22.53	9.75	32.28	56.00	-23.72	QP		
4		0.6900	13.06	9.75	22.81	46.00	-23.19	AVG		
5		1.3220	20.79	9.76	30.55	56.00	-25.45	QP		
6		1.3220	12.09	9.76	21.85	46.00	-24.15	AVG		
7		2.1580	25.58	9.85	35.43	56.00	-20.57	QP		
8	*	2.1580	17.35	9.85	27.20	46.00	-18.80	AVG		
9		3.2580	20.99	9.97	30.96	56.00	-25.04	QP		
10		3.2580	13.00	9.97	22.97	46.00	-23.03	AVG		
11		4.4660	19.32	10.08	29.40	56.00	-26.60	QP		
12		4.4660	11.38	10.08	21.46	46.00	-24.54	AVG		

*:Maximum data x:Over limit !:over margin

(Reference Only)

Receiver: ESPI_1

Spectrum Analyzer: ESPI

Test Result: Pass


6.3 Frequency Stability

Test Standard	47 CFR Part 15, Subpart E 15.407(g)
Test Method	ANSI C63.10-2013 Cluase6.8
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX

6.3.1 Limit

The frequency tolerance shall be maintained within the band of operation frequency over a temperature variation of 0 degrees to 35 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C.

6.3.2 Test setup



6.3.3 Test data

Pass: Please refer to appendix A for details

6.4 Maximum conducted output Power

Test Standard	47 CFR Part 15, Subpart E 15.407 (a)
Test Method	KDB 789033 D02 II E
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX


6.4.1 Limit

Frequency band(MHz)	Limit
5150-5250	$\leq 1\text{W}(30\text{dBm})$ for master device
	$\leq 250\text{mW}(24\text{dBm})$ for client device
5250-5350	$\leq 250\text{mW}(24\text{dBm})$ for client device or $11\text{dBm}+10\log B^*$
5470-5725	$\leq 250\text{mW}(24\text{dBm})$ for client device or $11\text{dBm}+10\log B^*$
5725-5850	$\leq 1\text{W}(30\text{dBm})$

Remark:* Where B is the 26dB emission bandwidth in MHz.

The maximum conducted output power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage.

6.4.2 Test setup



6.4.3 Test data

Pass: Please refer to appendix A for details

BlueAsia

6.5 Peak power spectrum density


Test Standard	47 CFR Part 15, Subpart E 15.407 (a)
Test Method	KDB 789033 D02 II F
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX

6.5.1 Limit

Frequency band(MHz)	Limit
5150-5250	≤17dBm in 1MHz for master device
	≤11dBm in 1MHz for client device
5250-5350	≤11dBm in 1MHz for client device
5470-5725	≤11dBm in 1MHz for client device
5725-5850	≤30dBm in 500 kHz

Remark: The maximum power spectral density is measured as a conducted emission by direct connection of a calibrated test instrument to the equipment under test.

6.5.2 Test setup



6.5.3 Test data

Pass: Please refer to appendix A for details

BlueAsia of Technical Services (Shenzhen) Co., Ltd.

Tel: +86-755-23059481

Email: marketing@cblueasia.com www.cblueasia.com

Report version : V1.3


6.6 Minimum 6dB bandwidth (5.725-5.85 GHz band)

Test Standard	47 CFR Part 15, Subpart E 15.407 (e)
Test Method	KDB 789033 D02 II C 2
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX

6.6.1 Limit

≥500 kHz

6.6.2 Test setup



6.6.3 Test data


Pass: Please refer to appendix A for details

6.7 26dB Emission bandwidth

Test Standard	47 CFR Part 15, Subpart E 15.407 (a)
Test Method	KDB 789033 D02 II C 1
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX

6.7.1 Limit

6.7.2 Test setup



6.7.3 Test data


Pass: Please refer to appendix A for details

6.8 99% Bandwidth

Test Standard	N/A
Test Method	KDB 789033 II D
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX

6.8.1 Limit

6.8.2 Test setup




6.8.3 Test data

Pass: Please refer to appendix A for details

6.9 Duty Cycle

Test Standard	47 CFR Part 15, Subpart E 15.407
Test Method	KDB 789033 II B 1
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX

6.9.1 Test setup



6.9.2 Test data

Pass: Please refer to appendix A for details

6.10 Conducted Band Edges Measurement

Test Standard	47 CFR Part 15, Subpart C 15.407(b)(4)
Test Method	ANSI C63.10-2013 Cluase7.8.8 & Section 11.13.3.2
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX

6.10.1 Limit


In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.

If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20dB.

Attenuation below the general limits specified in §15.209(a) is not required.

In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

6.10.2 Test setup



6.10.3 Test data

Pass: Please refer to appendix A for details

BlueAsia

6.11 Conducted spurious emissions

Test Standard	47 CFR Part 15, Subpart C 15.407
Test Method	ANSI C63.10-2013 Cluase7.8.6 & Section 11.11
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX

6.11.1 Limit


In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.

If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20dB.

Attenuation below the general limits specified in §15.209(a) is not required.

In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

6.11.2 Test setup



6.11.3 Test data

Pass: Please refer to appendix A for details

BlueAsia

6.12 Radiated emissions

Test Standard	47 CFR Part 15, Subpart E 15.407
Test Method	KDB 789033 D02 II G
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX


6.12.1 Limit

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3


Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

6.12.2 Test setup

Below 1GHz:



30MHz-1GHz:



Above 1GHz:

