



SMD CERAMIC ANTENNA

Data Sheet

TS3216E245D05

For 2400-2484MHz
3.2x1.6mm [EIA1206]

FEATURES

- Light weight,compact
- Wide bandwidth,lowcost
- Built-in antenna with high gain
- Operating Temp. : -40°C~+85°C


APPLICATIONS

- Bluetooth, Wireless LAN, Mobile TV
- IEEE802.11g/b
- Zigbee systems,etc...
- Home RF system, etc



TS3216E245D05

SHAPES AND DIMENSIONS Dimensions in mm



L	W	A	A1	H
3.2 ± 0.1	1.6 ± 0.1	0.15 ± 0.05	0.4 ± 0.15	0.55 ± 0.1

***切記：** SMT貼片需黑色面朝上


■ **Electrical Characteristics per line(TA=25°C)**

Parameter	Specification	Units
Frequency Band	2400~2483	MHz
Polarization	Linear	
Peak Gain	0.98	dBi
Impedance	50	

■ **PART NUMBERING SYSTEM**


TS - 3216 - E - 2450 - D - 05

Brand Dimension Material Frequency Feeding mode Type



Typical Characteristics



Fig.1 VSWR




Radiation Pattern

The Gain pattern is measured in FAR-field chamber. DUT is placed on the table of rotator , a standard horn antenna and Vector Network Analyzer is used to collect data.


Fig.2 FAR-field Chamber




3D Gain Pattern (2400 MHz)




3D Gain Pattern (2450 MHz)




3D Gain Pattern (2500 MHz)



Gain (dB)



Efficiency (%)



Item	Condition	Specification
Thermal shock	2. 30±3 minutes at -40°C±5°C, 3. Convert to +105°C (5 minutes) 4. 30±3 minutes at +105°C±5°C, 5. Convert to -40°C (5 minutes) 6. Total 100 continuous cycles	No apparent damage Fulfill the electrical spec. after test.
Humidity resistance	1. Humidity: 85% R.H. 2. Temperature: 85±5°C 3. Time: 1000 hours.	No apparent damage Fulfill the electrical spec. after test.
High temperature resistance	No apparent damage Fulfill the electrical spec. after test.	1. Temperature: 150°C±5°C 2. Time: 1000 hours.
Low temperature resistance	1. Temperature: -40°C±5°C 2. Time: 1000 hours.	No apparent damage Fulfill the electrical spec. after test.
Soldering heat resistance	1. Solder bath temperature : 260±5°C 2. Bathing time: 10±1 seconds	No apparent damage
Solderability	The dipped surface of the terminal shall be at least 95% covered with solder after dipped in solder bath of 245±5°C for 3±1 seconds.	No apparent damage

(2)) Storage Condition


(a) At warehouse: The temperature should be within 0 ~ 30°C and humidity should be less than 60% RH. The product should be used within 1 year from the time of elivery.

(b) On board: The temperature should be within -40~85°C and humidity should be less than 85% RH.

(3) Operating Temperature Range

Operating temperature range : -40°C to +85°C.

Recommended Reflow Solder curve



A	1 st rising temperature	The normal to Preheating temperature	30s to 60s
B	Preheating	140℃ to 160℃	60s to 120s
C	2 nd rising temperature	Preheating to 200℃	20s to 40s
D	Main heating	if 220℃	50s ~ 60s
		if 230℃	40s ~ 50s
		if 240℃	30s ~ 40s
		if 250℃	20s ~ 40s
E	Regular cooling	200℃ to 100℃	1℃/s ~ 4℃/s

*reference: J-STD-020C

(1)) Soldering Gun Procedure

Note the follows, in case of using solder gun for replacement.


- (a) The tip temperature must be less than 350°C for the period within 3 seconds by using soldering gun under 30 W.
- (b) The soldering gun tip shall not touch this product directly.

(2) Soldering Volume


Note that excess of soldering volume will easily get crack the body of this product.

■ PACKAGING STYLE

□ REEL DIMENSIONS



□ TAPE DIMENSIONS



Feature	Specifications	Tolerances
W	12.00	±0.30
P	4.00	±0.10
E	1.75	±0.10
F	5.50	±0.10
P2	2.00	±0.10
D	1.50	+0.10 -0.00
P0	4.00	±0.10
10P0	40.00	±0.20

Typing Quantity: 5000 pieces per 7" reel

Order Information

Device	Package	Net Weight	Carrier	Quantity	HSF Status
TS3216E245D05	3216	0.0089g	Tape&Reel	5000pcs	RoHS compliant

Revision history

Date	Revision	Description of changes
2022-12-09	v1.0	First Version
2025-04-10	v1.1	Second Version

The contents of this data sheet are subject to change without notice.
Please confirm the specifications and delivery conditions when placing your order.

© Copyright 2015, All rights reserved