

## TEST REPORT

**Product** : Projector  
**Trade mark** : N/A  
**Model/Type reference** : AX20, AX22, AX24, AX26, AD2, AD4, AD12, AD14  
**Serial Number** : N/A  
**Report Number** : EED32R80287201  
**FCC ID** : 2BOK8-AX20  
**Date of Issue** : May 21, 2025  
**Test Standards** : 47 CFR Part 15 Subpart C  
**Test result** : PASS

Prepared for:

**Shenzhen IFERRET Technology Co., Ltd**  
**Room 601, Building A8, Tianrui Industrial Park, Fuyuan Road, Fuhai Street, Baoan District, Shenzhen, Guangdong**

Prepared by:

**Centre Testing International Group Co., Ltd.**  
**Hongwei Industrial Zone, Bao'an 70 District,**  
**Shenzhen, Guangdong, China**

**TEL: +86-755-3368 3668**

**FAX: +86-755-3368 3385**

Compiled by:

*Keven Tan*

Reviewed by:

*Frazer Li*

Approved by:

*Keven Tan**Frazer Li**Aaron Ma*

Date:

May 21, 2025




Check No.: 4714050325

## 1 Content

<b>1 CONTENT</b> .....	2
<b>2 VERSION</b> .....	3
<b>3 TEST SUMMARY</b> .....	4
<b>4 GENERAL INFORMATION</b> .....	5
4.1 CLIENT INFORMATION .....	5
4.2 GENERAL DESCRIPTION OF EUT .....	5
4.3 TEST CONFIGURATION .....	6
4.4 TEST ENVIRONMENT .....	7
4.5 DESCRIPTION OF SUPPORT UNITS .....	7
4.6 TEST LOCATION .....	7
4.7 MEASUREMENT UNCERTAINTY (95% CONFIDENCE LEVELS, K=2) .....	8
<b>5 EQUIPMENT LIST</b> .....	9
<b>6 TEST RESULTS AND MEASUREMENT DATA</b> .....	12
6.1 ANTENNA REQUIREMENT .....	12
6.2 CONDUCTED EMISSIONS .....	13
6.3 MAXIMUM CONDUCTED OUTPUT POWER .....	16
6.4 DTS BANDWIDTH .....	17
6.5 MAXIMUM POWER SPECTRAL DENSITY .....	18
6.6 BAND EDGE MEASUREMENTS AND CONDUCTED SPURIOUS EMISSION .....	19
6.7 RADIATED SPURIOUS EMISSION & RESTRICTED BANDS .....	20
<b>7 APPENDIX A</b> .....	35
<b>8 PHOTOGRAPHS OF TEST SETUP</b> .....	36
<b>9 PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS</b> .....	38

**2 Version**

Version No.	Date	Description
00	May 21, 2025	Original



### 3 Test Summary

Test Item	Test Requirement	Result
<b>Antenna Requirement</b>	47 CFR Part 15 Subpart C Section 15.203/15.247 (c)	PASS
<b>AC Power Line Conducted Emission</b>	47 CFR Part 15 Subpart C Section 15.207	PASS
<b>DTS Bandwidth</b>	47 CFR Part 15 Subpart C Section 15.247 (a)(2)	PASS
<b>Maximum Conducted Output Power</b>	47 CFR Part 15 Subpart C Section 15.247 (b)(3)	PASS
<b>Maximum Power Spectral Density</b>	47 CFR Part 15 Subpart C Section 15.247 (e)	PASS
<b>Band Edge Measurements</b>	47 CFR Part 15 Subpart C Section 15.247(d)	PASS
<b>Conducted Spurious Emissions</b>	47 CFR Part 15 Subpart C Section 15.247(d)	PASS
<b>Radiated Spurious Emission &amp; Restricted bands</b>	47 CFR Part 15 Subpart C Section 15.205/15.209	PASS

Remark:  
Model No.: AX20, AX22, AX24, AX26, AD2, AD4, AD12, AD14  
Only the model AX20 was tested. They have same electrical, PCB and layout, only the model name are different for marketing requirements.

## 4 General Information

### 4.1 Client Information

Applicant:	Shenzhen IFERRET Technology Co., Ltd
Address of Applicant:	Room 601, Building A8, Tianrui Industrial Park, Fuyuan Road, Fuhai Street, Baoan District, Shenzhen, Guangdong
Manufacturer:	Shenzhen IFERRET Technology Co., Ltd
Address of Manufacturer:	Room 601, Building A8, Tianrui Industrial Park, Fuyuan Road, Fuhai Street, Baoan District, Shenzhen, Guangdong
Factory:	Mito Technology (Shenzhen) Co., Ltd.
Address of Factory:	Second Floor, Building 5, Chuangjian II Industrial Zone, Yingrenshi Community, Shiyan Street, Shenzhen

### 4.2 General Description of EUT

Product Name:	Projector	
Model No.:	AX20, AX22, AX24, AX26, AD2, AD4, AD12, AD14	
Test Model No.:	AX20	
Trade mark:	N/A	
Product Type:	<input type="checkbox"/> Mobile <input type="checkbox"/> Portable <input checked="" type="checkbox"/> Fixed Location	
Operation Frequency:	2402MHz~2480MHz	
Modulation Type:	GFSK	
Transfer Rate:	<input checked="" type="checkbox"/> 1Mbps <input checked="" type="checkbox"/> 2Mbps	
Number of Channel:	40	
Antenna Type:	FPC antenna	
Antenna Gain:	3.63dBi	
Power Supply:	Adapter:	DC 12V
Test Voltage:	DC 12V	
Sample Received Date:	Mar. 17, 2025	
Sample tested Date:	Mar. 17, 2025 to Apr. 27, 2025	

Operation Frequency each of channel							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	19	2440	29	2460	39	2480

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Channel	Frequency(MHz)
The lowest channel (CH0)	2402
The middle channel (CH19)	2440
The highest channel (CH39)	2480

### 4.3 Test Configuration

EUT Test Software Settings:				
Test Software:	Adb.exe			
EUT Power Grade:	Default (Power level is built-in set parameters and cannot be changed and selected)			
Use test software to set the lowest frequency, the middle frequency and the highest frequency keep transmitting of the EUT.				
Test Mode	Modulation	Rate	Channel	Frequency(MHz)
Mode a	GFSK	1Mbps	CH0	2402
Mode b	GFSK	1Mbps	CH19	2440
Mode c	GFSK	1Mbps	CH39	2480
Mode d	GFSK	2Mbps	CH0	2402
Mode e	GFSK	2Mbps	CH19	2440
Mode f	GFSK	2Mbps	CH39	2480

#### 4.4 Test Environment

<b>Operating Environment:</b>	
<b>Radiated Spurious Emissions:</b>	
Temperature:	22~25.0 °C
Humidity:	50~55 % RH
Atmospheric Pressure:	1010mbar
<b>Conducted Emissions:</b>	
Temperature:	22~25.0 °C
Humidity:	50~55 % RH
Atmospheric Pressure:	1010mbar
<b>RF Conducted:</b>	
Temperature:	22~25.0 °C
Humidity:	50~55 % RH
Atmospheric Pressure:	1010mbar

#### 4.5 Description of Support Units

The EUT has been tested with associated equipment below.

##### 1) Support equipment

Description	Manufacturer	Model No.	Certification	Supplied by
Netbook	Dell	P77F	FCC&CE	CTI

#### 4.6 Test Location

All tests were performed at:

Centre Testing International Group Co., Ltd

Building C, Hongwei Industrial Park Block 70, Bao'an District, Shenzhen, China

Telephone: +86 (0) 755 33683668 Fax:+86 (0) 755 33683385

No tests were sub-contracted.

FCC Designation No.: CN1164

**4.7 Measurement Uncertainty (95% confidence levels, k=2)**

No.	Item	Measurement Uncertainty
1	Radio Frequency	$7.9 \times 10^{-8}$
2	RF power, conducted	0.46dB (30MHz-1GHz)
		0.55dB (1GHz-40GHz)
3	Radiated Spurious emission test	3.3dB (9kHz-30MHz)
		4.3dB (30MHz-1GHz)
		4.5dB (1GHz-18GHz)
		3.4dB (18GHz-40GHz)
4	Conduction emission	3.5dB (9kHz-150kHz)
		3.1dB (150kHz-30MHz)
5	Temperature test	0.64°C
6	Humidity test	3.8%
7	DC power voltages	0.026%

## 5 Equipment List

RF test system					
Equipment	Manufacturer	Model No.	Serial Number	Cal. Date (mm-dd-yyyy)	Cal. Due date (mm-dd-yyyy)
Communication test set	R&S	CMW500	107929	06-26-2024	06-25-2025
Signal Generator	R&S	SMBV100A	1407.6004K02-262149-CV	09-02-2024	09-01-2025
Spectrum Analyzer	R&S	FSV40	101200	07-18-2024	07-17-2025
RF control unit(power unit)	MWRF-test	MW100-RFCB	MW220620CTI-42	06-25-2024	06-24-2025
High-low temperature test chamber	Dong Guang Qin Zhuo	LK-80GA	QZ20150611879	11-30-2024	11-29-2025
Temperature/ Humidity Indicator	biaozhi	HM10	1804186	05-29-2024	05-28-2025
BT&WI-FI Automatic test software	MWRF-test	MTS 8310	V2.0.0.0	---	---
Spectrum Analyzer	R&S	FSV3044	101509	02-14-2025	02-13-2026

Conducted disturbance Test					
Equipment	Manufacturer	Model No.	Serial Number	Cal. date (mm-dd-yyyy)	Cal. Due date (mm-dd-yyyy)
Receiver	R&S	ESCI	100435	04-18-2024 04-08-2025	04-17-2025 04-07-2026
Temperature/ Humidity Indicator	Defu	TH128	/	04-25-2024 03-31-2025	04-24-2025 03-30-2026
LISN	R&S	ENV216	100098	09-19-2024	09-18-2025
Barometer	changchun	DYM3	1188	---	---
Test software	Fara	EZ-EMC	EMC-CON 3A1.1	---	---
Capacitive voltage probe	Schwarzbeck	CVP 9222C	00124	06-18-2024	06-17-2025
ISN	TESEQ	ISN T800	30297	12-05-2024	12-04-2025

3M Semi-anechoic Chamber (2)- Radiated disturbance Test					
Equipment	Manufacturer	Model No.	Serial Number	Cal. date	Cal. Due date
				(mm-dd-yyyy)	(mm-dd-yyyy)
3M Chamber & Accessory Equipment	TDK	SAC-3	---	05/22/2022	05/21/2025
Receiver	R&S	ESCI7	100938-003	09/07/2024	09/06/2025
Spectrum Analyzer	R&S	FSV40	101200	07/18/2024	07/17/2025
TRILOG Broadband Antenna	schwarzbeck	VULB 9163	9163-618	05/22/2022	05/21/2025
Loop Antenna	Schwarzbeck	FMZB 1519B	1519B-076	04/16/2024 04/07/2025	04/15/2025 04/06/2026
Microwave Preamplifier	Tonscend	EMC051845SE	980380	12/05/2024	12/04/2025
Horn Antenna	A.H.SYSTEMS	SAS-574	374	07/02/2023	07/01/2026
Horn Antenna	ETS-LINGREN	BBHA 9120D	9120D-1869	04/16/2024 04/07/2025	04/15/2025 04/06/2026
Preamplifier	Agilent	11909A	12-1	03/03/2025	03/02/2026
Preamplifier	CD	PAP-1840-60	6041.6042	06/19/2024	06/18/2025
Test software	Fara	EZ-EMC	EMEC-3A1-Pre	---	---
Cable line	Fulai(7M)	SF106	5219/6A	05/22/2022	05/21/2025
Cable line	Fulai(6M)	SF106	5220/6A	05/22/2022	05/21/2025
Cable line	Fulai(3M)	SF106	5216/6A	05/22/2022	05/21/2025
Cable line	Fulai(3M)	SF106	5217/6A	05/22/2022	05/21/2025

3M full-anechoic Chamber					
Equipment	Manufacturer	Model No.	Serial Number	Cal. Date (mm-dd-yyyy)	Cal. Due date (mm-dd-yyyy)
Fully Anechoic Chamber	TDK	FAC-3	---	01-09-2024	01-08-2027
Receiver	Keysight	N9038A	MY57290136	01-04-2025	01-03-2026
Spectrum Analyzer	Keysight	N9020B	MY57111112	01-14-2025	01-13-2026
Spectrum Analyzer	Keysight	N9030B	MY57140871	01-14-2025	01-13-2026
TRILOG Broadband Antenna	Schwarzbeck	VULB 9163	9163-1148	04-28-2024 04-12-2025	04-27-2025 04-11-2026
Horn Antenna	Schwarzbeck	BBHA 9170	9170-832	04-16-2024 04-12-2025	04-15-2025 04-11-2026
Horn Antenna	ETS-LINDGREN	3117	57407	07-03-2024	07-02-2025
Preamplifier	EMCI	EMC001330	980563	03-03-2025	03-02-2026
Preamplifier	Tonscend	TAP-011858	AP21B806112	07-18-2024	07-17-2025
Preamplifier	Tonscend	EMC051845SE	980380	12-05-2024	12-04-2025
Communication test set	R&S	CMW500	102898	01-04-2025	01-03-2026
Temperature/Humidity Indicator	biaozhi	GM1360	EE1186631	04-07-2024 03-31-2025	04-06-2025 03-30-2026
RSE Automatic test software	JS Tonscend	JS36-RSE	V4.0.0.0	---	---
Cable line	Times	SFT205-NMSM-2.50M	394812-0001	01-09-2024	01-08-2027
Cable line	Times	SFT205-NMSM-2.50M	394812-0002	01-09-2024	01-08-2027
Cable line	Times	SFT205-NMSM-2.50M	394812-0003	01-09-2024	01-08-2027
Cable line	Times	SFT205-NMSM-2.50M	393495-0001	01-09-2024	01-08-2027
Cable line	Times	EMC104-NMNM-1000	SN160710	01-09-2024	01-08-2027
Cable line	Times	SFT205-NMSM-3.00M	394813-0001	01-09-2024	01-08-2027
Cable line	Times	SFT205-NMNM-1.50M	381964-0001	01-09-2024	01-08-2027
Cable line	Times	SFT205-NMSM-7.00M	394815-0001	01-09-2024	01-08-2027
Cable line	Times	HF160-KMKM-3.00M	393493-0001	01-09-2024	01-08-2027

## 6 Test results and Measurement Data


### 6.1 Antenna Requirement

<b>Standard requirement:</b>	47 CFR Part 15C Section 15.203 /247(c)
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.	
15.247(b) (4) requirement: The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.	
<b>EUT Antenna:</b>	Please see Internal photos
The antenna is FPC antenna. The best case gain of the antenna is 3.63dBi.	

## 6.2 Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.207														
Test Method:	ANSI C63.10: 2013														
Test Frequency Range:	150kHz to 30MHz														
Receiver setup:	RBW=9 kHz, VBW=30 kHz, Sweep time=auto														
Limit:	<table border="1"> <thead> <tr> <th rowspan="2">Frequency range (MHz)</th> <th colspan="2">Limit (dBuV)</th> </tr> <tr> <th>Quasi-peak</th> <th>Average</th> </tr> </thead> <tbody> <tr> <td>0.15-0.5</td><td>66 to 56*</td><td>56 to 46*</td></tr> <tr> <td>0.5-5</td><td>56</td><td>46</td></tr> <tr> <td>5-30</td><td>60</td><td>50</td></tr> </tbody> </table>	Frequency range (MHz)	Limit (dBuV)		Quasi-peak	Average	0.15-0.5	66 to 56*	56 to 46*	0.5-5	56	46	5-30	60	50
Frequency range (MHz)	Limit (dBuV)														
	Quasi-peak	Average													
0.15-0.5	66 to 56*	56 to 46*													
0.5-5	56	46													
5-30	60	50													


\* Decreases with the logarithm of the frequency.

Test Setup:	
Test Procedure:	<ol style="list-style-type: none"> <li>1) The mains terminal disturbance voltage test was conducted in a shielded room.</li> <li>2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a <math>50\Omega/50\mu\text{H} + 5\Omega</math> linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.</li> <li>3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane.</li> <li>4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.</li> <li>5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10: 2013 on conducted measurement.</li> </ol>
Test Mode:	All modes were tested, only the worst case mode d was recorded in the report.

Test Results:	Pass
---------------	------

## Measurement Data


Live line:



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Margin	Comment
			Level	Factor	ment			
		MHz	dBuV	dB	dBuV	dB	Detector	
1		0.4605	41.25	10.08	51.33	56.68	-5.35	QP
2		0.4695	28.47	10.08	38.55	46.52	-7.97	AVG
3 *		0.6000	41.80	10.10	51.90	56.00	-4.10	QP
4		0.6045	31.71	10.10	41.81	46.00	-4.19	AVG
5		0.6630	41.52	10.12	51.64	56.00	-4.36	QP
6		0.6630	30.75	10.12	40.87	46.00	-5.13	AVG
7		0.7260	39.21	10.14	49.35	56.00	-6.65	QP
8		0.7260	28.25	10.14	38.39	46.00	-7.61	AVG
9		0.7935	38.60	10.18	48.78	56.00	-7.22	QP
10		0.7935	28.50	10.18	38.68	46.00	-7.32	AVG
11		10.2705	42.55	9.95	52.50	60.00	-7.50	QP
12		24.2970	29.50	9.81	39.31	50.00	-10.69	AVG

Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level =Receiver Reading + LISN Factor + Cable Loss.
3. If the Peak value under Average limit, the Average value is not recorded in the report.




No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Margin		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1		0.4740	38.93	10.08	49.01	56.44	-7.43	QP	
2		0.4740	27.94	10.08	38.02	46.44	-8.42	AVG	
3		0.5910	40.03	10.10	50.13	56.00	-5.87	QP	
4		0.6000	30.72	10.10	40.82	46.00	-5.18	AVG	
5	*	0.6630	42.88	10.12	53.00	56.00	-3.00	QP	
6		0.6630	32.11	10.12	42.23	46.00	-3.77	AVG	
7		0.7304	39.55	10.15	49.70	56.00	-6.30	QP	
8		0.7304	32.01	10.15	42.16	46.00	-3.84	AVG	
9		0.7935	27.71	10.18	37.89	46.00	-8.11	AVG	
10		9.9645	41.04	9.95	50.99	60.00	-9.01	QP	
11		12.3225	41.32	9.91	51.23	60.00	-8.77	QP	
12		24.2925	30.98	9.81	40.79	50.00	-9.21	AVG	


Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level =Receiver Reading + LISN Factor + Cable Loss.
3. If the Peak value under Average limit, the Average value is not recorded in the report.


### 6.3 Maximum Conducted Output Power

Test Requirement:	47 CFR Part 15C Section 15.247 (b)(3)
Test Method:	ANSI C63.10 2013
Test Setup:	 <p>Remark: Offset=Cable loss+ attenuation factor.</p>
Test Procedure:	<ol style="list-style-type: none"> <li>Set the RBW <math>\geq</math> DTS bandwidth.</li> <li>Set VBW <math>\geq 3 \times</math> RBW.</li> <li>Set span <math>\geq 3 \times</math> RBW</li> <li>Sweep time = auto couple.</li> <li>Detector = peak.</li> <li>Trace mode = max hold.</li> <li>Allow trace to fully stabilize.</li> <li>Use peak marker function to determine the peak amplitude level.</li> </ol>
Limit:	30dBm
Test Mode:	Refer to clause 5.3
Test Results:	Refer to Appendix A


## 6.4 DTS Bandwidth

Test Requirement:	47 CFR Part 15C Section 15.247 (a)(2)
Test Method:	ANSI C63.10 2013
Test Setup:	 <p>Remark: Offset=Cable loss+ attenuation factor.</p>
Test Procedure:	<ol style="list-style-type: none"> <li>Set RBW = 100 kHz.</li> <li>Set the VBW <math>\geq [3 \times \text{RBW}]</math>.</li> <li>Detector = peak.</li> <li>Trace mode = max hold.</li> <li>Sweep = auto couple.</li> <li>Allow the trace to stabilize.</li> <li>Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.</li> </ol>
Limit:	$\geq 500$ kHz
Test Mode:	Refer to clause 5.3
Test Results:	Refer to Appendix A

## 6.5 Maximum Power Spectral Density

Test Requirement:	47 CFR Part 15C Section 15.247 (e)
Test Method:	ANSI C63.10 2013
Test Setup:	 <p>Remark: Offset=Cable loss+ attenuation factor.</p>
Test Procedure:	<ol style="list-style-type: none"> <li>Set analyzer center frequency to DTS channel center frequency.</li> <li>Set the span to 1.5 times the DTS bandwidth.</li> <li>Set the RBW to <math>3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}</math>.</li> <li>Set the VBW <math>\geq [3 \times \text{RBW}]</math>.</li> <li>Detector = peak.</li> <li>Sweep time = auto couple.</li> <li>Trace mode = max hold.</li> <li>Allow trace to fully stabilize.</li> <li>Use the peak marker function to determine the maximum amplitude level within the RBW.</li> <li>If measured value exceeds requirement, then reduce RBW (but no less than 3 kHz) and repeat.</li> </ol>
Limit:	$\leq 8.00 \text{ dBm}/3\text{kHz}$
Test Mode:	Refer to clause 5.3
Test Results:	Refer to Appendix A



## 6.6 Band Edge measurements and Conducted Spurious Emission

Test Requirement:	47 CFR Part 15C Section 15.247 (d)
Test Method:	ANSI C63.10 2013
Test Setup:	 <p>Remark: Offset=Cable loss+ attenuation factor.</p>
Test Procedure:	<ol style="list-style-type: none"> <li>Set RBW =100KHz.</li> <li>Set VBW = 300KHz.</li> <li>Sweep time = auto couple.</li> <li>Detector = peak.</li> <li>Trace mode = max hold.</li> <li>Allow trace to fully stabilize.</li> <li>Use peak marker function to determine the peak amplitude level.</li> </ol>
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test Mode:	Refer to clause 5.3
Test Results:	Refer to Appendix A

## 6.7 Radiated Spurious Emission & Restricted bands

Test Requirement:	47 CFR Part 15C Section 15.209 and 15.205				
Test Method:	ANSI C63.10 2013				
Test Site:	Measurement Distance: 3m (Semi-Anechoic Chamber)				
Receiver Setup:	Frequency	Detector	RBW	VBW	Remark
	0.009MHz-0.090MHz	Peak	10kHz	30kHz	Peak
	0.009MHz-0.090MHz	Average	10kHz	30kHz	Average
	0.090MHz-0.110MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	0.110MHz-0.490MHz	Peak	10kHz	30kHz	Peak
	0.110MHz-0.490MHz	Average	10kHz	30kHz	Average
	0.490MHz -30MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	100 kHz	300kHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Peak	1MHz	10kHz	Average
Limit:	Frequency	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
	0.009MHz-0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz-30MHz	30	-	-	30
	30MHz-88MHz	100	40.0	Quasi-peak	3
	88MHz-216MHz	150	43.5	Quasi-peak	3
	216MHz-960MHz	200	46.0	Quasi-peak	3
	960MHz-1GHz	500	54.0	Quasi-peak	3
	Above 1GHz	500	54.0	Average	3

Note: 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.



<b>Test Procedure:</b>	<ol style="list-style-type: none"> <li>1) Below 1G: The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.                      2) Above 1G: The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.                      Note: For the radiated emission test above 1GHz:                      Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.</li> <li>The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.</li> <li>The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both</li> </ol>
------------------------	--


	<p>horizontal and vertical polarizations of the antenna are set to make the measurement.</p> <p>d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.</p> <p>e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</p> <p>f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.</p> <p>g. Test the EUT in the lowest channel (2402MHz), the middle channel (2440MHz), the Highest channel (2480MHz)</p> <p>h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.</p> <p>i. Repeat above procedures until all frequencies measured was complete.</p>
Test Mode:	Refer to clause 5.3
Test Results:	Pass

## Radiated Spurious Emission below 1GHz:

During the test, the Radiated Emission from 30MHz to 1GHz was performed in all modes, only the worst case highest channel of GFSK 1M was recorded in the report.


Horizontal:

**Test Graph**



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Antenna Height cm	Table Degree degree	Comment
1		166.6221	23.94	11.18	35.12	43.50	-8.38	QP 199	170	
2		207.2315	23.38	13.06	36.44	43.50	-7.06	QP 199	352	
3		359.1230	14.69	18.36	33.05	46.00	-12.95	QP 100	167	
4		558.2405	12.13	22.29	34.42	46.00	-11.58	QP 199	352	
5		682.2288	11.35	24.08	35.43	46.00	-10.57	QP 100	220	
6	*	868.2164	17.85	26.55	44.40	46.00	-1.60	QP 100	178	

Vertical:

**Test Graph**


No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Margin	Antenna	Table		
			Level	Factor	ment						
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		30.9022	19.52	12.40	31.92	40.00	-8.08	QP	100	11	
2		35.4308	20.51	12.67	33.18	40.00	-6.82	QP	100	288	
3	!	49.4374	20.45	14.48	34.93	40.00	-5.07	QP	100	267	
4	*	76.7808	28.68	9.92	38.60	40.00	-1.40	QP	200	103	
5		128.7434	26.21	11.00	37.21	43.50	-6.29	QP	100	299	
6	!	165.1678	29.43	11.07	40.50	43.50	-3.00	QP	100	256	

### Radiated Spurious Emission above 1GHz:

During the test, the Radiated Spurious Emission from above 1GHz was performed in all modes, only the worst case BLE 1M was recorded in the report.

Mode:			Bluetooth LE GFSK Transmitting			Channel:		2402 MHz	
NO	Freq. [MHz]	Factor [dB]	Reading [dB $\mu$ V]	Level [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]	Result	Polarity	Remark
1	1255.4837	11.79	37.86	49.65	74.00	24.35	Pass	H	PK
2	1650.5767	14.01	37.14	51.15	74.00	22.85	Pass	H	PK
3	3717.6478	-12.81	51.77	38.96	74.00	35.04	Pass	H	PK
4	5401.9101	-6.71	49.04	42.33	74.00	31.67	Pass	H	PK
5	7740.1116	-1.48	45.50	44.02	74.00	29.98	Pass	H	PK
6	11727.4818	2.53	45.16	47.69	74.00	26.31	Pass	H	PK
7	1193.3462	11.57	38.07	49.64	74.00	24.36	Pass	V	PK
8	1627.6418	13.80	36.87	50.67	74.00	23.33	Pass	V	PK
9	3408.8773	-13.95	52.91	38.96	74.00	35.04	Pass	V	PK
10	4892.2762	-8.32	49.62	41.30	74.00	32.70	Pass	V	PK
11	7539.2526	-2.28	47.11	44.83	74.00	29.17	Pass	V	PK
12	11752.8335	2.41	45.48	47.89	74.00	26.11	Pass	V	PK

Mode:			Bluetooth LE GFSK Transmitting			Channel:		2440 MHz	
NO	Freq. [MHz]	Factor [dB]	Reading [dB $\mu$ V]	Level [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]	Result	Polarity	Remark
1	1186.0124	11.50	38.86	50.36	74.00	23.64	Pass	H	PK
2	1702.5802	14.09	37.23	51.32	74.00	22.68	Pass	H	PK
3	3824.255	-12.27	52.92	40.65	74.00	33.35	Pass	H	PK
4	5849.79	-5.42	48.68	43.26	74.00	30.74	Pass	H	PK
5	8414.2109	-0.75	46.27	45.52	74.00	28.48	Pass	H	PK
6	11440.1627	2.45	44.84	47.29	74.00	26.71	Pass	H	PK
7	1203.3469	11.66	37.74	49.40	74.00	24.60	Pass	V	PK
8	1610.3074	13.73	37.24	50.97	74.00	23.03	Pass	V	PK
9	3800.8534	-12.44	52.69	40.25	74.00	33.75	Pass	V	PK
10	5433.1122	-6.52	49.52	43.00	74.00	31.00	Pass	V	PK
11	7437.8459	-2.55	47.47	44.92	74.00	29.08	Pass	V	PK
12	12020.0013	3.04	44.81	47.85	74.00	26.15	Pass	V	PK

Mode:			Bluetooth LE GFSK Transmitting			Channel:		2480 MHz	
NO	Freq. [MHz]	Factor [dB]	Reading [dB $\mu$ V]	Level [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]	Result	Polarity	Remark
1	1294.2863	12.04	37.48	49.52	74.00	24.48	Pass	H	PK
2	1782.1855	14.27	37.21	51.48	74.00	22.52	Pass	H	PK
3	3726.0984	-12.82	52.27	39.45	74.00	34.55	Pass	H	PK
4	5851.0901	-5.43	48.65	43.22	74.00	30.78	Pass	H	PK
5	8169.1446	-1.27	46.50	45.23	74.00	28.77	Pass	H	PK
6	11376.4584	2.35	45.53	47.88	74.00	26.12	Pass	H	PK
7	1192.1461	11.56	38.69	50.25	74.00	23.75	Pass	V	PK
8	1460.4307	13.01	37.18	50.19	74.00	23.81	Pass	V	PK
9	3826.8551	-12.25	52.38	40.13	74.00	33.87	Pass	V	PK
10	5747.0831	-5.89	48.16	42.27	74.00	31.73	Pass	V	PK
11	8247.7999	-0.98	45.72	44.74	74.00	29.26	Pass	V	PK
12	12047.3032	2.90	45.25	48.15	74.00	25.85	Pass	V	PK

## Remark:


- 1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:  
Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor
- 2) Scan from 9kHz to 25GHz, the disturbance above 10GHz and below 30MHz was very low. As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. So, only the peak measurements were shown in the report.

## Restricted bands:

Test plot as follows:

EUT_Name		Test_Model	
Test_Mode	BLE 1M GFSK Transmitting	Test_Frequency	2402MHz
Tset_Engineer	chenjun	Test_Date	2025/04/22
Remark			


## Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dB $\mu$ V]	Level [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]	Result	Polarity	Remark
1	2390	15.96	34.16	50.12	74.00	23.88	PASS	Horizontal	PK
2	2390	15.96	19.31	35.27	54.00	18.73	PASS	Horizontal	AV

EUT_Name		Test_Model	
Test_Mode	BLE 1M GFSK Transmitting	Test_Frequency	2402MHz
Tset_Engineer	chenjun	Test_Date	2025/04/22
Remark			


### Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dB $\mu$ V]	Level [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]	Result	Polarity	Remark
1	2390	15.96	34.38	50.34	74.00	23.66	PASS	Vertical	PK
2	2390	15.96	20.68	36.64	54.00	17.36	PASS	Vertical	AV

EUT_Name		Test_Model	
Test_Mode	BLE 1M GFSK Transmitting	Test_Frequency	2480MHz
Tset_Engineer	chenjun	Test_Date	2025/04/22
Remark			


### Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dB $\mu$ V]	Level [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]	Result	Polarity	Remark
1	2483.5	16.29	35.96	52.25	74.00	21.75	PASS	Horizontal	PK
2	2483.5	16.29	21.96	38.25	54.00	15.75	PASS	Horizontal	AV

EUT_Name		Test_Model	
Test_Mode	BLE 1M GFSK Transmitting	Test_Frequency	2480MHz
Tset_Engineer	chenjun	Test_Date	2025/04/22
Remark			


**Test Graph**



<b>Suspected List</b>									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	2483.5	16.29	37.51	53.80	74.00	20.20	PASS	Vertical	PK
2	2483.5	16.29	24.15	40.44	54.00	13.56	PASS	Vertical	AV

EUT_Name		Test_Model	
Test_Mode	BLE 2M GFSK Transmitting	Test_Frequency	2402MHz
Tset_Engineer	chenjun	Test_Date	2025/04/22
Remark			


### Test Graph



Suspected List										
NO	Freq. [MHz]	Factor [dB]	Reading [dB $\mu$ V]	Level [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]	Result	Polarity	Remark	
1	2390	15.96	33.95	49.91	74.00	24.09	PASS	Horizontal	PK	
2	2390	15.96	18.98	34.94	54.00	19.06	PASS	Horizontal	AV	

EUT_Name		Test_Model	
Test_Mode	BLE 2M GFSK Transmitting	Test_Frequency	2402MHz
Tset_Engineer	chenjun	Test_Date	2025/04/22
Remark			

### Test Graph




### Suspected List

NO	Freq. [MHz]	Factor [dB]	Reading [dB $\mu$ V]	Level [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]	Result	Polarity	Remark
1	2390	15.96	34.10	50.06	74.00	23.94	PASS	Vertical	PK
2	2390	15.96	19.82	35.78	54.00	18.22	PASS	Vertical	AV

EUT_Name		Test_Model	
Test_Mode	BLE 2M GFSK Transmitting	Test_Frequency	2480MHz
Tset_Engineer	chenjun	Test_Date	2025/04/22
Remark			


### Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	2483.5	16.29	36.17	52.46	74.00	21.54	PASS	Horizontal	PK
2	2483.5	16.29	23.43	39.72	54.00	14.28	PASS	Horizontal	AV

EUT_Name		Test_Model	
Test_Mode	BLE 2M GFSK Transmitting	Test_Frequency	2480MHz
Tset_Engineer	chenjun	Test_Date	2025/04/22
Remark			

### Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	2483.5	16.29	39.06	55.35	74.00	18.65	PASS	Vertical	PK
2	2483.5	16.29	26.48	42.77	54.00	11.23	PASS	Vertical	AV

### Note:

The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading - Correct Factor

Correct Factor = Preamplifier Factor - Antenna Factor - Cable Factor

## 7 Appendix A

Refer to Appendix: Bluetooth LE of EED32R80287201

## Statement

1. This report is considered invalid without approved signature, special seal and the seal on the perforation;
2. The Company Name shown on Report and Address, the sample(s) and sample information was/were provided by the applicant who should be responsible for the authenticity which CTI hasn't verified;
3. The result(s) shown in this report refer(s) only to the sample(s) tested;
4. Unless otherwise stated, the decision rule for conformity reporting is based on Binary Statement for Simple Acceptance Rule stated in ILAC-G8:09/2019/CNAS-GL015:2022;
5. Without written approval of CTI, this report can't be reproduced except in full;

\*\*\* End of Report \*\*\*