



## 1 General Information

#### **Client Information**

Applicant ...... : Zhongshan Luojia Electric Technology Co., Ltd

Address of applicant ...... : 4th Floor, No. 8 Industrial Avenue Middle, Jidong Second

Community Industrial Zone, Xiaolan Town, Zhongshan City, China

Manufacturer .....: The same as above

Address of manufacturer.....: The same as above

**General Description of E.U.T** 

FCC ID..... : 2BOKV-NJ-FCC21J

Product Name .....: Wireless Remote Control

Model No. ..... NJ-FCC21J

Model Description .....: : ---

Rated Voltage.....: Battery 3V (2\*1.5V AAA)

Battery Capacity .....:: : ---

Power Adapter .....: : ---

**Technical Characteristics of EUT** 

Operating Frequency .....: 433.92 MHz

Max. Field Strength ...... : 73.17 dBuV/m (at 3m distance)

Modulation....: ASK

Type of Antenna ..... : PCB Antenna

Antenna Gain .....: 0 dBi



# 2 RF Exposure Exemption

According to S1.1307(b)(3) and 447498 D04 Interim General RF Exposure Guidance v01, system operating under the provisions of this section shall be operating in a manner that the public is not exposed to radiofrequency energy level in excess limit for maximum permissible exposure.

FCC Rule Part 1.1307 (b)(3)(i)(A): The available maximum time-averaged power is no more than 1 mW, regardless of separation distance. This exemption may not be used in conjunction with other exemption criteria other than those in paragraph (b)(3)(ii)(A) of this section. Medical implant devices may only use this exemption and that in paragraph (b)(3)(ii)(A).

# 3 RF Exposure Evaluation

Calculated the EIRP from the radiated field strength in the far field using Equation:

$$EIRP=E_{Meas}+20log(d_{Meas})-104.7$$

Where

EIRP is the equivalent isotropically radiated power, in dBm

E<sub>Meas</sub> is the field strength of the emission at the measurement distance, in dBμV/m

 $d_{\text{Meas}}$  is the measurement distance, in m

## 4 Calculation Result

Radio Access Technology	Min. Distance (cm)	Prediction Frequency (MHz)	Max. Field Strength (dBµV/m)	EIRP (dBm)	EIRP (mW)	SAR Test Exclusion Threshold (mW)	Result
SRD	0.5	433.92	73.17	-21.99	0.01	1 1	Pass

====End of Report=====