

TEST REPORT NUMBER: (8525)077-0146(B)

TEST REPORT

Applicant:	SHANTOU CHENGHAI DISTRICT	Fax:	---
	DACHANG TOY TECHNOLOGY CO.,LTD	E-mail:	---
Address :	INDUSTRIAL BUILDINGS OF MEIXING HARDWARE CO., LTD.,DONGGANG ROAD,FENGXIANG STREET,CHENGHAI DISTRICT, SHANTOU		
Test Date :	2025-3-24 to 2025-3-28		

Manufacturer or Supplier :	SHANTOU CHENGHAI DISTRICT DACHANG TOY TECHNOLOGY CO.,LTD
Address :	INDUSTRIAL BUILDINGS OF MEIXING HARDWARE CO., LTD.,DONGGANG ROAD,FENGXIANG STREET,CHENGHAI DISTRICT, SHANTOU
Sample Description:	Brookstone Cosmic Rover
Model number:	719468BRS
Additional Model :	719468BRS, DC098
Rated Voltage:	DC 3V (2*1.5V AA batteries)
FCC ID :	2BOLR-DC098
The submitted sample of the above equipment has been tested according to following standard(s)	
47 CFR Part 15, Subpart C Section 15.227	
CONCLUSION: The submitted sample was found to COMPLY with the test requirement	

Assistant Manager



Name: Nick Lung

Date: MAY 23,2025

1 Contents

	Page
TEST REPORT	1
1 CONTENTS	2
.....	2
2 GENERAL INFORMATION	3
2.1 CLIENT INFORMATION	3
2.2 GENERAL DESCRIPTION OF EUT	3
2.3 GENERAL DESCRIPTION OF 2.4G CUSTOM	3
3 SAR EVALUATION	4
3.1 RF EXPOSURE COMPLIANCE REQUIREMENT	4
3.1.1 <i>Standard Requirement</i>	4
3.1.2 <i>Limits</i>	4
3.1.3 <i>EUT RF Exposure</i>	6

TEST REPORT NUMBER: (8525)077-0146(B)

2 General Information

2.1 Client Information

Applicant:	SHANTOU CHENGHAI DISTRICT DACHANG TOY TECHNOLOGY CO.,LTD
Address of Applicant:	INDUSTRIAL BUILDINGS OF MEIXING HARDWARE CO., LTD.,DONGGANG ROAD,FENGXIANG STREET,CHENGHAI DISTRICT, SHANTOU
Manufacturer:	SHANTOU CHENGHAI DISTRICT DACHANG TOY TECHNOLOGY CO.,LTD
Address of Manufacturer:	INDUSTRIAL BUILDINGS OF MEIXING HARDWARE CO., LTD.,DONGGANG ROAD,FENGXIANG STREET,CHENGHAI DISTRICT, SHANTOU

2.2 General Description of EUT

Product Name:	Brookstone Cosmic Rover
Model No.:	719468BRS, DC098
Test Model No	719468BRS
Trade Mark:	N/A
EUT Supports Radios application:	27MHz
Software Version:	V1.0
Hardware Version:	V1.0
Sample Type:	☐ Mobile ☒ Portable
EUT Power Supply:	DC 3V (2*1.5V AA batteries)

Note:

Model No.: 719468BRS, DC098.

Only the model 719468BRS was tested, since the circuit design ,layout ,and component used of the sample were identical between item (719468BRS) and item(DC098).

2.3 General Description of 2.4G custom

Operation Frequency:	27MHz
Modulation Technique:	Non Frequency Hopping Spread Spectrum(NFHSS)
Modulation Type:	ASK
Number of Channel:	1
Antenna Type:	External antenna
Antenna Gain:	0dBi

3 SAR Evaluation

3.1 RF Exposure Compliance Requirement

3.1.1 Standard Requirement

447498 D04 Interim General RF Exposure Guidance v01

3.2. SAR Test Reduction Guidance

SAR test reduction procedures [Glossary] allow using a particular set of test data as representative of other, similar, test conditions. This may be applied for data within different test positions (e.g. body, head, extremity), wireless modes (e.g. Wi-Fi, cellular), and frequency bands. This test reduction process provides for the use of test data for one specific channel, while referencing to those data for demonstrating compliance in other required channels for each test position of an exposure condition, within the operating mode of a frequency band. This is limited specifically to when the reported 1-g or 10-g SAR for the mid-band or highest output power channel meets any of the following conditions.

3.1.2 Limits

SAR-based thresholds are derived based on frequency, power, and separation distance of the RF source. The formula defines the thresholds in general for either available maximum time-averaged power or maximum time-averaged ERP, whichever is greater.

If the ERP of a device is not easily determined, such as for a portable device with a small form factor, the applicant may use the available maximum time-averaged power exclusively if the device antenna or radiating structure does not exceed an electrical length of $\lambda/4$.

As for devices with antennas of length greater than $\lambda/4$ where the gain is not well defined, but always less than that of a half-wave dipole (length $\lambda/2$), the available maximum time-averaged power generated by the device may be used in place of the maximum time-averaged ERP, where that value is not known.

The separation distance is the smallest distance from any part of the antenna or radiating structure for all persons, during operation at the applicable ERP. In the case of mobile or portable devices, the separation distance is from the outer housing of the device where it is closest to the antenna.

The SAR-based exemption formula of § 1.1307(b)(3)(i)(B), repeated here as Formula (B.2), applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power or effective radiated power (ERP), whichever is greater, of less than or equal to the threshold P_{th} (mW).

This method shall only be used at separation distances from 0.5 cm to 40 cm and at frequencies from 0.3 GHz to 6 GHz (inclusive). P_{th} is given by Formula (B.2).

TEST REPORT NUMBER: (8525)077-0146(B)

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

(B. 2)

where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right)$$

and f is in GHz, d is the separation distance (cm), and $ERP_{20\text{cm}}$ is per Formula (B.1).
The example values shown in Table B.2 are for illustration only.

Table B.2—Example Power Thresholds (mW)

Frequency (MHz)	Distance (mm)									
	5	10	15	20	25	30	35	40	45	50
300	39	65	88	110	129	148	166	184	201	217
450	22	44	67	89	112	135	158	180	203	226
835	9	25	44	66	90	116	145	175	207	240
1900	3	12	26	44	66	92	122	157	195	236
2450	3	10	22	38	59	83	111	143	179	219
3600	2	8	18	32	49	71	96	125	158	195
5800	1	6	14	25	40	58	80	106	136	169

3.1.3 EUT RF Exposure

Measurement Data

$$EIRP = E_{Meas} + 20\log(d_{Meas}) - 104.7$$

where

$EIRP$ is the equivalent isotropically radiated power, in dBm
 E_{Meas} is the field strength of the emission at the measurement distance, in dBμV/m
 d_{Meas} is the measurement distance, in m

Channel	EIRP (dBuv/m)	EIRP (dBm)	ERP (dBm)	Maximum tune-up Power (mW)	Exclusion threshold (mW)
27MHz	60.34	-34.81	-32.66	0.0005	1.0

Remark: The Max Conducted Peak Output Power data refer to report Report No.: (8525)077-0146(A)

*** END OF REPORT ***