

FCC 47 CFR MPE REPORT

Mercer Vale Corporation

Bluetooth speaker

Model Number: HD

Additional Model: HD * where “**” can be blank, number(s), letter(s), hyphen, or their combination, denoting properties other than mechanical and electrical features.

FCC ID: 2BONC-HD

Applicant:	Mercer Vale Corporation
Address:	Unit CDE, 8F Nanyuan Maple Leaf Building, 1088 Nanshan Avenue,
	Shenzhen, Guangdong Province, China
Prepared By:	EST Technology Co., Ltd.
	Chilingxiang, Qishantou, Santun, Houjie, Dongguan, Guangdong, China
	Tel: 86-769-83081888-808

Report Number:	ESTE-R2504287
Date of Test:	Dec. 17, 2024~ Apr. 19, 2025
Date of Report:	Apr. 24, 2025

Maximum Permissible Exposure

1. Applicable Standards

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

1.1. Limits for Maximum Permissible Exposure (MPE)

(a) Limits for Occupational/Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-10000			5	6

(b) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-10000			1.0	30

Note: f=frequency in MHz; *Plane-wave equivalent power density

1.2. MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric Field (V/m)

P = Peak RF output Power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained

2. Conducted Power Result

Mode	Frequency (MHz)	Peak output power (dBm)	Peak output power (mW)
GFSK	2402	5.59	3.622
	2441	5.62	3.648
	2480	5.74	3.750
$\pi/4$ -DQPSK	2402	7.53	5.662
	2441	7.42	5.521
	2480	7.46	5.572
8-DPSK	2402	8.04	6.368
	2441	7.86	6.109
	2480	7.86	6.109
BLE 1M	2402	9.22	8.356
	2440	9.45	8.810
	2480	9.77	9.484
BLE 2M	2402	9.26	8.433
	2440	9.49	8.892
	2480	9.8	9.550

3. Calculated Result and Limit

Mode	Peak output power (dBm)	Target power (dBm)	MAX Target power (dBm)	Antenna gain		Power Density (S) (mW /cm ²)	Limited of Power Density (S) (mW /cm ²)	Test Result
				(dBi)	(Linear)			
GFSK	5.74	5±1	6	1.88	1.54	0.00122	1	Complies
π/4-DQPSK	7.53	7±1	8	1.88	1.54	0.00194	1	Complies
8-DPSK	8.04	8±1	9	1.88	1.54	0.00244	1	Complies
BLE 1M	9.77	9±1	10	1.88	1.54	0.00307	1	Complies
BLE 2M	9.8	9±1	10	1.88	1.54	0.00307	1	Complies

End of Test Report