



Manual for smart devices

目录

CONTENTS

1

产品介绍
product introduction

2

基础操作
basic operations

设备介绍

equipment introduction

遥控器说明 Remote control manual

系统菜单键

system menu key

数字键

number key

音量键

volume key

开机键

power button

方向键和确认键

direction keys and
confirmation key

暂停键

pause key



Equipment Introduction

Playback Format Description

Model number	Resolution	Video format	Image format
Loom (Dual Screen)	Up 1920 x 1080	Video H265, audio MP3	JPG
	Below 1920 multiplied by 360	Video H265, audio MP3	JPG
	Full screen: 1920*1440	Video H265, audio MP3	JPG
Loom (single screen)	1920 x 1080	Video H265, audio MP3	JPG
Vertical machine	1080 by 1920	Video H265, audio MP3	JPG
Vertical machine (dual-screen)	Up 1920 x 1080	Video H265, audio MP3	JPG
	Below 768 x 136	Video H265, audio MP3	JPG
Vertical monitor (25 inches)	1080 x 2560	Video H265, audio MP3	JPG

Basic operations

Basic Information

The screen time indicates that this display can be turned off by setting the switch.

Basic information such as time, model, public key time, etc.

Network information such as 4G strength, ICCID, server login status, etc.

Software version information of different modules of the device

Date: 2025-01-17 14:38 Friday	Local Advertisement: > FM_FACTORY.MPL
Internal storage space: Total: 24.26GB Available: 24.07GB	Advertisement interlude: No schedule file
Location: 9998999999992	Live broadcast list: No schedule file
SN: 74346320	Local Subtitle: No schedule file
Model: V32-A020-K01	Subtitles: No schedule file
Network Stop Module: Standalone, 1 group, 51.1.1.250111.1	Local linkage: List is normal
Single-player: 1	Broadcasting Failure: No Content Available
Screen reference: 320EUNDPBS400	
Root certificate: Verification successful, China	
Public key validity period: June 6, 2022 - June 3, 2032	
Card Production: No card production information	
WiFi chip: No device. Bluetooth status: No device.	
Network mode: Woodworking (Network Module)	
Weak signal strength: No signal. Network status: Not connected.	
IoT server: Log in	Push subtitle status: Waiting to start pushing subtitle updates
Product Key: a1o4hVhDsPt	Waiting to start pushing program status: Waiting to start pushing program updates
Network authentication: Unknown (70, 57)	Waiting to start pushing program updates: Waiting to start live broadcast program status
ICCID: Retrieval in progress	Waiting to start live broadcast program updates: Waiting to start
Operator: Retrieval in progress	OTA download status: Waiting to start
4G module version: YG_Jan 08 2024 15:04:05	Import successful: 2025-01-17 11:12:50-u
Display driver version: 1.4.3.250111.1	Device shadow: Subscription has not started
Software version: A2.4.1228.1	Synchronization time: Subscription has not yet started
- version: 20241228.124339	OSS Token: Subscription has not started
G driver version: YG_Nov 20 2024 14:46:51	Number of reports submitted by the monitor: 6
Encryption 1.0: Activated Key	
Encryption 2.0: Key Activation Completed	

Playback Information

The list information of the devices being played

The download status of information programs, updates and other files pushed via the network

This interface can be accessed by pressing the remote control to enter the password. After that, press "GOTO" + "1" to open.

Basic operations

time setting

Select date settings



After setting the time using the arrow keys, choose save and return.

This interface through the remote control to open input password, click open system menu

Basic operations

Basic operations

Select scheduled settings
Unified setting: Repeat every day
Set by week: Set separately for each of the 7 days within a week



Three sets of startup and shutdown time groups can be set.

This interface can be opened using the remote control. After entering the password, press the system menu button to open it.

Basic operations

Time-based volume settings

Select volume settings, open time-of-day volume settings



Default provision of three sets of time-based volume settings (maximum can be 20 sets).



This interface can be opened using the remote control. After entering the password, press the system menu button to open it.