

**CFR 47 FCC PART 15 SUBPART C
ISED RSS-247 Issue 3**

TEST REPORT

For

LED Lamp

FCC MODEL NUMBER: KO-B30-09-120D-DC1-01

FCC SERIES MODEL: KO-B30-09-120D-DC1-xx ("xx" may be "00" to "99")

IC MODEL NUMBER: KO-B30-09-120D-DC1-01

REPORT NUMBER: 4791745577-1-RF-2

FCC ID:2BOODB3009120D

IC: 33820-B3009120D

ISSUE DATE: May 7, 2025

Prepared for

**Korrus, Inc
843 N Spring Street, Suite 404 Los Angeles, CA 90012 United States**

Prepared by

**UL Verification Services (Guangzhou) Co., Ltd., Song Shan Lake Branch
Room 101, Building 2, No.4, Information Road, Songshan Lake, Dongguan,
Guangdong, China**

Tel: +86 769 22038881

Fax: +86 769 33244054

Website: www.ul.com

The results reported herein have been performed in accordance with the laboratory's terms of accreditation. This report shall not be reproduced except in full without the written approval of the Laboratory. The results in this report apply to the test sample(s) mentioned above at the time of the testing period only and are not to be used to indicate applicability to other similar products.

Revision History

Rev.	Issue Date	Revisions	Revised By
V0	May 7, 2025	Initial Issue	

Summary of Test Results

Test Item	Clause	Limit/Requirement	Result
Antenna Requirement	N/A	FCC Part 15.203/15.247 (c) RSS-GEN Clause 6.8	Pass
AC Power Line Conducted Emission	ANSI C63.10-2013, Clause 6.2	FCC Part 15.207 RSS-GEN Clause 8.8	Pass
Conducted Output Power	ANSI C63.10-2013, Clause 11.9.2.3.1	FCC Part 15.247 (b)(3) RSS-247 Clause 5.4 (d)	Pass
6dB Bandwidth and 99% Occupied Bandwidth	ANSI C63.10-2013, Clause 11.8.1	FCC Part 15.247 (a)(2) RSS-247 Clause 5.2 (a) ISED RSS-Gen Clause 6.7	Pass
Power Spectral Density	ANSI C63.10-2013, Clause 11.10.2	FCC Part 15.247 (e) RSS-247 Clause 5.2 (b)	Pass
Conducted Band edge and spurious emission	ANSI C63.10-2013, Clause 11.11	FCC Part 15.247(d) RSS-247 Clause 5.5	Pass
Radiated Band edge and Spurious Emission	ANSI C63.10-2013, Clause 11.12 & Clause 11.13	FCC Part 15.247 (d) FCC Part 15.205/15.209 RSS-247 Clause 5.5 RSS-GEN Clause 8.9	Pass
Duty Cycle	ANSI C63.10-2013, Clause 11.6	None; for reporting purposes only.	Pass

*This test report is only published to and used by the applicant, and it is not for evidence purpose in China.

*The measurement result for the sample received is <Pass> according to <CFR 47 FCC PART 15 SUBPART C
ISED RSS-247 Issue 3> when <Simple Acceptance> decision rule is applied.

CONTENTS

1. ATTESTATION OF TEST RESULTS	6
2. TEST METHODOLOGY	7
3. FACILITIES AND ACCREDITATION	7
4. CALIBRATION AND UNCERTAINTY	8
4.1. MEASURING INSTRUMENT CALIBRATION	8
4.2. MEASUREMENT UNCERTAINTY	8
5. EQUIPMENT UNDER TEST	9
5.1. DESCRIPTION OF EUT	9
5.2. CHANNEL LIST	9
5.3. MAXIMUM POWER	9
5.4. TEST CHANNEL CONFIGURATION	10
5.5. THE WORSE CASE POWER SETTING PARAMETER	10
5.6. DESCRIPTION OF AVAILABLE ANTENNAS	11
5.7. SUPPORT UNITS FOR SYSTEM TEST	12
6. MEASURING EQUIPMENT AND SOFTWARE USED	13
7. ANTENNA PORT TEST RESULTS	16
7.1. CONDUCTED OUTPUT POWER	16
7.2. 6DB BANDWIDTH AND 99% OCCUPIED BANDWIDTH	17
7.3. POWER SPECTRAL DENSITY	19
7.4. CONDUCTED BAND EDGE AND SPURIOUS EMISSION	20
7.5. DUTY CYCLE	22
8. RADIATED TEST RESULTS	23
8.1. RESTRICTED BANDEDGE	31
8.2. SPURIOUS EMISSIONS(1 GHZ~3 GHZ)	49
8.3. SPURIOUS EMISSIONS(3 GHZ~18 GHZ)	55
8.4. SPURIOUS EMISSIONS(9 KHZ~30 MHZ)	79
8.5. SPURIOUS EMISSIONS(18 GHZ~26 GHZ)	82
8.6. SPURIOUS EMISSIONS(30 MHZ~1 GHZ)	84
9. ANTENNA REQUIREMENT	86
10. AC POWER LINE CONDUCTED EMISSION	87
11. TEST DATA	91

11.1.	APPENDIX A: DTS BANDWIDTH	91
11.1.1.	Test Result	91
11.1.2.	Test Graphs	92
11.2.	APPENDIX B: OCCUPIED CHANNEL BANDWIDTH	96
11.2.1.	Test Result	96
11.2.2.	Test Graphs	97
11.3.	APPENDIX C: MAXIMUM CONDUCTED OUTPUT POWER	101
11.3.1.	Test Result	101
11.4.	APPENDIX D: MAXIMUM POWER SPECTRAL DENSITY	102
11.4.1.	Test Result	102
11.4.2.	Test Graphs	103
11.5.	APPENDIX E: BAND EDGE MEASUREMENTS	107
11.5.1.	Test Result	107
11.5.2.	Test Graphs	108
11.6.	APPENDIX F: CONDUCTED SPURIOUS EMISSION	111
11.6.1.	Test Result	111
11.6.2.	Test Graphs	112
11.7.	APPENDIX G: DUTY CYCLE	124
11.7.1.	Test Result	124
11.7.2.	Test Graphs	125

1. ATTESTATION OF TEST RESULTS

Applicant Information

Company Name: Korrus, Inc
Address: 843 N Spring Street, Suite 404 Los Angeles, CA 90012 United States

Manufacturer Information

Company Name: Korrus, Inc
Address: 843 N Spring Street, Suite 404 Los Angeles, CA 90012 United States

EUT Information

EUT Name: LED Lamp
FCC Model: KO-B30-09-120D-DC1-01
IC Model: KO-B30-09-120D-DC1-01
FCC Series Model: KO-B30-09-120D-DC1-xx ("xx" may be "00" to "99")
FCC Model difference: Please refer to section 5.1
Brand: Korrus
Sample Received Date: April 10, 2025
Sample Status: Normal
Sample ID: 8340892
Date of Tested: April 11, 2025 to May 7, 2025

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 FCC PART 15 SUBPART C ISED RSS-247 Issue 3	Pass

Prepared By:



Daniel Zhang
Project Engineer

Checked By:



Kebo Zhang
Senior Project Engineer

Approved By:



Stephen Guo
Operations Manager

2. TEST METHODOLOGY

All tests were performed in accordance with the standard CFR 47 FCC PART 15 SUBPART C ISSED RSS-247 Issue 3, KDB 558074 D01 15.247 Meas Guidance v05r02, KDB 414788 D01 Radiated Test Site v01r01, CFR 47 FCC Part 2, ANSI C63.10-2013 and ISSED RSS-GEN Issue 5

3. FACILITIES AND ACCREDITATION

Accreditation Certificate	A2LA (Certificate No.: 4102.01) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with A2LA. FCC (FCC Designation No.: CN1187) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. Has been recognized to perform compliance testing on equipment subject to the Commission's Declaration of Conformity (DoC) and Certification rules. ISED (Company No.: 21320) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been registered and fully described in a report filed with ISSED. The Company Number is 21320 and the test lab Conformity Assessment Body Identifier (CABID) is CN0046.
---------------------------	---

Note 1:

All tests measurement facilities use to collect the measurement data are located at Room 101, Building 2, No.4, Information Road, Songshan Lake, Dongguan, Guangdong, China.

Note 2:

The test anechoic chamber in UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch had been calibrated and compared to the open field sites and the test anechoic chamber is shown to be equivalent to or worst case from the open field site.

Note 3:

For below 30 MHz, lab had performed measurements at test anechoic chamber and comparing to measurements obtained on an open field site. And these measurements below 30 MHz had been correlated to measurements performed on an OFS.

4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations and is traceable to recognized national standards.

4.2. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Test Item	Uncertainty
Conduction emission	3.62 dB
Radiated Emission (Included Fundamental Emission) (9 kHz ~ 30 MHz)	2.2 dB
Radiated Emission (Included Fundamental Emission) (30 MHz ~ 1 GHz)	4.00 dB
Radiated Emission (Included Fundamental Emission) (1 GHz to 26 GHz)	5.78 dB (1 GHz ~ 18 GHz)
	5.23 dB (18 GHz ~ 26 GHz)
Duty Cycle	±0.028%
DTS and 99% Occupied Bandwidth	±0.0196%
Maximum Conducted Output Power	±0.686 dB
Maximum Power Spectral Density Level	±0.743 dB
Conducted Band-edge Compliance	±1.328 dB
Conducted Unwanted Emissions In Non-restricted Frequency Bands	±0.746 dB (9 kHz ~ 1 GHz)
	±1.328dB (1 GHz ~ 26 GHz)
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	

5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

EUT Name	LED Lamp
FCC Model	KO-B30-09-120D-DC1-01
IC Model	KO-B30-09-120D-DC1-01
FCC Series Model	KO-B30-09-120D-DC1-xx ("xx" may be "00" to "99")
FCC Model difference	Where "xx" may be "00" to "99", which designates for different beam angle, color of eyelet contact, different package of style and CCT.

Frequency Range:	2412 MHz to 2462 MHz
Type of Modulation:	IEEE 802.11b: DSSS(CCK, DQPSK, DBPSK) IEEE 802.11g/n: OFDM(64-QAM, 16-QAM, QPSK, BPSK)
Radio Technology:	IEEE 802.11b/g/n HT20/n HT40
Normal Test Voltage:	AC 120 V 60 Hz
EUT Test software:	EspRFTTestTool_v2.7

5.2. CHANNEL LIST

Channel List For Bandwidth=20 MHz							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	4	2427	7	2442	10	2457
2	2417	5	2432	8	2447	11	2462
3	2422	6	2437	9	2452	/	/

Channel List For Bandwidth=40 MHz							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
3	2422	5	2432	7	2442	9	2452
4	2427	6	2437	8	2447	/	/

5.3. MAXIMUM POWER

IEEE Std. 802.11	Frequency (MHz)	Channel Number	Maximum Conducted AVG Output Power (dBm)	Maximum AVG EIRP (dBm)
b	2412 ~ 2462	1-11[11]	17.20	20.05
g	2412 ~ 2462	1-11[11]	15.81	18.66
n HT20	2412 ~ 2462	1-11[11]	15.57	18.42
n HT40	2422 ~ 2452	3-9[7]	14.86	17.71

5.4. TEST CHANNEL CONFIGURATION

IEEE Std. 802.11	Test Channel Number	Frequency
b	CH 1(Low Channel), CH 6(MID Channel), CH 11(High Channel)	2412 MHz, 2437 MHz, 2462 MHz
g	CH 1(Low Channel), CH 6(MID Channel), CH 11(High Channel)	2412 MHz, 2437 MHz, 2462 MHz
n HT20	CH 1(Low Channel), CH 6(MID Channel), CH 11(High Channel)	2412 MHz, 2437 MHz, 2462 MHz
n HT40	CH 3(Low Channel), CH 6(MID Channel), CH 9(High Channel)	2422 MHz, 2437 MHz, 2452 MHz

5.5. THE WORSE CASE POWER SETTING PARAMETER

The Worse Case Power Setting Parameter under 2400 ~ 2483.5MHz Band							
Test Software		EspRFTTestTool_v2.7					
Modulation Mode	Transmit Antenna Number	Test Channel					
		NCB: 20MHz			NCB: 40MHz		
		CH 1	CH 6	CH 11	CH 3	CH 6	CH 9
802.11b	1	0	0	0	/		
802.11g	1	7	4	9			
802.11n HT20	1	2	0	4			
802.11n HT40	1	/			4	0	8

WORST-CASE CONFIGURATIONS

The EUT was tested in the following configuration(s):

Controlled in test mode using a software application on the EUT supplied by customer. The application was used to enable a continuous transmission and to select the mode, test channels, bandwidth, data rates as required.

Test channels referring to section 5.4.

Maximum power setting referring to section 5.5.

Worst-case data rates as provided by the client were:

802.11b mode: 1 Mbps
802.11g mode: 6 Mbps
802.11n HT20 mode: MCS0
802.11n HT40 mode: MCS0

The measured additional path loss was included in any path loss calculations for all RF cable used during tested.

5.6. DESCRIPTION OF AVAILABLE ANTENNAS

Antenna	Frequency (MHz)	Antenna Type	MAX Antenna Gain (dBi)
1	2412-2462	PCB antenna	2.85

Test Mode	Transmit and Receive Mode	Description
IEEE 802.11b	☒ 1TX, 1RX	ANT 1 can be used as transmitting/receiving antenna.
IEEE 802.11g	☒ 1TX, 1RX	ANT 1 can be used as transmitting/receiving antenna.
IEEE 802.11n HT20	☒ 1TX, 1RX	ANT 1 can be used as transmitting/receiving antenna.
IEEE 802.11n HT40	☒ 1TX, 1RX	ANT 1 can be used as transmitting/receiving antenna.

Note:

- 1.BT&WLAN 2.4G can't transmit simultaneously. (declared by client)
- 2.EUT does not support diversity or MIMO mode. (declared by client)

5.7. SUPPORT UNITS FOR SYSTEM TEST

SUPPORT EQUIPMENT

Item	Equipment	Brand Name	Model Name	Remark
1	PC	Lenovo	E14	/
2	AC Power Line	/	/	1.5m

I/O CABLES

Cable No	Port	Connector Type	Cable Type	Cable Length(m)	Remarks
1	USB	/	/	1.0	/


ACCESSORIES

Item	Accessory	Brand Name	Model Name	Description
/	/	/	/	/

TEST SETUP

The EUT can work in engineering mode with a software through a Laptop.
All tests are done under the condition that EUT operates in packet-based transmission mode.

SETUP DIAGRAM FOR TESTS



Note: AC Adaptor only use for AC POWER LINE CONDUCTED EMISSION test

6. MEASURING EQUIPMENT AND SOFTWARE USED

R&S TS 8997 Test System					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due. Date
Power sensor, Power Meter	R&S	OSP120	100921	Dec.27,2024	Dec.26,2025
Vector Signal Generator	R&S	SMBV100A	261637	Sep.28, 2024	Sep.27, 2025
Signal Generator	R&S	SMB100A	178553	Sep.28, 2024	Sep.27, 2025
Signal Analyzer	R&S	FSV40	101118	Sep.28, 2024	Sep.27, 2025
Software					
Description	Manufacturer		Name		Version
For R&S TS 8997 Test System	Rohde & Schwarz		EMC 32		10.60.10
Tonsend RF Test System					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due. Date
Wireless Connectivity Tester	R&S	CMW270	1201.0002N75-102	Sep.13, 2024	Sep.12, 2025
PXA Signal Analyzer	Keysight	N9030A	MY55410512	Sep.28, 2024	Sep.27, 2025
MXG Vector Signal Generator	Keysight	N5182B	MY56200284	Sep.28, 2024	Sep.27, 2025
MXG Vector Signal Generator	Keysight	N5172B	MY56200301	Sep.28, 2024	Sep.27, 2025
DC power supply	Keysight	E3642A	MY55159130	Sep.28, 2024	Sep.27, 2025
Temperature & Humidity Chamber	SANMOOD	SG-80-CC-2	2088	Sep.28, 2024	Sep.27, 2025
Attenuator	Aglient	8495B	2814a12853	Sep.28, 2024	Sep.27, 2025
RF Control Unit	Tonscend	JS0806-2	23B80620666	Dec.27,2024	Dec.26,2025
Software					
Description	Manufacturer	Name			Version
Tonsend SRD Test System	Tonsend	JS1120-3 RF Test System			V3.2.22

Conducted Emissions					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
EMI Test Receiver	R&S	ESR3	101961	Sep.28, 2024	Sep.27, 2025
Two-Line V-Network	R&S	ENV216	101983	Sep.28, 2024	Sep.27, 2025
Artificial Mains Networks	Schwarzbeck	NSLK 8126	8126465	Sep.28, 2024	Sep.27, 2025
Software					
Description			Manufacturer	Name	Version
Test Software for Conducted Emissions			Farad	EZ-EMC	Ver. UL-3A1

Radiated Emissions					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
MXE EMI Receiver	KESIGHT	N9038A	MY56400036	Sep.28, 2024	Sep.27, 2025
Hybrid Log Periodic Antenna	TDK	HLP-3003C	130960	June 28, 2024	June.27 2027
Preamplifier	HP	8447D	2944A09099	Sep.28, 2024	Sep.27, 2025
EMI Measurement Receiver	R&S	ESR26	101377	Sep.28, 2024	Sep.27, 2025
Horn Antenna	ETS-Lindgren	3117	213191	Jan.29, 2023	Jan.28, 2026
Preamplifier	TDK	PA-02-0118	TRS-305-00067	Sep.28, 2024	Sep.27, 2025
Horn Antenna	Schwarzbeck	BBHA9170	697	Jun 30, 2024	Jun 29, 2027
Preamplifier	TDK	PA-02-2	TRS-307-00003	Sep.28, 2024	Sep.27, 2025
Preamplifier	TDK	PA-02-3	TRS-308-00002	Sep.28, 2024	Sep.27, 2025
Loop antenna	Schwarzbeck	1519B	00008	Dec.09, 2024	Dec.08, 2027
High Pass Filter	Wi	WHKX10-2700-3000-18000-40SS	23	Sep.28, 2024	Sep.27, 2025
Band Reject Filter	Wainwright	WRCJV8-2350-2400-2483.5-2533.5-40SS	4	Sep.28, 2024	Sep.27, 2025
Software					
Description			Manufacturer	Name	Version
Test Software for Radiated Emissions			Farad	EZ-EMC	Ver. UL-3A1

Other Instrument					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
Temperature humidity probe	OMEGA	ITHX-SD-5	18470007	Oct.8, 2024	Oct.7, 2025
Barometer	Yiyi	Baro	N/A	Oct.10, 2024	Oct.9, 2025
Attenuator	Agilent	8495B	2814a12853	Sep.28, 2024	Sep.27, 2025

7. ANTENNA PORT TEST RESULTS

7.1. CONDUCTED OUTPUT POWER

LIMITS

CFR 47 FCC Part15 (15.247) Subpart C ISED RSS-247 ISSUE 3			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC 15.247(b)(3) ISED RSS-247 5.4 (d)	AVG Output Power	1 watt or 30 dBm	2400-2483.5

TEST PROCEDURE


Refer to ANSI C63.10-2013 clause 11.9.2.3.1.

Connect the EUT to a low loss RF cable from the antenna port to the power sensor (video bandwidth is greater than the occupied bandwidth).

Measure peak emission level, the indicated level is the average output power, after any corrections for external attenuators and cables.

The test result in dBm by adding $[10 \log (1 / D)]$, where D is the duty cycle.

TEST SETUP



TEST ENVIRONMENT

Temperature	22.5°C	Relative Humidity	55.1%
Atmosphere Pressure	101kPa	Test Voltage	AC 120V 60Hz

TEST DATE / ENGINEER

Test Date	April 17, 2025	Test By	Walker Yuan
-----------	----------------	---------	-------------

TEST RESULTS

Please refer to section "Test Data" - Appendix C

7.2. 6DB BANDWIDTH AND 99% OCCUPIED BANDWIDTH

LIMITS

CFR 47 FCC Part15 (15.247) Subpart C ISED RSS-247 ISSUE 3			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC 15.247(a)(2) ISED RSS-247 5.2 (a)	6 dB Bandwidth	≥ 500 kHz	2400-2483.5
ISED RSS-Gen Clause 6.7	99 % Occupied Bandwidth	For reporting purposes only.	2400-2483.5

TEST PROCEDURE


Refer to ANSI C63.10-2013 clause 11.8 for DTS bandwidth and clause 6.9 for Occupied Bandwidth.

Connect the EUT to the spectrum analyzer and use the following settings:

Center Frequency	The center frequency of the channel under test
Frequency Span	For 6 dB Bandwidth: Enough to capture all products of the modulation carrier emission For 99 % Occupied Bandwidth: Between 1.5 times and 5.0 times the OBW
Detector	Peak
RBW	For 6 dB Bandwidth: 100 kHz For 99 % Occupied Bandwidth: 1 % to 5 % of the occupied bandwidth
VBW	For 6 dB Bandwidth: $\geq 3 \times$ RBW For 99 % Occupied Bandwidth: $\geq 3 \times$ RBW
Trace	Max hold
Sweep	Auto couple

a) Use the 99 % power bandwidth function of the instrument, allow the trace to stabilize and report the measured bandwidth.

b) Allow the trace to stabilize and measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

TEST SETUP**TEST ENVIRONMENT**

Temperature	22.5℃	Relative Humidity	55.1%
Atmosphere Pressure	101kPa	Test Voltage	AC 120V 60Hz

TEST DATE / ENGINEER

Test Date	April 17, 2025	Test By	Walker Yuan
-----------	----------------	---------	-------------

TEST RESULTS

Please refer to section "Test Data" - Appendix A&B

7.3. POWER SPECTRAL DENSITY

LIMITS

CFR 47 FCC Part15 (15.247) Subpart C ISED RSS-247 ISSUE 3			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC §15.247 (e) ISED RSS-247 5.2 (b)	Power Spectral Density	8 dBm in any 3 kHz band	2400-2483.5

TEST PROCEDURE

Refer to ANSI C63.10-2013 clause 11.10.2.


Connect the EUT to the spectrum analyzer and use the following settings:

Center Frequency	The center frequency of the channel under test
Detector	power averaging (rms)
RBW	$3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$
VBW	$\geq 3 \times \text{RBW}$
Span	$1.5 \times \text{OBW bandwidth}$
Trace	Employ trace averaging(rms)mode over a minimum of 100 traces
Sweep time	Auto couple

Allow trace to fully stabilize and use the peak marker function to determine the maximum amplitude level within the RBW.

If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

TEST SETUP



TEST ENVIRONMENT

Temperature	22.5°C	Relative Humidity	55.1%
Atmosphere Pressure	101kPa	Test Voltage	AC 120V 60Hz

TEST DATE / ENGINEER

Test Date	April 17, 2025	Test By	Walker Yuan
-----------	----------------	---------	-------------

TEST RESULTS

Please refer to section "Test Data" - Appendix D

7.4. CONDUCTED BAND EDGE AND SPURIOUS EMISSION

LIMITS

CFR 47 FCC Part15 (15.247) Subpart C ISED RSS-247 ISSUE 3		
Section	Test Item	Limit
CFR 47 FCC §15.247 (d) ISED RSS-247 5.5	Conducted Bandedge and Spurious Emissions	at least 30 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power

TEST PROCEDURE

Refer to ANSI C63.10-2013 clause 11.11 and 11.13.

Connect the EUT to the spectrum analyzer and use the following settings for reference level measurement:


Center Frequency	The center frequency of the channel under test
Detector	Peak
RBW	100 kHz
VBW	$\geq 3 \times \text{RBW}$
Span	1.5 x DTS bandwidth
Trace	Max hold
Sweep time	Auto couple.

Allow trace to fully stabilize and use the peak marker function to determine the maximum PSD level.

Change the settings for emission level measurement:

Span	Set the center frequency and span to encompass frequency range to be measured
Detector	Peak
RBW	100 kHz
VBW	$\geq 3 \times \text{RBW}$
measurement points	$\geq \text{span}/\text{RBW}$
Trace	Max hold
Sweep time	Auto couple.

Allow trace to fully stabilize and use the peak marker function to determine the maximum PSD level. Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum requirements specified in 11.11.

TEST SETUP**TEST ENVIRONMENT**

Temperature	22.5℃	Relative Humidity	55.1%
Atmosphere Pressure	101kPa	Test Voltage	AC 120V 60Hz

TEST DATE / ENGINEER

Test Date	April 17, 2025	Test By	Walker Yuan
-----------	----------------	---------	-------------

TEST RESULTS

Please refer to section "Test Data" - Appendix E&F

7.5. DUTY CYCLE


LIMITS

None; for reporting purposes only.

TEST PROCEDURE

Refer to ANSI C63.10-2013 clause 11.6 Zero – Span Spectrum Analyzer method.

TEST SETUP



TEST ENVIRONMENT

Temperature	22.5°C	Relative Humidity	55.1%
Atmosphere Pressure	101kPa	Test Voltage	AC 120V 60Hz

TEST DATE / ENGINEER

Test Date	April 17, 2025	Test By	Walker Yuan
-----------	----------------	---------	-------------

TEST RESULTS

Please refer to section "Test Data" - Appendix G

8. RADIATED TEST RESULTS

LIMITS

Please refer to CFR 47 FCC §15.205 and §15.209.

Please refer to ISSED RSS-GEN Clause 8.9 and Clause 8.10.

Radiation Disturbance Test Limit for FCC (Class B) (9 kHz ~ 1 GHz)

Emissions radiated outside of the specified frequency bands above 30 MHz			
Frequency Range (MHz)	Field Strength Limit ($\mu\text{V/m}$) at 3 m	Field Strength Limit (dBuV/m) at 3 m	
		Quasi-Peak	
30 - 88	100	40	
88 - 216	150	43.5	
216 - 960	200	46	
Above 960	500	54	
Above 1000	500	Peak	Average
		74	54

FCC Emissions radiated outside of the specified frequency bands below 30 MHz		
Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30

ISSED General field strength limits at frequencies below 30 MHz

Table 6 – General field strength limits at frequencies below 30 MHz		
Frequency	Magnetic field strength (H-Field) ($\mu\text{A/m}$)	Measurement distance (m)
9 - 490 kHz ^{Note 1}	6.37/F (F in kHz)	300
490 - 1705 kHz	63.7/F (F in kHz)	30
1.705 - 30 MHz	0.08	30

Note 1: The emission limits for the ranges 9-90 kHz and 110-490 kHz are based on measurements employing a linear average detector.

ISED Restricted bands please refer to ISED RSS-GEN Clause 8.10

MHz	MHz	GHz
0.090 - 0.110	149.9 - 150.05	9.0 - 9.2
0.495 - 0.505	156.52475 - 156.52525	9.3 - 9.5
2.1735 - 2.1905	156.7 - 156.9	10.6 - 12.7
3.020 - 3.026	162.0125 - 167.17	13.25 - 13.4
4.125 - 4.128	167.72 - 173.2	14.47 - 14.6
4.17725 - 4.17775	240 - 285	15.35 - 16.2
4.20725 - 4.20775	322 - 335.4	17.7 - 21.4
5.677 - 5.683	399.9 - 410	22.01 - 23.12
6.215 - 6.218	608 - 614	23.6 - 24.0
6.26775 - 6.26825	960 - 1427	31.2 - 31.8
6.31175 - 6.31225	1435 - 1626.5	36.43 - 36.5
8.291 - 8.294	1645.5 - 1646.5	Above 38.6
8.362 - 8.366	1660 - 1710	
8.37625 - 8.38675	1718.8 - 1722.2	
8.41425 - 8.41475	2200 - 2300	
12.29 - 12.293	2310 - 2390	
12.51975 - 12.52025	2483.5 - 2500	
12.57675 - 12.57725	2655 - 2900	
13.36 - 13.41	3260 - 3267	
16.42 - 16.423	3332 - 3339	
16.69475 - 16.69525	3345.8 - 3358	
16.80425 - 16.80475	3500 - 4400	
25.5 - 25.67	4500 - 5150	
37.5 - 38.25	5350 - 5460	
73 - 74.6	7250 - 7750	
74.8 - 75.2	8025 - 8500	
108 - 138		

Note 1: Certain frequency bands listed in table 7 and in bands above 38.6 GHz are designated for licence-exempt applications. These frequency bands and the requirements that apply to related devices are set out in the 200 and 300 series of RSSs.

FCC Restricted bands of operation refer to FCC §15.205 (a):

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(²)
13.36-13.41			

Note: ¹Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

²Above 38.6c

TEST PROCEDURE

Below 30 MHz

The setting of the spectrum analyzer

RBW	200 Hz (From 9 kHz to 0.15 MHz)/ 9 kHz (From 0.15 MHz to 30 MHz)
VBW	200 Hz (From 9 kHz to 0.15 MHz)/ 9 kHz (From 0.15 MHz to 30 MHz)
Sweep	Auto

1. The testing follows the guidelines in ANSI C63.10-2013 clause 6.4.
2. The EUT was arranged to its worst case and then turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both Horizontal, Face-on and Face-off polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80 cm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a 1 m height antenna tower.
5. The radiated emission limits are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz Radiated emission limits in these three bands are based on measurements employing an average detector.
6. For measurement below 1 GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak and average detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak and average detector and reported.
7. Although these tests were performed other than open field site, adequate comparison measurements were confirmed against 30m open field site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field site based on KDB 414788.
8. The limits in CFR 47, Part 15, Subpart C, paragraph 15.209 (a), are identical to those in RSS-GEN Section 8.9, Table 6, since the measurements are performed in terms of magnetic field strength and converted to electric field strength levels (as reported in the table) using the free space impedance of 377Ω. For example, the measurement frequency X kHz resulted in a level of Y dBuV/m, which is equivalent to $Y - 51.5 = Z$ dBuA/m, which has the same margin, W dB, to the corresponding RSS-GEN Table 6 limit as it has to be 15.209(a) limit.

Below 1 GHz and above 30 MHz

The setting of the spectrum analyzer

RBW	120 kHz
VBW	300 kHz
Sweep	Auto
Detector	Peak/QP
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013 clause 6.5.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80 cm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement below 1 GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.


Above 1 GHz

The setting of the spectrum analyzer

RBW	1 MHz
VBW	PEAK: 3 MHz AVG: see note 6
Sweep	Auto
Detector	Peak
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013 clause 6.6.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 1.5 m above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement above 1 GHz, the emission measurement will be measured by the peak detector. This peak level, once corrected, must comply with the limit specified in Section 15.209.
6. For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 3 MHz for peak measurements and 1 MHz resolution bandwidth with 1/T video bandwidth with peak detector for average measurements. For the Duty Cycle please refer to clause 7.5. ON TIME AND DUTY CYCLE.

X axis, Y axis, Z axis positions:



Note 1: For all radiated test, EUT in each of three orthogonal axis emissions had been tested, but only the worst case (X axis) data recorded in the report.

For Restricted Bandedge:

Note:

1. Measurement = Reading Level + Correct Factor.
2. If the peak values are less than the average limit of 54 dBuV/m, the average result is deemed to comply with average limit.
3. PK=Peak: Peak detector.
4. AV=Average: VBW=1/Ton, where: Ton is the transmitting duration.
5. For the transmitting duration, please refer to clause 7.5.
6. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.
7. Both horizontal and vertical have been tested, only the worst data was recorded in the report.
8. All modes have been tested, but only the worst data was recorded in the report.

For Radiate Spurious emission (9 kHz ~ 30 MHz):

Note:

1. Measurement = Reading Level + Correct Factor.
2. If the peak values are less than the QP limit, the QP result is deemed to comply with QP limit.
3. All 3 polarizations (Horizontal, Face-on and Face-off) of the loop antenna had been tested, but only the worst data recorded in the report.
4. All modes have been tested, but only the worst data was recorded in the report.
5. $\text{dBuA/m} = \text{dBuV/m} - 20\log_{10}[120\pi] = \text{dBuV/m} - 51.5$

For Radiate Spurious Emission (30 MHz ~ 1 GHz):

Note:

1. Result Level = Read Level + Correct Factor.
2. If the peak values are less than the QP limit, the QP result is deemed to comply with QP limit.
3. All modes have been tested, but only the worst data was recorded in the report.

For Radiate Spurious Emission (1 GHz ~ 3 GHz):

Note:

1. Measurement = Reading Level + Correct Factor.
2. If the peak values are less than the average limit of 54 dBuV/m, the average result is deemed to comply with average limit.
3. Peak: Peak detector.
4. AVG: VBW=1/Ton, where: Ton is the transmitting duration.
5. For the transmitting duration, please refer to clause 7.5.
6. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.
7. Proper operation of the transmitter prior to adding the filter to the measurement chain.
8. All modes have been tested, but only the worst data was recorded in the report.

For Radiate Spurious Emission (3 GHz ~ 18 GHz):

Note:


1. Peak Result = Reading Level + Correct Factor.
2. If the peak values are less than the average limit of 54 dBuV/m, the average result is deemed to comply with average limit.
3. Peak: Peak detector.
4. AVG: VBW=1/Ton, where: Ton is the transmitting duration.
5. For the transmitting duration, please refer to clause 7.5.
6. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
7. Proper operation of the transmitter prior to adding the filter to the measurement chain.
8. All modes have been tested, but only the worst data was recorded in the report.

For Radiate Spurious emission (18 GHz ~ 26 GHz):


Note:

1. Measurement = Reading Level + Correct Factor.
2. If the peak values are less than the average limit of 54 dBuV/m, the average result is deemed to comply with average limit.
3. Peak: Peak detector.
4. All modes have been tested, but only the worst data was recorded in the report.


TEST SETUP



Below 1 GHz and above 30 MHz



Above 1GHz



TEST ENVIRONMENT

Temperature	22.3°C	Relative Humidity	59%
Atmosphere Pressure	101kPa	Test Voltage	AC 120V_60Hz


TEST DATE / ENGINEER

Test Date	April 27, 2025	Test By	Mason Wang
-----------	----------------	---------	------------

TEST RESULTS


8.1. RESTRICTED BANDEDGE

Test Mode:	802.11b PK	Frequency(MHz):	2412
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2388.890	22.50	31.73	54.23	74.00	-19.77	peak
2	2390.000	20.96	31.73	52.69	74.00	-21.31	peak
3	2412.000	74.41	31.80	106.21	/	/	Fundamental

Test Mode:	802.11b AV	Frequency(MHz):	2412
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2388.890	7.04	31.73	38.77	54.00	-15.23	AVG
2	2390.000	6.92	31.73	38.65	54.00	-15.35	AVG

Test Mode:	802.11b PK	Frequency(MHz):	2412
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2387.970	23.65	32.55	56.20	74.00	-17.80	peak
2	2390.000	21.18	32.55	53.73	74.00	-20.27	peak
3	2412.000	76.05	32.62	108.67	/	/	Fundamental

Test Mode:	802.11b AV	Frequency(MHz):	2412
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2387.970	8.62	32.55	41.17	54.00	-12.83	AVG
2	2390.000	7.86	32.55	40.41	54.00	-13.59	AVG

Test Mode:	802.11b PK	Frequency(MHz):	2462
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	22.76	32.80	55.56	74.00	-18.44	peak
2	2487.650	25.66	32.81	58.47	74.00	-15.53	peak

Test Mode:	802.11b AV	Frequency(MHz):	2462
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	10.39	32.80	43.19	54.00	-10.81	AVG
2	2487.650	12.37	32.81	45.18	54.00	-8.82	AVG

Test Mode:	802.11g PK	Frequency(MHz):	2412
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2389.925	35.60	35.43	71.03	74.00	-2.97	peak
2	2390.000	36.24	35.43	71.67	74.00	-2.33	peak

Test Mode:	802.11g AV	Frequency(MHz):	2412
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2389.925	14.15	35.43	49.58	54.00	-4.42	AVG
2	2390.000	14.30	35.43	49.73	54.00	-4.27	AVG

Test Mode:	802.11g PK	Frequency(MHz):	2462
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	36.03	36.13	72.16	74.00	-1.84	peak
2	2483.600	36.76	36.13	72.89	74.00	-1.11	peak

Test Mode:	802.11g AV	Frequency(MHz):	2462
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	14.22	36.13	50.35	54.00	-3.65	AVG
2	2483.600	14.10	36.13	50.23	54.00	-3.77	AVG

Test Mode:	802.11n HT20 PK	Frequency(MHz):	2412
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2389.810	36.65	35.43	72.08	74.00	-1.92	peak
2	2390.000	36.09	35.43	71.52	74.00	-2.48	peak

Test Mode:	802.11n HT20 AV	Frequency(MHz):	2412
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2389.810	15.81	35.43	51.24	54.00	-2.76	AVG
2	2390.000	16.05	35.43	51.48	54.00	-2.52	AVG

Test Mode:	802.11n HT20 PK	Frequency(MHz):	2462
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	35.64	36.13	71.77	74.00	-2.23	peak
2	2483.600	36.31	36.13	72.44	74.00	-1.56	peak

Test Mode:	802.11n HT20 AV	Frequency(MHz):	2462
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	15.96	36.13	52.09	54.00	-1.91	AVG
2	2483.600	15.89	36.13	52.02	54.00	-1.98	AVG

Test Mode:	802.11n HT40 PK	Frequency(MHz):	2422
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2389.380	36.22	35.43	71.65	74.00	-2.35	peak
2	2390.000	35.42	35.43	70.85	74.00	-3.15	peak

Test Mode:	802.11n HT40 AV	Frequency(MHz):	2422
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2389.380	14.68	35.43	50.11	54.00	-3.89	AVG
2	2390.000	14.87	35.43	50.30	54.00	-3.70	AVG

Test Mode:	802.11n HT40 PK	Frequency(MHz):	2452
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	34.54	36.13	70.67	74.00	-3.33	peak


Test Mode:	802.11n HT40 AV	Frequency(MHz):	2452
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	16.56	36.13	52.69	54.00	-1.31	AVG


8.2. SPURIOUS EMISSIONS(1 GHZ~3 GHZ)

Test Mode:	802.11b	Frequency(MHz):	2412
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1162.000	60.60	-22.25	38.35	74.00	-35.65	peak
2	1330.000	58.53	-22.35	36.18	74.00	-37.82	peak
3	2000.000	58.54	-17.59	40.95	74.00	-33.05	peak
4	2412.000	57.49	-18.46	39.03	/	/	Fundamental
5	2564.000	58.08	-17.12	40.96	74.00	-33.04	peak
6	2952.000	57.16	-16.26	40.90	74.00	-33.10	peak

Test Mode:	802.11b	Frequency(MHz):	2412
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1164.000	59.34	-22.24	37.10	74.00	-36.90	peak
2	1496.000	58.70	-23.13	35.57	74.00	-38.43	peak
3	1994.000	56.94	-17.66	39.28	74.00	-34.72	peak
4	2412.000	62.59	-18.46	44.13	/	/	Fundamental
5	2666.000	64.98	-16.44	48.54	74.00	-25.46	peak
6	2978.000	57.72	-16.35	41.37	74.00	-32.63	peak

Test Mode:	802.11b	Frequency(MHz):	2437
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1162.000	60.39	-22.25	38.14	74.00	-35.86	peak
2	1802.000	57.38	-19.86	37.52	74.00	-36.48	peak
3	1994.000	59.15	-17.66	41.49	74.00	-32.51	peak
4	2320.000	58.77	-18.72	40.05	74.00	-33.95	peak
5	2568.000	58.47	-17.08	41.39	74.00	-32.61	peak
6	2856.000	56.93	-15.98	40.95	74.00	-33.05	peak

Test Mode:	802.11b	Frequency(MHz):	2437
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1160.000	60.43	-22.26	38.17	74.00	-35.83	peak
2	1496.000	59.98	-23.13	36.85	74.00	-37.15	peak
3	2064.000	61.53	-18.01	43.52	74.00	-30.48	peak
4	2437.000	63.22	-18.27	44.95	/	/	Fundamental
5	2664.000	64.69	-16.46	48.23	74.00	-25.77	peak
6	2890.000	57.38	-16.08	41.30	74.00	-32.70	peak

Test Mode:	802.11b	Frequency(MHz):	2462
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1160.000	60.61	-22.26	38.35	74.00	-35.65	peak
2	1328.000	59.74	-22.33	37.41	74.00	-36.59	peak
3	1800.000	57.49	-19.89	37.60	74.00	-36.40	peak
4	1998.000	60.88	-17.62	43.26	74.00	-30.74	peak
5	2570.000	59.43	-17.06	42.37	74.00	-31.63	peak
6	2792.000	56.85	-15.85	41.00	74.00	-33.00	peak


Test Mode:	802.11b	Frequency(MHz):	2462
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1166.000	60.03	-22.23	37.80	74.00	-36.20	peak
2	1500.000	59.22	-23.17	36.05	74.00	-37.95	peak
3	2062.000	57.48	-18.00	39.48	74.00	-34.52	peak
4	2462.000	59.94	-18.05	41.89	/	/	Fundamental
5	2662.000	64.28	-16.46	47.82	74.00	-26.18	peak
6	2968.000	57.98	-16.32	41.66	74.00	-32.34	peak

8.3. SPURIOUS EMISSIONS(3 GHZ~18 GHZ)


Test Mode:	802.11b	Frequency(MHz):	2412
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4815.000	64.52	-14.43	50.09	74.00	-23.91	peak
2	7230.000	64.19	-12.56	51.63	74.00	-22.37	peak
3	9645.000	71.37	-9.43	61.94	/	/	peak
4	12060.000	53.45	-4.17	49.28	74.00	-24.72	peak
5	14730.000	56.36	-5.36	51.00	74.00	-23.00	peak
6	17715.000	50.66	0.01	50.67	74.00	-23.33	peak

Note: Since Point 3 (9645MHz) is out of restricted bands, there is no peak or average limit for Point 3.


Test Mode:	802.11b	Frequency(MHz):	2412
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4815.000	69.16	-14.43	54.73	74.00	-19.27	peak
2	4815.000	61.17	-14.43	46.74	54.00	-7.26	AVG
3	7230.000	74.60	-12.56	62.04	/	/	peak
4	9645.000	68.53	-9.43	59.10	/	/	peak
5	11520.000	55.47	-6.43	49.04	74.00	-24.96	peak
6	14835.000	54.84	-4.94	49.90	74.00	-24.10	peak
7	17820.000	50.19	-0.22	49.97	74.00	-24.03	peak

Note: Since Point 3(7230MHz) and Point 4 (9645MHz) are out of restricted bands, there are no peak or average limits for Point 3 and Point 4.


Test Mode:	802.11b	Frequency(MHz):	2437
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4875.000	63.71	-14.85	48.86	74.00	-25.14	peak
2	7305.000	64.68	-12.56	52.12	74.00	-21.88	peak
3	9750.000	72.28	-9.74	62.54	/	/	peak
4	13095.000	54.47	-5.75	48.72	74.00	-25.28	peak
5	15195.000	53.73	-4.73	49.00	74.00	-25.00	peak
6	16860.000	51.90	-1.68	50.22	74.00	-23.78	peak

Note: Since Point 3 (9750MHz) is out of restricted bands, there is no peak or average limit for Point 3.


Test Mode:	802.11b	Frequency(MHz):	2437
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4875.000	68.61	-14.85	53.76	74.00	-20.24	peak
2	4875.000	62.19	-14.85	47.34	54.00	-6.66	AVG
3	7305.000	73.79	-12.56	61.23	74.00	-12.77	peak
4	7305.000	64.63	-12.56	52.07	54.00	-1.93	AVG
5	9750.000	71.62	-9.74	61.88	/	/	peak
6	11910.000	53.55	-4.59	48.96	74.00	-25.04	peak
7	14730.000	55.90	-5.36	50.54	74.00	-23.46	peak
8	17685.000	49.63	0.07	49.70	74.00	-24.30	peak

Note: Since Point 5 (9750MHz) is out of restricted bands, there is no peak or average limit for Point 5.


Test Mode:	802.11b	Frequency(MHz):	2462
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4920.000	63.82	-15.19	48.63	74.00	-25.37	peak
2	7380.000	62.82	-12.57	50.25	74.00	-23.75	peak
3	9840.000	71.41	-9.46	61.95	/	/	peak
4	13065.000	54.24	-5.43	48.81	74.00	-25.19	peak
5	14730.000	55.33	-5.36	49.97	74.00	-24.03	peak
6	17820.000	51.11	-0.22	50.89	74.00	-23.11	peak

Note: Since Point 3 (9840MHz) is out of restricted bands, there is no peak or average limit for Point 3.


Test Mode:	802.11b	Frequency(MHz):	2462
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4920.000	69.65	-15.19	54.46	74.00	-19.54	peak
2	4920.000	62.75	-15.19	47.56	54.00	-6.44	AVG
3	7380.000	73.15	-12.57	60.58	74.00	-13.42	peak
4	7380.000	63.58	-12.57	51.01	54.00	-2.99	AVG
5	9840.000	71.80	-9.46	62.34	/	/	peak
6	11925.000	52.95	-4.49	48.46	74.00	-25.54	peak
7	14730.000	54.78	-5.36	49.42	74.00	-24.58	peak
8	16860.000	51.90	-1.68	50.22	74.00	-23.78	peak

Note: Since Point 5 (9840MHz) is out of restricted bands, there is no peak or average limit for Point 5.


Test Mode:	802.11g	Frequency(MHz):	2412
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4815.000	61.56	-14.43	47.13	74.00	-26.87	peak
2	7230.000	62.52	-12.56	49.96	74.00	-24.04	peak
3	9645.000	64.73	-9.43	55.30	/	/	peak
4	12180.000	53.33	-4.57	48.76	74.00	-25.24	peak
5	14745.000	54.86	-5.32	49.54	74.00	-24.46	peak
6	16875.000	51.86	-1.88	49.98	74.00	-24.02	peak

Note: Since Point 3 (9645MHz) is out of restricted bands, there is no peak or average limit for Point 3.


Test Mode:	802.11g	Frequency(MHz):	2412
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4815.000	66.21	-14.43	51.78	74.00	-22.22	peak
2	7230.000	75.50	-12.56	62.94	/	/	peak
3	7995.000	62.91	-11.78	51.13	74.00	-22.87	peak
4	9660.000	61.91	-9.47	52.44	74.00	-21.56	peak
5	14730.000	55.64	-5.36	50.28	74.00	-23.72	peak
6	17790.000	50.11	-0.12	49.99	74.00	-24.01	peak

Note: Since Point 2 (7230MHz) is out of restricted bands, there is no peak or average limit for Point 2.


Test Mode:	802.11g	Frequency(MHz):	2437
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4860.000	61.95	-14.74	47.21	74.00	-26.79	peak
2	7305.000	64.81	-12.56	52.25	74.00	-21.75	peak
3	9735.000	68.51	-9.70	58.81	/	/	peak
4	13050.000	54.56	-5.26	49.30	74.00	-24.70	peak
5	14835.000	54.08	-4.94	49.14	74.00	-24.86	peak
6	16860.000	51.81	-1.68	50.13	74.00	-23.87	peak

Note: Since Point 3 (9735MHz) is out of restricted bands, there is no peak or average limit for Point 3.


Test Mode:	802.11g	Frequency(MHz):	2437
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4875.000	66.08	-14.85	51.23	74.00	-22.77	peak
2	7305.000	77.20	-12.56	64.64	74.00	-9.36	peak
3	7305.000	60.93	-12.56	48.37	54.00	-5.63	AVG
4	9750.000	68.52	-9.74	58.78	/	/	peak
5	11910.000	53.05	-4.59	48.46	74.00	-25.54	peak
6	15420.000	55.83	-6.35	49.48	74.00	-24.52	peak
7	17835.000	50.99	-0.27	50.72	74.00	-23.28	peak

Note: Since Point 4 (9750MHz) is out of restricted bands, there is no peak or average limit for Point 4.


Test Mode:	802.11g	Frequency(MHz):	2462
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4920.000	61.09	-15.19	45.90	74.00	-28.10	peak
2	7380.000	62.64	-12.57	50.07	74.00	-23.93	peak
3	9855.000	67.08	-9.30	57.78	/	/	peak
4	12180.000	53.52	-4.57	48.95	74.00	-25.05	peak
5	14730.000	55.27	-5.36	49.91	74.00	-24.09	peak
6	16695.000	50.14	-0.25	49.89	74.00	-24.11	peak

Note: Since Point 3 (9855MHz) is out of restricted bands, there is no peak or average limit for Point 3.


Test Mode:	802.11g	Frequency(MHz):	2462
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4920.000	65.93	-15.19	50.74	74.00	-23.26	peak
2	7380.000	74.03	-12.57	61.46	74.00	-12.54	peak
3	7380.000	55.49	-12.57	42.92	54.00	-11.08	AVG
4	9855.000	68.42	-9.30	59.12	/	/	peak
5	12150.000	53.80	-4.48	49.32	74.00	-24.68	peak
6	15195.000	53.76	-4.73	49.03	74.00	-24.97	peak
7	17730.000	49.84	-0.01	49.83	74.00	-24.17	peak

Note: Since Point 4 (9855MHz) is out of restricted bands, there is no peak or average limit for Point 4.


Test Mode:	802.11n HT20	Frequency(MHz):	2412
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4830.000	61.47	-14.53	46.94	74.00	-27.06	peak
2	7230.000	62.96	-12.56	50.40	74.00	-23.60	peak
3	9645.000	64.38	-9.43	54.95	/	/	peak
4	11895.000	53.18	-4.70	48.48	74.00	-25.52	peak
5	14730.000	54.18	-5.36	48.82	74.00	-25.18	peak
6	17805.000	50.43	-0.16	50.27	74.00	-23.73	peak

Note: Since Point 3 (9645MHz) is out of restricted bands, there is no peak or average limit for Point 3.


Test Mode:	802.11n HT20	Frequency(MHz):	2412
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4815.000	66.67	-14.43	52.24	74.00	-21.76	peak
2	7245.000	74.43	-12.55	61.88	/	/	peak
3	9660.000	64.37	-9.47	54.90	/	/	peak
4	11865.000	53.62	-4.91	48.71	74.00	-25.29	peak
5	14715.000	54.75	-5.41	49.34	74.00	-24.66	peak
6	17655.000	49.81	0.12	49.93	74.00	-24.07	peak

Note: Since Point 2 (7245MHz) and Point 3 (9645MHz) are out of restricted bands, there are no peak or average limits for Point 2 and Point 3.


Test Mode:	802.11n HT20	Frequency(MHz):	2437
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4875.000	62.26	-14.85	47.41	74.00	-26.59	peak
2	7305.000	65.12	-12.56	52.56	74.00	-21.44	peak
3	9750.000	66.89	-9.74	57.15	/	/	peak
4	11910.000	53.12	-4.59	48.53	74.00	-25.47	peak
5	14730.000	55.46	-5.36	50.10	74.00	-23.90	peak
6	17790.000	50.33	-0.12	50.21	74.00	-23.79	peak

Note: Since Point 3 (9750MHz) is out of restricted bands, there is no peak or average limit for Point 3.


Test Mode:	802.11n HT20	Frequency(MHz):	2437
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4860.000	66.38	-14.74	51.64	74.00	-22.36	peak
2	7305.000	74.55	-12.56	61.99	74.00	-12.01	peak
3	7305.000	58.97	-12.56	46.41	54.00	-7.59	AVG
4	9750.000	66.14	-9.74	56.40	/	/	peak
5	11895.000	54.21	-4.70	49.51	74.00	-24.49	peak
6	15240.000	54.20	-5.08	49.12	74.00	-24.88	peak
7	16860.000	52.27	-1.68	50.59	74.00	-23.41	peak

Note: Since Point 4 (9750MHz) is out of restricted bands, there is no peak or average limit for Point 4.


Test Mode:	802.11n HT20	Frequency(MHz):	2462
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4920.000	60.48	-15.19	45.29	74.00	-28.71	peak
2	7380.000	61.84	-12.57	49.27	74.00	-24.73	peak
3	9855.000	66.41	-9.30	57.11	/	/	peak
4	11970.000	53.17	-4.17	49.00	74.00	-25.00	peak
5	15285.000	54.88	-5.43	49.45	74.00	-24.55	peak
6	16860.000	51.28	-1.68	49.60	74.00	-24.40	peak

Note: Since Point 3 (9855MHz) is out of restricted bands, there is no peak or average limit for Point 3.


Test Mode:	802.11n HT20	Frequency(MHz):	2462
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4920.000	64.69	-15.19	49.50	74.00	-24.50	peak
2	7380.000	71.91	-12.57	59.34	74.00	-14.66	peak
3	7380.000	55.40	-12.57	42.83	54.00	-11.17	AVG
4	9855.000	66.21	-9.30	56.91	/	/	peak
5	12150.000	54.01	-4.48	49.53	74.00	-24.47	peak
6	14730.000	53.45	-5.36	48.09	74.00	-25.91	peak
7	17745.000	50.01	-0.04	49.97	74.00	-24.03	peak


Note: Since Point 4 (9855MHz) is out of restricted bands, there is no peak or average limit for Point 4.

Test Mode:	802.11n HT40	Frequency(MHz):	2422
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4830.000	59.42	-14.53	44.89	74.00	-29.11	peak
2	8820.000	54.82	-7.31	47.51	74.00	-26.49	peak
3	9675.000	61.93	-9.52	52.41	74.00	-21.59	peak
4	11895.000	53.15	-4.70	48.45	74.00	-25.55	peak
5	14715.000	55.48	-5.41	50.07	74.00	-23.93	peak
6	17805.000	50.38	-0.16	50.22	74.00	-23.78	peak

Test Mode:	802.11n HT40	Frequency(MHz):	2422
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4830.000	62.05	-14.53	47.52	74.00	-26.48	peak
2	7260.000	69.14	-12.56	56.58	74.00	-17.42	peak
3	7260.000	53.25	-12.56	40.69	54.00	-13.31	AVG
4	9690.000	61.09	-9.56	51.53	74.00	-22.47	peak
5	13035.000	54.19	-5.11	49.08	74.00	-24.92	peak
6	15270.000	54.93	-5.32	49.61	74.00	-24.39	peak
7	17715.000	50.64	0.01	50.65	74.00	-23.35	peak


Test Mode:	802.11n HT40	Frequency(MHz):	2437
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4860.000	59.66	-14.74	44.92	74.00	-29.08	peak
2	7290.000	61.26	-12.56	48.70	74.00	-25.30	peak
3	9750.000	64.41	-9.74	54.67	/	/	peak
4	11100.000	54.42	-5.90	48.52	74.00	-25.48	peak
5	14865.000	54.47	-4.74	49.73	74.00	-24.27	peak
6	16860.000	52.13	-1.68	50.45	74.00	-23.55	peak


Note: Since Point 3 (9750MHz) is out of restricted bands, there is no peak or average limit for Point 3.

Test Mode:	802.11n HT40	Frequency(MHz):	2437
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4875.000	63.83	-14.85	48.98	74.00	-25.02	peak
2	7305.000	71.50	-12.56	58.94	74.00	-15.06	peak
3	7305.000	54.84	-12.56	42.28	54.00	-11.72	AVG
4	9750.000	63.28	-9.74	53.54	74.00	-20.46	peak
5	13050.000	53.88	-5.26	48.62	74.00	-25.38	peak
6	15255.000	54.32	-5.20	49.12	74.00	-24.88	peak
7	17745.000	50.12	-0.04	50.08	74.00	-23.92	peak

Test Mode:	802.11n HT40	Frequency(MHz):	2452
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5310.000	58.47	-14.71	43.76	74.00	-30.24	peak
2	8730.000	55.17	-7.37	47.80	74.00	-26.20	peak
3	9810.000	59.95	-9.79	50.16	74.00	-23.84	peak
4	11970.000	53.34	-4.17	49.17	74.00	-24.83	peak
5	15225.000	54.65	-4.96	49.69	74.00	-24.31	peak
6	16860.000	51.76	-1.68	50.08	74.00	-23.92	peak


Test Mode:	802.11n HT40	Frequency(MHz):	2452
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5310.000	61.52	-14.71	46.81	74.00	-27.19	peak
2	7350.000	67.61	-12.57	55.04	74.00	-18.96	peak
3	7350.000	50.61	-12.57	38.04	54.00	-15.96	AVG
4	7995.000	63.80	-11.78	52.02	74.00	-21.98	peak
5	9825.000	60.47	-9.63	50.84	74.00	-23.16	peak
6	13875.000	57.63	-8.32	49.31	74.00	-24.69	peak
7	16860.000	51.19	-1.68	49.51	74.00	-24.49	peak


8.4. SPURIOUS EMISSIONS(9 KHZ~30 MHZ)

Test Mode:	802.11b	Frequency(MHz):	2412
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	ISED Result (dBuA/m)	ISED Limit (dBuA/m)	Margin (dB)	Remark
1	0.0100	75.22	-101.40	-26.18	47.60	-77.68	-3.9	-73.78	peak
2	0.0114	73.95	-101.40	-27.45	46.46	-78.95	-5.04	-73.91	peak
3	0.0198	70.78	-101.34	-30.56	41.67	-82.06	-9.83	-72.23	peak
4	0.0286	66.94	-101.38	-34.44	38.47	-85.94	-13.03	-72.91	peak
5	0.0539	60.76	-101.50	-40.74	32.97	-92.24	-18.53	-73.71	peak
6	0.0990	57.99	-101.80	-43.81	27.69	-95.31	-23.81	-71.50	peak

Test Mode:	802.11b	Frequency(MHz):	2412
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	ISED Result (dBuA/m)	ISED Limit (dBuA/m)	Margin (dB)	Remark
1	0.1711	73.85	-101.67	-27.82	22.94	-79.32	-28.56	-50.76	peak
2	0.1901	70.07	-101.70	-31.63	22.03	-83.13	-29.47	-53.66	peak
3	0.2346	66.85	-101.77	-34.92	20.19	-86.42	-31.31	-55.11	peak
4	0.2651	65.11	-101.82	-36.71	19.13	-88.21	-32.37	-55.84	peak
5	0.3402	61.74	-101.90	-40.16	16.97	-91.66	-34.53	-57.13	peak
6	0.4128	58.61	-101.98	-43.37	15.29	-94.87	-36.21	-58.66	peak


Test Mode:	802.11b	Frequency(MHz):	2412
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz



No.	Frequency	Reading	Correct	Result	Limit	ISED Result	ISED Limit	Margin	Remark
	(MHz)	(dBuV)	(dB/m)	(dBuV/m)	(dBuV/m)	(dBuA/m)	(dBuA/m)	(dB)	
1	0.6834	64.21	-62.11	2.10	30.91	-49.4	-20.59	-28.81	peak
2	1.5524	61.85	-62.02	-0.17	23.78	-51.67	-27.72	-23.95	peak
3	4.0948	55.96	-61.35	-5.39	29.54	-56.89	-21.96	-34.93	peak
4	8.5462	53.19	-61.00	-7.81	29.54	-59.31	-21.96	-37.35	peak
5	17.3992	52.43	-60.92	-8.49	29.54	-59.99	-21.96	-38.03	peak
6	29.3213	51.80	-60.02	-8.22	29.54	-59.72	-21.96	-37.76	peak


8.5. SPURIOUS EMISSIONS(18 GHZ~26 GHZ)

Test Mode:	802.11b	Frequency(MHz):	2412
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	18144.000	49.77	-5.48	44.29	74.00	-29.71	peak
2	19392.000	50.62	-5.57	45.05	74.00	-28.95	peak
3	20696.000	49.21	-5.16	44.05	74.00	-29.95	peak
4	22096.000	48.54	-4.38	44.16	74.00	-29.84	peak
5	23696.000	48.26	-3.18	45.08	74.00	-28.92	peak
6	25744.000	46.00	-0.64	45.36	74.00	-28.64	peak


Test Mode:	802.11b	Frequency(MHz):	2412
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	18304.000	48.97	-5.49	43.48	74.00	-30.52	peak
2	19144.000	48.94	-5.43	43.51	74.00	-30.49	peak
3	20224.000	48.52	-5.60	42.92	74.00	-31.08	peak
4	21568.000	47.94	-4.59	43.35	74.00	-30.65	peak
5	22776.000	46.11	-3.66	42.45	74.00	-31.55	peak
6	24568.000	46.60	-2.33	44.27	74.00	-29.73	peak


8.6. SPURIOUS EMISSIONS(30 MHZ~1 GHZ)

Test Mode:	802.11b	Frequency(MHz):	2412
Polarity:	Horizontal	Test Voltage:	AC 120V 60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	159.9800	46.50	-13.54	32.96	43.50	-10.54	QP
2	220.1200	49.04	-14.04	35.00	46.00	-11.00	QP
3	320.0300	51.52	-11.84	39.68	46.00	-6.32	QP
4	399.5700	38.59	-10.90	27.69	46.00	-18.31	QP
5	480.0800	47.31	-9.24	38.07	46.00	-7.93	QP
6	640.1300	29.32	-7.22	22.10	46.00	-23.90	QP

Test Mode:	802.11b	Frequency(MHz):	2412
Polarity:	Vertical	Test Voltage:	AC 120V 60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	30.9700	45.07	-14.65	30.42	40.00	-9.58	QP
2	38.7300	51.97	-15.03	36.94	40.00	-3.06	QP
3	76.5600	52.65	-16.32	36.33	40.00	-3.67	QP
4	159.9800	52.12	-13.54	38.58	43.50	-4.92	QP
5	480.0800	46.55	-9.24	37.31	46.00	-8.69	QP
6	640.1300	33.82	-7.22	26.60	46.00	-19.40	QP

9. ANTENNA REQUIREMENT

REQUIREMENT

Please refer to FCC part 15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Please refer to FCC part 15.247(b)(4)

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

DESCRIPTION

Pass

10. AC POWER LINE CONDUCTED EMISSION

LIMITS

Please refer to CFR 47 FCC §15.207 (a) and ISSED RSS-Gen Clause 8.8


FREQUENCY (MHz)	Quasi-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00

TEST PROCEDURE

The EUT is put on a table of non-conducting material that is 80 cm high. The vertical conducting wall of shielding is located 40 cm to the rear of the EUT. The power line of the EUT is connected to the AC mains through a Artificial Mains Network (A.M.N.). A EMI Measurement Receiver (R&S Test Receiver ESR3) is used to test the emissions from both sides of AC line. According to the requirements in Section 6.2 of ANSI C63.10-2013. Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode. The bandwidth of EMI test receiver is set at 9 kHz.

The arrangement of the equipment is installed to meet the standards and operating in a manner, which tends to maximize its emission characteristics in a normal application.

TEST SETUP



TEST ENVIRONMENT


Temperature	22.5°C	Relative Humidity	52.9%
Atmosphere Pressure	101kPa	Test Voltage	AC 120V_60Hz

TEST DATE / ENGINEER

Test Date	April 28, 2025	Test By	Deacon Tan
-----------	----------------	---------	------------

TEST RESULTS

Test Mode:	802.11b	Frequency(MHz):	2412
Line:	Line		




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1661	33.18	9.71	42.89	65.15	-22.26	QP
2	0.1661	21.76	9.71	31.47	55.15	-23.68	AVG
3	0.1962	32.43	9.65	42.08	63.77	-21.69	QP
4	0.1962	24.42	9.65	34.07	53.77	-19.70	AVG
5	0.2856	29.23	9.64	38.87	60.65	-21.78	QP
6	0.2856	21.93	9.64	31.57	50.65	-19.08	AVG
7	0.4506	26.40	9.64	36.04	56.86	-20.82	QP
8	0.4506	17.64	9.64	27.28	46.86	-19.58	AVG
9	1.7800	14.39	9.72	24.11	56.00	-31.89	QP
10	1.7800	10.38	9.72	20.10	46.00	-25.90	AVG
11	18.9619	19.95	9.74	29.69	60.00	-30.31	QP
12	18.9619	6.40	9.74	16.14	50.00	-33.86	AVG

Note:

1. Result = Reading + Correct Factor.
2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 200 Hz (9 kHz ~ 150 kHz), 9 kHz (150 kHz ~ 30 MHz).
4. Step size: 80 Hz (0.009 MHz ~ 0.15 MHz), 4 kHz (0.15 MHz ~ 30 MHz), Scan time: auto.

Note: All the modes have been tested, only the worst data was recorded in the report.

Test Mode:	802.11b	Frequency(MHz):	2412
Line:	Neutral		



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1619	33.07	9.64	42.71	65.37	-22.66	QP
2	0.1619	21.35	9.64	30.99	55.37	-24.38	AVG
3	0.1877	32.33	9.64	41.97	64.14	-22.17	QP
4	0.1877	22.59	9.64	32.23	54.14	-21.91	AVG
5	0.2473	30.83	9.64	40.47	61.85	-21.38	QP
6	0.2473	23.27	9.64	32.91	51.85	-18.94	AVG
7	0.3799	29.80	9.64	39.44	58.28	-18.84	QP
8	0.3799	24.93	9.64	34.57	48.28	-13.71	AVG
9	0.5296	28.52	9.64	38.16	56.00	-17.84	QP
10	0.5296	22.59	9.64	32.23	46.00	-13.77	AVG
11	18.8313	18.59	9.74	28.33	60.00	-31.67	QP
12	18.8313	5.83	9.74	15.57	50.00	-34.43	AVG

Note:

1. Result = Reading + Correct Factor.
2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 200 Hz (9 kHz ~ 150 kHz), 9 kHz (150 kHz ~ 30 MHz).
4. Step size: 80 Hz (0.009 MHz ~ 0.15 MHz), 4 kHz (0.15 MHz ~ 30 MHz), Scan time: auto.

Note: All the modes have been tested, only the worst data was recorded in the report.

11. TEST DATA

11.1. APPENDIX A: DTS BANDWIDTH

11.1.1. Test Result

Test Mode	Antenna	Frequency[MHz]	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
11B	Ant1	2412	8.320	2407.720	2416.040	≥ 0.5	PASS
		2437	9.520	2431.960	2441.480	≥ 0.5	PASS
		2462	9.880	2457.000	2466.880	≥ 0.5	PASS
11G	Ant1	2412	16.360	2403.800	2420.160	≥ 0.5	PASS
		2437	16.440	2428.720	2445.160	≥ 0.5	PASS
		2462	16.400	2453.760	2470.160	≥ 0.5	PASS
11N20SISO	Ant1	2412	17.080	2403.440	2420.520	≥ 0.5	PASS
		2437	16.920	2428.440	2445.360	≥ 0.5	PASS
		2462	16.280	2453.840	2470.120	≥ 0.5	PASS
11N40SISO	Ant1	2422	34.720	2404.720	2439.440	≥ 0.5	PASS
		2437	35.040	2419.480	2454.520	≥ 0.5	PASS
		2452	33.840	2435.440	2469.280	≥ 0.5	PASS

11.1.2. Test Graphs






11G Ant1 2412



11G Ant1 2437



11G Ant1 2462





11.2. APPENDIX B: OCCUPIED CHANNEL BANDWIDTH

11.2.1. Test Result

Test Mode	Antenna	Frequency[MHz]	OCB [MHz]	FL[MHz]	FH[MHz]
11B	Ant1	2412	12.981	2405.4444	2418.4254
		2437	13.114	2430.3871	2443.5011
		2462	13.086	2455.4227	2468.5087
11G	Ant1	2412	16.700	2403.6267	2420.3267
		2437	16.718	2428.6081	2445.3261
		2462	16.678	2453.6616	2470.3396
11N20SISO	Ant1	2412	17.459	2403.2369	2420.6959
		2437	17.431	2428.2513	2445.6823
		2462	17.476	2453.2673	2470.7433
11N40SISO	Ant1	2422	35.927	2404.0294	2439.9564
		2437	35.970	2419.0504	2455.0204
		2452	35.997	2434.0358	2470.0328

11.2.2. Test Graphs







