



FCS202508376W02

FCC RF Exposure

EUT Description:Portable Wireless Speaker

ModelNo.:D35, D1, D2, D5, D6, D7, D8, D9, D12, D15, D16, D17, D18, D19, D20, D22, D25, D29, D30

FCC ID: 2BOQP-D35

Equipment type: Portable devices

According to KDB 447498 D01 General RF Exposure Guidance v06 and part 2.1093, Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numericasimulation, is not required when the corresponding SAR Test Exclusion Thresholocondition(s), listed below, is (are) satisfied.

For 100 MHz to 6 GHz and test separation distances < 50 mm, the 1-g and 10-g SAR testexclusion thresholds are determined by the following:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance mm})] \cdot [f(\text{GHz})] < 3.0$ for 1-g SAR, and $s 7.5$ for 10-g extremity SAR, where $f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to one decimal place for comparison

conducted power (dBm)	Max tune-up(mW)	Frequency(MHz)	Min. distance(mm)	Calc. thresholds	limit
2.31	1.7022	2402	5	0.5276	3.0
3.34	2.1577	2441	5	0.6742	3.0
3.56	2.2699	2480	5	0.7149	3.0

Conclusion: No SAR is required