

深圳市美禾嘉科技有限公司

Shenzhen Meihejia Technology Co., Ltd.

TB02

ANT REPORT



测试环境

Test environment

| | 测试项目 | 设备 |
|---------------------|--------------------------------------|---------------------------------------------------------------------------------------------------------------------------|
| 1. S参数(S- | 1. 回波损耗 (Return Loss) | 网络分析仪: Agilent E5071B |
| parameter) | 2. 电压 驻波比(VSWR) | HP 8753D |
| 2. 有源测试 | 1. 发射功率 (TRP) | 1. 暗室: ETS 7x4x3 m (3D) Chamber |
| (Active) | 2. 接收灵敏度(TIS) | ETS 5x3x3 m (3D) Chamber 2.综合测试仪: Agilent 8960 E5515B × 2 StarPoint SP6011 |
| 3.无源测试 (Passive) | 1.天线增益 (Gain) 2.天线效率 (Efficiency) | 暗室: ETS 7x4x3 m (3D) Chamber ETS 5x3x3 m (3D) Chamber 网络分析仪: Agilent E5071B HP 8753D |




测试设备 Test Equipment















Antenna position


WIFI天线位置






Wifi**天线实测** Wifi Antenna test

测 试 环 境 : 办 公 室 内 距 离 路 由 器 距 离 : 约 1 5 米






| Passive Test For 2.4G | | | | | |
|-----------------------|--------|--------|-------|--|--|
| Freq | Effi | Effi | Gain | | |
| (MHz) | (%) | (dB) | (dBi) | | |
| 2400 | 19. 51 | -7.1 | -0.87 | | |
| 2410 | 19. 91 | -7.01 | -0.89 | | |
| 2420 | 19. 26 | -7.15 | -1.17 | | |
| 2430 | 19. 29 | -7.15 | -1.28 | | |
| 2440 | 18.82 | -7. 25 | -0.48 | | |
| 2450 | 19.85 | -7.02 | 0.19 | | |
| 2460 | 21.34 | -6.71 | 0.76 | | |
| 2470 | 22. 18 | -6.54 | 2.00 | | |
| 2480 | 23. 2 | -6.34 | 1.38 | | |
| 2490 | 24.19 | -6.16 | 1.83 | | |
| 2500 | 24. 88 | -6.04 | 1.24 | | |











| Passive Test For 5G-WIFI | | | | | |
|--------------------------|--------|-------------------|--------|--|--|
| Freq | Effi | Effi | Gain | | |
| (MHz) | (%) | (dB) | (dBi) | | |
| 5000 | 25. 2 | -5.99 | -0. 23 | | |
| 5100 | 26. 52 | -5.76 | -0.23 | | |
| 5200 | 24. 17 | -6.17 | -0.58 | | |
| 5300 | 30. 84 | -5.11 | 1.41 | | |
| 5400 | 37. 57 | -4. 25 | 1.48 | | |
| 5500 | 38. 25 | -4. 17 | 1.07 | | |
| 5600 | 32. 46 | - 4.89 | 1.02 | | |
| 5700 | 29. 73 | -5. 27 | 1.98 | | |
| 5800 | 31. 27 | -5.05 | 2.00 | | |
| 5900 | 20.68 | -6.84 | 1.08 | | |
| 6000 | 21. 97 | - 6.58 | 1.57 | | |





环境处理


Environmental treatment



主板背面露铜区域与屏 7屏蔽盖接地

摄像头排线用导电布 屏蔽





为客户提供更佳服务

联系人: 熊乾 17688765727

Address: Room 3005, Hongfenghua Creative Park, No. 1, Huangtianmen Gate,

Hangcheng Sub-district, Bao'an District, Shenzhen, China
