

FCC RF Exposure

EUT Description: Remote Control

Model Name: XMZ-YK-D2

Series Model: N/A

FCC ID: 2BOSF-XMZ-YK-D2

Series Model: N/A

Equipment type: portable device

According to KDB 447498 D01 General RF Exposure Guidance v06 and part 2.1093, Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Test Exclusion Threshold condition(s), listed below, is (are) satisfied.

For 100 MHz to 6 GHz and test separation distances < 50 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following: (max. power of channel, including tune-up tolerance, mW) / (min. test separation distance mm) \cdot [vfGHz] < 3.0 for 1-g SAR, and \leq 7.5 for 10-g extremity SAR, where f (GHz) is the RF channel transmit frequency in GHz. Power and distance are rounded to the nearest mW and mm before calculation. The result is rounded to one decimal place for comparison.

1. Test Result of RF Exposure Evaluation

$$\text{EIRP} = \text{EMeas} + 20 \log(\text{dmeas}) - 104.7$$

EIRP is the equivalent isotropically radiated power,

EMeas in dBm is the field strength of the emission at the measurement distance, in dB u V/m

dmeas is the measurement distance, in m

Field strength(dBuV/m)	EIRP(dBm)	(mW)	Frequency(MHz)	Min. distance(mm)	Calc. thresholds	limit
76.89	-18.31	0.014757065	433.92	5	0.001944	3.0

Conclusion: No SAR is required