

裁切线	辅助线
压痕线	牙 刀
V槽线	画 线
半穿刀	

■外表面视图□内表面视图

版本	变更描述	变更日期	包装结构	包装平面
A01	初始发行	2025/05/9	尹华红	李雪嫒

- 备注：
1. 材质：70g书写纸

2. 印刷颜色：1C

3. 成型尺寸：58x75mm

4. 展开尺寸：522x150mm

5. 尺寸公差：±1 mm

6. 印刷偏位：<=0.5 mm

7. 套印偏位：<=0.35 mm

8. 成型工艺：风琴折

9. 所有成品及辅料符合欧盟包装指令94/62/EC，美国TPCH，欧盟REACH

10. 印刷油墨（成品）矿物油含量需满足MOSH(C15-C36)小于0.1%；MOAH（1-7芳香环）小于0.1%；MOAH（3-7芳香环）小于0.0001%

SELECT				V							SCALE 1:1	UGREEN 绿联 深圳市绿联科技股份有限公司			
Dim	TOL	A	B	C	EPS	EPE	EPP	BAG	CTN	LABEL	SHEET 1/1	物料名称: W709 35569 说明书			
0~6		0.05	0.05	0.10						0.20		产品名称	料号	产品工程师	核准
6~30		0.10	0.15	0.20	0.50	0.50	0.50	3.00		0.20					
30~120		0.15	0.20	0.30	0.50	0.50	0.50	5.00	1.00	0.25					
120~300		0.20	0.30	0.40	1.00	1.00	1.00	10.00	1.00	0.30					
300~450		0.25	0.40	0.50	2.00	2.00	2.00	15.00	2.00	0.50					
450~600		0.30	0.50	0.60	3.00	3.00	3.00	20.00	3.00	0.80		无线充电器	/	张泽民	袁蓉辉
DRAFT TOLERANCE				± 0.20*		CRITICAL DIM. MARK				*					

裁切线

压痕线

V槽线

半穿刀

辅助线

牙 刀

画 线

■外表面视图

□内表面视图

无线充电器

CN

FCC 声明

本产品符合美国联邦通信委员会 (FCC) 规则第 15 部分的规定。操作时应确保：
(1) 无有害干扰产生。(2) 接收器故障可能引发意外操作的任何干扰。
警告：本设备使用非定向天线，增加发射本产品将可能导致您违反联邦本产品规定。

FCC 辐射暴露声明
本产品符合美国联邦通信委员会 (FCC) 对非定向环境辐射限制的要求。请注意，不要将本产品与任何附件天线或发射器放在一起或靠近使用。

注意：虽然 FCC 规则第 15 部分中规定，本产品已通过认证，符合 FCC 数字设备的限制要求，但制造商必须对设备使用中的任何意外操作负责。因此，本产品必须始终按照制造商的说明使用。否则，本产品可能会与某些设备产生干扰。本产品可能会产生有害干扰。然而，对于特定设备故障，制造商无法负责。本产品可能无法在某些情况下使用（通过利用任何产品或可接受的），建议通过以下一种或多种措施：

- 调整设备天线的位置。
- 保持本产品与接收器之间的距离。
- 调整本产品与接收器之间的频率与同一频道。
- 咨询制造商或经销商/授权技术人员获取专业帮助。

本产品符合美国联邦通信委员会 (FCC) 对非定向环境辐射限制的要求。在安装和使用本产品时，确保接收器与身体之间的距离不少于 20 厘米。

America Ugreen Limited
100 West, 137th Street, Wilmington, Delaware 19801, United States


PAP

UGREEN

User Instruction

M3

FC

EN

FCC Statement

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Warning: Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

FCC Radiation Exposure Statement
This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment. This transmitter must not be co-located or operating in conjunction with any other antenna or transmitter.

NOTE: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:


- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment. This equipment should be installed and operated with minimum distance of 20 cm between the radiator and your body.

America Ugreen Limited
100 West, 137th Street, Wilmington, Delaware 19801, United States

Warranty Information
A limited 2-year warranty applies to all UGREEN products purchased from authorized official store or authorized sellers. Please feel free to contact us if you run into any problems.

- 备注：
1. 材质：80g白牛皮纸
 2. 表面处理：/
 3. 印刷颜色：1C
 4. 成型尺寸：60x80mm
 5. 展开尺寸：120x80mm
 6. 尺寸公差：±0.5 mm
 7. 印刷偏位：<=0.5 mm
 8. 套印偏位：<=0.35 mm
 9. 成型工艺：风琴折
 10. 所有成品及辅料符合欧盟包装指令94/62/EC，美国TPCH，欧盟REACH
 - 11.印刷油墨（成品）矿物油含量需满足MOSH(C15-C36)小于0.1%；
MOAH（1-7芳香环）小于0.1%；MOAH（3-7芳香环）小于0.0001%

SELECT			V							SCALE	UGREEN 绿联 深圳市绿联科技股份有限公司			
Dim \ TOL.	A	B	C	EPS	EPE	EPP	BAG	CTN	LABEL	1:1	物料名称: (外贸说明卡M3) 无线充电器			
0~6	0.05	0.05	0.10						0.20					
6~30	0.10	0.15	0.20	0.50	0.50	0.50	3.00		0.20	SHEET	产品名称			
30~120	0.15	0.20	0.30	0.50	0.50	0.50	5.00	1.00	0.25	1/1				
120~300	0.20	0.30	0.40	1.00	1.00	1.00	10.00	1.00	0.30	UNIT	料号	项目工程师	核准	
300~450	0.25	0.40	0.50	2.00	2.00	2.00	15.00	2.00	0.50					mm
450~600	0.30	0.50	0.60	3.00	3.00	3.00	20.00	3.00	0.80			/	何艳芳	
DRAFT TOLERANCE			± 0.20°		CRITICAL DIM. MARK									*