



FCC TEST REPORT

FCC ID: 2BOTD-KT3

Applicant: MAHAL TRADE LLC

Address: 1360 W Hubbard St, apt 2W, Chicago, IL 60642, USA

Manufacturer: MAHAL TRADE LLC

Address: 1360 W Hubbard St, apt 2W, Chicago, IL 60642, USA

EUT: camera detector

Trade Mark: Tensaone

Model Number: KT3

Date of Receipt: Apr. 03, 2025

Test Date: Apr. 03, 2025 - Apr. 10, 2025

Date of Report: Apr. 10, 2025

Prepared By: Shenzhen DL Testing Technology Co., Ltd.

Address: 101-201, Building C, Shuanghuan, No.8, Baoqing Road, Baolong Industrial Zone, Baolong Street, Longgang District, Shenzhen, Guangdong, China

Applicable Standards: FCC Part 15 Subpart B
ANSI C63.4:2014

Test Result: Pass

Report Number: DLE-250403018R

Prepared (Test Engineer): Alisa Song

Reviewer (Supervisor): Jack Bu

Approved (Manager): Jade Yang



This test report is based on a single evaluation of one sample of above mentioned products. It is not permitted to be duplicated in extracts without written approval of Shenzhen DL Testing Technology Co., Ltd.

**TABLE OF CONTENT**

	Page
Test Report Declaration	Page
1. VERSION.....	3
2. TEST SUMMARY.....	3
3. GENERAL INFORMATION.....	4
4. TEST INSTRUMENT USED.....	6
5. CONDUCTED EMISSION TEST	7
6. RADIATION EMISSION TEST	11
7. TEST SEUUP PHOTO	17
8. EUT PHOTOGRAPHS	17

**1. VERSION**

Version No.	Date	Description
00	Apr. 10, 2025	Original

2. TEST SUMMARY

EMC Emission				
Standard	Test Item	Limit	Result	Remark
FCC PART 15 B	Conducted Emission at power ports	Class B	PASS	
	Radiated Emission below 1GHz	Class B	PASS	
	Radiated Emission above 1GHz	Class B	PASS	

NOTE:

(1)" N/A" denotes test is not applicable in this Test Report

(2) Test Facility: Shenzhen DL Testing Technology Co., Ltd.

Address: 101-201, Building C, Shuanghuan, No. 8, Baoqing Road, Baolong Industrial Zone, Baolong Street, Longgang District, Shenzhen, Guangdong, China



3. GENERAL INFORMATION

3.1 Description of Device (EUT)

EUT: camera detector

Trade Mark: Tensaone

Model Number: KT3

Test Model: KT3

Model Difference: N/A

Power Supply: DC 5V from adapter
DC 3.7V from battery

Working Frequency: 1MHz-6.5GHz(RX)

NOTE:

- (1) For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.
- (2) The EUT's all information provided by client.

3.2 Tested System Details

None.

3.3 Block Diagram of Test Set-up

Radiated Spurious Emission Test



Power Line Conducted Emission test





3.4 Test Mode Description

Mode1. On Mode

Mode2. Charging Mode

3.5 Test Auxiliary Equipment

Adapter (Provide by test lab):

Manufacturer: HAIWEI

Model: HW-0501000E

I/P: AC 100-240V 50/60Hz

O/P: DC 5V 1A

3.6 Test Uncertainty

Conducted Emission Uncertainty : $\pm 2.56\text{dB}$

Radiated Emission Uncertainty($< 1\text{GHz}$) : $\pm 3.24\text{dB}$

Radiated Emission Uncertainty($> 1\text{GHz}$) : $\pm 4.89\text{dB}$

**4. TEST INSTRUMENT USED****For Conducted Emission Test (843 Shielded Room)**

Equipment	Manufacturer	Model	Serial	Last Cal.	Next Cal.
843 Shielded Room	YIHENG	843 Room	843	Nov. 05, 2023	Nov. 04, 2026
EMI Receiver	R&S	ESR	101421	Nov. 01, 2024	Oct. 31, 2025
LISN	R&S	ENV216	102417	Nov. 01, 2024	Oct. 31, 2025
Clamp	COM-POWER	CLA-050	431072	Nov. 02, 2024	Nov. 01, 2025
3-Loop Antenna	DAZE	ZN30401	13021	Nov. 02, 2024	Nov. 01, 2025
ISN T8	Schwarzbeck	NTFM 8158	101135	Nov. 01, 2024	Oct. 31, 2025
ISN T5	Schwarzbeck	NTFM 8158	101136	Nov. 01, 2024	Oct. 31, 2025
843 Cable 1#	ChengYu	CE Cable	001	Nov. 01, 2024	Oct. 31, 2025
843 Cable 1#	ChengYu	CE Cable	002	Nov. 01, 2024	Oct. 31, 2025

For Radiated Emission Test (966 chamber)

Equipment	Manufacturer	Model	Serial	Last Cal.	Next Cal.
966 chamber	YIHENG	966 Room	966	Nov. 06, 2023	Nov. 05, 2026
Spectrum Analyzer	Agilent	E4408B	MY50140780	Nov. 01, 2024	Oct. 31, 2025
EMI Receiver	R&S	ESRP7	101393	Nov. 01, 2024	Oct. 31, 2025
Amplifier	Schwarzbeck	BBV9743B	00153	Nov. 01, 2024	Oct. 31, 2025
Amplifier	EMEC	EM01G8GA	00270	Nov. 01, 2024	Oct. 31, 2025
Broadband Trilog Antenna	Schwarzbeck	VULB9162	00306	Nov. 02, 2024	Nov. 01, 2025
Horn Antenna	Schwarzbeck	BBHA9120D	02139	Nov. 02, 2024	Nov. 01, 2025
966 Cable 1#	ChengYu	966	004	Nov. 01, 2024	Oct. 31, 2025
966 Cable 2#	ChengYu	966	003	Nov. 01, 2024	Oct. 31, 2025

Other


Name	Manufacturer	Model	Software version
EMC Conduction Test System	FALA	EZ_EMC	EMC-CON 3A1.1
EMC radiation test system	FALA	EZ_EMC	FA-03A2



5. CONDUCTED EMISSION TEST

5.1 Block Diagram of Test Setup

For Mains Terminals Test



Note:

1. Support units were connected to second LISN.
2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

5.2 Test Standard and Limit

FCC PART 15 B

Frequency MHz	Limits dB(μ V)	
	Quasi-peak Level	Average Level
0.15~0.50	66 ~ 56*	55 ~ 46*
0.50~5.00	56	46
5.00~30.00	60	50

Notes: 1. *Decreasing linearly with logarithm of frequency.

2. The lower limit shall apply at the transition frequencies.

5.3 EUT Configuration on Test

The following equipment's are installed on conducted emission test to meet FCC PART 15 B requirement and operating in a manner which tends to maximize its emission characteristics in a normal application.

5.4 Operating Condition of EUT

- 5.4.1 Setup the EUT and simulators as shown in Section 5.1.
- 5.4.2 Turn on the power of all equipments.
- 5.4.3 Let the EUT work in test modes and test it.



5.5 Test Procedure

The EUT is put on the table and connected to the AC mains through a Artificial Mains Network (AMN) or ISN. This provided a 50ohm coupling impedance for the tested equipments. Both sides of AC line are checked to find out the maximum conducted emission levels according to the **ANSI C63.4** regulations during conducted emission test.

The bandwidth of the test receiver (R&S Test Receiver ESR) is set at 10KHz.

The frequency range from 150 KHz to 30 MHz is investigated.


5.6 Test Result

PASS

Please refer to the following page.



Temperature:	25 °C	Relative Humidity:	54%
Pressure:	1010hPa	Phase :	L
Test Voltage :	AC 120V/60Hz	Test Mode:	Mode 2


**Remark:**

Margin = Limit – Level, Correct Factor = Cable loss + LISN insertion loss, Level= Reading + Correct factor

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.1680	22.63	10.03	32.66	65.06	-32.40	QP	P	
2	0.1680	10.07	10.03	20.10	55.06	-34.96	AVG	P	
3 *	0.6180	19.98	10.13	30.11	56.00	-25.89	QP	P	
4	0.6180	9.23	10.13	19.36	46.00	-26.64	AVG	P	
5	1.7340	12.60	10.06	22.66	56.00	-33.34	QP	P	
6	1.7340	-1.16	10.06	8.90	46.00	-37.10	AVG	P	
7	4.8840	14.43	10.36	24.79	56.00	-31.21	QP	P	
8	4.8840	0.91	10.36	11.27	46.00	-34.73	AVG	P	
9	14.4915	18.81	11.63	30.44	60.00	-29.56	QP	P	
10	14.4915	7.27	11.63	18.90	50.00	-31.10	AVG	P	
11	25.0800	11.11	12.73	23.84	60.00	-36.16	QP	P	
12	25.0800	-2.93	12.73	9.80	50.00	-40.20	AVG	P	



Temperature:	25 °C	Relative Humidity:	54%
Pressure:	1010hPa	Phase :	N
Test Voltage :	AC 120V/60Hz	Test Mode:	Mode 2

**Remark:**


Margin = Limit – Level, Correct Factor = Cable lose + LISN insertion loss, Level= Reading + Correct factor

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.1680	22.42	10.15	32.57	65.06	-32.49	QP	P	
2	0.1680	11.53	10.15	21.68	55.06	-33.38	AVG	P	
3 *	0.6134	19.40	10.16	29.56	56.00	-26.44	QP	P	
4	0.6134	8.20	10.16	18.36	46.00	-27.64	AVG	P	
5	1.7430	11.98	10.07	22.05	56.00	-33.95	QP	P	
6	1.7430	-3.20	10.07	6.87	46.00	-39.13	AVG	P	
7	6.9360	15.38	10.71	26.09	60.00	-33.91	QP	P	
8	6.9360	1.81	10.71	12.52	50.00	-37.48	AVG	P	
9	15.0495	14.75	11.58	26.33	60.00	-33.67	QP	P	
10	15.0495	1.30	11.58	12.88	50.00	-37.12	AVG	P	
11	27.4290	12.08	12.86	24.94	60.00	-35.06	QP	P	
12	27.4290	-2.02	12.86	10.84	50.00	-39.16	AVG	P	


6. RADIATION EMISSION TEST

6.1 Block Diagram of Test Setup

Below 1GHz



Above 1GHz



6.2 Test Standard and Limit

FCC PART 15 B

Below 1GHz



Frequency (MHz)	Distance (Meters)	Field Strengths Limits (dB μ V/m)
30 ~ 88	3	40.0
88 ~ 216	3	43.5
216 ~ 960	3	46.0
960 ~ 1000	3	54.0

Above 1GHz

Frequency MHz	Distance (Meters)	Field Strengths Limits dB(μ V/m)	Detector
1000 ~ 40000	3	74.0	PEAK
1000 ~ 40000	3	54.0	AVERAGE

Remark:

- (1) The smaller limit shall apply at the cross point between two frequency bands.
- (2) Distance refers to the distance in meters between the measuring instrument, antenna and the closed point of any part of the device or system.

6.3 EUT Configuration on Test

The FCC PART 15 B regulations test method must be used to find the maximum emission during radiated emission test.

The configuration of EUT is the same as used in conducted emission test.

Please refer to Section 5.3.

6.4 Operating Condition of EUT

Same as conducted emission test, which is listed in Section 5.4 except the test set up replaced as Section 6.2.

6.5 Test Procedure

- 1) The radiated emissions test was conducted in a semi-anechoic chamber.
- 2) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane, but separated from metallic contact with the ground reference plane by 0.8m of insulation.
- 3) Before final measurements of radiated emissions, a pre-scan was performed in the spectrum mode with the peak detector to find out the maximum emissions spectrum plots of the EUT.
- 4) The frequencies of maximum emission were determined in the final radiated emissions measurement. At each frequency, the EUT was rotated 360°, and the antenna was raised and lowered from 1 to 4 meters in order to determine the maximum disturbance. Measurements were performed for both horizontal and vertical antenna polarization.
- 5) The bandwidth setting on the field strength meter (R&S Test Receiver ESCI) is set at 120KHz.
- 6) The frequency range from 30MHz to 40000MHz is checked.
- 7) The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.


6.6 Test Result

PASS

Please refer to the following page.



Radiation Emission Test Data(Below 1GHz)			
Temperature:	24.5°C	Relative Humidity:	54%
Pressure:	1009hPa	Polarization:	Horizontal
Test Voltage:	DC 3.7V	Test Mode:	Mode 1



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Margin	
			Level	Factor	ment			
		MHz	dBuV	dB	dBuV/m	dB/m	dB	Detector
1	*	948.7610	30.04	-0.27	29.77	46.00	-16.23	QP
2		744.8661	30.62	-3.25	27.37	46.00	-18.63	QP
3		360.4476	31.44	-10.30	21.14	46.00	-24.86	QP
4		238.3102	31.61	-13.54	18.07	46.00	-27.93	QP
5		117.7725	31.65	-16.24	15.41	43.50	-28.09	QP
6		41.8596	28.33	-13.56	14.77	40.00	-25.23	QP


Remark:

Correct Factor=Cable loss+Antenna factor+Preamplifier

Measurement Level = Reading Level + Correct Factor; Margin = Measurement Level- Limit;



Radiation Emission Test Data(Below 1GHz)			
Temperature:	24.5°C	Relative Humidity:	54%
Pressure:	1009hPa	Polarization:	Vertical
Test Voltage:	DC 3.7V	Test Mode:	Mode 1



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Margin	Detector
			Level	Factor	ment			
		MHz	dBuV	dB	dBuV/m	dB/m	dB	
1	*	948.7610	29.89	-0.27	29.62	46.00	-16.38	QP
2		744.8661	30.59	-3.25	27.34	46.00	-18.66	QP
3		332.5187	29.62	-11.16	18.46	46.00	-27.54	QP
4		110.9571	32.90	-15.14	17.76	43.50	-25.74	QP
5		72.3376	37.32	-17.68	19.64	40.00	-20.36	QP
6		54.8348	31.06	-13.25	17.81	40.00	-22.19	QP

Remark:


Correct Factor=Cable loss+Antenna factor+Preamplifier

Measurement Level = Reading Level + Correct Factor; Margin = Measurement Level- Limit;



1GHz-40GHz has been tested, and the test margin above 6G is greater than 20dB, which is not recorded in the report.

Radiation Emission Test Data(Above 1GHz)			
Temperature:	24.5°C	Relative Humidity:	54%
Pressure:	1009hPa	Polarization:	Horizontal
Test Voltage:	DC 3.7V	Test Mode:	Mode 1



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin	Detector
		MHz	dBuV	dB	dBuV/m	dB/m	dB	
1		5217.416	45.63	-3.66	41.97	74.00	-32.03	peak
2		3505.144	53.91	-10.83	43.08	74.00	-30.92	peak
3	*	2806.824	58.06	-14.91	43.15	74.00	-30.85	peak
4		2164.628	56.18	-14.78	41.40	74.00	-32.60	peak
5		1708.706	57.75	-17.94	39.81	74.00	-34.19	peak
6		1351.230	60.37	-19.53	40.84	74.00	-33.16	peak


Remark:

Correct Factor=Cable loss+Antenna factor+Preamplifier

Measurement Level = Reading Level + Correct Factor; Margin = Measurement Level- Limit;



Radiation Emission Test Data(Above 1GHz)			
Temperature:	24.5°C	Relative Humidity:	54%
Pressure:	1009hPa	Polarization:	Vertical
Test Voltage:	DC 3.7V	Test Mode:	Mode 1



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Margin
			Level	Factor	ment		
		MHz	dBuV	dB	dBuV/m	dB/m	dB
1		5311.742	47.38	-3.81	43.57	74.00	-30.43
2		4488.391	50.38	-6.78	43.60	74.00	-30.40
3	*	2857.568	58.06	-14.38	43.68	74.00	-30.32
4		2164.628	56.18	-14.78	41.40	74.00	-32.60
5		1373.197	59.13	-19.33	39.80	74.00	-34.20
6		1166.597	60.42	-20.07	40.35	74.00	-33.65

Remark:

Correct Factor=Cable loss+Antenna factor+Preamplifier

Measurement Level = Reading Level + Correct Factor; Margin = Measurement Level- Limit;



7. TEST SEUUP PHOTO

Reference to the appendix I for details.

8. EUT PHOTOGRAPHS

Reference to the appendix II for details.

***** END OF REPORT *****