



EMC TEST REPORT

Applicant Dreamtek Intelligent Technology
Co., Ltd.

FCC ID 2BOUAD1

Product D1

Brand Dreamtek

Model D1

Report No. EFTA25040106-IE-01-E1

Issue Date July 30, 2025

Eurofins TA Technology (Shanghai) Co., Ltd. tested the above equipment in accordance with the requirements in **FCC Code CFR47 Part15B (2024)/ ANSI C63.4-2014**. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Prepared by: Liu Wei

Approved by: Xu Kai

Eurofins TA Technology (Shanghai) Co., Ltd.

Building 3, No.145, Jintang Rd, Pudong Shanghai, P.R.China

TEL: +86-021-50791141/2/3

FAX: +86-021-50791141/2/3-8000

Table of Contents

1	Test Laboratory	4
1.1	Notes of the Test Report.....	4
1.2	Test Facility.....	4
1.3	Testing Location.....	4
2	General Description of Equipment Under Test	5
2.1	Applicant and Manufacturer Information	5
2.2	General Information	5
2.3	Applied Standards	7
2.4	Test Mode	8
3	Test Case Results	9
3.1	Radiated Emission.....	9
3.2	Conducted Emission.....	14
4	Uncertainty Measurement.....	17
5	Main Test Instruments	18
	ANNEX A: The EUT Appearance	19
	ANNEX B: Test Setup Photos	20

Summary of measurement results

Number	Test Case	Clause in FCC Rules	Conclusion
1	Radiated Emission	FCC Part15.109, ANSI C63.4-2014	PASS
2	Conducted Emission	FCC Part15.107, ANSI C63.4-2014	PASS

Date of Testing: April 16, 2025 ~ April 29, 2025

Date of Sample Received: April 11, 2025

Note:

1. All indications of Pass/Fail in this report are opinions expressed by Eurofins TA Technology (Shanghai) Co., Ltd. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only.

1 Test Laboratory

1.1 Notes of the Test Report

This report shall not be reproduced in full or partial, without the written approval of **Eurofins TA Technology (Shanghai) Co., Ltd.** The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. Measurement Uncertainties were not taken into account and are published for informational purposes only. This report is written to support regulatory compliance of the applicable standards stated above.

1.2 Test Facility

FCC (Designation number: CN1179, Test Firm Registration Number: 446626)

Eurofins TA Technology (Shanghai) Co., Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform measurements.

A2LA (Certificate Number: 3857.01)

Eurofins TA Technology (Shanghai) Co., Ltd. has been listed by American Association for Laboratory Accreditation to perform measurement.

1.3 Testing Location

Company: Eurofins TA Technology (Shanghai) Co., Ltd.
Address: Building 3, No.145, Jintang Rd, Pudong Shanghai, P.R.China
City: Shanghai
Post code: 201201
Country: P. R. China
Contact: Xu Kai
Telephone: +86-021-50791141/2/3
Fax: +86-021-50791141/2/3-8000
Website: <https://www.eurofins.com/electrical-and-electronics>
E-mail: Kain.Xu@cpt.eurofinscn.com

2 General Description of Equipment Under Test

2.1 Applicant and Manufacturer Information

Applicant	Dreamtek Intelligent Technology Co., Ltd.
Applicant address	Room 508, Building A2, Area one of Zhongan Chuanggu Science Park, No. 900 of Wangjiang West Road, High-tech Zone, Hefei, Anhui, China
Manufacturer	Dreamtek Intelligent Technology Co., Ltd.
Manufacturer address	Room 508, Building A2, Area one of Zhongan Chuanggu Science Park, No. 900 of Wangjiang West Road, High-tech Zone, Hefei, Anhui, China

2.2 General Information

EUT Description			
Device Type	Portable Device		
Model	D1		
SN	DA00000389		
HW Version	H554-07-DC-0N4-32C-A1 H554-07-DC-0N5-32C-A1		
SW Version	1A.1.3(202503171200 INTL)		
Power Rating	DC 7.6V		
Connecting I/O Port(s)	Please refer to the User's Manual.		
Antenna Type	PIFA Antenna		
Frequency	Band	Tx (MHz)	Rx (MHz)
	GSM850	824 ~ 849	869 ~ 894
	GSM1900	1850 ~ 1910	1930 ~ 1990
	WCDMA Band V	824 ~ 849	869 ~ 894
	LTE Band 2	1850 ~ 1910	1930 ~ 1990
	LTE Band 5	824 ~ 849	869 ~ 894
	LTE Band 7	2500 ~ 2570	2620 ~ 2690
	LTE Band 38	2570 ~ 2620	2570 ~ 2620
	LTE Band 41	2496 ~ 2690	2496 ~ 2690
	Bluetooth	2400 ~ 2483.5	2400 ~ 2483.5
	Wi-Fi 2.4GHz	2400 ~ 2483.5	2400 ~ 2483.5
	Wi-Fi 5GHz (U-NII-1)	5150 ~ 5250	5150 ~ 5250
	Wi-Fi 5GHz (U-NII-2A)	5250 ~ 5350	5250 ~ 5350
	Wi-Fi 5GHz (U-NII-2C)	5470 ~ 5725	5470 ~ 5725
	Wi-Fi 5GHz (U-NII-3)	5725 ~ 5850	5725 ~ 5850

	NFC	13.56	13.56					
EUT Accessory								
Adapter 1	Manufacturer: SHENZHEN TIANYIN ELECTRONICS CO.,LTD Model: TPA-418G050200UU01							
Adapter 2	Manufacturer: Chongqing Lianmao Electronics Co.,Ltd. Model: LM-603U-050200U02UL							
Adapter 3	Manufacturer: SHENZHEN TIANYIN ELECTRONICS CO.,LTD. Model: TPA-418G050200VU01							
Adapter 4	Manufacturer: Chongqing Lianmao Electronics Co.,Ltd. Model: LM-603E-050200U02CE							
Battery 1	Manufacturer: Dongguan HongDe Battery Co.,Ltd. Model: BPK550-026-72-A							
Battery 2	Manufacturer: Guangdong Fenghua New Energy Co.,Ltd. Model: BPK550-026-74-B							
USB Cable 1	Manufacturer: Shanghai Wangxing Electronic Technology Co.,Ltd. Model: 809.001.0010							
USB Cable 2	Manufacturer: Chongqing Lianmao Electronics Co.,Ltd. Model: 809.001.0012							
Note: <ol style="list-style-type: none"> 1. The EUT is sent from the applicant to Eurofins TA and the information of the EUT is declared by the applicant. 2. There is more than one USB cable/Adapter/Battery, each one should be applied throughout the compliance test respectively, and however, only the worst case (USB cable 2/Adapter 4/ Battery 1) will be recorded in this report. 								
D1	Configurations 1 (D1+ Token Version with the 1st supply of main materials)	Configurations 2 (D1+ Token Version with the 2nd supply of main materials)	Configurations 3 (D1+ Standard Version with the 1st supply of main materials)	Configurations 4 (D1+ Standard Version with the 2nd supply of main materials)	Configurations 5 (D1A Token Version with the 1st supply of main materials)	Configurations 6 (D1A Token Version with the 2nd supply of main materials)	Configurations 7 (D1A Standard Version with the 1st supply of main materials)	Configurations 8 (D1A Standard Version with the 2nd supply of main materials)
Screen	6.517-inch	6.517-inch	6.517-inch	6.517-inch	5-inch	5-inch	5-inch	5-inch
Front Camera	2M FF	2M FF	2M FF	2M FF	0.3M FF	0.3M FF	0.3M FF	0.3M FF
Rear Camera	The 1st supplier	The 2nd supplier	The 1st supplier	The 2nd supplier	The 1st supplier	The 2nd supplier	The 1st supplier	The 2nd supplier
Printer	The 1st supplier	The 2nd supplier	The 1st supplier	The 2nd supplier	The 1st supplier	The 2nd supplier	The 1st supplier	The 2nd supplier
MSR	The 1st supplier	The 2nd supplier	The 1st supplier	The 2nd supplier	The 1st supplier	The 2nd supplier	The 1st supplier	The 2nd supplier
Button Cell CR2032	The 1st supplier	The 2nd supplier	The 1st supplier	The 2nd supplier	The 1st supplier	The 2nd supplier	The 1st supplier	The 2nd supplier
HW Version	H554-07-DC-0N5-32C-A1			H554-07-DC-0N4-32C-A1				
Note: This report tests all configurations 1, and other configurations only verify the data and are not recorded in the report								

2.3 Applied Standards

According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

Test standards

FCC Code CFR47 Part15B (2024)

ANSI C63.4-2014

2.4 Test Mode

Test Mode	
Mode 1	Adapter +USB cable + EUT+ Front camera On
Mode 2	Adapter +USB cable + EUT+ Rear camera On
Mode 3	Battery powered +EUT + Front camera On
Mode 4	Battery powered +EUT + Rear camera On

Test Type	Test Mode	Worst Mode
Radiated Emission	Mode 1, 2, 3, 4	Mode 2
Conducted Emission	Mode 1, 2	Mode 2

After technical evaluation or/and preliminary test, the test data of the worst-case condition was recorded in this report.

3 Test Case Results

3.1 Radiated Emission

Ambient Condition

Temperature	Relative humidity
15°C ~ 35°C	30% ~ 60%

Methods of Measurement

The EUT is placed on a non-metallic table 0.8m above the horizontal metal reference ground plane. The distance between EUT and receive antenna should be 3 meters. During the test, the EUT was operating in its typical mode. The test method is according to ANSI C63.4-2014. Sweep the whole frequency band through the range from 30MHz to the 5th harmonic of the carrier. During the test, the height of receive antenna shall be moved from 1 to 4 meters, and the antenna shall be performed under horizontal and vertical polarization. The turn table shall be rotated from 0 to 360 degrees for detecting the maximum of radiated signal level.

The data of cable loss and antenna factor has been calibrated in full testing frequency range before the testing. During the test, the EUT is worked at maximum output power.

Set the spectrum analyzer in the following:

Below 1GHz:

RBW=100 kHz / VBW=300 kHz / Sweep=AUTO

Above 1GHz:


(a) PEAK Detector: RBW=1MHz / VBW=3MHz/ Sweep=AUTO

(b) AVERAGE Detector: RBW=1MHz / VBW=3MHz / Sweep=AUTO


The radiated emission was measured in the following position: EUT stand-up position (Z axis), lie-down position (X, Y axis). The worst emission was found in lie-down position (X axis) and the worst case was recorded.

Test Setup

Below 1GHz



Above 1GHz



Note: Area side: 2.4mX3.6m

Antenna Tower meets ANSI C63.4 requirements for measurements above 1 GHz by keeping the antenna aimed at the EUT during the antenna's ascent/ descent along the antenna mast.

Limits**Class B**

Frequency (MHz)	Field Strength (dB μ V/m)	Detector
30 -88	40.0	Quasi-peak
88-216	43.5	Quasi-peak
216 – 960	46.0	Quasi-peak
960-1000	54.0	Quasi-peak
1000-5 th harmonic of the highest frequency or 40GHz, which is lower	54 74	Average Peak


Frequency range of radiated measurements

Highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper frequency of measurement range (MHz)
Below 1.705	30
1.705-108	1000
108-500	2000
500-1000	5000
Above 1000	5th harmonic of the highest frequency or 40 GHz, whichever is lower.

Test Results

Sweep the whole frequency band through the range from 30MHz to the 5th harmonic of the carrier. The Emissions in the frequency band 18GHz – 26.5GHz is more than 20dB below the limit are not reported.

The following graphs display the maximum values of horizontal and vertical by software. For above 1GHz, Blue trace uses the peak detection, Green trace uses the average detection.




Radiated Emission from 30MHz to 1GHz

Frequency (MHz)	Quasi-Peak (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Height (cm)	Polarization	Azimuth (deg)	Correct Factor (dB)
46.73	24.69	40.00	15.31	106.0	V	0.00	20
79.11	23.25	40.00	16.75	112.0	V	139.00	15
173.08	27.28	43.50	16.22	125.0	V	332.00	16
176.83	26.73	43.50	16.77	108.0	V	349.00	16
214.54	26.44	43.50	17.06	188.0	V	327.00	18
543.86	30.82	46.00	15.18	106.0	H	26.00	26

Remark: 1. Correction Factor = Antenna factor + Insertion loss(cable loss + amplifier gain)

2. Margin = Limit – Quasi-Peak


Radiated Emission from 1GHz to 18GHz

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Meas. Time (ms)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1342.13	---	19.64	54.00	34.36	1000.00	125.0	V	226.00	-13
1497.25	32.54	---	74.00	41.46	1000.00	101.0	V	280.00	-13
1873.38	---	22.69	54.00	31.31	1000.00	100.0	H	222.00	-11
1873.38	36.61	---	74.00	37.39	1000.00	101.0	H	234.00	-11
3373.63	---	26.27	54.00	27.73	1000.00	125.0	V	346.00	-6
4049.38	39.01	---	74.00	34.99	1000.00	112.0	V	294.00	-5
6212.63	45.60	---	74.00	28.40	1000.00	186.0	H	228.00	4
6767.25	---	34.12	54.00	19.88	1000.00	100.0	V	300.00	5
8448.13	47.85	---	74.00	26.15	1000.00	104.0	H	224.00	6
8607.50	---	34.98	54.00	19.02	1000.00	125.0	H	213.00	7
11064.00	50.58	---	74.00	23.42	1000.00	110.0	V	254.00	9
11102.25	---	37.88	54.00	16.12	1000.00	225.0	H	34.00	9

Remark: 1. Correction Factor = Antenna factor + Insertion loss (cable loss + amplifier gain)
2. Margin = Limit – MaxPeak / Average

3.2 Conducted Emission


Ambient Condition

Temperature	Relative humidity
15°C ~ 35°C	30% ~ 60%

Methods of Measurement

The EUT is placed on a non-metallic table of 80cm height above the horizontal metal reference ground plane. During the test, the EUT was operating in its typical mode. The test method is according to ANSI C63.4-2014. Connect the AC power line of the EUT to the L.I.S.N. Use EMI receiver to detect the average and Quasi-peak value. RBW is set to 9 kHz, VBW is set to 30kHz. The measurement result should include both L line and N line.

Test Setup



Note: Power Supply is AC Power source and it is used to change the voltage 120V/60Hz.

Limits


Frequency (MHz)	Class A (dB μ V)		Class B (dB μ V)	
	Quasi-peak	Average	Quasi-peak	Average
0.15 - 0.5	79	66	66 to 56 *	56 to 46*
0.5 - 5	73	60	56	46
5 - 30	73	60	60	50

*: Decreases with the logarithm of the frequency.

Note: The EUT should meet CLASS B limit.

Test Results

Following plots, Blue trace uses the peak detection; Green trace uses the average detection.




Frequency (MHz)	QuasiPeak (dBμV)	QuasiPeak Limit (dBμV)	QuasiPeak Margin (dB)	Average (dBμV)	Average Limit (dBμV)	Average Margin (dB)	Corr. (dB)	Line	Bandwidth (kHz)	Meas. Time (ms)
0.150	42.93	66.00	23.07	26.81	56.00	29.19	20.90	L1	9.000	1.000
0.479	34.63	56.37	21.73	26.53	46.37	19.84	20.80	L1	9.000	1.000
1.473	25.68	56.00	30.32	16.93	46.00	29.07	19.85	L1	9.000	1.000
4.171	22.90	56.00	33.10	14.46	46.00	31.54	19.42	L1	9.000	1.000
10.750	17.78	60.00	42.22	12.09	50.00	37.91	19.40	L1	9.000	1.000
23.467	18.76	60.00	41.24	11.59	50.00	38.41	19.75	L1	9.000	1.000

Remark: Correct factor=cable loss + LISN factor

L line

Conducted Emission from 150 kHz to 30 MHz



Frequency (MHz)	QuasiPeak (dB μ V)	QuasiPeak Limit (dB μ V)	QuasiPeak Margin (dB)	Average (dB μ V)	Average Limit (dB μ V)	Average Margin (dB)	Corr. (dB)	Line	Bandwidth (kHz)	Meas. Time (ms)
0.175	39.68	64.73	25.05	25.70	54.73	29.03	21.04	N	9.000	1.000
0.481	39.41	56.33	16.91	25.11	46.33	21.22	20.81	N	9.000	1.000
1.320	30.06	56.00	25.94	17.11	46.00	28.89	19.95	N	9.000	1.000
3.887	25.18	56.00	30.82	13.71	46.00	32.29	19.44	N	9.000	1.000
9.231	21.46	60.00	38.54	13.02	50.00	36.98	19.43	N	9.000	1.000
23.485	17.71	60.00	42.29	11.15	50.00	38.85	19.81	N	9.000	1.000
0.175	39.68	64.73	25.05	25.70	54.73	29.03	21.04	N	9.000	1.000
0.481	39.41	56.33	16.91	25.11	46.33	21.22	20.81	N	9.000	1.000
1.320	30.06	56.00	25.94	17.11	46.00	28.89	19.95	N	9.000	1.000
3.887	25.18	56.00	30.82	13.71	46.00	32.29	19.44	N	9.000	1.000
9.231	21.46	60.00	38.54	13.02	50.00	36.98	19.43	N	9.000	1.000

Remark: Correct factor=cable loss + LISN factor
N line
Conducted Emission from 150 kHz to 30 MHz

4 Uncertainty Measurement

Case	Uncertainty	Factor k
Radiated Emission 30MHz – 200MHz	4.17 dB	1.96
Radiated Emission 200MHz – 1GHz	4.84 dB	1.96
Radiated Emission 1GHz – 18GHz	4.35 dB	1.96
Radiated Emission 18GHz – 26.5GHz	5.90 dB	1.96
Radiated Emission 26.5GHz – 40GHz	5.92 dB	1.96
Conducted Emission	2.57 dB	2

5 Main Test Instruments

Name of Equipment	Manufacturer	Type/Model	Serial Number	Calibration Date	Expiration Time
Radiated Emission					
EMI Test Receiver	R&S	ESCI3	100948	2024-05-07	2025-05-06
Signal Analyzer	R&S	FSV40	101186	2024-05-07	2025-05-06
TRILOG Broadband Antenna	SCHWARZBECK	VULB 9163	1023	2023-07-14	2026-07-13
Horn Antenna	SCHWARZBECK	BBHA 9120D	430	2024-07-18	2027-07-17
Amplifier	MWPA.CN	MWLA-010200G 40	YQ2103039B0 1	2024-05-07	2025-05-06
Software	R&S	EMC32	9.26.01	/	/
Conducted Emission					
Artificial main network	R&S	ENV216	102191	2024-12-02	2026-12-01
EMI Test Receiver	R&S	ESR	101667	2024-05-07	2025-05-06
Software	R&S	EMC32	10.35.10	/	/

ANNEX A: The EUT Appearance

The EUT Appearance are submitted separately.

ANNEX B: Test Setup Photos

The Test Setup Photos are submitted separately.

***** END OF REPORT *****