Smart Motion Sensor
User manual

Version:V1.0

● Product parameter

1.Sensor X1	2.Manual X 1
3.Double-sided tape X1	

● Product parameter

Model	HZ-PIR-01
Battery Type	LR03 AAA X2
Operating Voltage	DC 3V
Quiescent Current	<65uA
Illuminance range	0 - 3000Lux
Communication	Zigbee3.0/Wifi (Optional)
Operating temperature&humidity	-10℃ ~ 55℃ <95% RH

● Operating instructions

1.Installing the battery
Pull down the bracket, open the back cover, and install 2 AAA batteries

Please pay special attention! The positive and negative poles of the battery are in the correct direction!
After installing the battery, snap the back cover of the bracket into the main body and push it upwards to secure the back cover.

3.Installation instructions
You can use the matching double-sided adhesive to fix the device to the wall, or use screws to fix it to the wall

Double-sided
Attention! Please do not aim the device at objects with high air flow or moving motion to avoid false alarms.
Please face the radar to the area that needs to be detected

● Please read the manual carefully and use the product correctly
Thank you for purchasing and using this product. Before using the product, please read the manual carefully and use the product correctly. In order to avoid damage to the equipment, such as all consequences caused by abnormal operation, The company will not bear any responsibility.
★ The pictures in this manual are used to guide the user's operation and are for reference only. Please refer to the actual product for

● Product description

Fresnel Lens

Light Sensor

Bracket

Indicator

● Download APP
Scan the QR code on the below, or in the app store Search for "Smart Life", download and install it The APP.

Smart Life

* Must connect to the zigbee gateway to use it. For details, see Zigbee Gateway Instruction manual, first bind Zigbee gateway to App.

2.Binding device description
Long press and hold the SET button for 3 seconds, the indicator light quickly flashes, and the device has entered the configuration network mode.

SET Button

* If the device is Zigbee , it must have a Zigbee gateway.And select Zigbee gateway.
When the APP finds the device, click the device icon and follow the APP prompts to complete the operation Bind.

● Function and working logic description
1.The red light flashes once, indicating that someone has been detected entering
2.The device collects light values every 1 minute, and if there is a change in the light value, it will automatically upload light data.
3.As it is a low-power device, after setting parameters, it needs to be triggered once or updated only when the device uploads data.

Radar parameter setting instructions

Scan QR to view