

**CFR 47 FCC PART 15 SUBPART C,  
ISED RSS-247 ISSUE 3 (DTS)**

**TEST REPORT**

*For*

**Smart Camera**

**MODEL NUMBER: E2**

**REPORT NUMBER: E04A25040355F00102**

**ISSUE DATE: July 11, 2025**

**FCC ID: 2BOVX-E2**

**IC: 33965-E2**

*Prepared for*

**FCC: Luna Home, LLC**

**IC: Luna Home LLC**

**FCC: 450 N 1500 W, Orem, Utah, United States, 84057**

**IC: 450 N 1500 W OREM UT 84057 United States Of America (Excluding The States  
Of Alaska)**

*Prepared by*

**Guangdong Global Testing Technology Co., Ltd.**

**Room 101-105, 203-210, Building 1, No.2, Keji 8 Road, Songshan Lake Park,  
Dongguan city, Guangdong, People's Republic of China, 523808**

**This report is based on a single evaluation of the submitted sample(s) of the above  
mentioned product, it does not imply an assessment of the production of the products.**

**This report shall not be reproduced, except in full, without the written approval of  
Guangdong Global Testing Technology Co., Ltd.**

## Revision History

| Rev. | Issue Date    | Revisions     | Revised By |
|------|---------------|---------------|------------|
| V0   | July 11, 2025 | Initial Issue |            |

### Summary of Test Results

| Test Item                                 | Clause  | Limit/Requirement   | Result |
|---|---|---|--------|
| Antenna Requirement                       | N/A   | FCC Part 15.203/15.247 (c)<br>RSS-GEN Clause 6.8  | Pass   |
| AC Power Line Conducted Emission          | ANSI C63.10-2013, Clause 6.2                  | FCC Part 15.207<br>RSS-GEN Clause 8.8   | Pass   |
| Conducted Output Power                    | ANSI C63.10-2013, Clause 11.9.1.3             | FCC Part 15.247 (b)(3)<br>RSS-247 Clause 5.4 (d)  | Pass   |
| 6dB Bandwidth and 99% Occupied Bandwidth  | ANSI C63.10-2013, Clause 11.8.1               | FCC Part 15.247 (a)(2)<br>RSS-247 Clause 5.2 (a)<br>ISED RSS-Gen Clause 6.7               | Pass   |
| Power Spectral Density                    | ANSI C63.10-2013, Clause 11.10.2              | FCC Part 15.247 (e)<br>RSS-247 Clause 5.2 (b)   | Pass   |
| Conducted Band edge and spurious emission | ANSI C63.10-2013, Clause 11.11                | FCC Part 15.247(d)<br>RSS-247 Clause 5.5  | Pass   |
| Radiated Band edge and Spurious Emission  | ANSI C63.10-2013, Clause 11.11 & Clause 11.12 | FCC Part 15.247 (d)<br>FCC Part 15.205/15.209<br>RSS-247 Clause 5.5<br>RSS-GEN Clause 8.9 | Pass   |
| Duty Cycle                                | ANSI C63.10-2013, Clause 11.6                 | None; for reporting purposes only.  | Pass   |

\*This test report is only published to and used by the applicant, and it is not for evidence purpose in China.

\*The measurement result for the sample received is <Pass> according to <CFR 47 FCC PART 15 SUBPART C, ISED RSS-247 ISSUE 3 (DTS)> when <Accuracy Method> decision rule is applied.

## CONTENTS

|   |    |
|---|----|
| 1. ATTESTATION OF TEST RESULTS.....                         | 5  |
| 2. TEST METHODOLOGY.....                                    | 6  |
| 3. FACILITIES AND ACCREDITATION.....                        | 6  |
| 4. CALIBRATION AND UNCERTAINTY .....                        | 7  |
| 4.1. <i>MEASURING INSTRUMENT CALIBRATION</i> .....          | 7  |
| 4.2. <i>MEASUREMENT UNCERTAINTY</i> .....                   | 7  |
| 5. EQUIPMENT UNDER TEST .....                               | 8  |
| 5.1. <i>DESCRIPTION OF EUT</i> .....                        | 8  |
| 5.2. <i>CHANNEL LIST</i> .....                              | 8  |
| 5.3. <i>MAXIMUM EIRP</i> .....                              | 8  |
| 5.4. <i>TEST CHANNEL CONFIGURATION</i> .....                | 9  |
| 5.5. <i>THE WORSE CASE POWER SETTING PARAMETER</i> .....    | 9  |
| 5.6. <i>DESCRIPTION OF AVAILABLE ANTENNAS</i> .....         | 9  |
| 5.7. <i>SUPPORT UNITS FOR SYSTEM TEST</i> .....             | 10 |
| 5.8. <i>SETUP DIAGRAM</i> .....                             | 10 |
| 6. MEASURING EQUIPMENT AND SOFTWARE USED.....               | 11 |
| 7. ANTENNA PORT TEST RESULTS .....                          | 13 |
| 7.1. <i>Conducted Output Power</i> .....                    | 13 |
| 7.2. <i>6dB Bandwidth and 99% Occupied Bandwidth</i> .....  | 14 |
| 7.3. <i>Power Spectral Density</i> .....                    | 16 |
| 7.4. <i>Conducted Band edge and spurious emission</i> ..... | 17 |
| 7.5. <i>Duty Cycle</i> .....                                | 19 |
| 8. RADIATED TEST RESULTS.....                               | 20 |
| 8.1. <i>Radiated Band edge and Spurious Emission</i> .....  | 26 |
| 9. ANTENNA REQUIREMENT .....                                | 38 |
| 10. AC POWER LINE CONDUCTED EMISSION .....                  | 40 |
| 11. TEST DATA - Appendix A.....                             | 43 |

## 1. ATTESTATION OF TEST RESULTS

### Applicant Information

Company Name: FCC: Luna Home, LLC  
 IC: Luna Home LLC  
 Address: FCC: 450 N 1500 W, Orem, Utah, United States, 84057  
 IC: 450 N 1500 W OREM UT 84057 United States Of America  
 (Excluding The States Of Alaska)

### Manufacturer Information

Company Name: Shenzhen Golden Vision Technology Development Co., Ltd  
 Address: No.6 Bao Fu Road, Bao Lai industrial Park, Shang Mu Gu  
 Villiage, Pinghu Street, Longgang District, Shenzhen City,  
 Guangdong Province, 518000, China

### EUT Information

Product Description: Smart Camera  
 Model: E2  
 Brand: /  
 Sample Received Date: April 28, 2025  
 Sample Status: Normal  
 Sample ID: A25040355 001  
 Date of Tested: April 28, 2025 to May 26, 2025

| APPLICABLE STANDARDS  |              |
|---|--------------|
| STANDARD  | TEST RESULTS |
| CFR 47 FCC PART 15 SUBPART C,<br>ISED RSS-247 ISSUE 3 (DTS) | Pass         |

Prepared By:

Jiajia Yang  
Project Engineer

Approved By:

Shawn Wen

Shawn Wen  
Laboratory Manager

Checked By:



 Alan He  
 Laboratory Leader

## 2. TEST METHODOLOGY

All tests were performed in accordance with the standard CFR 47 FCC PART 15 SUBPART C, ISED RSS-247 ISSUE 3 (DTS)

## 3. FACILITIES AND ACCREDITATION

|                           |  |
|---------------------------|--|
| Accreditation Certificate | <p><b>A2LA (Certificate No.: 6947.01)</b><br/>Guangdong Global Testing Technology Co., Ltd.<br/>has been assessed and proved to be in compliance with A2LA.</p> <p><b>FCC (FCC Designation No.: CN1343)</b><br/>Guangdong Global Testing Technology Co., Ltd.<br/>has been recognized to perform compliance testing on equipment<br/>subject to Supplier's Declaration of Conformity (SDoC) and<br/>Certification rules</p> <p><b>ISED (Company No.: 30714)</b><br/>Guangdong Global Testing Technology Co., Ltd.<br/>has been registered and fully described in a report filed with ISED.<br/>The Company Number is 30714 and the test lab Conformity<br/>Assessment Body Identifier (CABID) is CN0148.</p> |
|---------------------------|--|

Note: All tests measurement facilities use to collect the measurement data are located at  
Room 101-105, 203-210, Building 1, No.2, Keji 8 Road, Songshan Lake Park, Dongguan city,  
Guangdong, People's Republic of China, 523808

## 4. CALIBRATION AND UNCERTAINTY

### 4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations and is traceable to recognized national standards.

### 4.2. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

| Test Items                   | k    | Uncertainty   |
|------------------------------|------|---|
| DTS Bandwidth                | 1.96 | ±9.2 PPM  |
| 20dB Emission Bandwidth      | 1.96 | ±9.2 PPM  |
| Carrier Frequency Separation | 1.96 | ±9.2 PPM  |
| Time of Occupancy            | 1.96 | ±0.57%  |
| Conducted Output Power       | 1.96 | ±1.5 dB   |
| Power Spectral Density Level | 1.96 | ±1.9 dB   |
| Conducted Spurious Emission  | 1.96 | 9 kHz-30 MHz: ± 0.95 dB<br>30 MHz-1 GHz: ± 1.5 dB<br>1GHz-12.75GHz: ± 1.8 dB<br>12.75 GHz-26.5 GHz: ± 2.1dB |

Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=1.96.

| Test Item   | Measurement Frequency Range | K | U(dB) |
|---|-----------------------------|---|-------|
| Conducted emissions from the AC mains power ports (AMN) | 150 kHz ~ 30 MHz            | 2 | 3.37  |
| Radiated emissions                                      | 9 kHz ~ 30 MHz              | 2 | 4.16  |
| Radiated emissions                                      | 30 MHz ~ 1 GHz              | 2 | 3.79  |
| Radiated emissions                                      | 1 GHz ~ 18 GHz              | 2 | 5.62  |
| Radiated emissions                                      | 18 GHz ~ 40 GHz             | 2 | 5.54  |

Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

## 5. EQUIPMENT UNDER TEST

### 5.1. DESCRIPTION OF EUT

|                  |    |              |
|------------------|----|--------------|
| EUT Name         |    | Smart Camera |
| Model            |    | E2           |
| Hardware Version |    | V1.0         |
| Software Version |    | V1.0         |
| Ratings          |    | AC 100-240V  |
| Power Supply     | AC | 120V/60Hz    |

|                     |  |
|---------------------|--|
| Frequency Band:     | 2400 MHz to 2483.5 MHz   |
| Frequency Range:    | 2412 MHz to 2462 MHz   |
| Support Standards:  | 802.11b/g/n  |
| Type of Modulation: | IEEE 802.11b: DSSS(CCK, DQPSK, DBPSK)<br>IEEE 802.11g/n: OFDM(64-QAM, 16-QAM, QPSK, BPSK)  |
| Data Rate:          | IEEE 802.11b: Up to 11 Mbps<br>IEEE 802.11g: Up to 54 Mbps<br>IEEE 802.11n: Up to MCS7   |
| Number of Channels: | IEEE 802.11b/g/n-HT20: 11  |
| Maximum Peak Power: | IEEE 802.11b: 16.81 dBm<br>IEEE 802.11g: 18.10 dBm<br>IEEE 802.11n-HT20: 18.02 dBm   |
| Antenna Type:       | Internal antenna   |
| Antenna Gain:       | 2.04 dBi   |
| EUT Test software:  | SecureCRT.exe  |
| Note:               | The Antenna Gain was provided by customer, and this information may affect the validity of the results, customer should be responsible for this. |

### 5.2. CHANNEL LIST

| Channel List for 802.11b/g/n (20 MHz) |                 |         |                 |         |                 |         |                 |
|---------------------------------------|-----------------|---------|-----------------|---------|-----------------|---------|-----------------|
| Channel                               | Frequency (MHz) | Channel | Frequency (MHz) | Channel | Frequency (MHz) | Channel | Frequency (MHz) |
| 1                                     | 2412            | 4       | 2427            | 7       | 2442            | 10      | 2457            |
| 2                                     | 2417            | 5       | 2432            | 8       | 2447            | 11      | 2462            |
| 3                                     | 2422            | 6       | 2437            | 9       | 2452            | /       | /               |

### 5.3. MAXIMUM EIRP

| IEEE Std. 802.11 | Frequency (MHz) | Channel Number | Maximum Conducted Output Power (dBm) | Maximum EIRP (dBm) |
|------------------|-----------------|----------------|--------------------------------------|--------------------|
| b                | 2412 ~ 2462     | 1-11[11]       | 16.81                                | 18.85              |
| g                | 2412 ~ 2462     | 1-11[11]       | 18.10                                | 20.14              |
| n HT20           | 2412 ~ 2462     | 1-11[11]       | 18.02                                | 20.06              |

## 5.4. TEST CHANNEL CONFIGURATION

| IEEE Std. 802.11 | Test Channel Number  | Frequency                    |
|------------------|--|------------------------------|
| b                | CH 1(Low Channel), CH 6(MID Channel),<br>CH 11(High Channel) | 2412 MHz, 2437 MHz, 2462 MHz |
| g                | CH 1(Low Channel), CH 6(MID Channel),<br>CH 11(High Channel) | 2412 MHz, 2437 MHz, 2462 MHz |
| n HT20           | CH 1(Low Channel), CH 6(MID Channel),<br>CH 11(High Channel) | 2412 MHz, 2437 MHz, 2462 MHz |

## 5.5. THE WORSE CASE POWER SETTING PARAMETER

| The Worse Case Power Setting Parameter under 2400 ~ 2483.5MHz Band |                         |               |      |       |            |      |
|--|-------------------------|---------------|------|-------|------------|------|
| Test Software  |                         | SecureCRT.exe |      |       |            |      |
| Modulation Mode  | Transmit Antenna Number | Test Channel  |      |       |            |      |
|  |                         | NCB: 20MHz    |      |       | NCB: 40MHz |      |
|  |                         | CH 1          | CH 6 | CH 11 | CH 3       | CH 6 |
| 802.11b  | 1                       | -12           | -12  | -12   | NCB: 40MHz |      |
| 802.11g  | 1                       | -12           | -12  | -12   |            |      |
| 802.11n HT20   | 1                       | -16           | -16  | -16   |            |      |

## WORST-CASE CONFIGURATIONS

The EUT was tested in the following configuration(s):

Controlled in test mode using a software application on the EUT supplied by customer. The application was used to enable a continuous transmission and to select the mode, test channels, bandwidth, data rates as required.

Test channels referring to section 5.4.

Maximum power setting referring to section 5.5.

Worst-case data rates as provided by the client were:

802.11b mode: 1 Mbps  
802.11g mode: 6 Mbps  
802.11n HT20 mode: MCS0

## 5.6. DESCRIPTION OF AVAILABLE ANTENNAS

| Antenna | Frequency (MHz) | Antenna Type     | MAX Antenna Gain (dBi) |
|---------|-----------------|------------------|------------------------|
| 1       | 2412-2462       | Internal antenna | 2.04                   |

| Test Mode         | Transmit and Receive Mode                    | Description  |
|-------------------|--|--|
| IEEE 802.11b      | <input checked="" type="checkbox"/> 1TX, 1RX | ANT 1 can be used as transmitting/receiving antenna. |
| IEEE 802.11g      | <input checked="" type="checkbox"/> 1TX, 1RX | ANT 1 can be used as transmitting/receiving antenna. |
| IEEE 802.11n HT20 | <input checked="" type="checkbox"/> 1TX, 1RX | ANT 1 can be used as transmitting/receiving antenna. |

## 5.7. SUPPORT UNITS FOR SYSTEM TEST


| No. | Equipment  | Manufacturer | Model No. | Serial No. |
|-----|------------|--------------|-----------|------------|
| 1   | PC         | Lenovo       | T14       | /          |
| 2   | Test board | /            | /         | /          |

## 5.8. SETUP DIAGRAM


AC conducted emission :



Radiated Emission:



RF conducted:



## 6. MEASURING EQUIPMENT AND SOFTWARE USED

| Test Equipment of Conducted RF      |                 |                      |             |            |            |
|-------------------------------------|-----------------|----------------------|-------------|------------|------------|
| Equipment                           | Manufacturer    | Model No.            | Serial No.  | Last Cal.  | Due Date   |
| Spectrum Analyzer                   | Rohde & Schwarz | FSV40                | 102257      | 2024/09/14 | 2025/09/13 |
| Spectrum Analyzer                   | KEYSIGHT        | N9020A               | MY51285127  | 2024/09/14 | 2025/09/13 |
| EXG Analog Signal Generator         | KEYSIGHT        | N5173B               | MY61253075  | 2024/09/14 | 2025/09/13 |
| Vector Signal Generator             | Rohde & Schwarz | SMM100A              | 101899      | 2024/09/14 | 2025/09/13 |
| RF Control box                      | MWRF-test       | MW100-RFCB           | MW220926GTG | 2024/09/14 | 2025/09/13 |
| Wideband Radio Communication Tester | Rohde & Schwarz | CMW270               | 102792      | 2024/09/14 | 2025/09/13 |
| Wideband Radio Communication Tester | Rohde & Schwarz | CMW500               | 103235      | 2024/09/14 | 2025/09/13 |
| temperature humidity chamber        | Espec           | SH-241               | SH-241-2014 | 2024/09/14 | 2025/09/13 |
| RF Test Software                    | MWRF-test       | MTS8310E (Ver. V2/0) | N/A         | N/A        | N/A        |

| Test Equipment of Radiated emissions below 1GHz |                 |                         |            |            |            |
|---|-----------------|-------------------------|------------|------------|------------|
| Equipment                                       | Manufacturer    | Model No.               | Serial No. | Last Cal.  | Due Date   |
| 3m Semi-anechoic Chamber                        | ETS             | 9m*6m*6m                | Q2146      | 2022/08/30 | 2025/08/29 |
| EMI Test Receiver                               | Rohde & Schwarz | ESCI3                   | 101409     | 2024/09/14 | 2025/09/13 |
| Spectrum Analyzer                               | KEYSIGHT        | N9020A                  | MY51283932 | 2024/09/14 | 2025/09/13 |
| Pre-Amplifier                                   | HzEMC           | HPA-9K0130              | HYPA21001  | 2024/09/14 | 2025/09/13 |
| Biconilog Antenna                               | Schwarzbeck     | VULB 9168               | 01315      | 2022/10/10 | 2025/10/09 |
| Biconilog Antenna                               | ETS             | 3142E                   | 00243651   | 2025/02/22 | 2028/02/21 |
| Loop Antenna                                    | ETS             | 6502                    | 00243668   | 2025/02/22 | 2028/02/21 |
| Test Software                                   | Farad           | EZ-EMC (Ver.FA-03A2 RE) | N/A        | N/A        | N/A        |

| Test Equipment of Radiated emissions above 1GHz |                 |            |            |            |            |
|---|-----------------|------------|------------|------------|------------|
| Equipment                                       | Manufacturer    | Model No.  | Serial No. | Last Cal.  | Due Date   |
| 3m Semi-anechoic Chamber                        | ETS             | 9m*6m*6m   | Q2149      | 2022/08/30 | 2025/08/29 |
| Spectrum Analyzer                               | Rohde & Schwarz | FSV40      | 101413     | 2024/09/14 | 2025/09/13 |
| Spectrum Analyzer                               | KEYSIGHT        | N9020A     | MY51283932 | 2024/09/14 | 2025/09/13 |
| Pre-Amplifier                                   | HzEMC           | HPA-1G1850 | HYPA21003  | 2024/09/14 | 2025/09/13 |
| Horn antenna                                    | ETS             | 3117       | 00246069   | 2025/02/22 | 2028/02/21 |
| Pre-Amplifier                                   | HzEMC           | HPA-184057 | HYPA21004  | 2024/09/14 | 2025/09/13 |

|               |       |                                |          |            |            |
|---------------|-------|--------------------------------|----------|------------|------------|
| Horn antenna  | ETS   | 3116C                          | 00246265 | 2025/02/22 | 2028/02/21 |
| Test Software | Farad | EZ-EMC<br>(Ver.FA-03A2<br>RE+) | N/A      | N/A        | N/A        |

| Test Equipment of Conducted emissions |                 |                              |            |            |            |
|---------------------------------------|-----------------|------------------------------|------------|------------|------------|
| Equipment                             | Manufacturer    | Model No.                    | Serial No. | Last Cal.  | Due Date   |
| Shielded Room                         | CHENG YU        | 8m*5m*4m                     | N/A        | 2022/10/29 | 2025/10/28 |
| EMI Test Receiver                     | Rohde & Schwarz | ESR3                         | 102647     | 2024/09/14 | 2025/09/13 |
| LISN/AMN                              | Rohde & Schwarz | ENV216                       | 102843     | 2024/09/14 | 2025/09/13 |
| NNLK 8129 RC                          | Schwarzbeck     | NNLK 8129 RC                 | 5046       | 2024/09/14 | 2025/09/13 |
| Test Software                         | Farad           | EZ-EMC (Ver. EMC-con-3A1 1+) | N/A        | N/A        | N/A        |

## 7. ANTENNA PORT TEST RESULTS

### 7.1. CONDUCTED OUTPUT POWER

#### LIMITS


| CFR 47 FCC Part15 (15.247) Subpart C<br>ISED RSS-247 ISSUE 3 |                           |                  |                       |
|--|---------------------------|------------------|-----------------------|
| Section  | Test Item                 | Limit            | Frequency Range (MHz) |
| CFR 47 FCC 15.247(b)(3)<br>ISED RSS-247 5.4 (d)              | Peak Conduct Output Power | 1 watt or 30 dBm | 2400-2483.5           |

#### TEST PROCEDURE

Connect the EUT to a low loss RF cable from the antenna port to the power sensor (video bandwidth is greater than the occupied bandwidth).

Measure peak emission level, the indicated level is the peak output power, after any corrections for external attenuators and cables.

#### TEST SETUP



#### TEST ENVIRONMENT

|                     |        |                   |     |
|---------------------|--------|-------------------|-----|
| Temperature         | 24.5°C | Relative Humidity | 59% |
| Atmosphere Pressure | 101kPa |                   |     |

#### TEST RESULTS

Please refer to section "Test Data" - Appendix A

## 7.2. 6DB BANDWIDTH AND 99% OCCUPIED BANDWIDTH

### LIMITS

| CFR 47 FCC Part15 (15.247) Subpart C<br>ISED RSS-247 ISSUE 3 |                         |                              |                       |
|--|-------------------------|------------------------------|-----------------------|
| Section  | Test Item               | Limit                        | Frequency Range (MHz) |
| CFR 47 FCC 15.247(a)(2)<br>ISED RSS-247 5.2 (a)              | 6 dB Bandwidth          | $\geq 500$ kHz               | 2400-2483.5           |
| ISED RSS-Gen Clause 6.7                                      | 99 % Occupied Bandwidth | For reporting purposes only. | 2400-2483.5           |


### TEST PROCEDURE

Refer to ANSI C63.10-2013 clause 11.8 for DTS bandwidth and clause 6.9 for Occupied Bandwidth.

Connect the EUT to the spectrum analyser and use the following settings:

|                  |   |
|------------------|---|
| Center Frequency | The center frequency of the channel under test  |
| Frequency Span   | For 6 dB Bandwidth: Enough to capture all products of the modulation carrier emission<br>For 99 % Occupied Bandwidth: Between 1.5 times and 5.0 times the OBW |
| Detector         | Peak  |
| RBW              | For 6 dB Bandwidth: 100 kHz<br>For 99 % Occupied Bandwidth: 1 % to 5 % of the occupied bandwidth  |
| VBW              | For 6 dB Bandwidth: $\geq 3 \times$ RBW<br>For 99 % Occupied Bandwidth: $\geq 3 \times$ RBW   |
| Trace            | Max hold  |
| Sweep            | Auto couple   |

- Use the 99 % power bandwidth function of the instrument, allow the trace to stabilize and report the measured bandwidth.
- Allow the trace to stabilize and measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

**TEST SETUP****TEST ENVIRONMENT**

|                     |        |                   |     |
|---------------------|--------|-------------------|-----|
| Temperature         | 24.5°C | Relative Humidity | 59% |
| Atmosphere Pressure | 101kPa |                   |     |

**TEST RESULTS**

Please refer to section "Test Data" - Appendix A

### 7.3. POWER SPECTRAL DENSITY

#### LIMITS

| CFR 47 FCC Part15 (15.247) Subpart C<br>ISED RSS-247 ISSUE 3 |                        |                         |                       |
|--|------------------------|-------------------------|-----------------------|
| Section  | Test Item              | Limit                   | Frequency Range (MHz) |
| CFR 47 FCC §15.247 (e)<br>ISED RSS-247 5.2 (b)               | Power Spectral Density | 8 dBm in any 3 kHz band | 2400-2483.5           |

#### TEST PROCEDURE

Refer to ANSI C63.10-2013 clause 11.10.


Connect the EUT to the spectrum analyser and use the following settings:

|                  |  |
|------------------|--|
| Center Frequency | The center frequency of the channel under test       |
| Detector         | PEAK   |
| RBW              | $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$ |
| VBW              | $\geq 3 \times \text{RBW}$                           |
| Span             | $1.5 \times \text{DTS bandwidth}$                    |
| Trace            | Max hold   |
| Sweep time       | Auto couple  |

Allow trace to fully stabilize and use the peak marker function to determine the maximum amplitude level within the RBW.

If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

#### TEST SETUP



#### TEST ENVIRONMENT

|                     |        |                   |     |
|---------------------|--------|-------------------|-----|
| Temperature         | 24.5°C | Relative Humidity | 59% |
| Atmosphere Pressure | 101kPa |                   |     |

#### TEST RESULTS

Please refer to section "Test Data" - Appendix A

## 7.4. CONDUCTED BAND EDGE AND SPURIOUS EMISSION

### LIMITS

| CFR 47 FCC Part15 (15.247) Subpart C<br>ISED RSS-247 ISSUE 3 |   |   |
|--|---|---|
| Section  | Test Item                                       | Limit   |
| CFR 47 FCC §15.247 (d)<br>ISED RSS-247 5.5                   | Conducted<br>Bandedge and<br>Spurious Emissions | at least 20 dB below that in the 100 kHz<br>bandwidth within the band that contains<br>the highest level of the desired power |

### TEST PROCEDURE

Refer to ANSI C63.10-2013 clause 11.11 and 11.13.

Connect the EUT to the spectrum analyser and use the following settings for reference level measurement:


|                  |  |
|------------------|--|
| Center Frequency | The center frequency of the channel under test |
| Detector         | Peak   |
| RBW              | 100 kHz  |
| VBW              | $\geq 3 \times$ RBW                            |
| Span             | 1.5 x DTS bandwidth                            |
| Trace            | Max hold                                       |
| Sweep time       | Auto couple.                                   |

Allow trace to fully stabilize and use the peak marker function to determine the maximum PSD level.

Change the settings for emission level measurement:

|                    |   |
|--------------------|---|
| Span               | Set the center frequency and span to encompass frequency range to be measured |
| Detector           | Peak  |
| RBW                | 100 kHz   |
| VBW                | $\geq 3 \times$ RBW   |
| measurement points | $\geq$ span/RBW   |
| Trace              | Max hold  |
| Sweep time         | Auto couple.  |

Allow trace to fully stabilize and use the peak marker function to determine the maximum PSD level. Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum requirements specified in 11.11.

**TEST SETUP****TEST ENVIRONMENT**

|                     |        |                   |     |
|---------------------|--------|-------------------|-----|
| Temperature         | 24.5°C | Relative Humidity | 59% |
| Atmosphere Pressure | 101kPa |                   |     |

**TEST RESULTS**

Please refer to section "Test Data" - Appendix A

## 7.5. DUTY CYCLE


### LIMITS

None; for reporting purposes only.

### TEST PROCEDURE

Refer to ANSI C63.10-2013 clause 11.6 Zero – Span Spectrum Analyzer method.

### TEST SETUP



### TEST ENVIRONMENT

|                     |        |                   |     |
|---------------------|--------|-------------------|-----|
| Temperature         | 24.5°C | Relative Humidity | 59% |
| Atmosphere Pressure | 101kPa |                   |     |

### TEST RESULTS

Please refer to section "Test Data" - Appendix A

## 8. RADIATED TEST RESULTS

### LIMITS

Please refer to CFR 47 FCC §15.205 and §15.209.

Please refer to ISED RSS-GEN Clause 8.9 and Clause 8.10.

Radiation Disturbance Test Limit for FCC (Class B) (9 kHz ~ 1 GHz)

| Emissions radiated outside of the specified frequency bands above 30 MHz |                                    |                                      |         |
|--|------------------------------------|--------------------------------------|---------|
| Frequency Range (MHz)  | Field Strength Limit (uV/m) at 3 m | Field Strength Limit (dBuV/m) at 3 m |         |
|  |                                    | Quasi-Peak                           |         |
| 30 - 88  | 100                                | 40                                   |         |
| 88 - 216   | 150                                | 43.5                                 |         |
| 216 - 960  | 200                                | 46                                   |         |
| Above 960  | 500                                | 54                                   |         |
| Above 1000   | 500                                | Peak                                 | Average |
|  |                                    | 74                                   | 54      |

| FCC Emissions radiated outside of the specified frequency bands below 30 MHz |                                   |                               |
|--|-----------------------------------|-------------------------------|
| Frequency (MHz)  | Field strength (microvolts/meter) | Measurement distance (meters) |
| 0.009-0.490  | 2400/F(kHz)                       | 300                           |
| 0.490-1.705  | 24000/F(kHz)                      | 30                            |
| 1.705-30.0   | 30                                | 30                            |

ISED General field strength limits at frequencies below 30 MHz

| Table 6 – General field strength limits at frequencies below 30 MHz |  |                          |
|---|--|--------------------------|
| Frequency   | Magnetic field strength (H-Field) ( $\mu$ A/m) | Measurement distance (m) |
| 9 - 490 kHz <sup>Note 1</sup>                                       | 6.37/F (F in kHz)                              | 300                      |
| 490 - 1705 kHz  | 63.7/F (F in kHz)                              | 30                       |
| 1.705 - 30 MHz  | 0.08   | 30                       |

**Note 1:** The emission limits for the ranges 9-90 kHz and 110-490 kHz are based on measurements employing a linear average detector.

ISED Restricted bands please refer to ISED RSS-GEN Clause 8.10

| Table 7 – Restricted frequency bands <sup>Notes 1</sup> |                       |               |
|---|-----------------------|---------------|
| MHz   | MHz                   | GHz           |
| 0.090 - 0.110   | 149.9 - 150.05        | 9.0 - 9.2     |
| 0.495 - 0.505   | 156.52475 - 156.52525 | 9.3 - 9.5     |
| 2.1735 - 2.1905   | 156.7 - 156.9         | 10.6 - 12.7   |
| 3.020 - 3.026   | 162.0125 - 167.17     | 13.25 - 13.4  |
| 4.125 - 4.128   | 167.72 - 173.2        | 14.47 - 14.5  |
| 4.17725 - 4.17775                                       | 240 - 285             | 15.35 - 16.2  |
| 4.20725 - 4.20775                                       | 322 - 335.4           | 17.7 - 21.4   |
| 5.677 - 5.683   | 399.9 - 410           | 22.01 - 23.12 |
| 6.215 - 6.218   | 608 - 614             | 23.6 - 24.0   |
| 6.26775 - 6.26825                                       | 960 - 1427            | 31.2 - 31.8   |
| 6.31175 - 6.31225                                       | 1435 - 1626.5         | 36.43 - 36.5  |
| 8.291 - 8.294   | 1645.5 - 1646.5       | Above 38.6    |
| 8.362 - 8.366   | 1660 - 1710           |               |
| 8.37625 - 8.38675                                       | 1718.8 - 1722.2       |               |
| 8.41425 - 8.41475                                       | 2200 - 2300           |               |
| 12.29 - 12.293  | 2310 - 2390           |               |
| 12.51975 - 12.52025                                     | 2483.5 - 2500         |               |
| 12.57675 - 12.57725                                     | 2855 - 2900           |               |
| 13.36 - 13.41   | 3260 - 3287           |               |
| 16.42 - 16.423  | 3332 - 3339           |               |
| 16.69475 - 16.69525                                     | 3345.8 - 3358         |               |
| 16.80425 - 16.80475                                     | 3500 - 4400           |               |
| 25.5 - 25.67  | 4500 - 5150           |               |
| 37.5 - 38.25  | 5350 - 5460           |               |
| 73 - 74.6   | 7250 - 7750           |               |
| 74.8 - 75.2   | 8025 - 8500           |               |
| 108 - 138   |                       |               |

Note 1: Certain frequency bands listed in table 7 and in bands above 38.6 GHz are designated for licence-exempt applications. These frequency bands and the requirements that apply to related devices are set out in the 200 and 300 series of RSSs.

FCC Restricted bands of operation refer to FCC §15.205 (a):

| MHz                      | MHz                 | MHz           | GHz              |
|--------------------------|---------------------|---------------|------------------|
| 0.090-0.110              | 16.42-16.423        | 399.9-410     | 4.5-5.15         |
| <sup>1</sup> 0.495-0.505 | 16.69475-16.69525   | 608-614       | 5.35-5.46        |
| 2.1735-2.1905            | 16.80425-16.80475   | 960-1240      | 7.25-7.75        |
| 4.125-4.128              | 25.5-25.67          | 1300-1427     | 8.025-8.5        |
| 4.17725-4.17775          | 37.5-38.25          | 1435-1626.5   | 9.0-9.2          |
| 4.20725-4.20775          | 73-74.6             | 1645.5-1646.5 | 9.3-9.5          |
| 6.215-6.218              | 74.8-75.2           | 1660-1710     | 10.6-12.7        |
| 6.26775-6.26825          | 108-121.94          | 1718.8-1722.2 | 13.25-13.4       |
| 6.31175-6.31225          | 123-138             | 2200-2300     | 14.47-14.5       |
| 8.291-8.294              | 149.9-150.05        | 2310-2390     | 15.35-16.2       |
| 8.362-8.366              | 156.52475-156.52525 | 2483.5-2500   | 17.7-21.4        |
| 8.37625-8.38675          | 156.7-156.9         | 2690-2900     | 22.01-23.12      |
| 8.41425-8.41475          | 162.0125-167.17     | 3260-3267     | 23.6-24.0        |
| 12.29-12.293             | 167.72-173.2        | 3332-3339     | 31.2-31.8        |
| 12.51975-12.52025        | 240-285             | 3345.8-3358   | 36.43-36.5       |
| 12.57675-12.57725        | 322-335.4           | 3600-4400     | ( <sup>2</sup> ) |
| 13.36-13.41              |                     |               |                  |

Note: <sup>1</sup>Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

<sup>2</sup>Above 38.6c

### **TEST PROCEDURE**

Below 30 MHz

TRF No.: 04-E001-0B

Global Testing , Great Quality.

## The setting of the spectrum analyser

|       |  |
|-------|--|
| RBW   | 200 Hz (From 9 kHz to 0.15 MHz)/ 9 kHz (From 0.15 MHz to 30 MHz) |
| VBW   | 200 Hz (From 9 kHz to 0.15 MHz)/ 9 kHz (From 0.15 MHz to 30 MHz) |
| Sweep | Auto   |

1. The testing follows the guidelines in ANSI C63.10-2013 clause 6.4.
2. The EUT was arranged to its worst case and then turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both Horizontal, Face-on and Face-off polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80 cm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a 1 m height antenna tower.
5. The radiated emission limits are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz Radiated emission limits in these three bands are based on measurements employing an average detector.
6. For measurement below 1 GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak and average detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak and average detector and reported.
7. Although these tests were performed other than open field site, adequate comparison measurements were confirmed against 30m open field site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field site based on KDB 414788.
8. The limits in CFR 47, Part 15, Subpart C, paragraph 15.209 (a), are identical to those in RSS-GEN Section 8.9, Table 6, since the measurements are performed in terms of magnetic field strength and converted to electric field strength levels (as reported in the table) using the free space impedance of  $377\Omega$ . For example, the measurement frequency X KHz resulted in a level of Y dB<sub>uV</sub>/m, which is equivalent to  $Y - 51.5 = Z$  dB<sub>uA</sub>/m, which has the same margin, W dB, to the corresponding RSS-GEN Table 6 limit as it has to be 15.209(a) limit.

## Below 1 GHz and above 30 MHz

## The setting of the spectrum analyser

|          |          |
|----------|----------|
| RBW      | 120 kHz  |
| VBW      | 300 kHz  |
| Sweep    | Auto     |
| Detector | Peak/QP  |
| Trace    | Max hold |

1. The testing follows the guidelines in ANSI C63.10-2013 clause 6.5.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high

pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

3. The EUT was placed on a turntable with 80 cm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement below 1 GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.


#### Above 1G

##### The setting of the spectrum analyser

|          |                                |
|----------|--------------------------------|
| RBW      | 1 MHz                          |
| VBW      | PEAK: 3 MHz<br>AVG: see note 6 |
| Sweep    | Auto                           |
| Detector | Peak                           |
| Trace    | Max hold                       |


1. The testing follows the guidelines in ANSI C63.10-2013 clause 6.6.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 1.5 m above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement above 1 GHz, the emission measurement will be measured by the peak detector. This peak level, once corrected, must comply with the limit specified in Section 15.209.
6. For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 3 MHz for peak measurements and 1 MHz resolution bandwidth with 1/T video bandwidth with peak detector for average measurements. For the Duty Cycle please refer to clause 7.1.ON TIME AND DUTY CYCLE.


X axis, Y axis, Z axis positions:



Note 1: For all radiated test, EUT in each of three orthogonal axis emissions had been tested, but only the worst case (X axis) data recorded in the report.

### TEST SETUP






### TEST ENVIRONMENT

|                     |        |                   |     |
|---------------------|--------|-------------------|-----|
| Temperature         | 22.7°C | Relative Humidity | 49% |
| Atmosphere Pressure | 101kPa |                   |     |


### TEST RESULTS

## 8.1. RADIATED BAND EDGE AND SPURIOUS EMISSION



### Suspected Data List


| NO. | Frequency [MHz] | Reading [dBμV] | Level [dBμV/m] | Factor [dB/m] | Limit [dBμV/m] | Margin [dB] | Polarity | Detector | Verdict |
|-----|-----------------|----------------|----------------|---------------|----------------|-------------|----------|----------|---------|
| 1   | 299.66          | 60.68          | 42.00          | -18.68        | 46.00          | 4.00        | Vertical | PK       | PASS    |
| 2   | 350.10          | 59.14          | 42.94          | -16.2         | 46.00          | 3.06        | Vertical | PK       | PASS    |
| 3   | 426.73          | 55.16          | 41.33          | -13.83        | 46.00          | 4.67        | Vertical | PK       | PASS    |
| 4   | 450.01          | 55.69          | 42.01          | -13.68        | 46.00          | 3.99        | Vertical | PK       | PASS    |
| 5   | 549.92          | 51.43          | 41.94          | -9.49         | 46.00          | 4.06        | Vertical | PK       | PASS    |
| 6   | 600.36          | 47.26          | 37.83          | -9.43         | 46.00          | 8.17        | Vertical | PK       | PASS    |



| Suspected Data List |                 |                |                |               |                |             |            |          |         |
|---------------------|-----------------|----------------|----------------|---------------|----------------|-------------|------------|----------|---------|
| NO.                 | Frequency [MHz] | Reading [dBµV] | Level [dBµV/m] | Factor [dB/m] | Limit [dBµV/m] | Margin [dB] | Polarity   | Detector | Verdict |
| 1                   | 199.75          | 58.51          | 36.43          | -22.08        | 43.50          | 7.07        | Horizontal | PK       | PASS    |
| 2                   | 250.19          | 58.96          | 40.22          | -18.74        | 46.00          | 5.78        | Horizontal | PK       | PASS    |
| 3                   | 299.66          | 58.67          | 39.99          | -18.68        | 46.00          | 6.01        | Horizontal | PK       | PASS    |
| 4                   | 350.10          | 56.14          | 39.94          | -16.2         | 46.00          | 6.06        | Horizontal | PK       | PASS    |
| 5                   | 450.01          | 53.23          | 39.55          | -13.68        | 46.00          | 6.45        | Horizontal | PK       | PASS    |
| 6                   | 500.45          | 53.30          | 41.53          | -11.77        | 46.00          | 4.47        | Horizontal | PK       | PASS    |

Note:

1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.
3. Peak: Peak detector.
4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.




#### Suspected Data List


| NO. | Frequency [MHz] | Reading [dB $\mu$ V] | Level [dB $\mu$ V/m] | Factor [dB/m] | Limit [dB $\mu$ V/m] | Margin [dB] | Polarity | Detector | Verdict |
|-----|-----------------|----------------------|----------------------|---------------|----------------------|-------------|----------|----------|---------|
| 1   | 2408.00         | 54.80                | 46.28                | -8.52         | 74.00                | 27.72       | Vertical | PK       | PASS    |
| 2   | 2882.00         | 54.79                | 46.51                | -8.28         | 74.00                | 27.49       | Vertical | PK       | PASS    |
| 3   | 4824.00         | 57.88                | 46.41                | -11.47        | 74.00                | 27.59       | Vertical | PK       | PASS    |
| 4   | 11251.50        | 48.58                | 44.07                | -4.51         | 74.00                | 29.93       | Vertical | PK       | PASS    |
| 5   | 16272.00        | 47.32                | 46.14                | -1.18         | 74.00                | 27.86       | Vertical | PK       | PASS    |
| 6   | 17713.50        | 47.38                | 47.27                | -0.11         | 74.00                | 26.73       | Vertical | PK       | PASS    |




| Suspected Data List |                 |                |                |               |                |             |            |          |         |
|---------------------|-----------------|----------------|----------------|---------------|----------------|-------------|------------|----------|---------|
| NO.                 | Frequency [MHz] | Reading [dBμV] | Level [dBμV/m] | Factor [dB/m] | Limit [dBμV/m] | Margin [dB] | Polarity   | Detector | Verdict |
| 1                   | 2520.00         | 52.70          | 44.15          | -8.55         | 74.00          | 29.85       | Horizontal | PK       | PASS    |
| 2                   | 2998.00         | 53.23          | 46.22          | -7.01         | 74.00          | 27.78       | Horizontal | PK       | PASS    |
| 3                   | 4825.50         | 56.58          | 45.10          | -11.48        | 74.00          | 28.90       | Horizontal | PK       | PASS    |
| 4                   | 11929.50        | 48.87          | 44.36          | -4.51         | 74.00          | 29.64       | Horizontal | PK       | PASS    |
| 5                   | 15828.00        | 48.31          | 46.35          | -1.96         | 74.00          | 27.65       | Horizontal | PK       | PASS    |
| 6                   | 17676.00        | 47.45          | 47.76          | 0.31          | 74.00          | 26.24       | Horizontal | PK       | PASS    |




| Suspected Data List |                 |                      |                      |               |                      |             |            |          |         |
|---------------------|-----------------|----------------------|----------------------|---------------|----------------------|-------------|------------|----------|---------|
| NO.                 | Frequency [MHz] | Reading [dB $\mu$ V] | Level [dB $\mu$ V/m] | Factor [dB/m] | Limit [dB $\mu$ V/m] | Margin [dB] | Polarity   | Detector | Verdict |
| 1                   | 2370.00         | 54.29                | 45.83                | -8.46         | 74.00                | 28.17       | Horizontal | PK       | PASS    |
| 2                   | 2648.00         | 54.38                | 45.66                | -8.72         | 74.00                | 28.34       | Horizontal | PK       | PASS    |
| 3                   | 6078.00         | 52.23                | 44.12                | -8.11         | 74.00                | 29.88       | Horizontal | PK       | PASS    |
| 4                   | 6690.00         | 52.50                | 44.21                | -8.29         | 74.00                | 29.79       | Horizontal | PK       | PASS    |
| 5                   | 12538.50        | 48.47                | 44.36                | -4.11         | 74.00                | 29.64       | Horizontal | PK       | PASS    |
| 6                   | 17704.50        | 47.38                | 47.46                | 0.08          | 74.00                | 26.54       | Horizontal | PK       | PASS    |



| Suspected Data List |                 |                      |                      |               |                      |             |          |          |         |
|---------------------|-----------------|----------------------|----------------------|---------------|----------------------|-------------|----------|----------|---------|
| NO.                 | Frequency [MHz] | Reading [dB $\mu$ V] | Level [dB $\mu$ V/m] | Factor [dB/m] | Limit [dB $\mu$ V/m] | Margin [dB] | Polarity | Detector | Verdict |
| 1                   | 2370.00         | 53.39                | 44.93                | -8.46         | 74.00                | 29.07       | Vertical | PK       | PASS    |
| 2                   | 2992.00         | 54.98                | 47.99                | -6.99         | 74.00                | 26.01       | Vertical | PK       | PASS    |
| 3                   | 6043.50         | 51.84                | 43.62                | -8.22         | 74.00                | 30.38       | Vertical | PK       | PASS    |
| 4                   | 6919.50         | 51.08                | 43.03                | -8.05         | 74.00                | 30.97       | Vertical | PK       | PASS    |
| 5                   | 12603.00        | 48.53                | 44.30                | -4.23         | 74.00                | 29.70       | Vertical | PK       | PASS    |
| 6                   | 17568.00        | 46.85                | 46.35                | -0.5          | 74.00                | 27.65       | Vertical | PK       | PASS    |



| Suspected Data List |                 |                      |                      |               |                      |             |          |          |         |
|---------------------|-----------------|----------------------|----------------------|---------------|----------------------|-------------|----------|----------|---------|
| NO.                 | Frequency [MHz] | Reading [dB $\mu$ V] | Level [dB $\mu$ V/m] | Factor [dB/m] | Limit [dB $\mu$ V/m] | Margin [dB] | Polarity | Detector | Verdict |
| 1                   | 2358.00         | 52.99                | 44.62                | -8.37         | 74.00                | 29.38       | Vertical | PK       | PASS    |
| 2                   | 2834.00         | 53.49                | 45.72                | -7.77         | 74.00                | 28.28       | Vertical | PK       | PASS    |
| 3                   | 5100.00         | 54.51                | 44.09                | -10.42        | 74.00                | 29.91       | Vertical | PK       | PASS    |
| 4                   | 6081.00         | 53.13                | 45.00                | -8.13         | 74.00                | 29.00       | Vertical | PK       | PASS    |
| 5                   | 12408.00        | 49.20                | 44.47                | -4.73         | 74.00                | 29.53       | Vertical | PK       | PASS    |
| 6                   | 17677.50        | 48.30                | 48.60                | 0.3           | 74.00                | 25.40       | Vertical | PK       | PASS    |




| Suspected Data List |                 |                |                |               |                |             |            |          |         |
|---------------------|-----------------|----------------|----------------|---------------|----------------|-------------|------------|----------|---------|
| NO.                 | Frequency [MHz] | Reading [dBμV] | Level [dBμV/m] | Factor [dB/m] | Limit [dBμV/m] | Margin [dB] | Polarity   | Detector | Verdict |
| 1                   | 2514.00         | 53.54          | 45.05          | -8.49         | 74.00          | 28.95       | Horizontal | PK       | PASS    |
| 2                   | 2888.00         | 53.71          | 45.57          | -8.14         | 74.00          | 28.43       | Horizontal | PK       | PASS    |
| 3                   | 5130.00         | 52.82          | 42.55          | -10.27        | 74.00          | 31.45       | Horizontal | PK       | PASS    |
| 4                   | 5923.50         | 52.36          | 43.43          | -8.93         | 74.00          | 30.57       | Horizontal | PK       | PASS    |
| 5                   | 11628.00        | 47.77          | 42.85          | -4.92         | 74.00          | 31.15       | Horizontal | PK       | PASS    |
| 6                   | 17706.00        | 46.76          | 46.81          | 0.05          | 74.00          | 27.19       | Horizontal | PK       | PASS    |

Note:

1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.


For the frequency above 18 GHz, a pre-scan was performed, and the result was 20 dB lower than the limit line, the test data was not shown in the report.



| Suspected Data List |                 |                      |                      |               |                      |             |          |          |         |
|---------------------|-----------------|----------------------|----------------------|---------------|----------------------|-------------|----------|----------|---------|
| NO.                 | Frequency [MHz] | Reading [dB $\mu$ V] | Level [dB $\mu$ V/m] | Factor [dB/m] | Limit [dB $\mu$ V/m] | Margin [dB] | Polarity | Detector | Verdict |
| 1                   | 2388.65         | 28.05                | 50.74                | 22.69         | 74.00                | 23.26       | Vertical | PK       | PASS    |
| 2                   | 2390.00         | 27.55                | 50.27                | 22.72         | 74.00                | 23.73       | Vertical | PK       | PASS    |

|       |                     |        |              |
|-------|---------------------|--------|--------------|
| Mode: | 11G-2412            | Power: | AC 120V/60Hz |
| TE:   | Berny               | Date   | 2025/05/21   |
| T/A/P | 22.7°C/49%/101Kpa   |        |              |
| Note  | 2.310 GHz-2.440 GHz |        |              |

Test Graph




## Suspected Data List

| NO. | Frequency [MHz] | Reading [dB $\mu$ V] | Level [dB $\mu$ V/m] | Factor [dB/m] | Limit [dB $\mu$ V/m] | Margin [dB] | Polarity   | Detector | Verdict |
|-----|-----------------|----------------------|----------------------|---------------|----------------------|-------------|------------|----------|---------|
| 1   | 2387.35         | 31.02                | 53.69                | 22.67         | 74.00                | 20.31       | Horizontal | PK       | PASS    |
| 2   | 2390.00         | 28.80                | 51.52                | 22.72         | 74.00                | 22.48       | Horizontal | PK       | PASS    |

|       |                   |        |              |
|-------|-------------------|--------|--------------|
| Mode: | 11G-2462          | Power: | AC 120V/60Hz |
| TE:   | Berny             | Date   | 2025/05/21   |
| T/A/P | 22.7°C/49%/101Kpa |        |              |
| Note  | 2.440 GHz-2.6 GHz |        |              |


Test Graph



| Suspected Data List |                 |                      |                      |               |                      |             |            |          |         |
|---------------------|-----------------|----------------------|----------------------|---------------|----------------------|-------------|------------|----------|---------|
| NO.                 | Frequency [MHz] | Reading [dB $\mu$ V] | Level [dB $\mu$ V/m] | Factor [dB/m] | Limit [dB $\mu$ V/m] | Margin [dB] | Polarity   | Detector | Verdict |
| 1                   | 2483.50         | 28.98                | 52.13                | 23.15         | 74.00                | 21.87       | Horizontal | PK       | PASS    |
| 2                   | 2484.32         | 30.74                | 53.89                | 23.15         | 74.00                | 20.11       | Horizontal | PK       | PASS    |

|       |                   |        |              |
|-------|-------------------|--------|--------------|
| Mode: | 11G-2462          | Power: | AC 120V/60Hz |
| TE:   | Berny             | Date   | 2025/05/21   |
| T/A/P | 22.7°C/49%/101Kpa |        |              |
| Note  | 2.440 GHz-2.6 GHz |        |              |

Test Graph



| Suspected Data List |                 |                |                |               |                |             |          |          |         |
|---------------------|-----------------|----------------|----------------|---------------|----------------|-------------|----------|----------|---------|
| NO.                 | Frequency [MHz] | Reading [dBμV] | Level [dBμV/m] | Factor [dB/m] | Limit [dBμV/m] | Margin [dB] | Polarity | Detector | Verdict |
| 1                   | 2483.50         | 27.13          | 50.28          | 23.15         | 74.00          | 23.72       | Vertical | PK       | PASS    |
| 2                   | 2485.92         | 28.20          | 51.34          | 23.14         | 74.00          | 22.66       | Vertical | PK       | PASS    |

## Note:

1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

## 9. ANTENNA REQUIREMENT

### REQUIREMENT

Please refer to FCC §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Please refer to FCC §15.247(b)(4)

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

| Standard             | Requirement  |
|----------------------|--|
| RSS-Gen issue 5 6.8. | <p>The applicant for equipment certification shall provide a list of all antenna types that may be used with the transmitter, where applicable (i.e. for transmitters with detachable antenna), indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna. The test report shall demonstrate the compliance of the transmitter with the limit for maximum equivalent isotropically radiated power (e.i.r.p.) specified in the applicable RSS, when the transmitter is equipped with any antenna type, selected from this list.</p> <p>For expediting the testing, measurements may be performed using only the antenna with highest gain of each combination of transmitter and antenna type, with the transmitter output power set at the maximum level. However, the transmitter shall comply with the applicable requirements under all operational conditions and when in combination with any type of antenna from the list provided in the test report (and in the notice to be included in the user manual, provided below).</p> <p>When measurements at the antenna port are used to determine the RF output power, the effective gain of the device's antenna shall be stated, based on a measurement or on data from the antenna's manufacturer.</p> <p>The test report shall state the RF power, output power setting and spurious emission measurements with each antenna type that is used with the transmitter being tested.</p> <p>For licence-exempt equipment with detachable antennas, the user manual shall also contain the following notice in a conspicuous location:</p> <p>This radio transmitter [enter the device's ISED certification number] has been approved by Innovation, Science and Economic Development Canada to operate with the antenna types listed below, with the maximum permissible gain indicated. Antenna types not included in this list that have a gain greater than the maximum gain indicated for any type listed are strictly prohibited for use with this device.</p> |

|  |   |
|--|---|
|  | Immediately following the above notice, the manufacturer shall provide a list of all antenna types which can be used with the transmitter, indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna type. |
|--|---|

**DESCRIPTION**

Pass

## 10. AC POWER LINE CONDUCTED EMISSION

### LIMITS

Please refer to CFR 47 FCC §15.207 (a) and ISED RSS-Gen Clause 8.8


| FREQUENCY (MHz) | Quasi-peak | Average   |
|-----------------|------------|-----------|
| 0.15 -0.5       | 66 - 56 *  | 56 - 46 * |
| 0.50 -5.0       | 56.00      | 46.00     |
| 5.0 -30.0       | 60.00      | 50.00     |

### TEST PROCEDURE

The EUT is put on a table of non-conducting material that is 80 cm high. The vertical conducting wall of shielding is located 40 cm to the rear of the EUT. The power line of the EUT is connected to the AC mains through a Artificial Mains Network (A.M.N.). A EMI Measurement Receiver (R&S Test Receiver ESR3) is used to test the emissions from both sides of AC line. According to the requirements in Section 6.2 of ANSI C63.10-2013. Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode. The bandwidth of EMI test receiver is set at 9 kHz.


The arrangement of the equipment is installed to meet the standards and operating in a manner, which tends to maximize its emission characteristics in a normal application.

### TEST SETUP



### TEST ENVIRONMENT


|                     |         |                   |     |
|---------------------|---------|-------------------|-----|
| Temperature         | 26.1 °C | Relative Humidity | 57% |
| Atmosphere Pressure | 100kPa  |                   |     |

**TEST RESULTS**

Phase: L1

Mode: 802.11g 2412

| No. | Frequency<br>(MHz) | Reading<br>(dBuV) | Correct<br>(dB) | Result<br>(dBuV) | Limit<br>(dBuV) | Margin<br>(dB) | Remark |
|-----|--------------------|-------------------|-----------------|------------------|-----------------|----------------|--------|
| 1   | 0.1590             | 35.13             | 9.77            | 44.90            | 65.52           | -20.62         | QP     |
| 2   | 0.1590             | 17.51             | 9.77            | 27.28            | 55.52           | -28.24         | AVG    |
| 3   | 0.2040             | 31.38             | 9.78            | 41.16            | 63.45           | -22.29         | QP     |
| 4   | 0.2040             | 16.49             | 9.78            | 26.27            | 53.45           | -27.18         | AVG    |
| 5   | 0.2310             | 30.37             | 9.78            | 40.15            | 62.41           | -22.26         | QP     |
| 6   | 0.2310             | 15.07             | 9.78            | 24.85            | 52.41           | -27.56         | AVG    |
| 7   | 0.6720             | 33.25             | 9.80            | 43.05            | 56.00           | -12.95         | QP     |
| 8   | 0.6720             | 24.11             | 9.80            | 33.91            | 46.00           | -12.09         | AVG    |
| 9   | 0.6900             | 34.67             | 9.80            | 44.47            | 56.00           | -11.53         | QP     |
| 10  | 0.6900             | 20.59             | 9.80            | 30.39            | 46.00           | -15.61         | AVG    |
| 11  | 1.3380             | 27.46             | 9.82            | 37.28            | 56.00           | -18.72         | QP     |
| 12  | 1.3380             | 8.81              | 9.82            | 18.63            | 46.00           | -27.37         | AVG    |



Phase: N

Mode: 802.11g 2412

| No. | Frequency<br>(MHz) | Reading<br>(dBuV) | Correct<br>(dB) | Result<br>(dBuV) | Limit<br>(dBuV) | Margin<br>(dB) | Remark |
|-----|--------------------|-------------------|-----------------|------------------|-----------------|----------------|--------|
| 1   | 0.1545             | 35.28             | 9.67            | 44.95            | 65.75           | -20.80         | QP     |
| 2   | 0.1545             | 23.47             | 9.67            | 33.14            | 55.75           | -22.61         | AVG    |
| 3   | 0.1815             | 32.85             | 9.67            | 42.52            | 64.42           | -21.90         | QP     |
| 4   | 0.1815             | 21.81             | 9.67            | 31.48            | 54.42           | -22.94         | AVG    |
| 5   | 0.6675             | 36.74             | 9.70            | 46.44            | 56.00           | -9.56          | QP     |
| 6   | 0.6675             | 29.59             | 9.70            | 39.29            | 46.00           | -6.71          | AVG    |
| 7   | 0.6809             | 37.50             | 9.70            | 47.20            | 56.00           | -8.80          | QP     |
| 8   | 0.6809             | 25.59             | 9.70            | 35.29            | 46.00           | -10.71         | AVG    |
| 9   | 0.8700             | 28.28             | 9.70            | 37.98            | 56.00           | -18.02         | QP     |
| 10  | 0.8700             | 16.50             | 9.70            | 26.20            | 46.00           | -19.80         | AVG    |
| 11  | 1.1760             | 27.12             | 9.71            | 36.83            | 56.00           | -19.17         | QP     |
| 12  | 1.1760             | 19.71             | 9.71            | 29.42            | 46.00           | -16.58         | AVG    |

Note: 1. Result = Reading + Correct Factor.

2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 200 Hz (9 kHz ~ 150 kHz), 9 kHz (150 kHz ~ 30 MHz).


4. Step size: 80 Hz (0.009 MHz ~ 0.15 MHz), 4 kHz (0.15 MHz ~ 30 MHz), Scan time: auto.


Note: All the modes have been tested, only the worst data was recorded in the report.


## 11. TEST DATA - Appendix A


### Duty Cycle


| Condition | Mode | Frequency (MHz) | Antenna | On Time (ms) | Period (ms) | Duty Cycle (%) | Correction Factor (dB) | 1/T (kHz) |
|-----------|------|-----------------|---------|--------------|-------------|----------------|------------------------|-----------|
| NVNT      | b    | 2412            | Ant1    | -            | -           | 100            | 0                      | -         |
| NVNT      | b    | 2437            | Ant1    | -            | -           | 100            | 0                      | -         |
| NVNT      | b    | 2462            | Ant1    | -            | -           | 100            | 0                      | -         |
| NVNT      | g    | 2412            | Ant1    | -            | -           | 100            | 0                      | -         |
| NVNT      | g    | 2437            | Ant1    | -            | -           | 100            | 0                      | -         |
| NVNT      | g    | 2462            | Ant1    | -            | -           | 100            | 0                      | -         |
| NVNT      | n20  | 2412            | Ant1    | -            | -           | 100            | 0                      | -         |
| NVNT      | n20  | 2437            | Ant1    | -            | -           | 100            | 0                      | -         |
| NVNT      | n20  | 2462            | Ant1    | -            | -           | 100            | 0                      | -         |











## Maximum Conducted Output Power

| Condition | Mode | Frequency (MHz) | Antenna | Conducted Power (dBm) | Limit (dBm) | E.I.R.P (dBm) | E.I.R.P Limit (dBm) | Verdict |
|-----------|------|-----------------|---------|-----------------------|-------------|---------------|---------------------|---------|
| NVNT      | b    | 2412            | Ant1    | 16.81                 | 30          | 18.85         | <=36.02             | Pass    |
| NVNT      | b    | 2437            | Ant1    | 16.45                 | 30          | 18.49         | <=36.02             | Pass    |
| NVNT      | b    | 2462            | Ant1    | 16.68                 | 30          | 18.72         | <=36.02             | Pass    |
| NVNT      | g    | 2412            | Ant1    | 18.01                 | 30          | 20.05         | <=36.02             | Pass    |
| NVNT      | g    | 2437            | Ant1    | 17.89                 | 30          | 19.93         | <=36.02             | Pass    |
| NVNT      | g    | 2462            | Ant1    | 18.1                  | 30          | 20.14         | <=36.02             | Pass    |
| NVNT      | n20  | 2412            | Ant1    | 17.94                 | 30          | 19.98         | <=36.02             | Pass    |
| NVNT      | n20  | 2437            | Ant1    | 17.81                 | 30          | 19.85         | <=36.02             | Pass    |
| NVNT      | n20  | 2462            | Ant1    | 18.02                 | 30          | 20.06         | <=36.02             | Pass    |

Note1:Antenna Gain: 2.04dBi

Note2:E.I.R.P= Conducted Power+ Antenna Gain

**-6dB Bandwidth**

| Condition | Mode | Frequency (MHz) | Antenna | -6 dB Bandwidth (MHz) | Limit -6 dB Bandwidth (MHz) | Verdict |
|-----------|------|-----------------|---------|-----------------------|-----------------------------|---------|
| NVNT      | b    | 2412            | Ant1    | 10.11                 | 0.5                         | Pass    |
| NVNT      | b    | 2437            | Ant1    | 10.02                 | 0.5                         | Pass    |
| NVNT      | b    | 2462            | Ant1    | 10.11                 | 0.5                         | Pass    |
| NVNT      | g    | 2412            | Ant1    | 15.63                 | 0.5                         | Pass    |
| NVNT      | g    | 2437            | Ant1    | 16.11                 | 0.5                         | Pass    |
| NVNT      | g    | 2462            | Ant1    | 16.29                 | 0.5                         | Pass    |
| NVNT      | n20  | 2412            | Ant1    | 17.55                 | 0.5                         | Pass    |
| NVNT      | n20  | 2437            | Ant1    | 16.53                 | 0.5                         | Pass    |
| NVNT      | n20  | 2462            | Ant1    | 17.31                 | 0.5                         | Pass    |