



Radio Test Report

Report No.: STS2503179W02

Issued for

XPO Health Limited

East House, Braeside Business Park, Sterte Avenue West,
Poole, BH15 2BX, UK

Product Name: E4L miHealth 2.0

Brand Name: E4L

Model Name: E4L miHealth 2.0

Series Model(s): N/A

FCC ID: 2BOXK-MIHEALTH02

Test Standards: FCC Part15.247

The test results presented in this report relate only to the object tested. This report shall not be reproduced, except in full, without the written approval of the Shenzhen STS Test Services Co., Ltd.

**TEST REPORT****Applicant's Name**.....: XPO Health LimitedAddress: East House, Braeside Business Park, Sterte Avenue West, Poole,
BH15 2BX, UK**Manufacturer's Name**: Electronic Precepts

Address: 4525 140th Ave N Suite 900 Clearwater, FL 33762 USA

Product Description

Product Name.....: E4L miHealth 2.0

Brand Name: E4L

Model Name: E4L miHealth 2.0

Series Model(s): N/A

Test Standards: FCC Part15.247

Test Procedure: ANSI C63.10-2020

This device described above has been tested by STS, the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

The test results presented in this report relate only to the object tested. This report shall not be reproduced, except in full, without the written approval of the Shenzhen STS Test Services Co., Ltd.

Date of Test

Date of receipt of test item: 26 Mar. 2025

Date (s) of performance of tests: 26 Mar. 2025 ~ 19 Apr. 2025

Date of Issue.....: 19 Apr. 2025

Test Result.....: **Pass**

Testing Engineer :

Aaron Bu

(Aaron Bu)

Technical Manager :

Skylar Li

(Skylar Li)

Authorized Signatory :

Bovey Yang

(Bovey Yang)



**Table of Contents**

1. SUMMARY OF TEST RESULTS	6
1.1 TEST FACTORY	7
1.2 MEASUREMENT UNCERTAINTY	7
2. GENERAL INFORMATION	8
2.1 GENERAL DESCRIPTION OF THE EUT	8
2.2 DESCRIPTION OF THE TEST MODES	10
2.3 TEST SOFTWARE AND POWER LEVEL	10
2.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	11
2.5 DESCRIPTION OF NECESSARY ACCESSORIES AND SUPPORT UNITS	12
2.6 EQUIPMENTS LIST	13
3. EMC EMISSION TEST	14
3.1 CONDUCTED EMISSION MEASUREMENT	14
3.2 TEST PROCEDURE	15
3.3 TEST SETUP	15
3.4 EUT OPERATING CONDITIONS	15
3.5 TEST RESULTS	16
4. RADIATED EMISSION MEASUREMENT	18
4.1 RADIATED EMISSION LIMITS	18
4.2 TEST PROCEDURE	20
4.3 TEST SETUP	21
4.4 EUT OPERATING CONDITIONS	21
4.5 FIELD STRENGTH CALCULATION	22
4.6 TEST RESULTS	22
5. CONDUCTED SPURIOUS & BAND EDGE EMISSION	43
5.1 LIMIT	43
5.2 TEST PROCEDURE	43
5.3 TEST SETUP	43
5.4 EUT OPERATION CONDITIONS	43
5.5 TEST RESULTS	43
6. POWER SPECTRAL DENSITY TEST	44
6.1 LIMIT	44
6.2 TEST PROCEDURE	44
6.3 TEST SETUP	44



Table of Contents

6.4 EUT OPERATION CONDITIONS	44
6.5 TEST RESULTS	44
7. BANDWIDTH TEST	45
7.1 LIMIT	45
7.2 TEST PROCEDURE	45
7.3 TEST SETUP	45
7.4 EUT OPERATION CONDITIONS	45
7.5 TEST RESULTS	45
8. PEAK OUTPUT POWER TEST	46
8.1 LIMIT	46
8.2 TEST PROCEDURE	46
8.3 TEST SETUP	47
8.4 EUT OPERATION CONDITIONS	47
8.5 TEST RESULTS	47
9. ANTENNA REQUIREMENT	48
9.1 STANDARD REQUIREMENT	48
9.2 EUT ANTENNA	48
APPENDIX 1-TEST DATA	49
DUTY CYCLE	49
MAXIMUM AVERAGE CONDUCTED OUTPUT POWER	53
MAXIMUM PEAK CONDUCTED OUTPUT POWER	57
-6DB BANDWIDTH	61
MAXIMUM POWER SPECTRAL DENSITY LEVEL	65
BAND EDGE	69
CONDUCTED RF SPURIOUS EMISSION	74
APPENDIX 2- EUT TEST PHOTO	81

**Revision History**

Rev.	Issue Date	Report No.	Effect Page	Contents
00	19 Apr. 2025	STS2503179W02	ALL	Initial Issue



1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:
KDB 558074 D01 15.247 Meas Guidance v05r02.

FCC Part 15.247, Subpart C			
Standard Section	Test Item	Judgment	Remark
15.207	Conducted Emission	PASS	--
15.247 (a)(2)	6dB Bandwidth	PASS	--
15.247 (b)(3)	Output Power	PASS	--
15.209	Radiated Spurious Emission	PASS	--
15.247 (d)	Conducted Spurious & Band Edge Emission	PASS	--
15.247 (e)	Power Spectral Density	PASS	--
15.205	Restricted bands of operation	PASS	--
Part 15.247(d)/ Part 15.209(a)	Band Edge Emission	PASS	--
15.203	Antenna Requirement	PASS	--

NOTE:

- (1) 'N/A' denotes test is not applicable in this Test Report.
- (2) All tests are according to ANSI C63.10-2020.



1.1 TEST FACTORY

SHENZHEN STS TEST SERVICES CO., LTD

Add. : 101, Building B, Zhuoke Science Park, No.190 Chongqing Road, ZhanChengShequ, Fuhai Sub-District, Bao'an District, Shenzhen, Guang Dong, China

FCC test Firm Registration Number: 625569

IC test Firm Registration Number: 12108A

A2LA Certificate No.: 4338.01

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately **95 %**.

No.	Item	Uncertainty
1	RF output power, conducted	$\pm 0.755\text{dB}$
2	Unwanted Emissions, conducted	$\pm 2.874\text{dB}$
3	All emissions, radiated 9K-30MHz	$\pm 3.80\text{dB}$
4	All emissions, radiated 30M-1GHz	$\pm 4.18\text{dB}$
5	All emissions, radiated 1G-6GHz	$\pm 4.90\text{dB}$
6	All emissions, radiated >6G	$\pm 5.24\text{dB}$
7	Conducted Emission (9KHz-150KHz)	$\pm 2.19\text{dB}$
8	Conducted Emission (150KHz-30MHz)	$\pm 2.53\text{dB}$
9	Occupied Channel Bandwidth	$\pm 3.5\%$
10	Power Spectral Density, conducted	$\pm 1.245\text{dB}$
11	Duty Cycle	$\pm 3.2\%$



2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF THE EUT

Product Name	E4L miHealth 2.0	
Brand Name	E4L	
Model Name	E4L miHealth 2.0	
Series Model(s)	N/A	
Model Difference	N/A	
Product Description	The EUT is a E4L miHealth 2.0	
	Operation Frequency:	2402~2480 MHz
	Modulation Type:	GFSK
	Radio Technology:	BLE
	Bluetooth Configuration:	LE(Support 1M PHY,2M PHY)
	Number Of Channel:	40
	Antenna Type:	Ceramic Antenna
	Antenna Gain (dBi)	0.5dBi
Channel List	Please refer to the Note 3.	
Power Rating	DC 5V 0.5A	
Adapter	N/A	
Battery	Rated Voltage:3.7V Charge Limit Voltage: 4.2V Capacity: 2000mAh	
Hardware version number	Rev A8	
Software version number	1.3.7-1.2.10	
Connecting I/O Port(s)	Please refer to the Note 1.	

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User Manual.
2. The antenna information refer the manufacturer provide report, applicable only to the tested sample identified in the report. Due to the incorrect antenna information, a series of problems such as the accuracy of the test results will be borne by the customer.



3.

Channel List							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2402	10	2422	20	2442	30	2462
01	2404	11	2424	21	2444	31	2464
02	2406	12	2426	22	2446	32	2466
03	2408	13	2428	23	2448	33	2468
04	2410	14	2430	24	2450	34	2470
05	2412	15	2432	25	2452	35	2472
06	2414	16	2434	26	2454	36	2474
07	2416	17	2436	27	2456	37	2476
08	2418	18	2438	28	2458	38	2478
09	2420	19	2440	29	2460	39	2480



2.2 DESCRIPTION OF THE TEST MODES

For conducted test items and radiated spurious emissions
Each of these EUT operation mode(s) or test configuration mode(s) mentioned below was evaluated respectively.

Worst Mode	Description	Data/Modulation
Mode 1	TX CH00(2402MHz)	1M PHY /GFSK
Mode 2	TX CH19(2440MHz)	1M PHY /GFSK
Mode 3	TX CH39(2480MHz)	1M PHY /GFSK

Worst Mode	Description	Data/Modulation
Mode 4	TX CH00(2402MHz)	2M PHY /GFSK
Mode 5	TX CH19(2440MHz)	2M PHY /GFSK
Mode 6	TX CH39(2480MHz)	2M PHY /GFSK

Note:

- (1) The measurements are performed at all Bit Rate of Transmitter, the worst data was reported.
- (2) We have be tested for all avaiable U.S. voltage and frequencies(For 120V,50/60Hz and 240V, 50/60Hz) for which the device is capable of operation, and the worst case of 120V/60Hz is shown in the report.
- (3) The battery is fully-charged during the radited and RF conducted test.

For AC Conducted Emission

Test Case	
AC Conducted Emission	Mode 7 : Keeping BT TX


2.3 TEST SOFTWARE AND POWER LEVEL

During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level.


RF Function	Type	Mode Or Modulation type	ANT Gain(dBi)	Power Class	Software For Testing
BLE(With 2M PHY)	BLE_1M PHY	GFSK	0.5	Default	QRCT
	BLE_2M PHY	GFSK	0.5	Default	

2.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Radiated Spurious Emission Test



Conducted Emission Test





2.5 DESCRIPTION OF NECESSARY ACCESSORIES AND SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Note
E-1	Personal computer	DELL	Inspiron 3501	N/A
E-2	Adapter	ZTC	NB-A515A	N/A
C-1	Serial port board	XES	WTYZK	N/A
C-2	USB Cable	ZTC	NB-A515A	N/A

Item	Shielded Type	Ferrite Core	Length	Note
C-2	Shielded	NO	150cm	N/A

Note:

- (1) For detachable type I/O cable should be specified the length in cm in 『Length』 column.
- (2) “YES” is means “with core”; “NO” is means “without core”.



2.6 EQUIPMENTS LIST

RF Radiation Test Equipment					
Kind of Equipment	Manufacturer	Type No.	Serial No.	Last Calibration	Calibrated Until
Temperature & Humidity	SW-108	SuWei	N/A	2025.02.24	2026.02.23
Pre-Amplifier(0.1M-3GHz)	EM	EM330	060665	2025.02.22	2026.02.21
Pre-Amplifier(1G-18GHz)	SKET	LNPA-01018G-45	SK2018080901	2024.09.23	2025.09.22
Pre-Amplifier(18G-40GHz)	SKET	LNPA_1840-50	SK2018101801	2025.02.22	2026.02.21
Active loop Antenna	ZHINAN	ZN30900C	16035	2025.02.25	2026.02.24
Bilog Antenna	TESEQ	CBL6111D	34678	2024.09.30	2025.09.29
Horn Antenna	SCHWARZBECK	BBHA 9120D	02014	2023.09.24	2025.09.23
Horn Antenna	A-INFOMW	LB-180400-KF	J211020657	2023.10.10	2025.10.09
Positioning Controller	MF	MF-7802	MF-780208587	N/A	N/A
Signal Analyzer	R&S	FSV 40-N	101823	2024.09.23	2025.09.22
Switch Control Box	N/A	N/A	N/A	N/A	N/A
Filter Box	BALUN Technology	SU319E	BL-SZ1530051	N/A	N/A
Antenna Mast	MF	MFA-440H	N/A	N/A	N/A
Turn Table	MF	SC100_1	60531	N/A	N/A
AC Power Source	APC	KDF-11010G	F214050035	N/A	N/A
DC power supply	HONGSHENGFENG	DPS-305AF	17064939	2024.09.23	2025.09.22
Test SW	EZ-EMC	Ver.STSLAB-03A1 RE			
Conduction Test equipment					
Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
Test Receiver	R&S	ESCI	101427	2024.09.24	2025.09.23
Limtter	CYBERTEK	EM5010	N/A	2024.09.24	2025.09.23
LISN	R&S	ENV216	101242	2024.09.24	2025.09.23
LISN	EMCO	3810/2NM	23625	2024.09.24	2025.09.23
Temperature & Humidity	SW-108	SuWei	N/A	2025.02.24	2026.02.23
Test SW	EZ-EMC	Ver.STSLAB-03A1 CE			
RF Connected Test					
Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
Signal Analyzer	Agilent	N9020A	MY51510623	2025.02.22	2026.02.21
Power Sensor	Keysight	U2021XA	MY56120038	2024.09.23	2025.09.22
Temperature & Humidity	SW-108	SuWei	N/A	2025.02.24	2026.02.23
Test SW	MW	MTS 8310_2.0.0.0			



3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 POWER LINE CONDUCTED EMISSION LIMITS

The radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table.

FREQUENCY (MHz)	Conducted Emission limit (dBuV)	
	Quasi-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of “ * ” marked band means the limitation decreases linearly with the logarithm of the frequency in the range.


The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

3.2 TEST PROCEDURE

- The EUT is 0.8 m from the horizontal ground plane and 0.4 m from the vertical ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments are powered from additional LISN(s). The LISN provides 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- LISN is at least 80 cm from the nearest part of EUT chassis.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.3 TEST SETUP



Note: 1. Support units were connected to second LISN.

2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes support units.

3.4 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.



3.5 TEST RESULTS


Temperature:	25.1℃	Relative Humidity:	59%RH
Test Voltage:	AC 120V/60Hz	Phase:	L
Test Mode:	Mode 7		

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.4380	21.20	20.01	41.21	57.10	-15.89	QP
2	0.4380	11.64	20.01	31.65	47.10	-15.45	AVG
3	0.4980	21.72	20.01	41.73	56.03	-14.30	QP
4	0.4980	12.13	20.01	32.14	46.03	-13.89	AVG
5	0.7980	18.78	19.80	38.58	56.00	-17.42	QP
6	0.7980	7.53	19.80	27.33	46.00	-18.67	AVG
7	1.4220	17.67	19.78	37.45	56.00	-18.55	QP
8	1.4220	6.60	19.78	26.38	46.00	-19.62	AVG
9	2.6220	16.73	19.81	36.54	56.00	-19.46	QP
10	2.6220	5.66	19.81	25.47	46.00	-20.53	AVG
11	7.3340	23.72	19.89	43.61	60.00	-16.39	QP
12	7.3340	11.66	19.89	31.55	50.00	-18.45	AVG

Remark:

1. All readings are Quasi-Peak and Average values
2. Margin = Result (Result = Reading + Factor) – Limit
3. Factor = LISN factor + Cable loss + Limiter (10dB)

100.0 dBuV






Temperature:	25.1℃	Relative Humidity:	59%RH
Test Voltage:	AC 120V/60Hz	Phase:	N
Test Mode:	Mode 7		

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.4380	18.53	20.01	38.54	57.10	-18.56	QP
2	0.4380	5.42	20.01	25.43	47.10	-21.67	AVG
3	0.4900	17.40	19.97	37.37	56.17	-18.80	QP
4	0.4900	6.50	19.97	26.47	46.17	-19.70	AVG
5	0.8020	14.95	19.82	34.77	56.00	-21.23	QP
6	0.8020	2.13	19.82	21.95	46.00	-24.05	AVG
7	2.0300	16.37	19.88	36.25	56.00	-19.75	QP
8	2.0300	2.03	19.88	21.91	46.00	-24.09	AVG
9	4.3740	15.49	19.93	35.42	56.00	-20.58	QP
10	4.3740	1.60	19.93	21.53	46.00	-24.47	AVG
11	7.3980	22.30	19.86	42.16	60.00	-17.84	QP
12	7.3980	7.47	19.86	27.33	50.00	-22.67	AVG

Remark:

1. All readings are Quasi-Peak and Average values
2. Margin = Result (Result = Reading + Factor) – Limit
3. Factor = LISN factor + Cable loss + Limiter (10dB)

100.0 dBuV





4. RADIATED EMISSION MEASUREMENT

4.1 RADIATED EMISSION LIMITS

In any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the Restricted band specified on Part15.205(a)&209(a) limit in the table and according to ANSI C63.10-2020 below has to be followed.

LIMITS OF RADIATED EMISSION MEASUREMENT (Frequency Range 9kHz-1000MHz)

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	(dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

LIMITS OF RESTRICTED FREQUENCY BANDS

FREQUENCY (MHz)	FREQUENCY (MHz)	FREQUENCY (MHz)	FREQUENCY (GHz)
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	Above 38.6
13.36-13.41			



For Radiated Emission

Spectrum Parameter	Setting
Attenuation	Auto
Detector	Peak/QP/AV
Start Frequency	9 KHz/150KHz(Peak/QP/AV)
Stop Frequency	150KHz/30MHz(Peak/QP/AV)
RB / VB (emission in restricted band)	200Hz (From 9kHz to 0.15MHz)/ 9KHz (From 0.15MHz to 30MHz); 200Hz (From 9kHz to 0.15MHz)/ 9KHz (From 0.15MHz to 30MHz)

Spectrum Parameter	Setting
Attenuation	Auto
Detector	Peak/QP
Start Frequency	30 MHz(Peak/QP)
Stop Frequency	1000 MHz (Peak/QP)
RB / VB (emission in restricted band)	120 KHz / 300 KHz

Spectrum Parameter	Setting
Attenuation	Auto
Detector	Peak/AV
Start Frequency	1000 MHz(Peak/AV)
Stop Frequency	10th carrier hamonic(Peak/AV)
RB / VB (emission in restricted band)	1 MHz / 3 MHz(Peak) 1 MHz/1/T MHz(AVG)

For Restricted band

Spectrum Parameter	Setting
Detector	Peak/AV
Start/Stop Frequency	Lower Band Edge: 2310 to 2410 MHz Upper Band Edge: 2475 to 2500 MHz
RB / VB	1 MHz / 3 MHz(Peak) 1 MHz/1/T MHz(AVG)



Receiver Parameter	Setting
Start ~ Stop Frequency	9kHz~90kHz / RB 200Hz for PK & AV
Start ~ Stop Frequency	90kHz~110kHz / RB 200Hz for QP
Start ~ Stop Frequency	110kHz~490kHz / RB 200Hz for PK & AV
Start ~ Stop Frequency	490kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

4.2 TEST PROCEDURE


- The measuring distance at 3 m shall be used for measurements at frequency 0.009MHz up to 1GHz, and above 1GHz.
- The EUT was placed on the top of a rotating table 0.8 m (above 1GHz is 1.5 m) above the ground at a 3 m anechoic chamber test site. The table was rotated 360 degree to determine the position of the highest radiation.
- The height of the equipment shall be 0.8 m (above 1GHz is 1.5 m); the height of the test antenna shall vary between 1 m to 4 m. Horizontal and vertical polarization of the antenna are set to make the measurement.
- The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and QuasiPeak detector mode will be re-measured.
- If the Peak Mode measured value is compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and no additional QP Mode measurement was performed.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported.

4.3 TEST SETUP


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz



4.4 EUT OPERATING CONDITIONS

Please refer to section 3.4 of this report.



4.5 FIELD STRENGTH CALCULATION

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor (if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CL - AG$$

Where

FS = Field Strength

CL = Cable Attenuation Factor (Cable Loss)

RA = Reading Amplitude

AG = Amplifier Gain

AF = Antenna Factor

For example

Frequency	FS	RA	AF	CL	AG	Factor
(MHz)	(dBμV/m)	(dBμV/m)	(dB)	(dB)	(dB)	(dB)
300	40	58.1	12.2	1.6	31.9	-18.1

$$\text{Factor} = \text{AF} + \text{CL} - \text{AG}$$

4.6 TEST RESULTS

(Between 9KHz – 30 MHz)

Temperature:	23.4℃	Relative Humidity:	60%RH
Test Voltage:	DC 3.7V From Battery	Polarization:	--
Test Mode:	TX Mode		

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
--	--	--	--	PASS
--	--	--	--	PASS

Note:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor = $40 \log (\text{specific distance/test distance})$ (dB);

Limit line = specific limits(dBuv) + distance extrapolation factor.



(30MHz -1000MHz)


1M PHY

Temperature:	23.4℃	Relative Humidity:	60%RH
Test Voltage:	DC 3.7V From Battery	Phase:	Horizontal
Test Mode:	Mode 1/2/3 (Mode 3 worst mode)		

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/ m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	84.3200	40.91	-22.35	18.56	40.00	-21.44	peak
2	198.7800	60.44	-21.12	39.32	43.50	-4.18	peak
3	241.4600	55.03	-17.73	37.30	46.00	-8.70	peak
4	398.6000	47.57	-11.20	36.37	46.00	-9.63	peak
5	532.4600	46.61	-7.31	39.30	46.00	-6.70	peak
6	798.2400	42.99	-2.03	40.96	46.00	-5.04	peak

Remark:

1. Margin = Result (Result =Reading + Factor)-Limit
2. Factor= Antenna factor+Cable attenuation factor(cable loss)-Amplifier gain
3. All modes have been tested,only show the worst case.






Temperature:	23.4℃	Relative Humidity:	60%RH
Test Voltage:	DC 3.7V From Battery	Phase:	Vertical
Test Mode:	Mode 1/2/3 (Mode 3 worst mode)		

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/ m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	30.5306	32.39	-13.12	19.27	40.00	-20.73	peak
2	58.1300	42.05	-25.58	16.47	40.00	-23.53	peak
3	199.7500	60.98	-21.11	39.87	43.50	-3.63	peak
4	245.3400	54.61	-16.92	37.69	46.00	-8.31	peak
5	398.6000	48.47	-11.20	37.27	46.00	-8.73	peak
6	766.2300	42.11	-2.27	39.84	46.00	-6.16	peak

Remark:

1. Margin = Result (Result = Reading + Factor) – Limit
2. Factor= Antenna factor+Cable attenuation factor(cable loss)-Amplifier gain
3. All modes have been tested,only show the worst case.






2M PHY

Temperature:	23.4℃	Relative Humidity:	60%RH
Test Voltage:	DC 3.7V From Battery	Phase:	Horizontal
Test Mode:	Mode 1/2/3 (Mode 2 worst mode)		

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/ m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	99.8400	38.60	-20.15	18.45	43.50	-25.05	peak
2	199.7500	60.69	-21.11	39.58	43.50	-3.92	peak
3	239.5200	53.60	-18.10	35.50	46.00	-10.50	peak
4	399.5700	46.99	-11.16	35.83	46.00	-10.17	peak
5	533.4300	45.20	-7.25	37.95	46.00	-8.05	peak
6	796.3000	43.86	-2.02	41.84	46.00	-4.16	peak

Remark:

1. $\text{Margin} = \text{Result} (\text{Result} = \text{Reading} + \text{Factor}) - \text{Limit}$
2. $\text{Factor} = \text{Antenna factor} + \text{Cable attenuation factor} (\text{cable loss}) - \text{Amplifier gain}$
3. All modes have been tested, only show the worst case.






Temperature:	23.4℃	Relative Humidity:	60%RH
Test Voltage:	DC 3.7V From Battery	Phase:	Vertical
Test Mode:	Mode 1/2/3 (Mode 2 worst mode)		

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/ m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	31.1798	31.09	-13.46	17.63	40.00	-22.37	peak
2	58.1300	41.68	-25.58	16.10	40.00	-23.90	peak
3	199.7500	60.82	-21.11	39.71	43.50	-3.79	peak
4	241.4600	53.49	-17.73	35.76	46.00	-10.24	peak
5	399.5700	44.00	-11.16	32.84	46.00	-13.16	peak
6	796.3000	39.69	-2.02	37.67	46.00	-8.33	peak

Remark:

1. Margin = Result (Result =Reading + Factor)-Limit
2. Factor= Antenna factor+Cable attenuation factor(cable loss)-Amplifier gain
3. All modes have been tested,only show the worst case.






(1GHz-25GHz) Spurious emission Requirements

1M PHY

Horizontal -Low

RE_FCC Test Case_FCC 15C 1GHz-18GHz




Frequency (MHz)	Peak Level (dBuV/m)	Average Level (dBuV/m)	Factor (dB)	PK Limit (dBuV/m)	AV Limit (dBuV/m)	Over Limit (dB)	Table (o)	Height (cm)	ANT	Verdict
1131.500	55.58	45.06	-1.42	74.0	54.0	-8.94	167.30	100	Horizontal	Pass
2854.500	54.95	42.06	5.61	74.0	54.0	-11.94	123.80	100	Horizontal	Pass
6906.000	50.68	39.85	0.46	74.0	54.0	-14.15	60.10	100	Horizontal	Pass
10157.000	59.61	49.69	7.14	74.0	54.0	-4.31	122.20	100	Horizontal	Pass
10957.250	61.94	51.17	9.89	74.0	54.0	-2.83	53.10	100	Horizontal	Pass
14240.750	62.63	51.96	11.28	74.0	54.0	-2.04	307.60	100	Horizontal	Pass



Vertical

RE_FCC Test Case_FCC 15C 1GHz-18GHz




Frequency (MHz)	Peak Level (dBuV/m)	Average Level (dBuV/m)	Factor (dB)	PK Limit (dBuV/m)	AV Limit (dBuV/m)	Over Limit (dB)	Table (o)	Height (cm)	ANT	Verdict
1128.500	58.12	45.67	-1.43	74.0	54.0	-8.33	187.90	100	Vertical	Pass
2060.500	58.55	43.68	3.03	74.0	54.0	-10.32	187.90	100	Vertical	Pass
6550.000	49.88	39.00	-0.43	74.0	54.0	-15.00	128.80	100	Vertical	Pass
10124.000	59.84	49.62	7.16	74.0	54.0	-4.38	111.00	100	Vertical	Pass
11391.750	62.23	51.33	9.73	74.0	54.0	-2.67	99.50	100	Vertical	Pass
14416.750	62.69	51.84	11.23	74.0	54.0	-2.16	104.20	100	Vertical	Pass



Horizontal - Mid

RE_FCC Test Case_FCC 15C 1GHz-18GHz




Frequency (MHz)	Peak Level (dBuV/m)	Average Level (dBuV/m)	Factor (dB)	PK Limit (dBuV/m)	AV Limit (dBuV/m)	Over Limit (dB)	Table (o)	Height (cm)	ANT	Verdict
1130.500	55.49	42.31	-1.42	74.0	54.0	-11.69	162.60	100	Horizontal	Pass
2858.000	53.19	40.11	5.61	74.0	54.0	-13.89	276.20	100	Horizontal	Pass
6893.000	50.67	39.58	0.43	74.0	54.0	-14.42	287.40	100	Horizontal	Pass
10231.250	59.66	48.98	6.86	74.0	54.0	-5.02	56.90	100	Horizontal	Pass
10979.250	62.61	51.22	10.06	74.0	54.0	-2.78	265.40	100	Horizontal	Pass
14400.250	62.88	51.59	11.42	74.0	54.0	-2.41	1.80	100	Horizontal	Pass



Vertical

RE_FCC Test Case_FCC 15C 1GHz-18GHz




Frequency (MHz)	Peak Level (dBuV/m)	Average Level (dBuV/m)	Factor (dB)	PK Limit (dBuV/m)	AV Limit (dBuV/m)	Over Limit (dB)	Table (o)	Height (cm)	ANT	Verdict
1130.500	55.17	42.64	-1.42	74.0	54.0	-11.36	188.70	100	Vertical	Pass
2163.500	55.88	42.21	4.49	74.0	54.0	-11.79	208.40	100	Vertical	Pass
6528.000	50.68	39.25	-0.41	74.0	54.0	-14.75	333.30	100	Vertical	Pass
10132.250	60.22	49.83	7.16	74.0	54.0	-4.17	259.90	100	Vertical	Pass
11515.500	62.02	50.93	9.97	74.0	54.0	-3.07	353.40	100	Vertical	Pass
14972.250	63.35	51.90	10.26	74.0	54.0	-2.10	2.30	100	Vertical	Pass



Horizontal - High

RE_FCC Test Case_FCC 15C 1GHz-18GHz




Frequency (MHz)	Peak Level (dBuV/m)	Average Level (dBuV/m)	Factor (dB)	PK Limit (dBuV/m)	AV Limit (dBuV/m)	Over Limit (dB)	Table (o)	Height (cm)	ANT	Verdict
1133.000	53.80	40.65	-1.42	74.0	54.0	-13.35	241.60	100	Horizontal	Pass
2862.000	54.77	39.88	5.61	74.0	54.0	-14.12	119.20	100	Horizontal	Pass
6950.000	51.19	39.74	0.50	74.0	54.0	-14.26	157.00	100	Horizontal	Pass
10143.250	60.60	50.00	7.15	74.0	54.0	-4.00	262.80	100	Horizontal	Pass
11193.750	62.03	50.73	9.61	74.0	54.0	-3.27	351.40	100	Horizontal	Pass
17109.000	63.13	51.78	10.43	74.0	54.0	-2.22	23.90	100	Horizontal	Pass



Vertical

RE_FCC Test Case_FCC 15C 1GHz-18GHz




Frequency (MHz)	Peak Level (dBuV/m)	Average Level (dBuV/m)	Factor (dB)	PK Limit (dBuV/m)	AV Limit (dBuV/m)	Over Limit (dB)	Table (o)	Height (cm)	ANT	Verdict
1128.000	57.47	43.50	-1.43	74.0	54.0	-10.50	183.50	100	Vertical	Pass
2059.500	57.72	43.42	3.01	74.0	54.0	-10.58	179.20	100	Vertical	Pass
6887.000	50.93	39.95	0.40	74.0	54.0	-14.05	23.50	100	Vertical	Pass
8839.750	57.66	46.38	4.60	74.0	54.0	-7.62	0.00	100	Vertical	Pass
11422.000	61.82	50.93	9.79	74.0	54.0	-3.07	358.00	100	Vertical	Pass
14232.500	62.43	51.47	11.35	74.0	54.0	-2.53	53.20	100	Vertical	Pass



2M PHY

Horizontal -Low

RE_FCC Test Case_FCC 15C 1GHz-18GHz




Frequency (MHz)	Peak Level (dBuV/m)	Average Level (dBuV/m)	Factor (dB)	PK Limit (dBuV/m)	AV Limit (dBuV/m)	Over Limit (dB)	Table (o)	Height (cm)	ANT	Verdict
1133.500	57.16	41.81	-1.42	74.0	54.0	-12.19	76.40	100	Horizontal	Pass
2858.500	55.62	40.38	5.61	74.0	54.0	-13.62	118.40	100	Horizontal	Pass
6943.000	50.42	39.58	0.49	74.0	54.0	-14.42	304.80	100	Horizontal	Pass
10148.750	60.04	50.39	7.15	74.0	54.0	-3.61	111.90	100	Horizontal	Pass
11053.500	61.50	51.14	9.93	74.0	54.0	-2.86	338.00	100	Horizontal	Pass
15175.750	62.87	51.08	10.86	74.0	54.0	-2.92	28.50	100	Horizontal	Pass



Vertical

RE_FCC Test Case_FCC 15C 1GHz-18GHz




Frequency (MHz)	Peak Level (dBuV/m)	Average Level (dBuV/m)	Factor (dB)	PK Limit (dBuV/m)	AV Limit (dBuV/m)	Over Limit (dB)	Table (o)	Height (cm)	ANT	Verdict
1129.500	56.99	44.27	-1.42	74.0	54.0	-9.73	202.20	100	Vertical	Pass
2067.500	55.39	41.10	3.16	74.0	54.0	-12.90	190.80	100	Vertical	Pass
6892.000	50.94	40.21	0.42	74.0	54.0	-13.79	277.20	100	Vertical	Pass
10151.500	60.15	50.12	7.14	74.0	54.0	-3.88	0.60	100	Vertical	Pass
11320.250	62.24	51.01	9.57	74.0	54.0	-2.99	284.30	100	Vertical	Pass
14320.500	62.63	51.84	10.95	74.0	54.0	-2.16	0.80	100	Vertical	Pass



Horizontal - Mid

RE_FCC Test Case_FCC 15C 1GHz-18GHz




Frequency (MHz)	Peak Level (dBuV/m)	Average Level (dBuV/m)	Factor (dB)	PK Limit (dBuV/m)	AV Limit (dBuV/m)	Over Limit (dB)	Table (o)	Height (cm)	ANT	Verdict
1129.000	56.58	45.60	-1.43	74.0	54.0	-8.40	163.30	100	Horizontal	Pass
2855.000	55.07	42.05	5.61	74.0	54.0	-11.95	132.10	100	Horizontal	Pass
6945.000	51.01	39.67	0.49	74.0	54.0	-14.33	131.40	100	Horizontal	Pass
10093.750	61.18	50.03	7.05	74.0	54.0	-3.97	89.60	100	Horizontal	Pass
11391.750	62.24	51.58	9.73	74.0	54.0	-2.42	307.40	100	Horizontal	Pass
15008.000	63.87	51.39	10.39	74.0	54.0	-2.61	246.90	100	Horizontal	Pass



Vertical

RE_FCC Test Case_FCC 15C 1GHz-18GHz




Frequency (MHz)	Peak Level (dBuV/m)	Average Level (dBuV/m)	Factor (dB)	PK Limit (dBuV/m)	AV Limit (dBuV/m)	Over Limit (dB)	Table (o)	Height (cm)	ANT	Verdict
1129.000	57.79	42.83	-1.43	74.0	54.0	-11.17	187.90	100	Vertical	Pass
2061.500	56.26	43.45	3.05	74.0	54.0	-10.55	186.30	100	Vertical	Pass
6860.000	50.91	39.24	0.26	74.0	54.0	-14.76	111.50	100	Vertical	Pass
10091.000	59.92	49.48	7.00	74.0	54.0	-4.52	229.30	100	Vertical	Pass
11386.250	62.48	51.69	9.71	74.0	54.0	-2.31	300.60	100	Vertical	Pass
14988.750	62.83	51.21	10.34	74.0	54.0	-2.79	221.90	100	Vertical	Pass



Horizontal - High

RE_FCC Test Case_FCC 15C 1GHz-18GHz




Frequency (MHz)	Peak Level (dBuV/m)	Average Level (dBuV/m)	Factor (dB)	PK Limit (dBuV/m)	AV Limit (dBuV/m)	Over Limit (dB)	Table (o)	Height (cm)	ANT	Verdict
1130.000	53.81	42.39	-1.42	74.0	54.0	-11.61	157.90	100	Horizontal	Pass
2864.500	55.48	41.21	5.61	74.0	54.0	-12.79	122.40	100	Horizontal	Pass
6913.000	50.54	40.00	0.47	74.0	54.0	-14.00	14.30	100	Horizontal	Pass
10132.250	60.36	50.23	7.16	74.0	54.0	-3.77	60.60	100	Horizontal	Pass
11039.750	62.37	51.61	10.01	74.0	54.0	-2.39	96.50	100	Horizontal	Pass
14389.250	62.72	51.79	11.36	74.0	54.0	-2.21	78.60	100	Horizontal	Pass



Vertical


RE_FCC Test Case_FCC 15C 1GHz-18GHz




Frequency (MHz)	Peak Level (dBuV/m)	Average Level (dBuV/m)	Factor (dB)	PK Limit (dBuV/m)	AV Limit (dBuV/m)	Over Limit (dB)	Table (o)	Height (cm)	ANT	Verdict
1128.500	55.75	43.17	-1.43	74.0	54.0	-10.83	175.90	100	Vertical	Pass
2067.000	55.29	42.01	3.15	74.0	54.0	-11.99	188.60	100	Vertical	Pass
6553.000	50.15	39.27	-0.43	74.0	54.0	-14.73	22.10	100	Vertical	Pass
10107.500	60.21	49.80	7.17	74.0	54.0	-4.20	175.60	100	Vertical	Pass
10951.750	61.90	51.18	9.85	74.0	54.0	-2.82	171.30	100	Vertical	Pass
14235.250	63.60	51.74	11.33	74.0	54.0	-2.26	57.10	100	Vertical	Pass




4.6 TEST RESULTS (Restricted Bands Requirements)

1M PHY
GFSK-Low
Horizontal

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2370.700	27.00	4.05	31.05	54.00	-22.95	Peak
2	2390.000	26.61	4.34	30.95	54.00	-23.05	Peak


Vertical

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2379.500	26.90	4.18	31.08	54.00	-22.92	Peak
2	2390.000	26.54	4.34	30.88	54.00	-23.12	Peak

**GFSK-High**
Horizontal

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	26.86	4.60	31.46	54.00	-22.54	Peak
2	2484.050	27.70	4.61	32.31	54.00	-21.69	Peak

Vertical



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	26.59	4.60	31.19	54.00	-22.81	Peak
2	2485.600	26.84	4.61	31.45	54.00	-22.55	Peak




2M PHY
GFSK-Low
Horizontal




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2377.700	26.82	4.15	30.97	54.00	-23.03	Peak
2	2390.000	26.37	4.34	30.71	54.00	-23.29	Peak

Vertical




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2372.200	26.97	4.08	31.05	54.00	-22.95	Peak
2	2390.000	26.49	4.34	30.83	54.00	-23.17	Peak

**GFSK-High**
Horizontal

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	28.02	4.60	32.62	54.00	-21.38	Peak
2	2485.775	26.56	4.61	31.17	54.00	-22.83	Peak

Vertical



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	27.95	4.60	32.55	54.00	-21.45	Peak
2	2485.475	26.89	4.61	31.50	54.00	-22.50	Peak

Note: All modes have been measurement, only worst mode was reported.

5. CONDUCTED SPURIOUS & BAND EDGE EMISSION

5.1 LIMIT

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

5.2 TEST PROCEDURE

Spectrum Parameter	Setting
Detector	Peak
Start/Stop Frequency	30 MHz to 10th carrier harmonic
RB / VB (emission in restricted band)	100 KHz/300 KHz
Trace-Mode:	Max hold

For Band edge

Spectrum Parameter	Setting
Detector	Peak
Start/Stop Frequency	Lower Band Edge: 2300 – 2407 MHz Upper Band Edge: 2475 – 2500 MHz
RB / VB (emission in restricted band)	100 KHz/300 KHz
Trace-Mode:	Max hold

5.3 TEST SETUP



The EUT is connected to the Spectrum Analyzer; the RF load attached to the EUT antenna terminals is 50 Ohm; the path loss as the factor is calibrated to correct the reading. Make the measurement with the spectrum analyzer's resolution bandwidth(RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW.

5.4 EUT OPERATION CONDITIONS

Please refer to section 3.4 of this report.

5.5 TEST RESULTS

Note: The test data please refer to APPENDIX 1.



6. POWER SPECTRAL DENSITY TEST

6.1 LIMIT

FCC Part 15.247, Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(e)	Power Spectral Density	≤ 8 dBm (RBW ≥ 3 KHz)	2400-2483.5	PASS

6.2 TEST PROCEDURE

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS channel bandwidth.
3. Set the RBW to: $100 \text{ kHz} \geq \text{RBW} \geq 3 \text{ kHz}$.
4. Set the VBW $\geq 3 \times \text{RBW}$.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

6.3 TEST SETUP



6.4 EUT OPERATION CONDITIONS

Please refer to section 3.4 of this report.

6.5 TEST RESULTS

Note: The test data please refer to APPENDIX 1.

7. BANDWIDTH TEST

7.1 LIMIT

FCC Part 15.247, Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(a)(2)	Bandwidth	$\geq 500\text{KHz}$ (6dB bandwidth)	2400-2483.5	PASS

7.2 TEST PROCEDURE

The automatic bandwidth measurement capability of an instrument may be employed using the X dB bandwidth mode with X set to 6 dB, if the functionality described above (i.e., RBW = 100 kHz, VBW ≥ 3 RBW, peak detector with maximum hold) is implemented by the instrumentation function. When using this capability, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be ≥ 6 dB.

7.3 TEST SETUP



7.4 EUT OPERATION CONDITIONS

Please refer to section 3.4 of this report.

7.5 TEST RESULTS

Note: The test data please refer to APPENDIX 1.



8. PEAK OUTPUT POWER TEST

8.1 LIMIT

FCC Part 15.247, Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(b)(3)	Output Power	1 watt or 30dBm	2400-2483.5	PASS

8.2 TEST PROCEDURE

One of the following procedures may be used to determine the averaging conducted output power of a DTS EUT.

Method AVGSA-2 uses trace averaging across ON and OFF times of the EUT transmissions, followed by duty cycle correction. The procedure for this method is as follows:

- Measure the duty cycle D of the transmitter output signal as described in 11.6.
- Set span to at least 1.5 times the OBW.
- Set RBW = 1% to 5% of the OBW, not to exceed 1 MHz.
- Set VBW $\geq [3 \times \text{RBW}]$.
- Number of points in sweep $\geq [2 \times \text{span} / \text{RBW}]$. (This gives bin-to-bin spacing $\leq \text{RBW} / 2$, so that narrowband signals are not lost between frequency bins.)
- Sweep time = auto.
- Detector = RMS (i.e., power averaging), if available. Otherwise, use the sample detector mode.
- Do not use sweep triggering. Allow the sweep to "free run."
- Trace average at least 100 traces in power averaging (rms) mode; however, the number of traces to be averaged shall be increased above 100 as needed such that the average accurately represents the true average over the ON and OFF periods of the transmitter.
- Compute power by integrating the spectrum across the OBW of the signal using the instrument's band power measurement function with band limits set equal to the OBW band edges. If the instrument does not have a band power function, then sum the spectrum levels (in power units) at intervals equal to the RBW extending across the entire OBW of the spectrum.
- Add $[10 \log (1 / D)]$, where D is the duty cycle, to the measured power to compute the average power during the actual transmission times (because the measurement represents an average over both the ON and OFF times of the transmission). For example, add $[10 \log (1/0.25)] = 6 \text{ dB}$ if the duty cycle is 25%.

One of the following procedures may be used to determine the maximum peak conducted output power of a DTS EUT.

$\text{RBW} \geq \text{DTS bandwidth}$

The following procedure shall be used when an instrument with a resolution bandwidth that is greater than the DTS bandwidth is available to perform the measurement:

- Set the RBW $\geq$ DTS bandwidth.
- Set VBW $\geq [3 \times \text{RBW}]$.
- Set span $\geq [3 \times \text{RBW}]$.
- Sweep time = auto couple.
- Detector = peak.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use peak marker function to determine the peak amplitude level.

8.3 TEST SETUP



8.4 EUT OPERATION CONDITIONS

Please refer to section 3.4 of this report.

8.5 TEST RESULTS

Note: The test data please refer to APPENDIX 1.



9. ANTENNA REQUIREMENT

9.1 STANDARD REQUIREMENT

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

9.2 EUT ANTENNA

The EUT antenna is Ceramic Antenna. It comply with the standard requirement.



APPENDIX 1-TEST DATA


Duty Cycle

Condition	Mode	Frequency (MHz)	On Time (ms)	Period (ms)	Duty Cycle (%)	Correction Factor (dB)	1/T (kHz)
NVNT	BLE 1M	2402	0.391	0.625	62.56	2.04	2.56
NVNT	BLE 1M	2440	0.391	0.625	62.56	2.04	2.56
NVNT	BLE 1M	2480	0.391	0.625	62.56	2.04	2.56
NVNT	BLE 2M	2402	0.206	0.624	33.01	4.81	4.85
NVNT	BLE 2M	2440	0.206	0.624	33.01	4.81	4.85
NVNT	BLE 2M	2480	0.208	0.626	33.23	4.78	4.81




Test Graphs

Duty Cycle NVNT BLE 1M 2402MHz




Duty Cycle NVNT BLE 1M 2440MHz






Duty Cycle NVNT BLE 1M 2480MHz




Duty Cycle NVNT BLE 2M 2402MHz






Duty Cycle NVNT BLE 2M 2440MHz




Duty Cycle NVNT BLE 2M 2480MHz






Maximum Average Conducted Output Power

Condition	Mode	Frequency (MHz)	Conducted Power (dBm)	Duty Factor (dB)	Total Power (dBm)	Limit (dBm)	Verdict
NVNT	BLE 1M	2402	-5.82	2.04	-3.78	<=30	Pass
NVNT	BLE 1M	2440	-6.24	2.04	-4.2	<=30	Pass
NVNT	BLE 1M	2480	-5.61	2.04	-3.57	<=30	Pass
NVNT	BLE 2M	2402	-9.21	4.81	-4.4	<=30	Pass
NVNT	BLE 2M	2440	-9.1	4.81	-4.29	<=30	Pass
NVNT	BLE 2M	2480	-8.61	4.78	-3.83	<=30	Pass






Average Power NVNT BLE 1M 2480MHz




Average Power NVNT BLE 2M 2402MHz






Average Power NVNT BLE 2M 2440MHz




Average Power NVNT BLE 2M 2480MHz






Maximum Peak Conducted Output Power

Condition	Mode	Frequency (MHz)	Conducted Power (dBm)	Limit (dBm)	Verdict
NVNT	BLE 1M	2402	-3.58	<=30	Pass
NVNT	BLE 1M	2440	-3.93	<=30	Pass
NVNT	BLE 1M	2480	-3.24	<=30	Pass
NVNT	BLE 2M	2402	-4.13	<=30	Pass
NVNT	BLE 2M	2440	-4.21	<=30	Pass
NVNT	BLE 2M	2480	-3.53	<=30	Pass






Peak Power NVNT BLE 1M 2480MHz




Peak Power NVNT BLE 2M 2402MHz






Peak Power NVNT BLE 2M 2440MHz






Peak Power NVNT BLE 2M 2480MHz





**-6dB Bandwidth**

Condition	Mode	Frequency (MHz)	-6 dB Bandwidth (MHz)	Limit -6 dB Bandwidth (MHz)	Verdict
NVNT	BLE 1M	2402	0.6467	≥ 0.5	Pass
NVNT	BLE 1M	2440	0.664	≥ 0.5	Pass
NVNT	BLE 1M	2480	0.6612	≥ 0.5	Pass
NVNT	BLE 2M	2402	1.0922	≥ 0.5	Pass
NVNT	BLE 2M	2440	1.1109	≥ 0.5	Pass
NVNT	BLE 2M	2480	1.0686	≥ 0.5	Pass




**-6dB Bandwidth NVNT BLE 1M 2480MHz****-6dB Bandwidth NVNT BLE 2M 2402MHz**


**-6dB Bandwidth NVNT BLE 2M 2440MHz****-6dB Bandwidth NVNT BLE 2M 2480MHz**




Maximum Power Spectral Density Level

Condition	Mode	Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
NVNT	BLE 1M	2402	-18.8	≤ 8	Pass
NVNT	BLE 1M	2440	-19.22	≤ 8	Pass
NVNT	BLE 1M	2480	-18.79	≤ 8	Pass
NVNT	BLE 2M	2402	-21.85	≤ 8	Pass
NVNT	BLE 2M	2440	-21.68	≤ 8	Pass
NVNT	BLE 2M	2480	-20.99	≤ 8	Pass











Band Edge

Condition	Mode	Frequency (MHz)	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	BLE 1M	2402	-43.1	≤ -20	Pass
NVNT	BLE 1M	2480	-44.31	≤ -20	Pass
NVNT	BLE 2M	2402	-33.44	≤ -20	Pass
NVNT	BLE 2M	2480	-44.47	≤ -20	Pass







Band Edge NVNT BLE 1M 2480MHz Ref




Band Edge NVNT BLE 1M 2480MHz Emission








Band Edge NVNT BLE 2M 2480MHz Ref



Band Edge NVNT BLE 2M 2480MHz Emission






Conducted RF Spurious Emission

Condition	Mode	Frequency (MHz)	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	BLE 1M	2402	-41.94	≤ -20	Pass
NVNT	BLE 1M	2440	-41.35	≤ -20	Pass
NVNT	BLE 1M	2480	-42.4	≤ -20	Pass
NVNT	BLE 2M	2402	-41.3	≤ -20	Pass
NVNT	BLE 2M	2440	-41.81	≤ -20	Pass
NVNT	BLE 2M	2480	-41.35	≤ -20	Pass





Test Graphs


Tx. Spurious NVNT BLE 1M 2402MHz Ref



Tx. Spurious NVNT BLE 1M 2402MHz Emission











Tx. Spurious NVNT BLE 2M 2402MHz Ref




Tx. Spurious NVNT BLE 2M 2402MHz Emission






Tx. Spurious NVNT BLE 2M 2440MHz Ref




Tx. Spurious NVNT BLE 2M 2440MHz Emission






Tx. Spurious NVNT BLE 2M 2480MHz Ref



Tx. Spurious NVNT BLE 2M 2480MHz Emission





APPENDIX 2- EUT TEST PHOTO

Note: See test photos in setup photo document for the actual connections between Product and support equipment.

※※※※※END OF THE REPORT※※※※※