

99.5mm

37.5mm

BLUETTI

DC Power Hub **Model: Hub D1**

Input: 42V-58V \approx 20A

Output:
 USB-A: 5V \approx 3A total
 USB-C: 5/9/12/15/20V \approx 3A; 20V \approx 5A each port
 RV Port: 12V \approx 50A; 24V \approx 25A
 DC5521+Cigarette Lighter Port:
 12V \approx 10A total \times 2; 24V \approx 5A total \times 2
 Total Output: 700W Max.

PT POWEROAK ENERGY INDONESIA
 Address: Helong Industrial Park Type A Lot 07,
 Sungai Perunggut Village, Sagulung District,
 Batam City 29439, Riau Islands Province, Indonesia

Working Temperature: -20°C-45°C/-4°F-113°F

CAN ICES (B) / NMB (B)
 This device complies with Part 15 of the FCC Rules.
 Operation is subject to the following two conditions:
 (1) this device may not cause harmful interference, and
 (2) this device must accept any interference received,
 including interference that may cause undesired operation.

FC **TUV** **!** **i**
 FCC ID: 2B0XS-HUBD1 IC: 33872-HUBD1
 MADE IN INDONESIA P/N: 17.0301.1622-00AO

编码料号Coded material number

