



Königswinkel 10
32825 Blomberg, Germany
Phone: +49 (0) 52 35 / 95 00-0
Fax: +49 (0) 52 35 / 95 00-10
office@phoenix-testlab.de
www.phoenix-testlab.de

FCC RF Exposure Evaluation

Report Number:

F241823E6

Equipment under Test (EUT):

ANYiScan 2

Applicant:

CAISLEY International GmbH

Manufacturer:

CAISLEY International GmbH



References

- [1] **CFR 47 Rule part 1** Practice and Procedure
- [2] **CFR 47 Rule part 2** Frequency Allocations and Radio Treaty Matters; General Rules and Regulations
- [3] **KDB 447498 D04 Interim General RF Exposure Guidance v01**
- [4] **ANSI C63.10: 2020** American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices

Assessed and
written by:

Signature

Reviewed and
approved by:

Signature

This evaluation report is only valid in its original form.

Any reproduction of its contents in extracts without written permission of the accredited test laboratory PHOENIX TESTLAB GmbH is prohibited.

The test results herein refer only to the evaluated sample. PHOENIX TESTLAB GmbH is not responsible for any generalisations or conclusions drawn from these test results concerning further samples. Any modification of the referred samples is prohibited and leads to the invalidity of this evaluation report. Each page necessarily contains the PHOENIX TESTLAB Logo and the TEST REPORT NUMBER.

Contents:	Page
1 Identification	4
1.1 Applicant.....	4
1.2 Manufacturer	4
1.3 Test Laboratory	4
1.4 EUT (Equipment under Test)	5
1.5 Technical Data of Equipment	5
2 Evaluation Method	6
2.1 RF exposure test exemptions for single sources	6
2.1.1 General Exemption CFR 47 §1.1307(b)(3)(i)(A)	6
2.1.2 SAR Based Exemption CFR 47 §1.1307(b)(3)(i)(B).....	6
2.1.3 MPE Based Exemption CFR 47 §1.1307(b)(3)(i)(C)	6
2.1.4 Stand alone MPE evaluation limits	7
2.2 RF exposure test exemptions for simultaneous transmission sources	8
2.2.1 1 mW Test Exemption for simultaneous transmission sources.....	8
2.2.2 Simultaneous transmission SAR based and MPE based test exemptions	8
2.2.3 Test exemption based on the SAR to Peak Location Separation Ratio.....	9
3 Results of evaluation.....	9
3.1 Used evaluation methods.....	9
3.2 Evaluation Distance.....	9
3.3 RFID Emissions.....	10
4 Conclusion	10
5 Report History.....	10

1 Identification

1.1 Applicant

Name:	CAISLEY International GmbH
Address:	Harderhook 31, 46395 Bocholt
Country:	Germany
Name for contact purposes:	Mr. Thomas GÜLDENBERG
Phone:	02871-239-39-0
eMail address:	info@caisley.de
Applicant represented during the test by the following person:	None

1.2 Manufacturer

Name:	CAISLEY International GmbH
Address:	Harderhook 31, 46395 Bocholt
Country:	Germany
Name for contact purposes:	Mr. Thomas GÜLDENBERG
Phone:	02871-239-39-0
eMail address:	info@caisley.de
Manufacturer represented during the test by the following person:	None

1.3 Test Laboratory

The tests were carried out by:

PHOENIX TESTLAB GmbH
Königswinkel 10
32825 Blomberg
Germany

accredited by Deutsche Akkreditierungsstelle GmbH (DAkkS) according to DIN EN ISO/IEC 17025:2018. The accreditation is only valid for the scope of accreditation listed in the annex of the certificate D-PL-17186-01-00.

1.4 EUT (Equipment under Test)

Test object: *	RFID reader for electronic animal identification
Model name: *	ANYiScan 2
Model number: *	n.a.
Order number: *	n.a.
FCC ID: *	2BOY9-ANYISCAN2

* Declared by the applicant

Note: PHOENIX TESTLAB GmbH does not take samples. The samples used for tests are provided exclusively by the applicant.

1.5 Technical Data of Equipment

General			
Power supply EUT: *	DC via iPhone		
Supply voltage EUT: *	$U_{\text{nom}} = 3.6 \text{ V}_{\text{DC}}$	$U_{\text{min}} = 3.5 \text{ V}_{\text{DC}}$	$U_{\text{max}} = 4.2 \text{ V}_{\text{DC}}$
Temperature range: *	-10 °C to +55 °C		
Lowest / highest internal frequency: *	19.2 kHz / 17.1776 MHz		

* Declared by the applicant

RFID part	
Operating frequency: *	134 kHz
Number of channels: *	1
Type of modulation: *	ASK
Data rate: *	2/4 kHz
Duty cycle: *	50 %
Antenna type: *	Coil

* Declared by the applicant

2 Evaluation Method

2.1 RF exposure test exemptions for single sources

2.1.1 General Exemption CFR 47 §1.1307(b)(3)(i)(A)

The available maximum time-averaged power is no more than 1 mW, regardless of separation distance. This exemption may not be used in conjunction with other exemption criteria other than those in [paragraph \(b\)\(3\)\(ii\)\(A\)](#) of this section. Medical implant devices may only use this exemption and that in [paragraph \(b\)\(3\)\(ii\)\(A\)](#);

2.1.2 SAR Based Exemption CFR 47 §1.1307(b)(3)(i)(B)

The available maximum time-averaged power of effective radiated power (ERP), whichever is greater, is less than or equal to the threshold P_{th} (mW) described in the following formula. This method shall only be used at separation distances (cm) from 0.5 cm to 40 cm and at frequencies from 0.3 GHz to 6 GHz inclusive.

For the following separation distances [d] and frequency ranges P_{th} is given by the following formulas

	0.5 cm ≤ d ≤ 20cm	20 cm < d ≤ 40 cm
0.2 GHz ≤ f < 1.5 GHz	$P_{th}(mW) = ERP_{20cm} \left(\frac{d}{20} \right)^x$ $ERP_{20cm} (mW) = 2040f$ $x = -\log_{10} \left(\frac{60}{ERP_{20cm}\sqrt{f}} \right)$	$P_{th}(mW) = ERP_{20cm}$ $ERP_{20cm} (mW) = 2040f$
1.5 GHz ≤ f ≤ 6 GHz	$P_{th}(mW) = ERP_{20cm} \left(\frac{d}{20} \right)^x$ $ERP_{20cm} (mW) = 3060$ $x = -\log_{10} \left(\frac{60}{ERP_{20cm}\sqrt{f}} \right)$	$P_{th}(mW) = ERP_{20cm}$ $ERP_{20cm} (mW) = 3060$

2.1.3 MPE Based Exemption CFR 47 §1.1307(b)(3)(i)(C)

By using Table 1 and the minimum separation distance (d in meters) from the body of a nearby person for the frequency (f in MHz) at which the source operates, the ERP (watts) is no more than the calculated value prescribed for that frequency. For the exemption in Table 1 to apply, d must be at least $\lambda/2\pi$, where λ is the free-space operating wavelength in meters. If the ERP of a single RF source is not easily obtained, then the available maximum time-averaged power may be used in lieu of ERP if the physical dimensions of the radiating structure(s) do not exceed the electrical length of $\lambda/4$ or if the antenna gain is less than that of a half-wave dipole (1.64 linear value).

RF Source frequency [MHz]	Threshold ERP [W]
0.3 -1.34	$1920 d^2$
1.34 – 30	$3450 d^2/f^2$
30 – 300	$3.83 d^2$
300 – 1500	$0.0128 d^2/f$
1500 - 100000	$19.2 d^2$

d: Minimal separation distance from antenna to the user

2.1.4 Stand-alone MPE evaluation limits

The human exposure to RF emissions from such devices could be evaluated based on the MPE limits adopted by the FCC for electric and magnetic field strength and / or power density. The limits for General Population / Uncontrolled Exposure are given in the following table from CFR 47 §1.1310(e)1:

(i)Limits for Occupational/Controlled Exposure				
Frequency range [MHz]	Electric field strength (E) [V/m]	Magnetic field strength (H) [A/m]	Power density (S) [mW/cm ²]	Averaging time [min]
0.3 – 3.0	614	1.63	*(100)	≤6
3.0 – 30	1842/f	4.89/f	*(900/f ²)	<6
30 – 300	61.4	0.163	1.0	<6
300 – 1,500	-	-	f/300	<6
1,500 – 100,000	-	-	5	<6

(ii)Limits for General Population / Uncontrolled Exposure				
Frequency range [MHz]	Electric field strength (E) [V/m]	Magnetic field strength (H) [A/m]	Power density (S) [mW/cm ²]	Averaging time [min]
0.3 – 1.34	614	1.63	*(100)	< 30
1.34 – 30	824/f	2.19/f	*(180/f ²)	< 30
30 – 300	27.5	0.073	0.2	< 30
300 – 1500	-	-	f/1500	< 30
1500 – 100,000	-	-	1.0	< 30

Note: f = frequency in MHz; * Plane – wave equivalent power density

The power density is calculated as follows:

$$S = \frac{P \cdot G \cdot D}{4 \cdot \pi \cdot d^2}$$

Where:

P: conducted power

G: Antenna gain (linear)

D: Duty Cycle

d: Minimal separation distance from antenna to the user

2.2 RF exposure test exemptions for simultaneous transmission sources

2.2.1 1 mW Test Exemption for simultaneous transmission sources

As discussed in CFR 47 §1.1307(b)(3)(ii)(A) [1] the 1 mW exemption intended for single transmitters may be also applied to simultaneous transmission conditions, within the same host device, according one of the following criteria:

- a. When the maximum available power each individual transmitting antenna with the same time averaging period is ≤ 1 mW, and the nearest parts of the antenna structures of the simultaneously operating transmitters are separated by at least 2 cm
- b. When the aggregate maximum available power of all transmitting antennas is ≤ 1 mW in the same time-averaging period

This exemption may not be combined with any other exemption.

2.2.2 Simultaneous transmission SAR based and MPE based test exemptions

Although this is not a module integration in the sense of product approval, the procedure for simultaneous transmission specified in KDB 447498 D04 Interim General RF Exposure Guidance v01 [3] in chapter 2.2 was taken into account:

According to the RF exposure KDB 447498 D04 General RF Exposure Guidance v01 [3] in chapter 2.2.2: This case is described in detail in CFR 47 §1.1307(b)(3)(ii)(B) and covers the situations where both SAR-based and MPE-based exemption may be considered for test exemption in fixed, mobile, or portable device exposure conditions. For these cases, a device with multiple RF sources transmitting simultaneously will be considered an RF exempt device if the condition of the following formular is satisfied.

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{i=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure\ Limit_k} \leq 1$$

For these test exemptions to apply, the maximum output power, duty factor, and other applicable parameters used in the standalone ERP determination tests, must be the same, or corresponding to a more conservative choice, than those required for simultaneous transmission.

Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneously transmitting antennas incorporated in a host device is ≤ 1.0 , according to calculated/estimated, numerically modelled, or measured field strengths or power density. The MPE ratio of each antenna is determined at the minimum test separation distance required by the operating configurations and exposure conditions of the host device, according to the ratio of field strengths or power density to the MPE limit at the test frequency.

2.2.3 Test exemption based on the SAR to Peak Location Separation Ratio

When the ERP-based condition in the previous section does not apply, a test exemption may be still applicable based on the SAR to peak location separation ratio (SPLSR) procedure.

In this case, the simultaneously transmitting antennas in each operating mode and exposure condition combination must be considered one pair at a time to determine the SPLSR that qualifies for the additional test exemption.

This ratio is defined as:

$$SPLSR = (SAR_1 + SAR_2)^{\frac{1.5}{R_i}}$$

Where: SAR_1 and SAR_2 = highest reported SAR or estimated SAR values for the two sources in the pair i , and R_i is their distance in mm.

When $SPLSR \leq 0.0.4$ (rounded to two decimal digits), for all antenna pairs in the configuration, then the device qualifies for 1 g SAR test exemption.

When 10 g SAR applies (e.g. for extremities) the corresponding test exemption condition is $SPLSR \leq 0.10$.

If any antenna pair does not qualify for simultaneous transmission SAR test exemption, then the device must be tested for SAR compliance, according to the enlarged zoom scan and volume scan post-processing procedures in KDB Pub. 865664 D01.

3 Results of evaluation

3.1 Used evaluation methods

RF Exposure test exemptions for single sources			
Used	Method	See sub-clause	Comment
<input checked="" type="checkbox"/>	General Exemption acc. CFR 47 §1.1307(b)(3)(i)(A)	2.1.1	-
<input type="checkbox"/>	SAR Based Exemption acc. CFR 47 §1.1307(b)(3)(i)(B)	2.1.2	-
<input type="checkbox"/>	MPE Based Exemption acc. CFR 47 §1.1307(b)(3)(i)(C)	2.1.3	-
<input type="checkbox"/>	MPE Calculation	2.1.4	-

RF Exposure test exemptions for simultaneous transmission sources			
Used	Method	See sub-clause	Comment
<input checked="" type="checkbox"/>	Not applicable		No simultaneous possible
<input type="checkbox"/>	1 mW test Exemption acc. 2.2.1 [3]	2.2.1	-
<input type="checkbox"/>	SAR Based Exemption acc. 2.2.2 [3]	2.2.2	-
<input type="checkbox"/>	MPE Based Exemption acc. 2.2.2 [3]	2.2.2	-
<input type="checkbox"/>	SAR to Peak location separation ratio acc. 2.2.3 [3]	2.2.3	-

3.2 Evaluation Distance

No evaluation distance is given by the manufacturer / applicant. According to the CFR 47 §2.1091 the device as declared by the applicant is a fixed device.

3.3 RFID Emissions

The following information are based on Test-Report F241823E5 of PHOENIX TESTLAB GmbH.

General exemption CFR 47 §1.1307(b)(3)(i)(A)

The radiated field strength of the transmitter was measured at a distance of 3 m. This value is converted into an EIRP power with formula according to ANSI C63-10 clause G.2:

$$EIRP = (E \times d)^2 / 30$$

Where

- EIRP is the equivalent isotropically radiated power, in Watt
- E is the field strength, in V/m
- d_{Meas} is the measurement distance, in m

This formula is equal to:

$$EIRP = E_{Meas} + 20 \log(d_{Meas}) - 104.7$$

Where

- EIRP is the equivalent isotropically radiated power, in dBm
- E_{Meas} is the field strength of the emission at the measurement distance, in dB μ V/m
- d_{Meas} is the measurement distance, in m

The measured field strength at 3 m (= Reading @3m distance + Antenna factor) was 81.4 dB μ V/m.

$$EIRP = 81.4 \text{ dB}\mu\text{V/m} + 20 \log(3m) - 104.7 = -13.8 \text{ dBm}$$

This value is converted into an ERP power with formula according to ANSI C63-10 clause G.4:

$$ERP = EIRP - 2.15 = -15.95 \text{ dBm}$$

The ERP power of the transmitter is -15.95 dBm or 25.4 μ W. This is below the 1 mW limit.

4 Conclusion

The ANYiScan 2 is exempted from RF exposure testing according to CFR 47 §1.1307(b)(3)(i)(A).

5 Report History

Report Number	Date	Comment
F241823E6	13.08.2025	Initial Evaluation Report
-	-	-
-	-	-

----- end of evaluation report -----