

Huizhou Qitai Electronic Technology Co., LTD

## SPECIFICATIONS SHEET

CUSTOMER :	Luo Xin
DESCRIPTION :	E28A-00025
CUSTOMER P/N :	
PART NUMBER :	
DATE OF APPLICATION :	2025-9-17

### CLASSIFICATION OF SPEC. PRESENTATION. ( Tick the relevant box "√" )

- New application
- New part is added to accepted specification
- Revision of accepted specification

### ACCEPTANCE STAMP

	APPROVAL BY	CHECK BY	PREPARE BY
	 凌子奇		冯欣

ADDRESS : 7th Floor, Building A, Hongyang Changlong Zhichuang Park, Beiyi Road, Shiwan Town, Boluo County, Huizhou City

TELPHONE : 0752-6668681

E-MAIL : 839689578@qq.com

Huizhou Qitai Electronic Technology Co., LTD

Huizhou Qitai Electronic Technology Co., LTD

CUSTOMER P/N :


Dongguan kingtron  
electronics tech co.,LTD

PART NUMBER :

E28A-00025

1. DIMENSIONS : (Unit: mm)

Unit : mm



A	B	C	D	E	F	G
21Max	$14.5 \pm 0.5$	$7.5 \pm 0.5$	$24.5 \pm 1$	$7 \pm 1$	$2 \pm 1$	2.6Max

1. The back glue is  $\phi 18MM$  pure white back glue.
2. The magnetic sheet is hard magnetic(Y142).
3. Tape size: 25mm\*2.6mm.
4. Magnet Gaussian: 3400GS  $\pm$  200GS(Counter-episode).

APPROVED BY	CHECKED BY	PREPARED BY	DATE
晁子奇		冯欣	2025-9-17

Huizhou Qitai Electronic Technology Co., LTD

<b>Specification</b>	CUSTOMER P/N :	Dongguan kingtron electronics co.,LTD
	PART NUMBER :	E28A-00025

**2. WINDING DETAILS**

Coil1

Turns	Wire Dia	Wdg. Type Spred/Close	Wdg.Direction	Intersect Yes/Not
13TS	0.08*24P (Hot Air stranded Wire)	Close	Inverse around	Yes

**3. ELECTRICAL CHARACTERISTICS:**

TEMPERATURE:25±10°C, RELATIVE HUMIDITY:65±10%

NO.	TEM	TERMINAL	SPECIFICATION	TEST FREQUENCY	TEST EQUIPMENTS
Coil 1					
1.	IND	S-F	7.5uh±0.3uh	100kHz/V	UC2906A
2.	Q	S-F	20Min	100kHz/V	UC2906A
3.	DCR	S-F	125mΩ Max	100kHz/V	UC2906A

APPROVED BY	CHECKED BY	PREPARED BY	DATE
晁子奇		冯欣	2025-9-17