

RF TEST REPORT

Report Reference No...... : MAX250424010-P01R01RF

FCC ID..... : 2BOYL-8018T

Compiled by
(position+printed name+signature)... : Engineer/ Cindy Zheng

Cindy Zheng

Supervised by
(position+printed name+signature)... : Manager/Haley Wen

Haley Wen

Approved by
(position+printed name+signature)... : RF Manager/ Vivian Jiang

Vivian Jiang

Date of issue..... : April 25, 2025

Testing Laboratory Name..... : MAXLAB Testing Co.,Ltd.

Address..... : 1/F, Building B, Xinshidai GR Park, Shiyan Street, Bao'an District,
Shenzhen, Guangdong, 518052, People's Republic of China

Applicant's name..... : Yiwu Ouliang Tattoo Equipment Co., Ltd.

Address..... : 4th Floor, Elevator, No. 9, Building 6, No. 788 Chengdian Road,
Choujiang Sub-district, Yiwu City, Zhejiang Province, China

Test specification..... :

Standard..... : KDB 447498 D01

MAXLAB Testing Co.,Ltd.All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the MAXLAB Testing Co.,Ltd. is acknowledged as copyright owner and source of the material. MAXLAB Testing Co.,Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Equipment description..... : Tattoo transfer machine

Trade Mark..... : N/A

Manufacturer..... : Yiwu Ouliang Tattoo Equipment Co., Ltd.

Model/Type reference..... : 8018T

Listed Models : N/A

Modulation : GFSK

Frequency..... : From 2402MHz to 2480MHz

Ratings..... : DC 5.0V from USB Port or DC 7.4V from battery

Result..... : **PASS**

RF Exposure Evaluation

Limits

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

According to KDB 447498 D01 General RF Exposure Guidance v06, Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Test Exclusion Threshold condition(s), listed below, is (are) satisfied.

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f ²)	6
30–300	61.4	0.163	1.0	6
300–1500			f/300	6
1500–100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500			f/1500	30
1500–100,000			1.0	30

f = frequency in MHz

Friis transmission formula: $Pd = (Pout \cdot G) / (4 \cdot \pi \cdot r^2)$

Where

Pd = power density in mW/cm², **Pout** = output power to antenna in mW;

G = gain of antenna in linear scale, **Pi** = 3.1416;

R = distance between observation point and center of the radiator in cm

Pd is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

Test Result of RF Exposure Evaluation

Bluetooth BLE

Channel	Frequency (MHz)	Output power to antenna (dBm)	Output power to antenna (mW)	Power Density at R=20cm (mW/cm ²)	Limit (mW/cm ²)	Result
GFSK	2402	2.456	1.76	0.00035	1.0	PASS
	2440	2.652	1.84	0.00037	1.0	PASS
	2480	2.845	1.93	0.00038	1.0	PASS

Remark: antenna gain= -0.68dBi

Conclusion: No SAR is required.