

# FCC RF Exposure

EUT Description: Mecha Little Rubiks Cube Bluetooth Speaker

Model No.: A88

FCC ID: 2BOYY-A88

## 1. Limits

According to KDB 447498 D01 General RF Exposure Guidance v06 The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq$ 50 mm are determined by:

$[(\text{max power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR}$

Where:

Result =  $P/D \cdot \sqrt{f}$

F = the RF channel transmit frequency in GHz

P = Maximum turn-up power in mw

D = Min. test separation distance in mm

## 2. Test Result of RF Exposure Evaluation

Frequency (MHz)	Output power (dBm)	Tune Up Power (dBm)	Max Tune Up power (dBm/mW)	Min test separation distance (mm)	Result	Limit (mW/cm <sup>2</sup> )	SAR Test Exclusion
2402	1.12	1±1(2)	1.585	5	0.491	3.0	Pass

Note:

PK Output power = conducted power.

Conducted power see the test report HK2505192590-E, antenna gain = -0.58dBi

Per KDB 447498 D01, when the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine RF Exposure test exclusion. The test exclusion threshold is 0.491 which is  $\leq 3$ , RF Exposure testing is not required.

Note: Exclusion Thresholds Results =  $[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}]$

$f(\text{GHz})$  is the RF channel transmit frequency in GHz

Distance = 5mm