

**RF Exposure Report
(mobile devices)
47 CFR 2.1091
RSS-102 Issue 6**

Report No.: WIRS135499 – FCC & ISSED RF Exposure

Test Model: Instrumentation Unit

Received Date: 05/29/2025

Test Date(s): 06/19/2025 – 06/20/2025, 06/25/2025 – 06/27/2025

Issued Date: 07/23/2025

Applicant: Bloodhound Tracking Systems

Address: 309 Henrietta St, Webster, TX 77598

Issued By: Eurofins Electrical and Electronic Testing NA, Inc.

Lab Address: 3162 Belick St. Santa Clara CA, 95054



Certificates and reports shall not be reproduced except in full, without the written permission of Eurofins Electrical and Electronic Testing NA, Inc. While use of the A2LA logo in this report reflects Eurofins Electrical and Electronic Testing NA, Inc. accreditation under these programs, the report must not be used by the client to claim product certification, approval, or endorsement by A2LA, or any agency of the Federal Government. This letter of transmittal is not a part of the attached report.

Eurofins Electrical and Electronic Testing NA, Inc. is part of the Eurofins Electrical & Electronics (E&E) global compliance network.

1. Certificate of Conformity

Product: Bloodhound Tracking Device

Brand: Bloodhound Tracking Device

Test Model: Instrumentation Unit

Sample Status: Production

Applicant: Bloodhound Tracking Device

Test Date(s): 06/19/2025 – 06/20/2025, 06/25/2025 – 06/27/2025

Standard: 47 CFR FCC Part 2.1091 and FCC Part 1.1310
RSS-102 Issue 6



Chin Ming Lui
Senior Wireless Test Engineer

Engineering Statement: The measurements shown in this report were made in accordance with the procedures indicated, and the emissions from this equipment were found to be within the limits applicable. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them. It is further stated that upon the basis of the measurements made, the equipment tested is capable of operation in accordance with the requirements of Part 22 Subpart H and Part 24 Subpart E and Part 27 Subpart L of the FCC Rules under normal use and maintenance.

Report Status Sheet

Revision	Report Date	Reason for Revision
Ø	July 23, 2025	Initial Issue.
1	July 29, 2025	Updated Section 1: “EUT General Info”.

1. EUT General info

Bloodhound Tracking Device: BTU IU

Manufacturer: Bloodhound Tracking Device

Part Number: 100600

- Cellular Radio:
 - Manufacturer: Trasna Cellular S.p.A.
 - P/N: SARA-R510M8Sv1
 - FCC ID: XPYUBX19KM01
 - LTE-M Bands Enabled
 - Integrated GNSS receiver
 - Constellations enabled: (GPS)
- LoRa Radio:
 - P/N: SX1262IMLRTT
 - Manufacturer: Semtech
 - Chipset Design
 - Frequency Hopping: Not Implemented
 - FHSS: Not Implemented
 - Spectrum Access: Duty Cycle (1%)
 - Maximum Output Power: 14 dBm
 - Bandwidth: 500 kHz
 - Spreading Factor: 10
 - Coding Rate: 4/5
 - NA Band: 902 to 915MHz (Unit is parked at 902.5MHz)
- Simultaneous Transmitter Configuration:
 - LTE-M and LoRa are both enabled concurrently and can transmit at the same time.

Note: The information in this section is leveraged from the Operational Description supplied by Bloodhound Tracking Device.

2. RF Exposure Limits

In this document, we evaluate the RF Exposure to human body due the intentional transmission from the transmitter (EUT). The limits for Maximum Permissible Exposure (MPE) specified in FCC 1.1310 and RSS-102 issue 6 were followed.

2.1 FCC ID

FCC ID: 2BP2A-BTDIU1

IC: 34083-BTDIU1

2.2 FCC Limits

According to FCC 1.1310 Table 1: The criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to Radio-Frequency (RF) radiation as specified in 1.1307(b)

Table 1 to § 1.1310(e)(1) – LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
(A) Limits For Occupational / Control Exposures				
0.3 – 3.0	614	1.63	*100	6
3.0 – 30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0	6
300 - 1500	...	...	F/300	6
1500 - 100,000	...	...	5	6
(B) Limits For General Population / Uncontrolled Exposure				
0.3 – 1.34	614	1.63	*100	30
1.34 – 30	824/f	2.19/f	*180/f ²	30
30 – 300	27.5	0.073	0.2	30
300 - 1500	...	...	F/1500	30
1500 - 100,000	...	...	1.0	30

F = Frequency in MHz

* = plane wave equivalent density

2.3 ISED Limits

According to RSS-102, ISED has adopted the SAR and RF field strength limits established in Health Canada's RF exposure guideline, Safety Code 6.

Table 4: RF Field Strength Limits for Devices Used by the General Public (Uncontrolled Environment)				
Frequency Range	Electric Field	Magnetic Field	Power Density	Reference Period
(MHz)	(V/m rms)	(A/m rms)	(W/m ²)	(minutes)
0.003-10	83	90	-	Instantaneous*
0.1-10	-	$0.73/f$	-	6**
1.1-10	$87/f^{0.5}$	-	-	6**
10-20	27.46	0.0728	-2	6
20-48	$58.07/f^{0.25}$	$0.1540/f^{0.25}$	$8.944/f^{0.5}$	6
48-300	22.06	0.05852	1.291	6
300-6000	$3.142 f^{0.3417}$	$0.008335 f^{0.3417}$	$0.02619 f^{0.6834}$	6
6000-15000	61.4	0.163	10	6
15000-150000	61.4	0.163	10	$616000/f^{1.2}$
150000-300000	$0.158 f^{0.5}$	$4.21 \times 10^{-4} f^{0.5}$	$6.67 \times 10^{-5} f$	$616000/f^{1.2}$
Note: f is frequency in MHz. * Based on nerve stimulation (NS). ** Based on specific absorption rate (SAR).				

3 Test Results (Mobile Configuration)

3.1 Classification

Radio is installed inside a mobile host device. The antenna of the product, under normal use condition, is at least 20 cm away from the body of the user and accessible to the end user. Warning statement to the user for keeping at least 20 cm or more separation distance with the antenna should be included in user's manual.

3.2 Maximum RF Power

LoRa Radio:

Modulation	Frequency Range (MHz)	Max. RF output power ¹ (dBm)	Max. Antenna Gain ² (dBi)	Max. EIRP ³ (dBm)	Max. EIRP (mWatts)
LoRa	902 – 928	11.68	1.36	13.04	20.14

¹**Note:** Measured max. conducted output power obtained from test report WIRS135499-FCC 15.247

²**Note:** LoRa Antenna peak gain obtained from “Antenna Report for IU Antennas” provided by Bloodhound Tracking Devices. Antenna specification sheet is attached in Appendix A.

³**Note:** Max. EIRP (dBm) = Max RF Output Power (dBm) + Max Antenna Gain (dBi)

Cellular Radio:

Band	Frequency Range (MHz)	Max. RF output Power ¹ (W)	Max. RF output Power with Tune Up ² (dBm)	Max. Antenna Gain ³ (dBi)	Max EIRP ⁴ (dBm)	Max EIRP (mWatts)
LTE CAT-M1 B2	1850 – 1910	0.1976	25	3.48	28.48	704.69
LTE CAT-M1 B4	1710 – 1755	0.2128	25	3.48	28.48	704.69
LTE CAT-M1 B5	824 – 849	0.2027	25	1.99	26.99	500.03
LTE CAT-M1 B12	699 – 716	0.1995	25	1.99	26.99	500.03
LTE CAT-M1 B13	777 – 787	0.2065	25	1.99	26.99	500.03
LTE CAT-M1 B26	814 – 849	0.1883	25	1.99	26.99	500.03

¹**Note:** Maximum conducted output power for LTE CAT-M1 leveraged from u-blox AG Grant (FCC ID: XPYUBX19KM01).

²**Note:** Maximum conducted output power with tune-up tolerance leveraged from “RF Exposure and Maximum ERP/EIRP Assessment For SARA-R510M8S” (FCC ID: XPYUBX19KM01, IC: 8595A-UBX19KM01, Assessment Reference: MDE_UBLOX_1905_MPE_01_rev03) test report by 7layers

³**Note:** Cellular Antenna peak gain obtained from “Antenna Report for IU Antennas” provided by Bloodhound Tracking Devices. Antenna specification sheet is attached in Appendix A.

⁴**Note:** Max. EIRP (dBm) = Max RF Output Power with Tune Up (dBm) + Max Antenna Gain (dBi)

3.3 RF Exposure Calculation

FCC limits

Calculations for this report are based on highest power for each radio channel or band

LoRa Radio:

Evaluation of 20cm distance:

Modulation	Frequency Range (MHz)	Max. EIRP ¹ (dBm)	Max. EIRP (mW)	Power Density (mW/cm ²) @20 cm	FCC Limit (mW/cm ²)	Results
LoRa	902 – 928	13.04	20.14	0.004	1.0	Complies

¹Note: Max. EIRP (dBm) = Max RF Output Power (dBm) + Max Antenna Gain (dBi)

Cellular Radio:

Evaluation of 20cm distance:

Band	Frequency Range (MHz)	Max. EIRP ¹ (dBm)	Max. EIRP (mW)	Power Density (mW/cm ²) @20 cm	FCC Limit (mW/cm ²)	Results
LTE CAT-M1 B2	1850 – 1910	28.48	704.69	0.1402	1.0	Complies
LTE CAT-M1 B4	1710 – 1755	28.48	704.69	0.1402	1.0	Complies
LTE CAT-M1 B5	824 – 849	26.99	500.03	0.0995	0.549	Complies
LTE CAT-M1 B12	699 – 716	26.99	500.03	0.0995	0.466	Complies
LTE CAT-M1 B13	777 – 787	26.99	500.03	0.0995	0.518	Complies
LTE CAT-M1 B26	814 – 849	26.99	500.03	0.0995	0.543	Complies

¹Note: Max. EIRP (dBm) = Max RF Output Power with Tune Up (dBm) + Max Antenna Gain (dBi)

LoRa + Cellular Radios Simultaneous Transmission:

Worst-case scenario: LoRa and LTE CAT-M1 B4 transmitting simultaneously.

Power Density of Simultaneous Transmitting Radios = $0.004 \text{ mW/cm}^2 + 0.1402 \text{ mW/cm}^2 = 0.1442 \text{ mW/cm}^2$, which complies with the worst-case FCC limit of 0.466 mW/cm^2 .

ISED Limits

Calculations for this report are based on highest power for each radio channel or band

LoRa Radio:

Evaluation of 20cm distance:

Modulation	Frequency Range (MHz)	Max. EIRP ¹ (dBm)	Max. EIRP (mW)	Power Density (W/m ²) @20 cm	RSS Limit (W/m ²)	Results
LoRa	902 – 928	13.04	20.14	0.04	2.74	Complies

¹Note: Max. EIRP (dBm) = Max RF Output Power (dBm) + Max Antenna Gain (dBi)

Cellular Radio:

Evaluation of 20cm distance:

Technology	Frequency Range (MHz)	Max. EIRP ¹ (dBm)	Max. EIRP (mW)	Power Density (W/m ²) @20 cm	RSS Limit (W/m ²)	Results
LTE CAT-M1 B2	1850 – 1910	28.48	704.69	1.402	4.476	Complies
LTE CAT-M1 B4	1710 – 1755	28.48	704.69	1.402	4.242	Complies
LTE CAT-M1 B5	824 – 849	26.99	500.03	0.995	2.576	Complies
LTE CAT-M1 B12	699 – 716	26.99	500.03	0.995	2.302	Complies
LTE CAT-M1 B13	777 – 787	26.99	500.03	0.995	2.474	Complies
LTE CAT-M1 B26	814 – 849	26.99	500.03	0.995	2.554	Complies

¹Note: Max. EIRP (dBm) = Max RF Output Power with Tune Up (dBm) + Max Antenna Gain (dBi)

LoRa + Cellular Radios Simultaneous Transmission:

Worst-case scenario: LoRa and LTE CAT-M1 B4 transmitting simultaneously.

Power Density of Simultaneous Transmitting Radios = $0.04 \text{ W/m}^2 + 1.402 \text{ W/m}^2 = 1.442 \text{ W/m}^2$, which complies with the worst-case RSS limit of 2.302 W/m^2 .

Power Density Calculation

$$P_d = (P_{out} * G) / (4 * \pi * R^2)$$

Where:

P_d = Power density in W/m²

P_{out} = Output power from the antenna in watts (W)

G = Gain of the antenna in linear scale

R = Distance between observation point and center of the radiator in meters (m)

4 Conclusion

This device is compliant with RF Exposure requirements of the limits for Maximum Permissible Exposure (MPE) specified in FCC 1.1310 and RSS-102 Issue 6 for General Public (Uncontrolled Environment).

The LoRa and Cellular radios comply to both the FCC and ISED limits at 20cm away from the body of the user. Worst-case scenario of LoRa and LTE CAT-M1 B4 simultaneous transmission comply with both FCC and ISED MPE limits.

The LoRa and Cellular radios are capable of simultaneous transmission.

In conclusion, the EUT, under normal use condition, must be at least 20 cm away from the body of the user and accessible to the end user. Warning statement to the user for keeping at least 20 cm or more separation distance with the antenna should be included in user's manual.

Appendix A

Antenna Information:



BTD IU Antenna
Report_18Jul2025.pdf

Operational Description:



OP BTD IU PN
100600.pdf