


Test report No:
2530770R.701A

FCC TEST REPORT

Product Name	Smart Controller
Trademark	N/A
Model and /or type reference	GS-ONE
FCC ID	2BP40-GS-ONE
Applicant's name / address	Aerora North America, Inc. 2570 N. First St, Suite 200 San Jose, CA 95131
Test method requested, standard	47 CFR FCC Part 15 (Section 15.247) ANSI C63.10: 2020
Verdict Summary	IN COMPLIANCE
Tested by (name / position & signature)	Tim Cao / Project Manager 
Approved by (name / position & signature)	Frank He / Technical Manager 
Date of issue	2025-09-08
Report Version	V1.0
Report template No	Template_FCC Part 15C-RF-V1.0

INDEX

	page
General conditions	5
Environmental conditions	5
Possible test case verdicts	6
Abbreviations.....	6
Document History.....	7
Remarks and Comments	7
Used Equipment.....	8
Uncertainty	10
1 General Information	11
2 Description of Test Setup.....	12
3 Verdict summary section.....	13
3.1 Standards	13
3.2 Deviation(s) from the Standard(s) / Test Specification(s).....	13
3.3 Overview of results	14
3.4 Test Facility.....	15
4 Test Items of limit/setup/procedure.....	16
4.1 20dB Emission Bandwidth.....	16
4.1.1 Limit	16
4.1.2 Test Setup	16
4.1.3 Test Procedure	16
4.2 Maximum Conducted Output Power.....	17
4.2.1 Limit	17
4.2.2 Test Setup	17
4.2.3 Test Procedure	17
4.3 Carrier Frequency Separation	18
4.3.1 Limit	18
4.3.2 Test Setup	18
4.3.3 Test Procedure	18
4.4 Time of Occupancy.....	19
4.4.1 Limit	19
4.4.2 Test Setup	19
4.4.3 Test Procedure	19
4.5 Number of hopping Frequencies	20
4.5.1 Limit	20

4.5.2	Test Setup	20
4.5.3	Test Procedure	20
4.6	Band edge measurements	21
4.6.1	Limit	21
4.6.2	Test Setup	21
4.6.3	Test Procedure	21
4.7	Conducted Spurious Emission	22
4.7.1	Limit	22
4.7.2	Test Setup	22
4.7.3	Test Procedure	22
4.8	Duty cycle	23
4.8.1	Limit	23
4.8.2	Test Setup	23
4.8.3	Test Procedure	23
4.9	Emissions in Restricted Bands	24
4.9.1	Limit	24
4.9.2	Test Setup	26
4.10.3	Test Procedure	27
4.10	AC Power Line Conducted Emission.....	28
4.10.1	Limit	28
4.10.2	Test Setup	28
4.10.3	Test Procedure	28
4.11	Antenna Requirement.....	29
4.11.1	Limit	29
4.11.2	Antenna Connector Construction:	29
5	Test setup photo and EUT Photo	30
6	Test Result	31
	Appendix A: 20dB Emission Bandwidth.....	31
	Appendix B: Occupied Channel Bandwidth	35
	Appendix C: Maximum conducted output power	39
	Appendix D: Carrier frequency separation.....	40
	Appendix E: Time of occupancy	42
	Appendix F: Number of hopping channels.....	46
	Appendix G: Band Edge measurements	48
	Appendix H: Conducted Spurious Emission	60
	Appendix I: Duty Cycle.....	105
	Appendix J: Emissions in Restricted Bands	109



Appendix K: AC Power Line Conducted Emission	129
--	-----

COMPETENCES AND GUARANTEES

DEKRA is a testing laboratory competent to carry out the tests described in this report.

In order to assure the traceability to other national and international laboratories, DEKRA has a calibration and maintenance program for its measurement equipment.

DEKRA guarantees the reliability of the data presented in this report, which is the result of the measurements and the tests performed to the item under test on the date and under the conditions stated in the report and it is based on the knowledge and technical facilities available at DEKRA at the time of performance of the test.

DEKRA is liable to the client for the maintenance of the confidentiality of all information related to the item under test and the results of the test.

The results presented in this Test Report apply only to the particular item under test established in this document.

IMPORTANT: No parts of this report may be reproduced or quoted out of context, in any form or by any means, except in full, without the previous written permission of DEKRA.

GENERAL CONDITIONS

Test Location	No. 99, Hongye Road, Suzhou Industrial Park Suzhou, 215006, P.R. China
Date (receive sample)	Mar. 25, 2025
Date (start test)	Apr. 05, 2025
Date (finish test)	Apr. 25, 2025

1. This report is only referred to the item that has undergone the test.
2. This report does not constitute or imply on its own an approval of the product by the Certification Bodies or Competent Authorities.
3. This document is only valid if complete; no partial reproduction can be made without previous written permission of DEKRA.
4. This test report cannot be used partially or in full for publicity and/or promotional purposes without previous written permission of DEKRA.

ENVIRONMENTAL CONDITIONS

The climatic conditions during the tests are within the limits specified by the manufacturer for the operation of the EUT and the test equipment. The climatic conditions during the tests were within the following limits:

Ambient temperature	15 °C – 35 °C
Relative Humidity air	30% - 60%

If explicitly required in the basic standard or applied product / product family standard the climatic values are recorded and documented separately in this test report.

POSSIBLE TEST CASE VERDICTS

Test case does not apply to test object	N/A
Test object does meet requirement	P (Pass) / PASS
Test object does not meet requirement	F (Fail) / FAIL
Not measured	N/M

ABBREVIATIONS

For the purposes of the present document, the following abbreviations apply:

EUT	: Equipment Under Test
QP	: Quasi-Peak
CAV	: CISPR Average
AV	: Average
CDN	: Coupling Decoupling Network
SAC	: Semi-Anechoic Chamber
OATS	: Open Area Test Site
BW	: Bandwidth
AM	: Amplitude Modulation
PM	: Pulse Modulation
HCP	: Horizontal Coupling Plane
VCP	: Vertical Coupling Plane
U_N	: Nominal voltage
T_x	: Transmitter
R_x	: Receiver
N/A	: Not Applicable
N/M	: Not Measured

DOCUMENT HISTORY

Report No.	Version	Description	Issued Date
2530770R.701A	V1.0	Initial issue of report.	2025-09-08

REMARKS AND COMMENTS

1. The equipment under test (EUT) does meet the essential requirements of the stated standard(s)/test(s).
2. These test results on a sample of the device are for the purpose of demonstrating Compliance with 47 CFR FCC Part 15 (Section 15.247).
3. The measurement result is considered in conformance with the requirement if it is within the prescribed limit, It is not necessary to account the uncertainty associated with the measurement result.
4. The test results presented in this report relate only to the object tested.
5. The test report shall not be reproduced without the written approval of DEKRA Testing and Certification (Suzhou) Co., Ltd.
6. This report will not be used for social proof function in China market.
7. DEKRA declines any responsibility with the following test data provided by customer that may affect the validity of result:
 - Chapter 1 General Information.

USED EQUIPMENT

AC Power Line Conducted Emission / TR1

Instrument	Manufacturer	Model No.	Serial No.	Next Cal. Date
EMI Test Receiver	R&S	ESCI	100726	2026.05.17
Two-Line V-Network	R&S	ENV216	101044	2025.10.25
Current Probe	R&S	EZ-17	100678	2025.10.18
50ohm Coaxial Switch	Anritsu	MP59B	6200464462	2026.03.15
50ohm Termination	Xinghu	N/A	N/A	2026.01.10
Temperature/Humidity Meter	RTS	RTS-1909	THM-012	2026.04.29
Coaxial Cable	Suhner	RG 223	TR1-C1	2026.03.15
Dekra test software	Dekra	N/A	N/A	N/A

Conducted Test / TR8

Instrument	Manufacturer	Model No.	Serial No.	Next Cal. Date
Wireless Connectivity Tester	R&S	CMW 270	102593	2026.05.09
Coaxial Cable	N/A	N/A	2477	2025.06.10
Coaxial Cable	N/A	N/A	2478	2025.06.10
High and low temperature and fast temperature change test box	ASTUOD	ASTD-FBT-225K	N/A	2026.03.14
Temperature/Humidity Meter	RTS	RTS-8S	N/A	2025.07.10
MAX Signal Analyzer	Keysight	N9010A	THM-032	2025.10.25
Power Meter	Anritsu	MA2411B	1339267	2025.08.23
RF Control Unit	Tonscend	JS0806-2	MY48030494	2026.01.25
MXG-B RF Vector Signal Generator	Keysight	N5182B	22G8060594	2026.03.22
Frequency extender for EXG or MXG	Keysight	N5182BX07	MY61252529	2026.03.22
EXG-B MW Analog Signal Generator	Keysight	N5173B	MY59362500	2025.07.05
Test Software	Tonscend	TS1120	MY61252566	N/A

Radiated Emission(9KHz-1GHz) / AC2

Instrument	Manufacturer	Model No.	Serial No.	Next Cal. Date
EMI Test Receiver	R&S	ESCI	100573	2026.01.10
Loop Antenna	R&S	HFH2-Z2E	101149	2026.04.15
Bilog Antenna	Teseq GmbH	CBL6112D	27611	2026.03.23
Temperature/Humidity Meter	RTS	RTS-1909	THM-021	2026.04.29
Coaxial Cable	Huber+Suhner	SUCOFLEX 106	AC2-C	2026.03.15
Dekra test software	Dekra	N/A	N/A	N/A

Radiated Emission Band Edge / AC6

Instrument	Manufacturer	Model No.	Serial No.	Next Cal. Date
Anechoic chamber	Quietek	9m*5.5m*5.5m	AC6	2029.06.29
Signal Analyzer	Agilent	N9010A	MY55370495	2025.10.18

Loop Antenna	R&S	HFH2-Z2E	101149	2026.04.15
DRG Horn Antenna	RFSPIN	DRH18-E	CE2C07A18EN	2025.12.06
Broad-Band Horn Antenna	SCHWARZBECK	BBHA 9170	750	2025.11.23
Pre-Amplifier	Schwarzbeck	BBV 9721	'00114	2026.05.16
TRILOG Broadband Antenna	SCHWARZBECK	VULB 9168	1231	2026.05.27
Temperature/Humidity Meter	RTS	RTS-8S	RF07	2026.06.16
Temperature/Humidity Meter	RTS	RTS-8S	RF04	2026.06.16
Pre-amplifier	Tonscend	TAP01008028	806JSAP041204251019	2026.05.16
Pre-amplifier	Tonscend	TAP01018048S	806JSAP040204251009	2026.05.16
Wideband Radio Communication Tester	R&S	CMW 500	170870	2026.05.09
Test Software	Tonscend	JS36	JS36-RSE	N/A

AC Power Line Conducted Emission / TR1

Instrument	Manufacturer	Model No.	Serial No.	Firmware Version	Software version
EMI Test Receiver	R&S	ESCI	100726	4.42 SP3	N/A
Dekra test software	Dekra	N/A	N/A	N/A	3

Conducted Test / TR8

Instrument	Manufacturer	Model No.	Serial No.	Firmware Version	Software version
Wireless Connectivity Tester	R&S	CMW 270	102593	V 4.0.60	N/A
MAX Signal Analyzer	Keysight	N9010A	MY48030494	A.14.03	N/A
MXG-B RF Vector Signal Generator	Keysight	N5182B	MY61252529	B.01.96	N/A
EXG-B MW Analog Signal Generator	Keysight	N5173B	MY61252566	B.01.95	N/A
Test Software	Tonscend	TS1120	JS1120-3	N/A	V3.0.22

Radiated Emission(9KHz-1GHz) / AC2

Instrument	Manufacturer	Model No.	Serial No.	Firmware Version	Software version
EMI Test Receiver	R&S	ESCI	100573	4.42 SP2	N/A
Dekra test software	Dekra	N/A	N/A	N/A	3

Radiated Emission Band Edge / AC6

Instrument	Manufacturer	Model No.	Serial No.	Firmware Version	Software version
Signal Analyzer	Agilent	N9010A	MY55370495	A.18.17	N/A
Wideband Radio Communication Tester	R&S	CMW 500	170870	X 4.0.62.11	N/A
Dekra test software	Dekra	N/A	N/A	N/A	5.0.0

UNCERTAINTY

Uncertainties have been calculated according to the DEKRA internal document. The reported expanded uncertainties are based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95%. The Uncertainties is comply with standard required as below.

Test item Test Location	Uncertainty
AC Power Line Conducted Emission	9kHz~150kHz: 2.8 dB 150kHz~30MHz: 2.4 dB
Radiated Emission(30MHz~1GHz)	Horizontal: 30MHz~300MHz: 3.5 dB, 300MHz~1GHz: 3.6 dB Vertical: 30MHz~300MHz: 3.6 dB, 300MHz~1GHz: 3.5 dB
Radiated Emission(1GHz~40GHz)	Horizontal: 1GHz~18GHz: 5.0 dB Vertical: 1GHz~18GHz: 4.8 dB
Bandwidth	± 1.0 kHz
Carrier Frequency Separation	± 1.0 kHz
Number of Hopping Frequencies	± 1.0 kHz
Time of Occupancy (Dwell Time)	± 0.1 us
Peak OutputPower	± 1.3 dB
Emissions in non-restricted frequency bands	± 1.0 dB
Radiated Emission Band Edge	± 3.9 dB

1 GENERAL INFORMATION

Product Name	Smart Controller					
Trademark	N/A					
Model No.	GS-ONE					
FCC ID.	2BP40-GS-ONE					
Hardware Version	V1.3					
Software Version	T05					
Operating Temperature	-40°C ~ 70°C					
Power Supply	DC 7.4 V, 3 A 22.2 W from internal rechargeable battery which can be charged by AC/DC adapter.					
Manufacturer	Aerora North America, Inc.					
Manufacturer address	2570 N. First St, Suite 200 San Jose, CA 95131					
Factory	ROTOTEK VIETNAM CO., LTD					
Factory address	House S4_2nd floor, Hap Linh Industrial Park, Bac Ninh City, Vietnam					
Wireless specification	Bluetooth					
Operating frequency range(s)	2402~2480MHz					
Type of Modulation	GFSK					
PHYs	☒	GFSK	☒	Pi/4 DQPSK	☒	8DPSK
Data Rate	☒	1Mbit/s	☒	2Mbit/s	☒	3Mbit/s
Number of channels	79					
Antenna Type	FPC					
Antenna Gain	3.0 dBi					

Remark:

As above information is provided and confirmed by the applicant. DEKRA is not liable to the accuracy, suitability, reliability or/and integrity of the information.

2 DESCRIPTION OF TEST SETUP

Auxiliary equipment	Type / Version	Manufacturer	Supplied by
(1) Notebook	Think pad x220	Lenovo	Adapter
(2) USB Control Cable	N/A	N/A	N/A
(3) USB Control Cable	N/A	N/A	N/A
software	Type / Version	Manufacturer	Supplied by
QRCT	N/A	N/A	N/A

3 VERDICT SUMMARY SECTION

This chapter presents an overview of standards and results. Refer to the next chapters for details of measured test results and applied test levels.

3.1 Standards

Standard	Year	Description
CFR 47, FCC Part 15 C	2024	Operation within the bands 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz.
ANSI C63.10	2020	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices

3.2 Deviation(s) from the Standard(s) / Test Specification(s)

The following deviation(s) was / were made from the published requirements of the listed standards: N/A.

(Please define the deviations from the standard(s) if applicable)

3.3 Overview of results

Requirement – Test Item	Standard(s)	Verdict	Remark
20dB Emission Bandwidth	FCC 15.247(a)(1)	PASS	Test data please refer to Appendix A
Maximum conducted output power	FCC 15.247(b)(1)	PASS	Test data please refer to Appendix B
Carrier Frequency Separation	FCC 15.247(a)(1)	PASS	Test data please refer to Appendix C
Time of Occupancy (Dwell Time)	FCC 15.247(a)(1)(iii)	PASS	Test data please refer to Appendix D
Number of Hopping Frequencies	FCC 15.247(a)(1)(iii)	PASS	Test data please refer to Appendix E
Band edge measurements	FCC 15.247(d)	PASS	Test data please refer to Appendix F
Conducted Spurious Emission	FCC 15.247(d), FCC 15.209	PASS	Test data please refer to Appendix G
Duty Cycle	ANSI C63.10:2013	PASS	Test data please refer to Appendix H
Emissions in Restricted Bands	FCC 15.247(b)(3)	PASS	Test data please refer to Appendix I
AC Power Line Conducted Emission	FCC 15.207	PASS	Test data please refer to Appendix J
Antenna Requirement	FCC 15.203	PASS	---

3.4 Test Facility

Tset Location : FCC Designation Number: CN1199

4 TEST ITEMS OF LIMIT/SETUP/PROCEDURE


4.1 20dB Emission Bandwidth

VERDICT: PASS

4.1.1 Limit

Standard	FCC Part 15 Subpart C Paragraph 15.247(a)
☒	For frequency hopping systems operating in 2400-2483.5 MHz band, within frequency range.
☐	For frequency hopping systems operating in 902-928 MHz band, the maximum allowed 20 dB bandwidth of the hopping channel is 500 kHz.
☐	For frequency hopping systems operating in 5725-5850 MHz band, the maximum 20 dB bandwidth of the hopping channel is 1 MHz.

4.1.2 Test Setup




4.1.3 Test Procedure

References Rule	Chapter	Description
☒ ANSI C63.10	6.9	Occupied bandwidth tests
☒ ANSI C63.10	6.9.3	Occupied bandwidth—relative measurement procedure

4.2 Maximum Conducted Output Power**VERDICT: PASS****4.2.1 Limit**

Standard	FCC Part 15 Subpart C Paragraph 15.247(b);
☒	Frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.
☒	Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.
☐	For frequency hopping systems operating in the 902-928 MHz band: 1 watt for systems employing at least 50 hopping channels; and, 0.25 watts for systems employing less than 50 hopping channels, but at least 25 hopping channels

4.2.2 Test Setup**4.2.3 Test Procedure**

	References Rule	Chapter	Description
☒	ANSI C63.10	7.8	Evaluation of frequency-hopping device parameters
☒	ANSI C63.10	7.8.5	Output power test procedure for frequency-hopping spread-spectrum (FHSS) devices


4.3 Carrier Frequency Separation

VERDICT: PASS

4.3.1 Limit

Standard		FCC Part 15 Subpart C Paragraph 15.247(a);
☐	Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.	
☒	Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel.	
☐	The 20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 20 second period;	
☐	The 20 dB bandwidth of the hopping channel is 250 kHz or greater, the system shall use at least 25 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 10 second period. The maximum allowed 20 dB bandwidth of the hopping channel is 500 kHz.	
☐	Frequency hopping systems operating in the 5725-5850 MHz band shall use at least 75 hopping frequencies. The maximum 20 dB bandwidth of the hopping channel is 1 MHz.	

4.3.2 Test Setup




4.3.3 Test Procedure

References Rule		Chapter	Description
☒	ANSI C63.10	7.8	Evaluation of frequency-hopping device parameters
☒	ANSI C63.10	7.8.2	Carrier frequency separation

4.4 Time of Occupancy**VERDICT: PASS****4.4.1 Limit**


Standard	FCC Part 15 Subpart C Paragraph 15.247(a);
☒	Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.
☐	For frequency hopping systems operating in the 902-928 MHz band: if the 20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 20 second period
☐	For frequency hopping systems operating in the 902-928 MHz band: if the 20 dB bandwidth of the hopping channel is 250 kHz or greater, the system shall use at least 25 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 10 second period.
☐	Frequency hopping systems operating in the 5725-5850 MHz band shall use at least 75 hopping frequencies. The maximum 20 dB bandwidth of the hopping channel is 1 MHz. The average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 30 second period.

4.4.2 Test Setup**4.4.3 Test Procedure**

References Rule	Chapter	Description
☒ ANSI C63.10	7.8	Evaluation of frequency-hopping device parameters
☒ ANSI C63.10	7.8.4	Time of occupancy (dwell time)

4.5 Number of hopping Frequencies**VERDICT: PASS****4.5.1 Limit**

Standard		FCC Part 15 Subpart C Paragraph 15.247(a);
☒	For frequency hopping systems operating in the 2400-2483.5 MHz band shall use at least 15 hopping frequencies.	
☐	For frequency hopping systems operating in 902-928 MHz band, if the 20 dB bandwidth of the hopping channel is less than 250 kHz, shall use at least 50 hopping frequencies.	
☐	For frequency hopping systems operating in 902-928 MHz band, if the 20 dB bandwidth of the hopping channel is higher than 250 kHz, shall use at least 25 hopping frequencies.	
☐	For frequency hopping systems operating in the 5725-5850 MHz band shall use at least 75 hopping frequencies.	

4.5.2 Test Setup**4.5.3 Test Procedure**

References Rule		Chapter	Description
☒	ANSI C63.10	7.8.	Evaluation of frequency-hopping device parameters
☒	ANSI C63.10	7.8.3	Number of Hopping Frequencies

4.6 Band edge measurements


VERDICT: PASS

4.6.1 Limit

Standard				
FCC Part 15 Subpart C Paragraph 15.247(d) , 15.209;				
Frequency bands (MHz)	Detector	Limit (dB μ V/m)	RBW (MHz)	Distance (m)
2310-2390	PK	74	1	3
2483.5-2500	AV	54	1	3

Note: The field strength of emissions appearing within these frequency bands shall not exceed the limits.

4.6.2 Test Setup



4.6.3 Test Procedure


Test Method			
	References Rule	Chapter	Description
☐	DA 00-705	N/A	duty cycle correction factor
☒	ANSI C63.10	6.10	Band-edge testing
☒	ANSI C63.10	6.10.5	Restricted-band band-edge measurements
☐	ANSI C63.10	6.10.6	Marker-delta method
☐	ANSI C63.10	6.4	Radiated emissions from unlicensed wireless devices below 30 MHz
☐	ANSI C63.10	6.5	Radiated emissions from unlicensed wireless devices in the frequency range of 30 MHz to 1000 MHz
☐	ANSI C63.10	6.6	Radiated emissions from unlicensed wireless devices above 1 GHz

4.7 Conducted Spurious Emission**VERDICT: PASS****4.7.1 Limit**

Standard	FCC Part 15 Subpart C Paragraph 15.247(d);
RF Output power (Detection methods)	Limit(dB)
RF Output power(Average detector)	30dBc(Note1)
RF Output power(PK detector)	20dBc(Note2)

Note 1: If maximum conducted (average) output power was used to demonstrate compliance as described in 9.2, then the peak power in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 30 dB relative to the maximum in-band peak PSD level in 100 kHz (i.e., 30 dBc).

Note 2: If the maximum peak conducted output power procedure was used, then the peak output power measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz (i.e., 20 dBc).

4.7.2 Test Setup**4.7.3 Test Procedure**

References Rule	Chapter	Description
☒ ANSI C63.10	7.8	Evaluation of frequency-hopping device parameters
☒ ANSI C63.10	7.8.6	Band-edge measurements for RF conducted emissions


4.8 Duty cycle

VERDICT: PASS

4.8.1 Limit

N/A

4.8.2 Test Setup



4.8.3 Test Procedure

References Rule	Chapter	Description
☒ ANSI C63.10	11.6	Duty cycle (D), transmission duration (T), and maximum power control level

4.9 Emissions in Restricted Bands**VERDICT: PASS****4.9.1 Limit****Standard**

FCC Part 15 Subpart C Paragraph 15.205

Restricted Bands of operation

Frequency (MHz)	Frequency (MHz)	Frequency (MHz)	Frequency (GHz)
0.090 – 0.110	16.42 – 16.423	399.9 – 410	4.5 – 5.15
0.495 – 0.505	16.69475 – 16.69525	608 – 614	5.35 – 5.46
2.1735 – 2.1905	16.80425 – 16.80475	960 – 1240	7.25 – 7.75
4.125 – 4.128	25.5 – 25.67	1300 – 1427	8.025 – 8.5
4.17725 – 4.17775	37.5 – 38.25	1435 – 1626.5	9.0 – 9.2
4.20725 – 4.20775	73 – 74.6	1645.5 – 1646.5	9.3 – 9.5
6.215 – 6.218	74.8 – 75.2	1660 – 1710	10.6 – 12.7
6.26775 – 6.26825	108 – 121.94	1718.8 – 1722.2	13.25 – 13.4
6.31175 – 6.31225	123 – 138	2200 – 2300	14.47 – 14.5
8.291 – 8.294	149.9 – 150.05	2310 – 2390	15.35 – 16.2
8.362 – 8.366	156.52475 – 156.52525	2483.5 – 2500	17.7 – 21.4
8.37625 – 8.38675	156.7 – 156.9	2690 – 2900	22.01 – 23.12
8.81425 – 8.81475	162.0125 – 167.17	3260 – 3267	23.6 – 24.0
12.29 – 12.293	167.72 – 173.2	3332 – 3339	31.2 – 31.8
12.51975 – 12.52025	240 – 285	3345.8 – 3358	36.43 – 36.5
12.57675 – 12.57725	322 – 335.4	3600 – 4400	
13.36 – 13.41			

Restricted Band Emissions Limit

FCC Part 15 Subpart C Paragraph 15.209


Frequency (MHz)	Field strength ($\mu\text{V/m}$)	Field strength ($\text{dB}\mu\text{V/m}$)	Measurement distance (m)
0.009 - 0.49	2400/F(kHz)	48.5 – 13.8	300 _(Note 1)
0.49 - 1.705	24000/F(kHz)	33.8 - 23	30 _(Note 1)
1.705 - 30	30	29.5	30 _(Note 1)
30 - 88	100	40	3 _(Note 2)
88 - 216	150	43.5	3 _(Note 2)
216 - 960	200	46	3 _(Note 2)
Above 960	500	54	3 _(Note 2)

Note 1: At frequencies below 30 MHz, measurements may be performed at a distance closer than that specified in the regulations; however, an attempt should be made to avoid making measurements in the near field. Pending the development of an appropriate measurement procedure for measurements performed below 30 MHz, when performing measurements at a closer distance than specified, the results shall be extrapolated to the specified distance by either making measurements at a minimum of two distances on at least one radial to determine the proper extrapolation factor or by using the square of an inverse linear distance extrapolation factor (40 dB/decade).


Note 2: At frequencies at or above 30 MHz, measurements may be performed at a distance other than what is specified provided: measurements are not made in the near field except where it can be shown that near field measurements are appropriate due to the characteristics of the device; and it can be demonstrated that the signal levels needed to be measured at the distance employed can be detected by the measurement equipment. Measurements shall not be performed at a distance greater than 30 meters unless it can be further demonstrated that measurements at a distance of 30 meters or less are impractical. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse linear-distance for field strength measurements; inverse-linear-distance-squared for power density measurements).

4.9.2 Test Setup


Below 30MHz Test Setup:



30MHz-1GHz Test Setup:



Above 1GHz Test Setup:



4.10.3 Test Procedure

	References Rule		Chapter	Description	
☒	ANSI C63.10		11.12	Emissions in restricted frequency bands	
	☒	ANSI C63.10	11.12.1	Radiated emission measurements	
	☒	ANSI C63.10	6.3	Radiated spurious emission test	
		☒	ANSI C63.10	6.4	Radiated emissions from unlicensed wireless devices below 30 MHz
		☒	ANSI C63.10	6.5	Radiated emissions from unlicensed wireless devices in the frequency range of 30 MHz to 1000 MHz
		☒	ANSI C63.10	6.6	Radiated emissions from unlicensed wireless devices above 1 GHz

4.10 AC Power Line Conducted Emission**VERDICT: PASS****4.10.1 Limit**

Standard	FCC Part 15 Subpart C Paragraph 15.207; RSS-Gen Issue 5 Paragraph 8.8.	
Frequency range [MHz]	Limit: QP [dB(μV) ¹⁾]	Limit: AV [dB(μV) ¹⁾]
0,15 - 0,50	66 - 56 ²⁾	56 - 46 ²⁾
0,50 - 5,0	56	46
5,0 - 30	60	50


Frequency range [MHz]	Limit: QP [dB(μV) ¹⁾]	Limit: AV [dB(μV) ¹⁾]
0,15 - 0,50	66 - 56 ²⁾	56 - 46 ²⁾
0,50 - 5,0	56	46
5,0 - 30	60	50

¹⁾ At the transition frequency, the lower limit applies.

²⁾ The limit decreases linearly with the logarithm of the frequency.

NOTE 1: The exclusion band for transmitters shall be considered for transmitters operating at frequencies below 30 MHz.

NOTE 2: Where the AC output port is directly connected (or via a circuit breaker) to the AC power input port of the EUT the AC power output port need not to be tested.

4.10.2 Test Setup**4.10.3 Test Procedure**

	References Rule	Chapter	Item
☒	ANSI C63.10	6.2	Standard test method for ac power-line conducted emissions from unlicensed wireless devices

4.11 Antenna Requirement**VERDICT: PASS****4.11.1 Limit****Standard**

FCC Part 15 Subpart C Paragraph 15.247(d) , 15.209

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §15.211, §15.213, §15.217, §15.219, or §15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

4.11.2 Antenna Connector Construction:

- | | |
|-------------------------------------|--|
| ☒ | The use of a permanently attached antenna |
| ☐ | The antenna use of a unique coupling to the intentional radiator |
| ☐ | The use of a nonstandard antenna jack or electrical connector |

Please refer to the attached document "Internal Photograph" to show the antenna connector.

5 TEST SETUP PHOTO AND EUT PHOTO

Remark: The test setup photo and EUT Photo please see appendix.

6 TEST RESULT

Appendix A: 20dB Emission Bandwidth

TestMode	Frequency [MHz]	20db EBW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
DH5	2402	0.939	2401.565	2402.504	---	---
	2441	0.948	2440.562	2441.510	---	---
	2480	0.954	2479.559	2480.513	---	---
2DH5	2402	1.287	2401.385	2402.672	---	---
	2441	1.347	2440.343	2441.690	---	---
	2480	1.323	2479.358	2480.681	---	---
3DH5	2402	1.308	2401.367	2402.675	---	---
	2441	1.299	2440.370	2441.669	---	---
	2480	1.299	2479.370	2480.669	---	---

Test Graphs

DH5_Ant1_2402



DH5_Ant1_2441



DH5_Ant1_2480



2DH5_Ant1_2402




2DH5_Ant1_2441




2DH5_Ant1_2480



3DH5_Ant1_2402



3DH5_Ant1_2441




3DH5_Ant1_2480




Appendix B: Occupied Channel Bandwidth

TestMode	Frequency [MHz]	OCB [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
DH5	2402	0.84584	2401.5959	2402.4418	---	---
	2441	0.83493	2440.6015	2441.4364	---	---
	2480	0.83217	2479.6002	2480.4323	---	---
2DH5	2402	1.1873	2401.4287	2402.6160	---	---
	2441	1.1896	2440.4244	2441.6140	---	---
	2480	1.1854	2479.4249	2480.6103	---	---
3DH5	2402	1.1967	2401.4201	2402.6168	---	---
	2441	1.2098	2440.4113	2441.6211	---	---
	2480	1.1887	2479.4210	2480.6097	---	---

Test Graphs






DH5_Ant1_2480




2DH5_Ant1_2402




2DH5_Ant1_2441




2DH5_Ant1_2480




3DH5_Ant1_2402



3DH5_Ant1_2441



3DH5_Ant1_2480



Appendix C: Maximum conducted output power

Test Mode	Frequency [MHz]	Conducted Power [dBm]	Limit [dBm]	Verdict
DH5	2402	11.18	≤20.97	PASS
	2441	11.34	≤20.97	PASS
	2480	12.71	≤20.97	PASS
2DH5	2402	9.68	≤20.97	PASS
	2441	9.67	≤20.97	PASS
	2480	11.76	≤20.97	PASS
3DH5	2402	10.04	≤20.97	PASS
	2441	10.22	≤20.97	PASS
	2480	12.20	≤20.97	PASS

Appendix D: Carrier frequency separation


TestMode	Frequency[MHz]	Result[MHz]	Limit[MHz]	Verdict
DH5	Hop	1.16	≥ 0.954	PASS
2DH5	Hop	1.096	≥ 0.898	PASS
3DH5	Hop	1.132	≥ 0.872	PASS

Test Graphs


DH5_Ant1_Hop



2DH5_Ant1_Hop




3DH5_Ant1_Hop




Appendix E: Time of occupancy


TestMode	Frequency[MHz]	BurstWidth [ms]	TotalHops [Num]	Result[s]	Limit[s]	Verdict
DH1	Hop	0.370	320	0.118	≤0.4	PASS
DH3	Hop	-0.874	160	-0.14	≤0.4	PASS
DH5	Hop	2.874	106.67	0.307	≤0.4	PASS
2DH1	Hop	-0.874	320	-0.28	≤0.4	PASS
2DH3	Hop	-0.871	160	-0.139	≤0.4	PASS
2DH5	Hop	2.875	106.67	0.307	≤0.4	PASS
3DH1	Hop	0.376	320	0.12	≤0.4	PASS
3DH3	Hop	1.626	160	0.26	≤0.4	PASS
3DH5	Hop	2.878	106.67	0.307	≤0.4	PASS

Test Graphs







DH5_Ant1_Hop




2DH1_Ant1_Hop




2DH3_Ant1_Hop




2DH5_Ant1_Hop



3DH1_Ant1_Hop



3DH3_Ant1_Hop



3DH5_Ant1_Hop




Appendix F: Number of hopping channels

TestMode	Frequency[MHz]	Result[Num]	Limit[Num]	Verdict
DH5	Hop	79	≥15	PASS
2DH5	Hop	79	≥15	PASS
3DH5	Hop	79	≥15	PASS

Test Graphs


DH5_Ant1_Hop



2DH5_Ant1_Hop



3DH5_Ant1_Hop




Appendix G: Band Edge measurements

Test Report

Project Information

Profile:	2530770R	EUT:	Smart Controller
Mode:	Mode1:Transmit at 2402MHz by DH5	Voltage:	120 Vac / 60 Hz
Environment:	Temp: 25°C ; Humi:60%	Engineer	Reyn Chen
Test Standard:	FCC PART 15C		

Test Graph



Suspected Data List


NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2389.48	59.69	63.34	3.65	74.00	10.66	PK	Horizo	PASS
	2389.48	-	38.55	-	54.00	15.45	AV	Horizo	PASS
2	2390.00	59.09	62.74	3.65	74.00	11.26	PK	Horizo	PASS
	2390.00	-	37.95	-	54.00	16.05	AV	Horizo	PASS

Test Report

Project Information

Profile:	2530770R	EUT:	Smart Controller
Mode:	Mode1:Transmit at 2402MHz by DH5	Voltage:	120 Vac / 60 Hz
Environment:	Temp: 25°C ; Humi:60%	Engineer	Reyn Chen
Test Standard:	FCC PART 15C		

Test Graph



Suspected Data List


NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2389.61	64.88	68.53	3.65	74.00	5.47	PK	Vertic	PASS
	2389.61	-	43.74	-	54.00	10.26	AV	Vertic	PASS
2	2390.00	62.61	66.26	3.65	74.00	7.74	PK	Vertic	PASS
	2390.00	-	41.47	-	54.00	12.53	AV	Vertic	PASS

Test Report

Project Information

Profile:	2530770R	EUT:	Smart Controller
Mode:	Mode1:Transmit at 2480MHz by DH5	Voltage:	120 Vac / 60 Hz
Environment:	Temp: 25°C ; Humi:60%	Engineer	Reyn Chen
Test Standard:	FCC PART 15C		

Test Graph



Suspected Data List


NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2483.50	63.64	67.73	4.09	74.00	6.27	PK	Horizo	PASS
	2483.50	-	42.94	-	54.00	11.06	AV	Horizo	PASS
2	2483.55	64.23	68.32	4.09	74.00	5.68	PK	Horizo	PASS
	2483.55	-	43.53	-	54.00	10.47	AV	Horizo	PASS

Test Report

Project Information

Profile:	2530770R	EUT:	Smart Controller
Mode:	Mode1:Transmit at 2480MHz by DH5	Voltage:	120 Vac / 60 Hz
Environment:	Temp: 25°C ; Humi:60%	Enginee	Reyn Chen
Test Standard:	FCC PART 15C		

Test Graph



Suspected Data List


NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2483.50	64.12	68.21	4.09	74.00	5.79	PK	Vertic	PASS
	2483.50	-	43.42	-	54.00	10.58	AV	Vertic	PASS
2	2483.54	68.27	72.36	4.09	74.00	1.64	PK	Vertic	PASS
	2483.54	-	47.57	-	54.00	6.43	AV	Vertic	PASS

Test Report

Project Information

Profile:	2530770R	EUT:	Smart Controller
Mode:	Mode2:Transmit at 2402MHz by 2DH5	Voltage:	120 Vac / 60 Hz
Environment:	Temp: 25°C ; Humi:60%	Enginee	Reyn Chen
Test Standard:	FCC PART 15C		

Test Graph



Suspected Data List


NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2389.33	52.00	55.65	3.65	74.00	18.35	PK	Horizo	PASS
	2389.33	-	30.86	-	54.00	23.14	AV	Horizo	PASS
2	2390.00	51.19	54.84	3.65	74.00	19.16	PK	Horizo	PASS
	2390.00	-	30.05	-	54.00	23.95	AV	Horizo	PASS

Test Report

Project Information

Profile:	2530770R	EUT:	Smart Controller
Mode:	Mode2:Transmit at 2402MHz by 2DH5	Voltage:	120 Vac / 60 Hz
Environment:	Temp: 25°C ; Humi:60%	Enginee	Reyn Chen
Test Standard:	FCC PART 15C		

Test Graph



Suspected Data List


NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2389.86	57.87	61.52	3.65	74.00	12.48	PK	Vertic	PASS
	2389.86	-	36.73	-	54.00	17.27	AV	Vertic	PASS
2	2390.00	52.31	55.96	3.65	74.00	18.04	PK	Vertic	PASS
	2390.00	-	31.17	-	54.00	22.83	AV	Vertic	PASS

Test Report

Project Information

Profile:	2530770R	EUT:	Smart Controller
Mode:	Mode2:Transmit at 2480MHz by 2DH5	Voltage:	120 Vac / 60 Hz
Environment:	Temp: 25°C ; Humi:60%	Engineer	Reyn Chen
Test Standard:	FCC PART 15C		

Test Graph



Suspected Data List


NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2483.50	60.60	64.69	4.09	74.00	9.31	PK	Horizo	PASS
	2483.50	-	39.90	-	54.00	14.10	AV	Horizo	PASS
2	2483.60	60.14	64.23	4.09	74.00	9.77	PK	Horizo	PASS
	2483.60	-	39.44	-	54.00	14.56	AV	Horizo	PASS

Test Report

Project Information

Profile:	2530770R	EUT:	Smart Controller
Mode:	Mode2:Transmit at 2480MHz by 2DH5	Voltage:	120 Vac / 60 Hz
Environment:	Temp: 25°C ; Humi:60%	Engineer	Reyn Chen
Test Standard:	FCC PART 15C		

Test Graph



Suspected Data List


NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2483.50	63.77	67.86	4.09	74.00	6.14	PK	Vertic	PASS
	2483.50	-	43.07	-	54.00	10.93	AV	Vertic	PASS
2	2483.59	63.81	67.90	4.09	74.00	6.10	PK	Vertic	PASS
	2483.59	-	43.11	-	54.00	10.89	AV	Vertic	PASS

Test Report

Project Information

Profile:	2530770R	EUT:	Smart Controller
Mode:	Mode3:Transmit at 2402MHz by 3DH5	Voltage:	120 Vac / 60 Hz
Environment:	Temp: 25°C ; Humi:60%	Enginee	Reyn Chen
Test Standard:	FCC PART 15C		

Test Graph



Suspected Data List


NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2389.67	57.03	60.68	3.65	74.00	13.32	PK	Horizo	PASS
	2389.67	-	35.89	-	54.00	18.11	AV	Horizo	PASS
2	2390.00	56.62	60.27	3.65	74.00	13.73	PK	Horizo	PASS
	2390.00	-	35.48	-	54.00	18.52	AV	Horizo	PASS

Test Report

Project Information

Profile:	2530770R	EUT:	Smart Controller
Mode:	Mode3:Transmit at 2402MHz by 3DH5	Voltage:	120 Vac / 60 Hz
Environment:	Temp: 25°C ; Humi:60%	Engineer	Reyn Chen
Test Standard:	FCC PART 15C		

Test Graph



Suspected Data List


NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2389.67	62.62	66.27	3.65	74.00	7.73	PK	Vertic	PASS
	2389.67	-	41.48	-	54.00	12.52	AV	Vertic	PASS
2	2390.00	60.32	63.97	3.65	74.00	10.03	PK	Vertic	PASS
	2390.00	-	39.18	-	54.00	14.82	AV	Vertic	PASS

Test Report

Project Information

Profile:	2530770R	EUT:	Smart Controller
Mode:	Mode3:Transmit at 2480MHz by 3DH5	Voltage:	120 Vac / 60 Hz
Environment:	Temp: 25°C ; Humi:60%	Engineer	Reyn Chen
Test Standard:	FCC PART 15C		

Test Graph



Suspected Data List


NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2483.50	63.69	67.78	4.09	74.00	6.22	PK	Horizo	PASS
	2483.50	-	42.99	-	54.00	11.01	AV	Horizo	PASS
2	2483.69	63.13	67.22	4.09	74.00	6.78	PK	Horizo	PASS
	2483.69	-	42.43	-	54.00	11.57	AV	Horizo	PASS

Test Report

Project Information

Profile:	2530770R	EUT:	Smart Controller
Mode:	Mode3:Transmit at 2480MHz by 3DH5	Voltage:	120 Vac / 60 Hz
Environment:	Temp: 25°C ; Humi:60%	Engineer	Reyn Chen
Test Standard:	FCC PART 15C		

Test Graph



Suspected Data List

NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2483.50	66.90	70.99	4.09	74.00	3.01	PK	Vertic	PASS
	2483.50	-	46.20	-	54.00	7.80	AV	Vertic	PASS
2	2483.61	66.97	71.06	4.09	74.00	2.94	PK	Vertic	PASS
	2483.61	-	46.27	-	54.00	7.73	AV	Vertic	PASS

Note:


1. Level = Reading + Factor

2. Margin = Limit - Level

3. Margin = Limit - Level, AV Level = PK Level + Duty Cycle Factor

Appendix H: Conducted Spurious Emission Test Result for Band edge


DH5_Ant1_Low_2402



DH5_Ant1_High_2480




DH5_Ant1_Low_Hop_2402




DH5_Ant1_High_Hop_2480



2DH5_Ant1_Low_2402



2DH5_Ant1_High_2480




2DH5_Ant1_Low_Hop_2402



2DH5_Ant1_High_Hop_2480




3DH5_Ant1_Low_2402



3DH5_Ant1_High_2480



3DH5_Ant1_Low_Hop_2402




3DH5_Ant1_High_Hop_2480




Test Result for Spurious Emission


DH5_Ant1_2402_30~1000




DH5_Ant1_2402_1000~3000




DH5_Ant1_2402_3000~5000




DH5_Ant1_2402_5000~7000




DH5_Ant1_2402_7000~9000




DH5_Ant1_2402_9000~11000




DH5_Ant1_2402_11000~13000




DH5_Ant1_2402_13000~15000




DH5_Ant1_2402_15000~17000




DH5_Ant1_2402_17000~19000



DH5_Ant1_2402_19000~21000




DH5_Ant1_2402_21000~23000




DH5_Ant1_2402_23000~25000




DH5_Ant1_2441_30~1000




DH5_Ant1_2441_1000~3000




DH5_Ant1_2441_3000~5000




DH5_Ant1_2441_5000~7000




DH5_Ant1_2441_7000~9000



DH5_Ant1_2441_9000~11000



DH5_Ant1_2441_11000~13000



DH5_Ant1_2441_13000~15000