

# TEST REPORT

**Report No.:** 8331EU122503W2  
**Applicant:** VISCO LLC  
**Address:** 11 Vreeland Rd., Florham Park, NJ 07932 United States  
**Product Name:** Fast Charging Phone Holder  
**Model No.:** DLGR-WICH (refer to clause 2.4)  
**Trademark:** N/A  
**FCC ID:** 2BP8H-DLGRWICH  
**Test Standard(s):** 47 CFR Part 1 Subpart I Section 1.1310  
47 CFR Part 2, Subpart J, Section 2.1091  
**Test Result:** Pass  
**Date of Receipt:** Jun. 25, 2025  
**Test Date:** Jun. 25, 2025 – Jul. 14, 2025  
**Date of Issue:** Aug. 05, 2025

**ISSUED BY:**

SHENZHEN EU TESTING LABORATORY LIMITED



**Prepared by:**



Mikey Zhu/ Engineer

**Reviewed and Approved by:**



Sally Zhang/ Manager



## Revision Record

Report Version	Issued Date	Description	Status
V0	Aug. 05, 2025	Original	Valid





## Table of Contents

1	COVER PAGE.....	1
2	GENERAL INFORMATION .....	4
2.1	APPLICANT INFORMATION .....	4
2.2	MANUFACTURER INFORMATION .....	4
2.3	FACTORY INFORMATION.....	4
2.4	GENERAL DESCRIPTION OF E.U.T.....	4
2.5	TECHNICAL INFORMATION OF E.U.T.....	5
3	TEST SUMMARY.....	6
3.1	TEST STANDARD .....	6
3.2	TEST VERDICT.....	6
3.3	TEST LABORATORY .....	6
4	TEST CONFIGURATION.....	7
4.1	TEST ENVIRONMENT .....	7
4.2	TEST EQUIPMENT .....	7
4.3	TEST MODE .....	7
4.4	MEASUREMENT UNCERTAINTY .....	7
5	TEST METHODOLOGY.....	8
5.1	REFERENCE EVALUATION METHOD .....	8
5.2	TEST SETUP.....	9
5.3	EVALUATION RESULT .....	10
	ANNEX A TEST SETUP PHOTOS.....	11



## 2 General Information

### 2.1 Applicant Information

Applicant	VISCO LLC
Address	11 Vreeland Rd., Florham Park, NJ 07932 United States

### 2.2 Manufacturer Information

Manufacturer	VISCO LLC
Address	11 Vreeland Rd., Florham Park, NJ 07932 United States

### 2.3 Factory Information

Factory	VISCO LLC
Address	11 Vreeland Rd., Florham Park, NJ 07932 United States

### 2.4 General Description of E.U.T.

Product Name	Fast Charging Phone Holder
Model No. Under Test	DLGR-WICH
List Model No.	DLGR-WICH-HOL25
Description of Model differentiation	All models are same with electrical parameters and internal circuit structure, but only differ in appearance color and model name. (this information provided by the customer)
Rating(s)	Input: 5V---2A/9V---2A Wireless Charging Output: 5W/7.5W/10W/15W
Product Type	<input checked="" type="checkbox"/> Mobile <input type="checkbox"/> Portable <input type="checkbox"/> Fix Location
Test Sample No.	-1/2(Normal Sample), -2/2(Engineering Sample)
Hardware Version	V1.3
Software Version	V1.3
Remark	For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.



## 2.5 Technical Information of E.U.T.

Network and Wireless Connectivity	Wireless Power Transfer (WPT)
-----------------------------------	-------------------------------

The requirement for the following technical information of the EUT was tested in this report:

Technology	<b>WPT</b>
Operating Frequency	110.1-205KHz
Modulation Type	FSK
Antenna Type	Inductive Loop Coil Antenna
Antenna Gain(Peak)	0 dBi
Remark	The above information are declared by the applicant, EU-LAB is not responsible for the information accuracy provided by the applicant.



### 3 Test Summary

#### 3.1 Test Standard

The tests were performed according to following standards:

No.	Identity	Document Title
1	47 CFR Part 1 Subpart I Section 1.1310	Radio frequency radiation exposure limits.
2	47 CFR Part 2, Subpart J, Section 2.1091	Radiofrequency radiation exposure evaluation: mobile devices
3	KDB 680106 D01v04	RF exposure consideration for low power consumer wireless power transfer applications.

Remark:

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product maybe which result in lowering the emission/immunity should be checked to ensure compliance has been maintained.

#### 3.2 Test Verdict

No.	Description	FCC Part No.	Verdict	Remark
1	RF Exposure Evaluation	FCC 1.1310 FCC 2.1091 KDB 680106 D01 Wireless Power Transfer v04	Pass	--

#### 3.3 Test Laboratory

Test Laboratory	Shenzhen EU Testing Laboratory Limited
Address	101, Building B1, Fuqiao Fourth Area, Qiaotou Community, Fuhai Subdistrict, Baoan District, Shenzhen, Guangdong, China
Designation Number	CN1368
Test Firm Registration Number	952583



## 4 Test Configuration

### 4.1 Test Environment

During the measurement, the normal environmental conditions were within the listed ranges:

Relative Humidity	30% to 60%		
Atmospheric Pressure	86 kPa to 106 kPa		
Temperature	NT (Normal Temperature)		+15°C to +35°C
Working Voltage of the EUT	NV (Normal Voltage)		120 VAC, 60Hz

### 4.2 Test Equipment

Equipment	Manufacturer	Model No	Serial No	Cal Date	Cal Due Date
Electric and Magnetic Field Probe - Analyzer	Narda	EHP-200A	EE-405	2025/02/14	2026/02/13

### 4.3 Test Mode

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned bellow was evaluated respectively.

No.	Description	Remark
TM1	Adapter + Wireless Output (5W)	
TM2	Adapter + Wireless Output (7.5W)	
TM3	Adapter + Wireless Output (10W)	
TM4	Adapter + Wireless Output (15W)	
TM5	Standby	

Note:

1. EUT supports empty load, half load, full load working at the same time, so the all conditions have been tested. It is found that TM4 full load is the worst mode, and the data in the report only reflects the worst mode.

### 4.4 Measurement Uncertainty

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Test Item	Measurement Uncertainty
Magnetic field measurements(3kHz~10MHz)	±14.6%
Electric field measurements(3kHz~10MHz)	±17.3%



## 5 Test Methodology

### 5.1 Reference Evaluation Method

§1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in §1.1307(b), except in the case of portable devices which shall be evaluated according to the provisions of FCC part 2.1093 of this chapter.

**Table 1 to §1.1310(e)(1) - Limits for Maximum Permissible Exposure (MPE)**


Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
<b>(A) Limits for Occupational/Controlled Exposures</b>				
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f <sup>2</sup> )	6
30-300	61.4	0.163	1.0	6
300-1500	/	/	f/300	6
1500-100,000	/	/	5	6
<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

F=frequency in MHz

\*=Plane-wave equivalent power density

RF exposure compliance will need to be determined with respect to 1.1307(c) and (d) of the FCC rules. The emissions should be within the limits at 300kHz in Table 1 of 1.1310(use the 300kHz limits for 150kHz:614V/m,1.63A/m).

## 5.2 Test Setup



Note: Measurements should be made from all sides and the top of the primary/client pair, with the 20cm measured from the center of the probe(s) to the edge of the device.

- 1) The RF exposure test was performed in anechoic chamber.
- 2) The measurement probe was placed at test distance (20cm) which is between the edge of the charger and the geometric center of probe.
- 3) The highest emission level was recorded and compared with limit as soon as measurement of each points (A, B, C, D, E, F) were completed.
- 4) The EUT was measured according to the dictates of KDB 680106 D01 v04.



### 5.3 Evaluation Result

Test Condition: Test Mode 4 operating with client device (1% battery status of client device)

Test Position	E-field (V/m)			H-field (A/m)		
	Measurement	Limit	50% Limit (V/m)	Measurement	Limit	50% Limit (A/m)
Top	4.0956	614	307	0.1740	1.63	0.815
Bottom	4.8267			0.3100		
Front	2.5492			0.2920		
Rear	2.7671			0.1450		
Left	3.0208			0.2350		
Right	2.9987			0.0450		

Test Condition: Test Mode 4 operating with client device (50% battery status of client device)

Test Position	E-field (V/m)			H-field (A/m)		
	Measurement	Limit	50% Limit (V/m)	Measurement	Limit	50% Limit (A/m)
Top	4.0479	614	307	0.1392	1.63	0.815
Bottom	3.1371			0.2480		
Front	2.2295			0.2336		
Rear	3.7536			0.1160		
Left	4.6719			0.1880		
Right	2.8482			0.0360		

Test Condition: Test Mode 4 operating with client device (99% battery status of client device)

Test Position	E-field (V/m)			H-field (A/m)		
	Measurement	Limit	50% Limit (V/m)	Measurement	Limit	50% Limit (A/m)
Top	4.0781	614	307	0.2680	1.63	0.815
Bottom	4.0231			0.2848		
Front	2.9784			0.0928		
Rear	3.8045			0.1936		
Left	4.3482			0.0296		
Right	4.2597			0.2808		

Note 1: E-Field Strength at 20 cm surrounding the EUT and 20cm above the top surface of the EUT.

Note 2: H-Field Strength at 20 cm surrounding the EUT and 20cm above the top surface of the EUT.

## ANNEX A TEST SETUP PHOTOS

### PHOTO 1

Test Position: Top





## STATEMENT

1. The laboratory guarantees the scientificity, accuracy and impartiality of the test, and is responsible for all the information in the report, except the information provided by the customer. The customer is responsible for the impact of the information provided on the validity of the results.
2. The report without China inspection body and laboratory Mandatory Approval (CMA) mark has no effect of proving to the society.
3. For the report with CNAS mark or A2LA mark, the items marked with "☆" are not within the accredited scope.
4. This report is invalid if it is altered, without the signature of the testing and approval personnel, or without the "inspection and testing dedicated stamp" or test report stamp.
5. The test data and results are only valid for the tested samples provided by the customer.
6. This report shall not be partially reproduced without the written permission of the laboratory.
7. Any objection shall be raised to the laboratory within 30 days after receiving the report.

--- End of Report ---