

RF EXPOSURE REPORT

Equipment Under Test	Object Speaker
Model Name	Object-9
Variant Model Name	-
FCC ID	2BP8W-OBJECT-9
Applicant	analogizm
Manufacturer	analogizm
Date of Test(s)	2025. 06. 18 ~ 2025. 06. 26
Date of Issue	2025. 07. 03

In the configuration tested, the EUT complied with the standards specified above.

Issue to	Issue by
analogizm 34, Sangwon 12-gil, Seongdong-gu Seoul, Republic of Korea	DEKRA Korea Co., Ltd. 498-2, Geumeo-ro, Pogok-eup, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea, 17030
Tel.: +82-10-9397-1379 Fax: -	Tel.: +82-31-338-8837 Fax: +82-31-338-8847

RF EXPOSURE

1. Regulation

According to §15.247(i), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See § 1.1307(b)(1) of this Chapter.

Limits for Maximum Permissive Exposure: RF exposure is calculated.

Frequency Range	Electric Field Strength [V/m]	Magnetic Field Strength [A/m]	Power Density [mW/cm ²]	Averaging Time [minute]
Limits for General Population / Uncontrolled Exposure				
0.3 ~ 1.34	614	1.63	*(100)	30
1.34 ~ 30	824/f	2.19/f	*(180/f ²)	30
30 ~ 300	27.5	0.073	0.2	30
300 ~ 1 500	/	/	f/1 500	30
1 500 ~ 15 000	/	/	1	30

f=frequency in MHz, * = plane-wave equivalent power density

MPE (Maximum Permissive Exposure) Prediction

Predication of MPE limit at a given distance: Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2 \quad (\Rightarrow R = \sqrt{PG/4\pi S})$$

S = power density [mW/cm²]

P = Power input to antenna [mW]

G = Power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna [cm]

2. RF Exposure Compliance Issue

The information should be included in the user's manual:

This appliance and its antenna must not be co-located or operation in conjunction with any other antenna or transmitter. A minimum separation distance of 20 cm must be maintained between the antenna and the person for this appliance to satisfy the RF exposure requirements.

MPE Calculations : Bluetooth LE 1 Mbps

- Frequency Range : 2 402 MHz ~ 2 480 MHz
- Measured RF Output Power (Peak) : -7.01 dBm
- Target Power & Tolerance -7.00 dBm & \pm 1.00 dB
 - (Maximum : -6.00 dBm & Minimum : -8.00 dBm)
- Maximum Peak Antenna Gain : 3.35 dBi
- Maximum Output Power for the Calculation : -6.00 dBm**

The EUT will only be used with a separation of 20 centimeters or greater between the antenna and the body of the The MPE calculation for this exposure is shown below.

$ \begin{aligned} - \text{EIRP} &= P + G \\ &= \underline{-6.00} \text{ dBm} + \underline{3.35} \text{ dBi} \\ &= \underline{-2.65} \text{ dBm} \\ &= \underline{0.54} \text{ mW} \end{aligned} $	<p>- NOTE</p> <p>P : Max tuneup Power (dBm)</p> <p>G : Maximum Peak Antenna Gain (dBi)</p>
--	---

Power Density at the specific separation

$ \begin{aligned} - S &= \text{EIRP} / (4 \times R^2 \pi) \\ &= 0.54 / (4 \times 20^2 \times \pi) \\ &= \underline{0.000\ 108} \text{ mW/cm}^2 \end{aligned} $	<p>- NOTE</p> <p>S : Maximum Power Density (mW/cm²)</p> <p>EIRP : Equivalent Isotropic Radiated Power (mW)</p> <p>R : Distance to the center of the radiation of the antenna (<u>20</u> cm)</p>
--	---

RF Exposure Compliance Issue

Therefore, EUT is not required the SAR Evaluation.