



FCC TEST REPORT

FCC ID: 2BPGGWLD1

Product	:	Pet Washing Machine
Model Name	:	QJXK-PWM-WWLD1
Brand	:	N/A
Report No.	:	PTC25042308101E-FC05
Prepared for		
Allviews Technology LLC		
1125 E Broadway Rd Tempe, AZ 85282 United States		
Prepared by		
Precise Testing & Certification Co., Ltd.		
Building 1, No. 6, Tongxin Road, Dongcheng Street, Dongguan, Guangdong, China.		



Report No.: PTC25042308101E-FC05

TEST RESULT CERTIFICATION

Applicant's name : Allviews Technology LLC
Address : 1125 E Broadway Rd Tempe, AZ 85282 United States
Manufacture's name : Allviews Technology LLC
Address : 1125 E Broadway Rd Tempe, AZ 85282 United States
Product name : Pet Washing Machine
Model name : QJXK-PWM-WWLD1
Test procedure : FCC CFR47 Part 1.1307(b)(1)
Test Date : May 12, 2025 to August 13, 2025
Date of Issue : August 13, 2025
Test Result : PASS

This device described above has been tested by PTC, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of PTC, this document may be altered or revised by PTC, personal only, and shall be noted in the revision of the document.

Test Engineer:

A handwritten signature in black ink, appearing to read 'Jack Zhou'.

Jack Zhou / Engineer

Technical Manager:

A handwritten signature in black ink, appearing to read 'Simon Pu'.

Simon Pu / Manager



Contents

	Page
2 TEST SUMMARY	4
3 GENERAL INFORMATION	5
3.1 GENERAL DESCRIPTION OF E.U.T.	5
4 RF EXPOSURE	6
4.1 REQUIREMENTS	6
4.2 THE PROCEDURES / LIMIT	6
4.3 MPE CALCULATION METHOD	7
4.4 TEST RESULT	7



Report No.: PTC25042308101E-FC05

2 Test Summary

Test Items	Test Requirement	Result
Maximum Permissible Exposure (Exposure of Humans to RF Fields)	15.247 (i)	PASS
Remark:		
N/A: Not Applicable		



3 General Information

3.1 General Description of E.U.T.

Product Name	:	Pet Washing Machine
Model Name	:	QJXK-PWM-WWLD1
Specification	:	Bluetooth BDR+EDR; Bluetooth BLE 802.11b/g/n HT20/HT40 802.11a/n HT20/HT40/ac20/ac40/ac80
Operation Frequency	:	2402-2480MHz for BT 2412-2462MHz for 802.11b/g/ n(HT20) 2422-2452MHz for 802.11 n(HT40) 5G Wifi: 5180-5240MHz 5.8G Wifi: 5745-5825MHz
Number of Channel	:	79 channels for BDR+EDR 40 channels For DTS 11 channels for 802.11b/g/ n(HT20) 7 channels for 802.11n(HT40) 4 channels for 802.11a/n20/ac20 5180-5240 MHz 5 channels for 802.11a/n20/ac20 5745MHz~5825MHz 2 channels for 802.11n40/ac40 5190-5230 MHz 2 channels for 802.11n40/ac40 5755MHz~5795MHz 1 channels for 802.11 ac80
Type of Modulation	:	GFSK, $\pi/4$ -DQPSK, 8DPSK For DSS GFSK, For DTS DSSS with DBPSK/DQPSK/CCK for 802.11b; OFDM with BPSK/QPSK/16QAM/64QAM for 802.11g/n; OFDM with BPSK/QPSK/16QAM/64QAM for 802.11g/n/a/ac
Antenna installation	:	Integrated Antenna
Antenna Gain	:	2.4G:2.49 dBi;5G Wi-Fi:2.93 dBi
Power supply	:	Input: 200-240V~, 50-60 Hz Adapter:ADP-96H12 Input: 100-240V~, 50-60 Hz, 1.5A Max Output:12V= 8A
Hardware Version	:	N/A
Software Version	:	N/A



4 RF Exposure

Test Requirement : FCC Part 1.1307(b)(1)

Evaluation Method : KDB 447498 D01 General RF Exposure Guidance v06

4.1 Requirements

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2 m normally can be maintained between the user and the device.

4.2 The procedures / limit

(A) Limits for Occupational / Controlled Exposure

Frequency Range	Electric Field	Magnetic Field	Power Density (S)	Averaging Time
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range	Electric Field	Magnetic Field	Power Density (S)	Averaging Time
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz ; *Plane-wave equivalent power density



4.3 MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } P_d \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric field (V/m)

P = Peak RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$P_d = \frac{30 \times P \times G}{377 \times d^2} \theta_{\phi}$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained

4.4 Test Result

Mode	Antenna Gain (numeric)	Max. Peak Output Power (dBm)	Tune up tolerance (dBm)	Max Tune Up Power (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)	Result
2480(3DH5)	1.77	10.13	10.13 ± 1	12.971793	0.004578	1	Pass
2440(BLE_1M)	1.77	9.52	9.52 ± 1	11.271975	0.003979	1	Pass
2437(11N40)	1.77	14.47	14.47 ± 1	35.237087	0.012437	1	Pass
5795(11N40)	1.96	15.93	15.93 ± 1	49.317380	0.019263	1	Pass

Conclusion:

1. Calculate in the worst-case mode.
2. Max. Tune Up Power is declared by manufacturer, and used to calculate.
3. BT and WLAN can't transmit simultaneously.

*****THE END REPORT*****