



RF Exposure Evaluation Report

APPLICANT : Nomadic Controls
EQUIPMENT : Helix Pulse-Smart 10in Touchscreen
MODEL NAME : NT-SC-00V-R0-SCP-10T
FCC ID : 2BPQYHP01
STANDARD : 47 CFR Part 2.1091
FCC KDB 447498 D01 v06

The product evaluation date was started from May 29, 2025 and completed on May 29, 2025. We, Sporton International Inc. (Kunshan), would like to declare that the device has been evaluated in accordance with 47 CFR Part 2.1091 and FCC KDB 447498 D01 v06, and pass the limit. Without written approval of Sporton International Inc. (Kunshan), the test report shall not be reproduced except in full.



Approved by: Si Zhang

Sportun International Inc. (Kunshan)

No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300
People's Republic of China



Table of Contents

1. ADMINISTRATION DATA	4
1.1. Testing Laboratory	4
2. DESCRIPTION OF EQUIPMENT UNDER TEST (EUT)	5
3. MAXIMUM RF AVERAGE OUTPUT TUNE UP POWER AMONG PRODUCTION UNITS	6
4. RF EXPOSURE LIMIT INTRODUCTION	7
5. RADIO FREQUENCY RADIATION EXPOSURE EVALUATION	8
5.1. Standalone Power Density Calculation	8
5.2. Collocated Power Density Calculation.....	8



Revision History



1. Administration Data

1.1. Testing Laboratory

Sportun International Inc. (Kunshan) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Testing Laboratory			
Test Firm	Sportun International Inc. (Kunshan)		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158		
Test Site No.	Sportun Site No.	FCC Designation No.	FCC Test Firm Registration No.
	SAR01-KS	CN1257	314309

Applicant	
Company Name	Nomadic Controls
Address	2904 Airport Pkwy Elkhart, IN 46514 United States

Manufacturer	
Company Name	Nomadic Controls
Address	2904 Airport Pkwy Elkhart, IN 46514 United States



2. Description of Equipment Under Test (EUT)

Product Feature & Specification	
EUT Type	Helix Pulse-Smart 10in Touchscreen
Model Name	NT-SC-00V-R0-SCP-10T
FCC ID	2BPQYHP01
Wireless Technology and Frequency Range	WLAN 2.4GHz Band: 2412 MHz ~ 2462 MHz Bluetooth: 2402 MHz ~ 2480 MHz ZigBee: 2405 MHz ~ 2480 MHz
Mode	WLAN 2.4GHz 802.11b/g/n HT20/HT40 Bluetooth BR/EDR/LE ZigBee: QPSK
Antenna Gain	WLAN2.4GHz/Bluetooth: 3.91 dBi BLE: 0.73 dB ZigBee: 2.65 dBi
Antenna Type	Bluetooth: IPEX Antenna WLAN: IPEX Antenna ZigBee: IPEX Antenna
HW Version	V1.0
SW Version	V2.X.X

Remark:

1. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.
2. The WLAN/Bluetooth Antenna don't support Bluetooth LE mode, and BLE Antenna supports Bluetooth LE mode only.
3. This is a change FCC ID report. Since no changes have been made to this device, therefore, all the results were leveraged from original report (FCC ID: 2A789-TPA10, Sporton Report Number FA350402).

Comments and Explanations:

1. The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.
2. The maximum RF output tune up power, antenna gain also the safe distance used for evaluate RF exposure were declared by manufacturer.



3. Maximum RF average output tune up power among production units

<2.4GHz WLAN >

Mode		Maximum Average Power (dBm)
2.4GHz	802.11b	17.0
	802.11g	16.0
	802.11n-HT20	15.0
	802.11n-HT40	15.0
Bluetooth	BR/EDR	8.0

<Bluetooth>

Mode		Maximum Average power(dBm)
Bluetooth	LE	8.0

<ZigBee>

Mode		Maximum Average power(dBm)
2.4GHz	ZigBee	20.0



4. RF Exposure Limit Introduction

According to ANSI/IEEE C95.1-1992, the criteria listed in Table 1 shall be used to evaluate the environmental impact of human exposure to radio frequency (RF) radiation as specified in §1.1310.

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f ²)	6
30-300	61.4	0.163	1.0	6
300-1500			f/300	6
1500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500			f/1500	30
1500-100,000			1.0	30

The MPE was calculated at 20 cm to show compliance with the power density limit.

The following formula was used to calculate the Power Density:

$$S = \frac{PG}{4\pi R^2}$$

Where:

S = Power Density

P = Output Power at Antenna Terminals

G = Gain of Transmit Antenna (linear gain)

R = Distance from Transmitting Antenna



5. Radio Frequency Radiation Exposure Evaluation

5.1. Standalone Power Density Calculation

Band	Frequency (MHz)	Antenna Gain (dBi)	Maximum Power (dBm)	Maximum EIRP (dBm)	Average EIRP (mW)	Power Density at 20cm (mW/cm^2)	Limit (mW/cm^2)	Power Density / Limit
Bluetooth	2402.0	3.91	8.00	11.910	15.524	0.003	1.000	0.003
2.4GHz WLAN	2412.0	3.91	17.00	20.910	123.310	0.025	1.000	0.025
ZigBee	2405.0	2.65	20.00	22.650	184.077	0.037	1.000	0.037

Note:

1. For conservativeness, the lowest frequency of each band is used to determine the MPE limit of that band.
2. Chose the maximum power to do MPE analysis.
3. Chose the maximum RF output tune up power of all antennas among same frequency BT/BLE bands and the maximum antenna gain to perform MPE calculation conservatively.

5.2. Collocated Power Density Calculation

Bluetooth Power Density / Limit	ZigBee Power Density / Limit	WLAN 2.4GHz Power Density / Limit	Σ (Power Density / Limit) of Bluetooth + ZigBee + WLAN 2.4GHz
0.003	0.037	0.025	0.065

Note:

1. According to the EUT characteristic, WLAN 2.4GHz and WLAN 5GHz cannot transmit simultaneously.
2. Σ (Power Density / Limit): This is a summation of [(power density for each transmitter/antenna included in the simultaneous transmission)/ (corresponding MPE limit)], for Bluetooth + ZigBee/WLAN2.4GHz, Bluetooth +ZigBee + WLAN2.4GHz.
3. Considering the WLAN/ZigBee module collocation with Bluetooth transmitter of the EIRP performance listed in the table above, the aggregated (power density /limit) is smaller than 1, and MPE of collocated transmitters is compliant.

Conclusion:

According to 47 CFR §2.1091, the RF exposure analysis concludes that the RF Exposure is FCC compliant.

-----THE END-----