

RF TEST REPORT

Report Reference No..... : MAX250427015P01-R01RF

FCC ID..... : 2BPRQ-V5

Compiled by
(position+printed name+signature)... : Engineer/ Cindy Zheng

Cindy zheng

Supervised by
(position+printed name+signature)... : Manager/Haley Wen

Haley wen

Approved by
(position+printed name+signature)... : RF Manager/ Vivian Jiang

Vivian Jiang

Date of issue..... : May 21, 2025

Testing Laboratory Name..... : MAX Testing Co.,Ltd.

Address..... : 1/F, Building B, Xinshidai GR Park, Shiyan Street, Bao'an District,
Shenzhen, Guangdong, 518052, People's Republic of China

Applicant's name..... : Hangzhou Zansheng Digital Co., Ltd.

Address..... : 501-2, Building 17, No.1008 Xiangwang Street, Cangqian Street,
Yuhang District, Hangzhou City, Zhejiang Province, China

Test specification..... :

Standard..... : KDB 447498 D01

MAX Testing Co.,Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the MAX Testing Co.,Ltd. is acknowledged as copyright owner and source of the material. MAX Testing Co.,Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Equipment description..... : Headset microphone

Trade Mark..... : N/A

Manufacturer..... : Dongguan Xingnan Digital Technology Co., Ltd.

Model/Type reference..... : V5

Listed Models : V11, V16, U18, S1, S2, S3, S5, V38, V36, V35, V31, V33, V32, V38

Modulation : FM

Frequency..... : 195.0MHz

Ratings..... : DC 3.7V from battery or DC 5V by USB port

Result..... : **PASS**

RF Exposure Evaluation

1. The corresponding SAR Exclusion Threshold condition, listed below:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}]$
The test Result is less than 3.0 for 1-g SAR and ≤ 7.5 for 10-g extremity SAR.

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, 16 where

- > $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- > Power and distance are rounded to the nearest mW and mm before calculation
- > The result is rounded to one decimal place for comparison

2. CLASSIFICATION

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

EUT Specification

Antenna type:	Metal antenna
Antenna gain (Max)	0dBi
Evaluation applied	☐ MPE Evaluation ☒ SAR Evaluation

3. SAR TEST EXCLUSION THRESHOLDS

Frequency	RF Output power	Tolerance	Max Tune Up power		Antenna Gain	min. test separation distance	Result	Limit
(MHz)	(dBm)	(dBm)	(dBm)	(mW)	(dBi)	(mm)		
195.0	-1.585	-1±1	0	1.0	0	5	0.088	3

Per KDB 447498 D01, when the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine RF Exposure test exclusion. The test exclusion threshold is 0.3013 which is ≤ 3, RF Exposure testing is not required.

Note: Exclusion Thresholds Results = $\frac{(\text{max. power of channel, including tune-up tolerance, mW})}{(\text{min. test separation distance, mm})} \cdot \sqrt{f(\text{GHz})}$

f(GHz) is the RF channel transmit frequency in GHz

Distance = 5mm

Conclusion: No SAR is required.