

FCC TEST REPORT

FCC ID:2BPRW-M93

Report No. : SSP25050181-1E

Applicant : Mofa Technology (Shenzhen) co.,Ltd

Product Name : wireless microphone

Model Name : M93, M93A, M93B, M93C

Test Standard : FCC Part 15.249

Date of Issue : 2025-05-28



Shenzhen CCUT Quality Technology Co., Ltd.

1F, Building 35, Changxing Technology Industrial Park, Yutang Street, Guangming District, Shenzhen,
Guangdong, China; (Tel.:+86-755-23406590 website: www.ccuttest.com)

This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by Shenzhen CCUT Quality Technology Co., Ltd.

Test Report Basic Information

Applicant:	Mofa Technology (Shenzhen) co.,Ltd
Address of Applicant.....:	B1411, Jiansheng Building, No.1 Pingji Avenue, Longgang District, Shenzhen China
Manufacturer:	Mofa Technology (Shenzhen) co.,Ltd
Address of Manufacturer.....:	B1411, Jiansheng Building, No.1 Pingji Avenue, Longgang District, Shenzhen China
Product Name:	wireless microphone
Brand Name:	N/A
Main Model:	M93
Series Models:	M93A, M93B, M93C
Test Standard:	FCC Part 15 Subpart C ANSI C63.10-2013
Date of Test	May 08, 2025 to May 16, 2025
Test Result:	PASS
Tested By	<u>Choco Qiu</u> (Choco Qiu)
Reviewed By:	<u>Lieber Ouyang</u> (Lieber Ouyang)
Authorized Signatory:	<u>Lahm Peng</u> (Lahm Peng)
Note : This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by Shenzhen CCUT Quality Technology Co., Ltd.. All test data presented in this test report is only applicable to presented test sample.	



CONTENTS

1. General Information	5
1.1 Product Information	5
1.2 Test Setup Information	6
1.3 Compliance Standards	7
1.4 Test Facilities	7
1.5 List of Measurement Instruments	8
1.6 Measurement Uncertainty	9
2. Summary of Test Results	10
3. Antenna Requirement	11
3.1 Standard and Limit	11
3.2 Test Result	11
4. Conducted Emissions	12
4.1 Standard and Limit	12
4.2 Test Procedure	12
4.3 Test Data and Results	13
5. Radiated Emissions, Field Strength of The Fundamental Signal	16
5.1 Standard and Limit	16
5.2 Test Procedure	16
5.3 Test Data and Results	18
6. Band-edge Emissions	27
6.1 Standard and Limit	27
6.2 Test Procedure	27
6.3 Test Data and Results	27
7. Occupied Bandwidth	29
7.1 Standard and Limit	29
7.2 Test Procedure	29
7.3 Test Data and Results	29

Revision History

Revision	Issue Date	Description	Revised By
V1.0	2025-05-28	Initial Release	Lahm Peng

1. General Information

1.1 Product Information

Product Name:	wireless microphone
Trade Name:	N/A
Main Model:	M93
Series Models:	M93A, M93B, M93C
Rated Voltage:	DC 3.7V
Battery:	DC 3.7V
Test Sample No:	1-1(Normal Sample), 1-2(Engineering Sample)
Hardware Version:	N/A
Software Version:	N/A
Note 1: The test data is gathered from a production sample, provided by the manufacturer.	
Note 2: Only the model names are different, but the circuit and the electronic construction are the same, declared by the manufacturer.	

Wireless Specification	
Wireless Standard:	Bluetooth BR/EDR
Operating Frequency:	2402MHz ~ 2480MHz
Max. Field Strength:	99.14dBuV/m
Quantity of Channel:	79
Channel Separation:	1MHz
Modulation:	GFSK, Pi/4 DQPSK, 8DPSK
Antenna Gain:	1.68dBi
Type of Antenna:	Internal antenna
Type of Device:	☒ Portable Device ☐ Mobile Device ☐ Modular Device

1.2 Test Setup Information

List of Test Modes			
Test Mode	Description	Remark	
TM1	Transmitting	2402/2441/2480MHz	
/	/	/	
List and Details of Auxiliary Cable			
Description	Length (cm)	Shielded/Unshielded	With/Without Ferrite
-	-	-	-
-	-	-	-
List and Details of Auxiliary Equipment			
Description	Manufacturer	Model	Serial Number
Adapter	HUAWEI	H302	-
-	-	-	-

List of Channels							
No. of Channel	Frequency (MHz)	No. of Channel	Frequency (MHz)	No. of Channel	Frequency (MHz)	No. of Channel	Frequency (MHz)
01	2402	21	2422	41	2442	61	2462
02	2403	22	2423	42	2443	62	2463
03	2404	23	2424	43	2444	63	2464
04	2405	24	2425	44	2445	64	2465
05	2406	25	2426	45	2446	65	2466
~	~	~	~	~	~	~	~
16	2417	36	2437	56	2457	76	2477
17	2418	37	2438	57	2458	77	2478
18	2419	38	2439	58	2459	78	2479
19	2420	39	2440	59	2460	79	2480
20	2421	40	2441	60	2461		

1.3 Compliance Standards

Compliance Standards	
FCC Part 15 Subpart C	FEDERAL COMMUNICATIONS COMMISSION, RADIO FREQUENCY DEVICES, Intentional Radiators
All measurements contained in this report were conducted with all above standards	
According to standards for test methodology	
FCC Part 15 Subpart C	FEDERAL COMMUNICATIONS COMMISSION, RADIO FREQUENCY DEVICES, Intentional Radiators
ANSI C63.10-2013	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices
Maintenance of compliance is the responsibility of the manufacturer or applicant. Any modification of the product, which result is lowering the emission, should be checked to ensure compliance has been maintained.	

1.4 Test Facilities

Laboratory Name:	Shenzhen CCUT Quality Technology Co., Ltd. 1F, Building 35, Changxing Technology Industrial Park, Yutang Street, Guangming District, Shenzhen, Guangdong, China
CNAS Laboratory No.:	L18863
A2LA Certificate No.:	6893.01
FCC Registration No.:	583813
ISED Registration No.:	CN0164
All measurement facilities used to collect the measurement data are located at 1F, Building 35, Changxing Technology Industrial Park, Yutang Street, Guangming District, Shenzhen, Guangdong, China.	

1.5 List of Measurement Instruments

Description	Manufacturer	Model	Serial Number	Cal. Date	Due. Date
Conducted Emissions					
AMN	ROHDE&SCHWARZ	ENV216	101097	2024-08-07	2025-08-06
EMI Test Receiver	ROHDE&SCHWARZ	ESPI	100242	2024-08-07	2025-08-06
Test Cable	N/A	Cable 5	N/A	2024-08-07	2025-08-06
EMI Test Software	FARA	EZ-EMC	EMEC-3A1+	N/A	N/A
Radiated Emissions					
EMI Test Receiver	ROHDE&SCHWARZ	ESPI	100154	2024-08-07	2025-08-06
Spectrum Analyzer	KEYSIGHT	N9020A	MY48030972	2024-08-07	2025-08-06
Spectrum Analyzer	ROHDE&SCHWARZ	FSV40-N	101692	2024-08-07	2025-08-06
Amplifier	SCHWARZBECK	BBV 9743B	00251	2024-08-07	2025-08-06
Amplifier	HUABO	YXL0518-2.5-45	--	2024-08-07	2025-08-06
Amplifier	COM-MW	DLAN-18G-4G-02	10229104	2024-08-07	2025-08-06
Loop Antenna	DAZE	ZN30900C	21104	2024-08-03	2025-08-02
Broadband Antenna	SCHWARZBECK	VULB 9168	01320	2024-08-03	2025-08-02
Horn Antenna	SCHWARZBECK	BBHA 9120D	02553	2024-08-03	2025-08-02
Horn Antenna	COM-MW	ZLB7-18-40G-950	12221225	2024-08-03	2025-08-02
Attenuator	QUANJUDA	6dB	220731	2024-08-07	2025-08-06
Test Cable	N/A	Cable 1	N/A	2024-08-07	2025-08-06
Test Cable	N/A	Cable 2	N/A	2024-08-07	2025-08-06
Test Cable	N/A	Cable 3	N/A	2024-08-07	2025-08-06
Test Cable	N/A	Cable 4	N/A	2024-08-07	2025-08-06
Test Cable	N/A	Cable 8	N/A	2024-08-07	2025-08-06
Test Cable	N/A	Cable 9	N/A	2024-08-07	2025-08-06
EMI Test Software	FARA	EZ-EMC	FA-03A2 RE+	N/A	N/A
Conducted RF Testing					
RF Test System	MWRFTTest	MW100-RFCB	220418SQS-37	2024-08-07	2025-08-06
Spectrum Analyzer	KEYSIGHT	N9020A	ATO-90521	2024-08-07	2025-08-06
RF Test Software	MWRFTTest	MTS 8310	N/A	N/A	N/A
Laptop	Lenovo	ThlnkPad E15 Gen 3	SPPOZ22485	N/A	N/A

1.6 Measurement Uncertainty

Test Item	Conditions	Uncertainty
Conducted Emissions	9kHz ~ 30MHz	±1.64 dB
Radiated Emissions	9kHz ~ 30MHz	±2.88 dB
	30MHz ~ 1GHz	±3.32 dB
	1GHz ~ 18GHz	±3.50 dB
	18GHz ~ 40GHz	±3.66 dB
Occupied Bandwidth	9kHz ~ 26GHz	±4.0 %

2. Summary of Test Results

FCC Rule	Description of Test Item	Result
FCC Part 15.203	Antenna Requirement	Passed
FCC Part 15.207	Conducted Emissions	Passed
FCC Part 15.209, 15.249(a)&(d)	Radiated Emissions	Passed
FCC part 15.249 (d)/15.205, 15.209	Band-edge Emissions	Passed
FCC Part 15.215(c)	Occupied Bandwidth	Passed
Passed: The EUT complies with the essential requirements in the standard Failed: The EUT does not comply with the essential requirements in the standard N/A: Not applicable		

3. Antenna Requirement

3.1 Standard and Limit

According to FCC Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

3.2 Test Result

This product has an integral antenna, fulfill the requirement of this section.

4. Conducted Emissions

4.1 Standard and Limit


According to the rule FCC Part 15.207, Conducted emissions limit, the limit for a wireless device as below:

Frequency of Emission (MHz)	Conducted emissions (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50

Note 1: Decreases with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz
 Note 2: The lower limit applies at the band edges

4.2 Test Procedure

Test is conducting under the description of ANSI C63.10 - 2013 section 6.2.



Test Setup Block Diagram

a) The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

b) The following is the setting of the receiver

Attenuation: 10dB

Start Frequency: 0.15MHz

Stop Frequency: 30MHz

IF Bandwidth: 9kHz

c) The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipment powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.

- d) Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- e) I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- f) LISN is at least 80 cm from nearest part of EUT chassis.
- g) For the actual test configuration, please refer to the related Item - photographs of the test setup.

4.3 Test Data and Results

Based on all tested data, the EUT complied with the FCC Part 15.207 standard limit for a wireless device, and with the worst case as below:

Remark: Level = Reading + Factor, Margin = Level - Limit


Test Plots and Data of Conducted Emissions

Tested Mode: TM1

Test Voltage: AC 120V/60Hz

Test Power Line: Neutral

Remark:



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.1680	26.74	9.58	36.32	65.06	-28.74	QP	P
2	0.1680	3.44	9.58	13.02	55.06	-42.04	AVG	P
3	0.4964	25.48	9.61	35.09	56.06	-20.97	QP	P
4	0.4964	16.35	9.61	25.96	46.06	-20.10	AVG	P
5	0.6404	26.57	9.69	36.26	56.00	-19.74	QP	P
6	0.6404	16.96	9.69	26.65	46.00	-19.35	AVG	P
7 *	0.8745	30.83	9.60	40.43	56.00	-15.57	QP	P
8	0.8745	18.55	9.60	28.15	46.00	-17.85	AVG	P
9	1.0589	25.19	9.53	34.72	56.00	-21.28	QP	P
10	1.0589	12.98	9.53	22.51	46.00	-23.49	AVG	P
11	2.6745	23.19	9.65	32.84	56.00	-23.16	QP	P
12	2.6745	12.13	9.65	21.78	46.00	-24.22	AVG	P


Test Plots and Data of Conducted Emissions

Tested Mode: TM1

Test Voltage: AC 120V/60Hz

Test Power Line: Live

Remark:



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.1500	24.82	9.51	34.33	66.00	-31.67	QP	P
2	0.1500	7.60	9.51	17.11	56.00	-38.89	AVG	P
3	0.4740	23.02	9.62	32.64	56.44	-23.80	QP	P
4	0.4740	13.17	9.62	22.79	46.44	-23.65	AVG	P
5	0.6450	24.26	9.69	33.95	56.00	-22.05	QP	P
6	0.6450	14.98	9.69	24.67	46.00	-21.33	AVG	P
7 *	0.8835	27.46	9.60	37.06	56.00	-18.94	QP	P
8	0.8835	16.71	9.60	26.31	46.00	-19.69	AVG	P
9	1.0680	22.19	9.53	31.72	56.00	-24.28	QP	P
10	1.0680	8.35	9.53	17.88	46.00	-28.12	AVG	P
11	2.3145	17.51	9.69	27.20	56.00	-28.80	QP	P
12	2.3145	6.19	9.69	15.88	46.00	-30.12	AVG	P

5. Radiated Emissions, Field Strength of The Fundamental Signal

5.1 Standard and Limit

According to §15.249(a), the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

Fundamental frequency	Field strength of fundamental (milli-volts/meter)	Field strength of Harmonics (micro-volts/meter)
902-928 MHz	50	500
2400-2483.5 MHz	50	500
5725-5875 MHz	50	500
24.0-24.25 GHz	250	2500

According to §15.249(d) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

According to the rule FCC Part 15.209, Radiated emission limit for a wireless device as below:


Frequency of emission (MHz)	Radiated emissions (3m)
	Quasi-peak (dBuV/m)
30-88	40
88-216	43.5
216-960	46
Above 960	54
Note: The more stringent limit applies at transition frequencies.	

The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in §15.35 for limiting peak emissions apply. Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.


Note: Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.

5.2 Test Procedure


Test is conducting under the description of ANSI C63.10 - 2013 section 6.3 to 6.6.



Block Diagram of Radiated Emission Below 30MHz



Block Diagram of Radiated Emission From 30MHz to 1GHz



Block Diagram of Radiated Emission Above 1GHz

- a) The EUT is placed on a turntable, which is 0.8m above ground plane for test frequency range below 1GHz, and 1.5m above ground plane for test frequency range above 1GHz.
- b) EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
- c) Use the following spectrum analyzer settings:
Span = wide enough to fully capture the emission being measured
RBW = 1 MHz for $f \geq 1\text{GHz}$, 100 kHz for $f < 1\text{GHz}$, 10kHz for $f < 30\text{MHz}$
VBW $\geq$ RBW, Sweep = auto
Detector function = peak
Trace = max hold
- d) Follow the guidelines in ANSI C63.4-2014 with respect to maximizing the emission by rotating the EUT, adjusting the measurement antenna height and polarization, etc. The peak reading of the emission, after being corrected by the antenna factor, cable loss, pre-amp gain, etc., is the peak field strength, submit this data. Each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
- e) The peak level, once corrected, must comply with the limit specified in Section 15.209. Set the RBW = 1MHz, VBW = 10Hz, Detector = PK for AV value, while maintaining all of the other instrument settings.
- f) For the actual test configuration, please refer to the related item - EUT test photos.

5.3 Test Data and Results

Based on all tested data, the EUT complied with the FCC Part 15.249 standard limit for a wireless device, and with the worst case GFSK_2402MHz as below:


Remark: Level = Reading + Factor, Margin = Level - Limit

Radiated Emission Test Data (30MHz to 1GHz)

Tested Mode: TM1

Test Antenna Polarization: Horizontal

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	143.3261	33.30	-15.42	17.88	43.50	-25.62	QP
2	175.0368	37.99	-16.40	21.59	43.50	-21.91	QP
3	209.3129	40.24	-18.32	21.92	43.50	-21.58	QP
4	545.1826	28.15	-10.74	17.41	46.00	-28.59	QP
5	716.6820	28.59	-7.87	20.72	46.00	-25.28	QP
6 *	909.6667	29.66	-5.10	24.56	46.00	-21.44	QP

Radiated Emission Test Data (30MHz to 1GHz)

Tested Mode: TM1

Test Antenna Polarization: Vertical

Remark:



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	40.4170	32.69	-15.92	16.77	40.00	-23.23	QP
2	96.7750	34.22	-19.56	14.66	43.50	-28.84	QP
3	144.8417	35.53	-15.30	20.23	43.50	-23.27	QP
4 *	182.5592	40.05	-17.41	22.64	43.50	-20.86	QP
5	446.4140	30.87	-12.05	18.82	46.00	-27.18	QP
6	989.5354	29.10	-4.36	24.74	54.00	-29.26	QP

Test Frequency 1GHz-25GHz:

GFSK

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Low Channel:2402MHz									
V	4804.000	51.74	30.55	5.77	24.66	51.62	74.00	-22.38	Pk
V	4804.000	43.66	30.55	5.77	24.66	43.54	54.00	-10.46	AV
V	7206.000	51.81	30.33	6.32	24.55	52.35	74.00	-21.65	Pk
V	7206.000	44.33	30.33	6.32	24.55	44.87	54.00	-9.13	AV
V	9608.000	52.21	30.85	7.45	24.69	53.5	74.00	-20.5	Pk
V	9608.000	43.49	30.85	7.45	24.69	44.78	54.00	-9.22	AV
V	12010.000	54.27	31.02	8.99	25.57	57.81	74.00	-16.19	Pk
V	12010.000	45.5	31.02	8.99	25.57	49.04	54.00	-4.96	AV
H	4804.000	50.83	30.55	5.77	24.66	50.71	74.00	-23.29	Pk
H	4804.000	44.87	30.55	5.77	24.66	44.75	54.00	-9.25	AV
H	7206.000	52.81	30.33	6.32	24.55	53.35	74.00	-20.65	Pk
H	7206.000	43.77	30.33	6.32	24.55	44.31	54.00	-9.69	AV
H	9608.000	52.96	30.85	7.45	24.69	54.25	74.00	-19.75	Pk
H	9608.000	41.87	30.85	7.45	24.69	43.16	54.00	-10.84	AV
H	12010.000	51.92	31.02	8.99	25.57	55.46	74.00	-18.54	Pk
H	12010.000	43.25	31.02	8.99	25.57	46.79	54.00	-7.21	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Middle Channel:2441MHz									
V	4882.00	52.69	30.55	5.77	24.66	52.57	74.00	-21.43	Pk
V	4882.00	44.11	30.55	5.77	24.66	43.99	54.00	-10.01	AV
V	7323.00	52.81	30.33	6.32	24.55	53.35	74.00	-20.65	Pk
V	7323.00	43.79	30.33	6.32	24.55	44.33	54.00	-9.67	AV
V	9764.00	54.67	30.85	7.45	24.69	55.96	74.00	-18.04	Pk
V	9764.00	43.33	30.85	7.45	24.69	44.62	54.00	-9.38	AV
V	12205.00	50.24	31.02	8.99	25.57	53.78	74.00	-20.22	Pk
V	12205.00	44.58	31.02	8.99	25.57	48.12	54.00	-5.88	AV
H	4882.00	54.62	30.55	5.77	24.66	54.5	74.00	-19.5	Pk
H	4882.00	43.82	30.55	5.77	24.66	43.7	54.00	-10.3	AV
H	7323.00	53.55	30.33	6.32	24.55	54.09	74.00	-19.91	Pk
H	7323.00	46.13	30.33	6.32	24.55	46.67	54.00	-7.33	AV
H	9764.00	51.94	30.85	7.45	24.69	53.23	74.00	-20.77	Pk
H	9764.00	45.05	30.85	7.45	24.69	46.34	54.00	-7.66	AV
H	12205.00	53.93	31.02	8.99	25.57	57.47	74.00	-16.53	Pk
H	12205.00	42.11	31.02	8.99	25.57	45.65	54.00	-8.35	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
High Channel:2480MHz									
V	4960.00	55.18	30.55	5.77	24.66	55.06	74.00	-18.94	Pk
V	4960.00	43.61	30.55	5.77	24.66	43.49	54.00	-10.51	AV
V	7440.00	51.07	30.33	6.32	24.55	51.61	74.00	-22.39	Pk
V	7440.00	44.20	30.33	6.32	24.55	44.74	54.00	-9.26	AV
V	9920.00	51.96	30.85	7.45	24.69	53.25	74.00	-20.75	Pk
V	9920.00	43.81	30.85	7.45	24.69	45.1	54.00	-8.9	AV
V	12400.00	53.32	31.02	8.99	25.57	56.86	74.00	-17.14	Pk
V	12400.00	43.79	31.02	8.99	25.57	47.33	54.00	-6.67	AV
H	4960.00	52.29	30.55	5.77	24.66	52.17	74.00	-21.83	Pk
H	4960.00	44.04	30.55	5.77	24.66	43.92	54.00	-10.08	AV
H	7440.00	52.22	30.33	6.32	24.55	52.76	74.00	-21.24	Pk
H	7440.00	43.54	30.33	6.32	24.55	44.08	54.00	-9.92	AV
H	9920.00	52.82	30.85	7.45	24.69	54.11	74.00	-19.89	Pk
H	9920.00	43.68	30.85	7.45	24.69	44.97	54.00	-9.03	AV
H	12400.00	54.35	31.02	8.99	25.57	57.89	74.00	-16.11	Pk
H	12400.00	43.04	31.02	8.99	25.57	46.58	54.00	-7.42	AV

Note: 1. The testing has been conformed to $10 \times 2480\text{MHz} = 24800\text{MHz}$.

2. All other emissions more than 30dB below the limit.

3. Factor = Antenna Factor + Cable Loss - Pre-amplifier.

Emission Level = Reading + Factor

Margin=Emission Level-Limit

4. All the modes have tested and recorded the worst mode(GFSK) in the report

5. Testing is carried out with frequency rang 9kHz to the tenth harmonics. The measurements greater than 20dB below the limit from 9kHz to 30MHz.

6. From 9kHz to 30MHz, 18 GHz to 26.5 GHz, no recording is required when the amplitude of stray radiation attenuates by more than 20 dB below the allowable value

Field Strength of The Fundamental Signal Data

GFSK

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	Limit	Margin
				Height	Polar				
(MHz)	(dBμV/m)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
Low Channel: 2402MHz									
2402	102.69	PK	286	1.4	H	-4.06	98.63	114.00	-15.37
2402	87.71	Ave	342	1.1	V	-4.06	83.65	94.00	-10.35
2402	102.21	PK	39	1.7	H	-4.06	98.15	114.00	-15.85
2402	87.88	Ave	319	1.5	V	-4.06	83.82	94.00	-10.18

Mid CH

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	Limit	Margin
				Height	Polar				
(MHz)	(dBμV/m)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
Middle Channel:2441MHz									
2441	103.11	PK	229	1.4	H	-3.97	99.14	114.00	-14.86
2441	86.87	Ave	41	1.1	V	-3.97	82.90	94.00	-11.10
2441	102.52	PK	341	1.9	H	-3.97	98.55	114.00	-15.45
2441	85.93	Ave	238	1.0	V	-3.97	81.96	94.00	-12.04

High CH

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	Limit	Margin
				Height	Polar				
(MHz)	(dBμV/m)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
High Channel: 2480MHz									
2480	102.72	PK	295	2.0	H	-3.90	98.82	114.00	-15.18
2480	88.65	Ave	178	1.6	V	-3.90	84.75	94.00	-9.25
2480	101.75	PK	277	1.0	H	-3.90	97.85	114.00	-16.15
2480	86.55	Ave	279	1.4	V	-3.90	82.65	94.00	-11.35

PI/4 DQPSK

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	Limit	Margin
				Height	Polar				
(MHz)	(dBμV/m)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
Low Channel: 2402MHz									
2402	102.66	PK	70	1.6	H	-4.06	98.60	114.00	-15.4
2402	85.76	Ave	9	1.3	V	-4.06	81.70	94.00	-12.3
2402	102.21	PK	64	1.5	H	-4.06	98.15	114.00	-15.85
2402	88.70	Ave	176	1.7	V	-4.06	84.64	94.00	-9.36

Mid CH

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	Limit	Margin
				Height	Polar				
(MHz)	(dBμV/m)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
Middle Channel:2441MHz									
2441	102.02	PK	150	1.3	H	-3.97	98.05	114.00	-15.95
2441	85.17	Ave	25	1.2	V	-3.97	81.20	94.00	-12.80
2441	101.63	PK	317	1.3	H	-3.97	97.66	114.00	-16.34
2441	85.44	Ave	314	1.3	V	-3.97	81.47	94.00	-12.53

High CH

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	Limit	Margin
				Height	Polar				
(MHz)	(dBμV/m)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
High Channel: 2480MHz									
2480	102.54	PK	272	1.8	H	-3.90	98.64	114.00	-15.36
2480	87.69	Ave	225	1.7	V	-3.90	83.79	94.00	-10.21
2480	102.11	PK	308	1.7	H	-3.90	98.21	114.00	-15.79
2480	87.62	Ave	60	1.3	V	-3.90	83.72	94.00	-10.28

8DPSK

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	Limit	Margin
				Height	Polar				
(MHz)	(dBμV/m)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
Low Channel: 2402MHz									
2402	102.31	PK	196	1.2	H	-4.06	98.25	114.00	-15.75
2402	86.74	Ave	141	1.7	V	-4.06	82.68	94.00	-11.32
2402	102.62	PK	19	1.3	H	-4.06	98.56	114.00	-15.44
2402	88.33	Ave	192	1.2	V	-4.06	84.27	94.00	-9.73

Mid CH

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	Limit	Margin
				Height	Polar				
(MHz)	(dBμV/m)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
Middle Channel:2441MHz									
2441	102.45	PK	282	1.3	H	-3.97	98.48	114.00	-15.52
2441	84.52	Ave	322	1.2	V	-3.97	80.55	94.00	-13.45
2441	101.76	PK	214	1.9	H	-3.97	97.79	114.00	-16.21
2441	84.74	Ave	111	1.4	V	-3.97	80.77	94.00	-13.23

High CH

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	Limit	Margin
				Height	Polar				
(MHz)	(dBμV/m)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
High Channel: 2480MHz									
2480	101.69	PK	160	1.4	H	-3.90	97.79	114.00	-16.21
2480	87.16	Ave	158	1.5	V	-3.90	83.26	94.00	-10.74
2480	102.69	PK	325	1.9	H	-3.90	98.79	114.00	-15.21
2480	87.65	Ave	120	1.4	V	-3.90	83.75	94.00	-10.25


6. Band-edge Emissions

6.1 Standard and Limit

According to §15.249(d) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

6.2 Test Procedure

Test is conducting under the description of ANSI C63.10 - 2013 section 6.3 to 6.6 and section 6.10.



Test Setup Block Diagram

As the radiated emissions testing, set the Lowest and Highest Transmitting Channel, observed the outside band of 2310MHz to 2400MHz and 2483.5MHz to 2500MHz, than mark the higher-level emission for comparing with the FCC rules.

6.3 Test Data and Results

Based on all tested data, the EUT complied with the FCC Part 15.249 standard limit, and with the worst case as below:

Radiated Emission Test Data (Band edge emissions)							
Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
MHz	dBuV/m	dB/m	dBuV/m	dBuV/m	dB	H/V	PK/AV
Lowest Channel (2402MHz)							
2310	69.66	-21.34	48.32	74	-25.68	H	PK
2310	50.64	-21.34	29.3	54	-24.7	H	AV
2390	65.09	-20.96	44.13	74	-29.87	H	PK
2390	51.41	-20.96	30.45	54	-23.55	H	AV
2310	69.31	-21.34	47.97	74	-26.03	V	PK
2310	51.26	-21.34	29.92	54	-24.08	V	AV
2390	69.27	-20.96	48.31	74	-25.69	V	PK
2390	51.17	-20.96	30.21	54	-23.79	V	AV
Highest Channel (2480MHz)							
2483.50	66.78	-20.51	46.27	74	-27.73	H	PK
2483.50	49.41	-20.51	28.9	54	-25.1	H	AV
2500	65.74	-20.43	45.31	74	-28.69	H	PK
2500	52.35	-20.43	31.92	54	-22.08	H	AV
2483.50	69.11	-20.51	48.6	74	-25.4	V	PK
2483.50	50.35	-20.51	29.84	54	-24.16	V	AV
2500	66.53	-20.43	46.1	74	-27.9	V	PK
2500	51.88	-20.43	31.45	54	-22.55	V	AV

Remark: Level = Reading + Factor, Margin = Level - Limit

7. Occupied Bandwidth

7.1 Standard and Limit

According to 15.215 (c), intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated. The requirement to contain the designated bandwidth of the emission within the specified frequency band includes the effects from frequency sweeping, frequency hopping and other modulation techniques that may be employed as well as the frequency stability of the transmitter over expected variations in temperature and supply voltage. If a frequency stability is not specified in the regulations, it is recommended that the fundamental emission be kept within at least the central 80% of the permitted band in order to minimize the possibility of out-of-band operation.

7.2 Test Procedure

According to the ANSI 63.10-2013, section 6.9, the emission bandwidth test method as follows.

- 1) Remove the antenna from the EUT and connect to the spectrum analyzer via a low loss RF cable.
- 2) Set the spectrum analyzer to any one measured frequency within its operating range.
- 3) Set RBW = 1%~5% of 99% bandwidth, VBW $\geq [3 \times \text{RBW}]$, Sweep = Auto.
- 4) Set a reference level on the measuring instrument equal to the highest peak value.
- 5) Measure the frequency difference of two frequencies that were attenuated 20dB from the reference level. Record the frequency difference as the emission bandwidth.
- 6) Repeat the above procedures until all frequencies measured were complete.

All the trace to stabilize, use the marker-to-peak function to set the marker to the peak of the emission, use the marker-delta function to measure and record the 20dB down and 99% bandwidth of the emission.




Test Setup Block Diagram

7.3 Test Data and Results


Test Channel	Test Frequency	20dB Bandwidth (MHz)	99% Bandwidth (MHz)
Lowest Channel	2402MHz	0.952	0.869
Middle Channel	2441MHz	0.948	0.865
Highest Channel	2480MHz	0.950	0.858

Test Plots of Occupied Bandwidth


2402MHz



2441MHz



2480MHz



***** END OF REPORT *****