


Test Report Number:	LCZE25050060	Total Page(s): 3			
Applicant Name:	Jiangmen Lecolux Lighting Appliance Co.,LTD				
Applicant Address:	Jiu Ding Wang Kitchenware A building 3rd Floor, No.11 Xinyi Road, Jianghai High-tech Zone, Jiangmen City				
Product Name:	Solar camping light - Bluetooth model				
Model / Type Reference:	LYD-LY-4				
FCC ID:	2BPSF-LYD-LY-4				
Date of Issue:	2025-05-26				
Testing Laboratory:	LCTECH Guangdong Testing Services Co., Ltd. 2/F.,Technology and Enterprise Development Center, Guangyuan Road, Xiaolan, Zhongshan, Guangdong, China				
Test Specification:	KDB 447498 D01 General RF Exposure Guidance v06				
Test Result:	Passed				
Compiled by:	Reviewed by:				
2025-05-26	Rex He		2025-05-26	Tension Li	
Date	Name	Signature	Date	Name	Signature
Remark:					
N/A					
<p>The duplication of this report or parts of it and its use for advertising purposes is only allowed with permission of the testing laboratory. This report contains the result of the examination of the product sample submitted by the applicant. A general statement concerning the quality of the products from the series manufacture cannot be derived therefore.</p>					

RF Exposure Evaluation

Limits

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density(mW /cm ²)	Averaging time (minutes)
(A)Limits for Occupational/Controlled Exposures				
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f ²)	6
30-300	61.4	0.163	1.0	6
300-1500			f/300	6
1500-100,000			5	6
(B)Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500			f/1500	30
1500-100,000			1.0	30

f = frequency in MHz

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * r^2)$

Where

Pd = power density in mW/cm², **Pout** = output power to antenna in mW;

G = gain of antenna in linear scale, **Pi**=3.1416;

R = distance between observation point and center of the radiator in cm

Pd is the limit of MPE, 1mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

Test Result of RF Exposure Evaluation

BLE mode

Channel	Output power to antenna(dBm)	Output power to antenna(mW)	Power Density at R=20cm (mW/cm ²)	Limit (mW/cm ²)	Result
2480MHz	-1.606	0.691	0.00008	1.0	PASS

Remark: antenna gain=-0.58dBi

The max power density is less than MPE exempt limit, so it is compliance.