



RF Exposure Report

Product name : Router

Trademark : n.a.

Model no...... : NB-RBEN3601

Series Model(s)..... : n.a.

FCC ID : 2BPWCRBEN360

Report No : C250429188-RF04

Test Standards : CFR47 FCC Part 2: Section 2.1093
CFR47 FCC Part 1: Section 1.1310

Applicant..... : Beijing ittim Technology Co.,Ltd.
Room 901, 8th Floor, Building 7, Courtyard 7, Ronghua

Address of applicant : South Road, Beijing Economic and Technological
Development Zone, Beijing

Manufacturer..... : Beijing ittim Technology Co.,Ltd.
Room 901, 8th Floor, Building 7, Courtyard 7, Ronghua


Manufacturer Address : South Road, Beijing Economic and Technological
Development Zone, Beijing

Date of Test Date..... : May 06, 2025 to Jun 05, 2025


Date of issue. : Jun 24, 2025

Test result..... : Compliance


Prepared By

: 
Adil Yang/Engineer

Reviewed By

: 
Greg Zhang/Engineer

Approved By

: 
Tom Gan/Manager

The test results in the report only apply to the tested sample. The test report shall be invalid without all the signatures of preparer, reviewer and approver. Any objections must be raised to CSIC within 15 days since the date when the report is received. It will not be taken into consideration beyond this limit.

Revision History

Rev.	Issue Date	Description	Note	Revised By
R00	Jun 24, 2025	Original Report	Valid	Adil Yang

Table of Contents**Page**

1	TEST SUMMARY	4
1.1	TEST FACILITY	4
2	GENERAL INFORMATION	5
2.1	GENERAL DESCRIPTION OF EUT	5
3	MAXIMUM PERMISSIBLE EXPOSURE (MPE).....	7
3.1	RF EXPOSURE.....	7

1 TEST SUMMARY

1.1 Test Facility

Shenzhen Central Standard International Center Co., Ltd. (CSIC)

Room 201, Building 1, Mogen Fashion Industrial Park, No. 10, Shilongzai Road, Xinshi Community, Dalang Street, Longhua District, Shenzhen.

The test facility is recognized, certified or accredited by the following organizations:

CNAS Registration No.: L11671

FCC Registration No.: 0031378433 Designation Number: CN1317

IC CAB identifier: CN0051

A2LA Lab Cert. No.: 6426.01

2 GENERAL INFORMATION

2.1 General Description of EUT

EUT(Product Specifications)	
Product Name:	Router
Model:	NB-RBEN3601
Series Model(s):	n.a.
Power supply:	DC 12V 1.5A
Hardware version:	V3.0.00
Software version:	V1.0.10
WIFI-2.4G (RF Specifications)	
Supported type:	802.11 b/g/n(HT20)/n(HT40)/ax(HE20)/ax(HE40)/be(EHT20)/be(EHT40)
Modulation:	DSSS(DBPSK/DQPSK/CCK) for 802.11b OFDM(BPSK, QPSK, 16QAM, 64QAM) for 802.11g/n(HT20)/n(HT40) OFDMA(BPSK, QPSK, 16QAM, 64QAM,256QAM,1024QAM) for ax(HE20)/ax(HE40) OFDMA(BPSK, QPSK, 16QAM, 64QAM,256QAM,1024QAM,4096QAM) for be(EHT20)/be(EHT40)
Operation frequency:	2412MHz~2462MHz 2422MHz~2452MHz
Operation bandwidth:	20MHz, 40MHz
Channel number:	802.11b/g/n(HT20): 11 802.11n(HT40): 9
Antenna type:	ANT1/2:Dipole Antenna
Antenna gain:	ANT1/2:5.81 dBi.
WIFI-5G (RF Specifications)	
Operating Frequency	5150-5350MHz, 5725-5850MHz
Channel number:	5180-5320MHz, 14CHs, 802.11 a/n20/n40/ac20/ac40/ac80/ac160/ax(HE20)/ax(HE40)/ax(HE80)/ ax(HE160)/be(EHT20)/be(EHT40)/be(EHT80)/be(EHT160) 5745-5825MHz, 8CHs, 802.11 a/n20/n40/ac20/ac40/ac80/ax(HE20)/ax(HE40)/ax(HE80) /be(EHT20)/be(EHT40)/be(EHT80)
Channel Spacing	20MHz, 40MHz, 80MHz, 160MHz
Modulation	OFDM (BPSK, QPSK, 16QAM, 64QAM,256QAM) OFDMA (BPSK, QPSK, 16QAM, 64QAM,256QAM, 1024QAM,4096QAM)
Type of Product	Adaptive equipment and does not support non-adaptive mode: LBT based Detect and Avoid (load-based equipment)
Type of Product	Master Device
TX Power Control (TPC)	Supported
Antenna Type	ANT1/2: Dipole Antenna



Antenna Gain	ANT1/2: 5150MHz to 5350MHz: 5.56 dBi, 5725MHz to 5850MHz: 4.68 dBi
--------------	--

Remark: The above information and materials are provided by the Manufacturer.

3 Maximum Permissible Exposure (MPE)

3.1 RF Exposure

3.1.1 Limit

The limit for Maximum Permissible Exposure (MPE) specified in FCC 1.1310 is followed. The gain of the antennas used in the product is extracted from the Antenna data sheets provided and also the maximum total power input to the antenna is measured. Through the Friis transmission formula and the maximum gain of the antenna, we can calculate the distance, away from the product, where the limit of MPE is reached.

Although the Friis Transmission formula is far field assumption, the calculated result of that is an over-prediction for near field power density. It is taken as worst case to specify the safety range.

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environmental impact of the human exposure to radio frequency (RF) radiation as specified in 1.1307 (b).

The limit for Maximum Permissible Exposure (MPE) specified in RSS-102 is followed. The gain of the antennas used in the product is extracted from the Antenna data sheets provided and also the maximum total power input to the antenna is measured. Through the Friis transmission formula and the maximum gain of the antenna, we can calculate the distance, away from the product, where the limit of MPE is reached.

Although the Friis Transmission formula is far field assumption, the calculated result of that is an over-prediction for near field power density. It is taken as worst case to specify the safety range.

According to RSS-102: The criteria listed in the following table shall be used to evaluate the environmental impact of the human exposure to radio frequency (RF) radiation as specified in 2.5.2

For FCC:

Frequency Range	Electric Field Strength	Magnetic Field Strength	Power Density
[MHz]	[V/m]	[A/m]	[mW/cm ²]
Limits for Occupational / controlled Exposures			
300 - 1500	--	--	f/300
1500 - 100000	--	--	5.0
Limits for General population / Uncontrolled Exposure			
300 - 1500	--	--	f/1500
1500 - 100000	--	--	1.0

NOTE: f = Frequency in MHz

3.1.2 Friss Formula

Per KDB 447498 D01 v06, simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on calculated or measured field strengths or power density, is ≤ 1.0 .

If we know the maximum gain of the antenna and the total output power to the antenna, through calculation, we will know MPE value at distance 20cm.

3.1.3 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. Warning statement to the user for keeping at least 20cm or more separation distance from the antenna should be included in the User manual. So, this device is classified as Mobile device.

3.1.4 EUT Operating Conditions

EUT was enabled to transmit and receive at lowest, middle and highest channels.

3.1.5 Evaluation Result

1) tand-alone transmission MPE

For FCC

Test Results of RF Exposure Calculations for FCC, Stand-alone mode

Test Mode	Max. conducted power incl. tune-up (dBm)	Distance (cm)	MPE (mW/cm ²)	Threshold power (mW/cm ²)	Result
WIFI 2.4G	17.267	20	0.0402	1.0	Pass
WIFI 5G Band I	19.011	20	0.0573	1.0	Pass
WIFI 5G Band II	16.467	20	0.0317	1.0	Pass
WIFI 5G Band IV	15.940	20	0.0229	1.0	Pass

Test Results of RF Exposure Calculations for FCC, Simultaneous mode

Co-location Mode	Sum of the MPE ratios	Limit	Result
WIFI 2.4G + WIFI 5G	$0.0402/1 + 0.0573/1 < 1.0$	1.0	Pass

3.1.6 Conclusion

Therefore, the maximum calculations result of above are meet the requirement of Radio Frequency Exposure (MPE) limit.

*****THE END*****